




TDS



Technical Data Sheet



Category:
Earth

Technology:
BPO

Product: MMA Initiator

BPO based 50% active initiator for MMA systems.

*Mixed with MMA and PUMA resins this additive initiates polymerisation and cure.
Please see the chart below for addition levels.*

USAGE:

The dosage rate of the MMA Initiator is varied based on the ambient temperatures and also on the MMA or PUMA formulation it is added to. The accurate dosage rates are specified on the resin data sheets rather than this data sheet although typically its added at 2%.

MIXING:

The area should be prepared, the resin to be catalysed should be opened and then the correct amount of MMA Initiator is weighed out. Other additives required (eg pigments) should all be added and mixed before adding the MMA Initiator, whereas the catalyst should be added before mixing in any fillers.

Add the catalyst mix thoroughly and immediately use the mixed product to avoid heat build up.

Packaging

25kg, 24kg (12 x 2kg) box, or individual 2kg units

Health & Safety Precautions

Safety data sheet must be understood before use. Note: heating the initiator creates a risk of fire. Keep away from all heat sources.

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.



Turkey: Tel: 0090 546 827 6151 Email: info@elementalperformancematerials.com Web: www.elementalperformancematerials.com
Daire 4, Kat 1, No.21 Noter Sokak, Suadiye İstanbul, Turkey

UK: Tel: 0044 8000 680363 Email: contactus@premierconstructionproducts.co.uk Web: www.premierconstructionproducts.co.uk
Premier Construction Products Ltd. Hartford Business Centre, Hartford, Cheshire, CW8 2AB, UK