

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: EleDeck Epoxy Top Coat - Base A

REACH registered number(s): BIS A-01-2119456619-26/BIS F-01-2119454392-40/ALIPHATIC GLYCIDYL ETHER-01-2119485289-22

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Compositions for the building and civil engineering industries e.g. flooring compounds, adhesives, mortars and grouts, solvent free and high-solids coatings, laminating binders

1.3. Details of the supplier of the safety data sheet

Company name: Premier Construction Products Ltd.
22 Wenlock Road, London, N1 7GU, UK
Tel.: +44 (0) 8000 680363
Email: contactus@premierconstructionproducts.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark
GHS09: Environmental



Signal words: Warning

[cont...]

Precautionary statements: P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
P264: Wash hands thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321: Specific treatment (see instructions on this label)

2.3. Other hazards

Other hazards: Not classified as flammable but will burn.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} - REACH registered number(s): 01-2119456619-26

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|------------|-----------|--|---------|
| 500-033-5 | 25068-38-6 | - | Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411 | 50-70% |

BISPHENOL F EPICHLOROHYDRIN RESIN WITH NUMBER AVERAGE - REACH registered number(s): 01-2119454392-40

| | | | | |
|-----------|-----------|---|--|--------|
| 500-006-8 | 9003-36-5 | - | Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411; Eye Irrit. 2: H319 | 10-30% |
|-----------|-----------|---|--|--------|

ALIPHATIC GLYCIDYLETHER - REACH registered number(s): 01-2119485289-22-XXXX

| | | | | |
|-----------|------------|---|--|--------|
| 271-846-8 | 68609-97-2 | - | Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411; Eye Irrit. 2: H319 | 10-30% |
|-----------|------------|---|--|--------|

Contains: Blend of liquid epoxy resin(s) and a reactive diluent.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

[cont...]



PCP

Premier Construction
Products Ltd.

Material Safety Data Sheet According to 1907/2006/EC, Article 31
Page: 3 Revised: 30/09/21

Premier Construction Products Ltd.

Mail: 20-22 Wenlock Road, London, N1 7GU, UK
Tel: +44 (0) 8000 680363

Email: contactus@premierconstructionproducts.co.uk
Web: www.premierconstructionproducts.co.uk

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Barely perceptible odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: 11.6 mg/l @ 20°C

Viscosity: 0,7 - 1,1 Pa.s : 25°C ASTM D-445

Boiling point/range°C: 150°C

Part.coeff. n-octanol/water: Not determined

Vapour pressure: <0.1 mbar at 20°C

pH: 6 - 8

Flash point°C: >150

Autoflammability°C: ca.400°C

Relative density: 1.120kg/m3 at 25°C

9.2. Other information

Other information: No data available.

[cont...]



PCP

Premier Construction
Products Ltd.

Material Safety Data Sheet According to 1907/2006/EC, Article 31
Page: 4 Revised: 30/09/21

Premier Construction Products Ltd.

Mail: 20-22 Wenlock Road, London, N1 7GU, UK
Tel: +44 (0) 8000 680363

Email: contactus@premierconstructionproducts.co.uk
Web: www.premierconstructionproducts.co.uk

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

| Route | Species | Test | Value | Units |
|-------|---------|------|-------|-------|
| ORL | - | LD50 | >2000 | mg/kg |
| SKN | - | LD50 | >2000 | mg/kg |

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

| | | | | |
|-----|-----|------|-------|-------|
| ORL | MUS | LD50 | 15600 | mg/kg |
| ORL | RAT | LD50 | 11400 | mg/kg |
| SKN | RBT | LD50 | >20 | ml/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|--------------------------------|-------|-----------------------|
| Skin corrosion/irritation | DRM | Hazardous: calculated |
| Serious eye damage/irritation | OPT | Hazardous: calculated |
| Respiratory/skin sensitisation | DRM | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

[cont...]



PCP

Premier Construction
Products Ltd.

Material Safety Data Sheet According to 1907/2006/EC, Article 31
Page: 5 Revised: 30/09/21

Premier Construction Products Ltd.

Mail: 20-22 Wenlock Road, London, N1 7GU, UK
Tel: +44 (0) 8000 680363

Email: contactus@premierconstructionproducts.co.uk
Web: www.premierconstructionproducts.co.uk

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Drain container thoroughly. Rinse three times with suitable solvent. Treat rinsings as for product disposal. After draining, vent in a safe place away from sparks and fire. Where practical, containers and packaging should be recycled by a licensed contractor. Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(LIQUID EPOXY RESIN)

[cont...]



PCP

Premier Construction
Products Ltd.

Material Safety Data Sheet According to 1907/2006/EC, Article 31
Page: 6 Revised: 30/09/21

Premier Construction Products Ltd.

Mail: 20-22 Wenlock Road, London, N1 7GU, UK
Tel: +44 (0) 8000 680363

Email: contactus@premierconstructionproducts.co.uk
Web: www.premierconstructionproducts.co.uk

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: Notification status:

EU - EINECS List : On or in compliance with the inventory.

USA - TSCA : Included on Inventory

IECSC : All components listed.

Philippines - PICCS : Included on Inventory.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]



PCP

Premier Construction
Products Ltd.

Material Safety Data Sheet According to 1907/2006/EC, Article 31
Page: 7 Revised: 30/09/21

Premier Construction Products Ltd.

Mail: 20-22 Wenlock Road, London, N1 7GU, UK
Tel: +44 (0) 8000 680363

Email: contactus@premierconstructionproducts.co.uk
Web: www.premierconstructionproducts.co.uk