



SAFETY DATA SHEET

Page 1 of 4

Hard Wax Oil

Revision 24
Revision date 5-Jan-2010

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Hard Wax Oil
Company Fiddes & Son Ltd
Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX
info@fiddes.co.uk
www.fiddes.co.uk
Telephone +44 (0)29 2034 0323
Fax +44 (0)29 2034 3235

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Dearomatised White Spirit	30-40%	64742-48-9	265-150-3	Xn; R65 Xi; R66 R10

ADDITIONAL INFORMATION The product does not require a hazard warning label in accordance with EC Directive 88/379

3. HAZARDS IDENTIFICATION

Main hazards None according to EU directive 1999/45/EC. Flammable Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Other hazards The product is classified in accordance with 67/548/EEC.

4. FIRST AID MEASURES

Skin contact Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Inhalation Move the exposed person to fresh air. Seek medical attention.
Ingestion DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water. Seek medical attention.
General information If you feel unwell, seek medical advice (show the label where possible). Keep the affected person warm and at rest. Remove contaminated clothing. Wash all contaminated clothing before reuse.

5. FIRE FIGHTING MEASURES

Extinguishing media Use extinguishing media appropriate to the surrounding fire conditions. Do NOT use ... Water jet.
Protective equipment Wear: Self-contained breathing apparatus.

Print date 5-Jan-2010

Hard Wax Oil

Revision 24
Revision date 5-Jan-2010

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area. Keep personnel away from spill. Evacuate personnel to a safe area. Eliminate all sources of ignition.
Environmental precautions	Do not allow product to enter drains.
Clean up methods	Clean spillage area thoroughly with plenty of water. Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

7. HANDLING AND STORAGE

Handling	Wear suitable protective equipment. Do not breathe gas/fumes/vapour/spray. Use in a well ventilated area. Vapours are heavier than air. Avoid contact with eyes and skin.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Wear: Suitable respiratory equipment. Self-contained breathing apparatus.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles. Avoid contact with eyes.
Protective equipment	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing. Apron (Plastic or rubber) Rubber boots.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Amber.
Odour	Mild.
Flash point	43°C
Water solubility	insoluble.
VOC (Volatile organic compounds)	555 g/l

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	Heat, sparks and open flames.
Materials to avoid	Oxidising agents. Acids.
Hazardous decomposition products	Carbon oxides. Nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Acute toxicity	Headache, nausea and vomiting. In severe cases, may cause loss of consciousness. Harmful if absorbed through the skin.
Corrosivity	May cause irritation to skin.
Repeated or prolonged exposure	Prolonged or repeated exposure may cause irritation to skin and mucous membranes. Repeated or prolonged exposure may cause dermatitis.

12. ECOLOGICAL INFORMATION

Ecotoxicity	No data is available on this product.
--------------------	---------------------------------------

Hard Wax Oil

Revision 24
Revision date 5-Jan-2010

13. DISPOSAL CONSIDERATIONS

General information Can be incinerated if in compliance with local and national regulations. Dispose of in compliance with all local and national regulations.

Disposal of packaging Empty containers can be sent for disposal or recycling.

14. TRANSPORT INFORMATION

ADR/RID

UN 1263	Packing group II
Class 3	Hazard ID 33
Proper Shipping Name PAINT RELATED MATERIAL .	

IMDG

UN 1263	Packing group II
Class 3	Marine pollutant .
EmS Code F-E S-E	

IATA

UN 1263	Packing group II
Class 3	Subsidiary risk -
Packing Instruction 307 (Cargo)	Maximum quantity 60 L
Packing Instruction 305 (Passenger)	Maximum quantity 5 L

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Symbols Xn - Harmful



Risk phrases R10 - Flammable.
R65 - Harmful: may cause lung damage if swallowed.
R66 - Repeated exposure may cause skin dryness or cracking.

Safety phrases S1/2 - Keep locked up and out of the reach of children.
S13 - Keep away from food, drink and animal feedingstuffs.
S46 - If swallowed, seek medical advice immediately and show this container or label.
S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Hard Wax Oil

Revision 24
Revision date 5-Jan-2010

16. OTHER INFORMATION

Text of risk phrases in Section 2	R10 - Flammable. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking.
General information	S1/2 - Keep locked up and out of the reach of children. S13 - Keep away from food, drink and animal feedingstuffs. S7/9 - Keep container tightly closed and in a well-ventilated place. S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S37/39 - Wear suitable gloves and eye/face protection.
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. The product is classified in accordance with 67/548/EEC.
Revision	This document differs from the previous version in the following areas: 14 - aDR/RID. 14 - iMDG. 14 - iATA. 15 - symbols.
Product Subcategory	Interior/exterior trim varnishes and woodstains, including opaque woodstains. 500 g/l
Maximum content of VOC	555 g/l