



DIRECT CONNECT SOLUTIONS LLC

ORDERS EMAIL: ORDERS@DIRECTCONNECTSOLUTIONS.NET

BOHME EXPERT BLUE ADHESIVE

(4") PART # TEF-100MM-BL

Expert Blue fiberglass with PTFE coating, PTFE content ~65%, thickness approx. 0.15 mm, 100mm width, silicone adhesive, 30 meter roll (98'4")

(6") PART # TEF-150MM-BL

Expert Blue fiberglass with PTFE coating, PTFE content ~65%, thickness approx. 0.15 mm, 150mm width, silicone adhesive, 30 meter roll (98'4")

(7") PART # TEF-180MM-BL

Expert Blue fiberglass with PTFE coating, PTFE content ~65%, thickness approx. 0.15 mm, 180mm width, silicone adhesive, 30 meter roll (98'4")

(8") PART # TEF-200MM-BL

Expert Blue fiberglass with PTFE coating, PTFE content ~65%, thickness approx. 0.15 mm, 200mm width, silicone adhesive, 30 meter roll (98'4")

(9") PART # TEF-230MM-BL

Expert Blue fiberglass with PTFE coating, PTFE content ~65%, thickness approx. 0.15 mm, 230mm width, silicone adhesive, 30 meter roll (98'4")

(10") PART # TEF-250MM-BL

Expert Blue fiberglass with PTFE coating, PTFE content ~65%, thickness approx. 0.15 mm, 250mm width, silicone adhesive, 30 meter roll (98'4")

(11") PART # TEF-280MM-BL

Expert Blue fiberglass with PTFE coating, PTFE content ~65%, thickness approx. 0.15 mm, 280mm width, silicone adhesive, 30 meter roll (98'4")

WELD PAPER MUST BE APPLIED TO HEAT PLATE AND REMOVED FROM HEATPLATE AT APPROXIMATELY 500 DEGREES F. PLATE MUST BE CLEANED PRIOR TO APPLYING A NEW TEFLON. IT MAY BE REQUIRED TO WIPE DOWN PLATE WITH ACETONE PRIOR TO APPLYING NEW PAPER TO REMOVE ALL OLD ADHESIVE.

Adhesive goods on rolls of 30 lm length up to 2 partial lengths on 1 roll; Tolerance of delivery ±10 %.