



# CATALYST FOR GENUINE 3900 Series Flexible Game Line Paint System

## SECTION 1. IDENTIFICATION

**Product Identifier** CATALYST FOR GENUINE 3900 Series Flexible Game Line Paint System  
**Other Means of Identification** 2 component polyurethane  
**Product Family** Organic coating  
**Manufacturer** PBWW Inc., 3452 Grey Avenue, Montreal, Quebec, H4A 3N5, Canada, H&S Department, 1-800-361-6652  
**Emergency Phone No.** Robert Adams 9 AM to 5 PM Monday through Friday, 514-992-9510  
IN THE U.S.A. CALL INFOTRAC EMERGENCY RESPONSE HOTLINE, 1-800-535-5053  
**SDS No.** 0109

## SECTION 2. HAZARD IDENTIFICATION

Classified according to Canada's Hazardous Products Regulations (WHMIS 2015).

Classified according to the US Hazard Communication Standard (HCS 2012).

Classified according to Canada's Hazardous Products Regulations (WHMIS 2015) and the US Hazard Communication Standard (HCS 2012).

### Classification

Flammable liquid - Category 2; Acute toxicity (Inhalation) - Category 2; Skin irritation - Category 2; Serious eye damage - Category 1; Aspiration hazard - Category 1; Aquatic hazard (Acute) - Category 2

### Label Elements



Danger

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage.

Toxic to aquatic life.

### Prevention:

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTRE/doctor

Wear respiratory protection (NIOSH approved self-contained breathing apparatus (SCBA) or supplied air respirator).

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Hexamethylene diisocyanate based	28182-81-2	60-100%		

Product Identifier: CATALYST FOR GENUINE 3900 Series Flexible Game Line Paint  
Date of Preparation: décembre 13, 2023  
Date of Last Revision:

SDS No.: 0109

Page 01 of 06

isocyanurates				
n-Butyl acetate	123-86-4	3-7%		
Xylene (mixed isomers)	1330-20-7	3-7%		
Hexamethylene diisocyanate	822-06-0	0.1-1%		

## SECTION 4. FIRST-AID MEASURES

### First-aid Measures

#### Inhalation

Move to fresh air. Keep at rest in a position comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor.

#### Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Call a Poison Centre or doctor if you feel unwell.

#### Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice or attention.

#### Ingestion

Rinse mouth with water. Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Immediately call a Poison Centre or doctor.

#### First-aid Comments

Some of the first-aid procedures recommended here require advanced first-aid training.

## SECTION 5. FIRE-FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam.

#### Unsuitable Extinguishing Media

Water is not effective for extinguishing a fire. It may not cool product below its flash point.

### Specific Hazards Arising from the Product

Reactive flammable. Heating increases the release of toxic vapour.

Flammable chemicals; irritating chemicals; toxic chemicals; very toxic carbon monoxide, carbon dioxide.

### Special Protective Equipment and Precautions for Fire-fighters

Use extreme caution. Fight fire from a safe distance or a protected location.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment, and Emergency Procedures

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Eliminate all ignition sources. Use grounded, explosion-proof equipment.

### Environmental Precautions

It is good practice to prevent releases into the environment. Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

### Methods and Materials for Containment and Cleaning Up

Stop or reduce leak if safe to do so. Contain and soak up spill with absorbent that does not react with spilled product. Do not use absorbents. Contain spill using noncombustible material such as vermiculite, earth or sand. Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal.

### Other Information

Report spills to local health, safety and environmental authorities, as required.

## SECTION 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Prevent all skin contact. Obtain special instructions before use. Only use where there is adequate ventilation. Avoid release to the environment. Immediately report leaks, spills or failures of the safety equipment (e.g. ventilation system).

### Conditions for Safe Storage

Store in an area that is: cool, temperature-controlled, dry, well-ventilated, clear of combustible and flammable materials (e.g. old rags, cardboard). Restrict access to authorized personnel only.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
n-Butyl acetate	100 ppm	100 ppm	100 ppm			
Hexamethylene diisocyanate based isocyanurates	0,00500 ppm	0,00500 ppm	0,00500 ppm			
Hexamethylene diisocyanate	0,0050 ppm	0,0050 ppm	0,0050 ppm			
Xylene (mixed isomers)	100 ppm A4	150 ppm A4	100 ppm			

### Appropriate Engineering Controls

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Control static electricity discharges which includes bonding of equipment to ground. Provide eyewash and safety shower if contact or splash hazard exists.

### Individual Protection Measures

#### Eye/Face Protection

Wear chemical safety goggles.

#### Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

Nitrile rubber.

#### Respiratory Protection

Wear a NIOSH approved air-purifying respirator with an organic vapour cartridge.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Basic Physical and Chemical Properties

**Appearance** Colourless. Particle Size: Not applicable

**Odour** Ethereal

**Odour Threshold** Not available

**pH** Not applicable

**Melting Point/Freezing Point** Not available (melting); -58 °C (freezing)

**Boiling point/Initial boiling point** 98 °C

**Boiling Range** Not available

**Flash Point** 4 °C

**Evaporation Rate** 1

**Flammability (solid, gas)** Not available

**Upper/Lower Flammability or Explosive Limit** 7% (upper); 2% (lower)

**Vapour Pressure** > 56 kPa

**Vapour Density (air = 1)** 5

Product Identifier: CATALYST FOR GENULINE 3900 Series Flexible Game Line Paint

SDS No.: 0109

Date of Preparation: décembre 13, 2023

Date of Last Revision:

Page 03 of 06

<b>Relative Density (water = 1)</b>	1
<b>Solubility</b>	Slightly soluble in water; Soluble in all proportions in common organic solvents.
<b>Partition Coefficient, n-Octanol/Water (Log Kow)</b>	Not available
<b>Auto-ignition Temperature</b>	589 °C
<b>Decomposition Temperature</b>	Not applicable
<b>Viscosity</b>	1 mm <sup>2</sup> /s (kinematic); Not available (dynamic)
<b>Other Information</b>	
<b>Physical State</b>	Liquid
<b>Molecular Formula</b>	Not available
<b>Molecular Weight</b>	Not available
<b>Bulk Density</b>	Not available
<b>Surface Tension</b>	Not available
<b>Critical Temperature</b>	Not available
<b>Vapour Pressure at 50 deg C</b>	Not available

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

May cause or intensify fire.

### Chemical Stability

Normally stable.

### Possibility of Hazardous Reactions

Reacts in the presence of acidic conditions (low pH).

### Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources. Acidic conditions (low pH). Incompatible materials. Temperatures above 40 °C

### Incompatible Materials

Organic acids (e.g. acetic acid).

Not corrosive to metals.

### Hazardous Decomposition Products

Very toxic carbon monoxide, carbon dioxide.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
n-Butyl acetate	2000 mg/L (rat) (4-hour exposure)	10760 mg/kg (female rat)	14112 mg/kg (rabbit)
Hexamethylene diisocyanate based isocyanurates	462 mg/m <sup>3</sup> (rat) (4-hour exposure)	19800 mg/kg (rat)	< 15800 mg/kg (rabbit)
Hexamethylene diisocyanate	350 mg/kg (rat) (4-hour exposure)	746 mg/kg (rat)	570 mg/kg (rabbit)
Xylene (mixed isomers)	6700 ppm (rat) (4-hour exposure)	3523 mg/kg (rat)	Not available

### Skin Corrosion/Irritation

Human experience shows moderate or severe irritation.

### Serious Eye Damage/Irritation

Product Identifier: CATALYST FOR GENULINE 3900 Series Flexible Game Line Paint  
Date of Preparation: décembre 13, 2023  
Date of Last Revision:

SDS No.: 0109

Page 04 of 06

Human experience and animal tests show mild irritation.

#### **STOT (Specific Target Organ Toxicity) - Single Exposure**

##### **Inhalation**

May be harmful based on animal tests.

##### **Skin Absorption**

Harmful based on human experience and animal tests.

##### **Ingestion**

Based on human experience and animal tests.

#### **Aspiration Hazard**

Symptoms may include coughing, choking, shortness of breath, difficult or rapid breathing, and wheezing.

#### **STOT (Specific Target Organ Toxicity) - Repeated Exposure**

Based on studies in people and animals.

#### **Respiratory and/or Skin Sensitization**

Not known to be a respiratory sensitizer.

#### **Carcinogenicity**

Chemical Name	IARC	ACGIH®	NTP	OSHA
n-Butyl acetate	Not evaluated			
Hexamethylene diisocyanate based isocyanurates	Not evaluated	Not Listed	Not Listed	
Xylene (mixed isomers)	Group 3			

#### **Reproductive Toxicity**

##### **Development of Offspring**

No information was located.

##### **Sexual Function and Fertility**

No information was located.

##### **Effects on or via Lactation**

No information was located.

## **SECTION 12. ECOLOGICAL INFORMATION**

(Xylene (mixed isomers)) (Ethyl benzene). (Light aromatic solvent naphtha). (n-Butyl acetate).

#### **Persistence and Degradability**

Does not degrade rapidly based on quantitative tests.

#### **Bioaccumulative Potential**

This product and its degradation products are not known to bioaccumulate.

#### **Mobility in Soil**

If released into the environment, this product can move rapidly through the soil.

#### **Other Adverse Effects**

This product contains volatile organic compounds.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal Methods**

Recycle and reuse product, if possible. Contact local environmental authorities for approved disposal or recycling methods in your jurisdiction. Dispose of or recycle empty containers through an approved waste management facility.

## SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
US DOT	1263	CATALYST FOR GENULINE 3900 Series Flexible Game Line Paint System	3	II

**Special Precautions** Not applicable

**Transport in Bulk according to International Maritime Organization Instruments**

Not applicable

## SECTION 15. REGULATORY INFORMATION

**Safety, Health and Environmental Regulations**

**Canada**

**Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)**

Listed on the DSL.

**CEPA - National Pollutant Release Inventory (NPRI)**

Part 1A.

**USA**

**Toxic Substances Control Act (TSCA) Section 8(b)**

All ingredients are listed on the TSCA Inventory.

## SECTION 16. OTHER INFORMATION

**Date of Preparation** décembre 13, 2023

**Key to Abbreviations** ACGIH® = American Conference of Governmental Industrial Hygienists  
AIHA® = AIHA® Guideline Foundation HSDB® = Hazardous Substances Data Bank  
IARC = International Agency for Research on Cancer  
NFPA = National Fire Protection Association NIOSH = National Institute for Occupational Safety and Health  
NTP = National Toxicology Program  
OSHA = US Occupational Safety and Health Administration  
RTECS® = Registry of Toxic Effects of Chemical Substances

Product Identifier: CATALYST FOR GENULINE 3900 Series Flexible Game Line Paint

SDS No.: 0109

Date of Preparation: décembre 13, 2023

Date of Last Revision:

Page 06 of 06