

RT135

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ Compact Dimensions
- ✓ Pilot Joystick Controls
- ✓ IdealTrax™ Automatic Track Tensioning
- ✓ All-Tach Attachment System (Universal Type)
- ✓ ROPS/FOPS Level II

KEY SPECIFICATIONS

- ✓ 1,350 lbs. (612 kg) Rated Operating Capacity (35%)
- ✓ 46.6 hp (34.3 kW) Yanmar Engine / Tier IV
- ✓ 110" (2794 mm) Height to Hinge Pin
- ✓ 57" (1448 mm) Overall Machine Width
- ✓ 76" (1930 mm) Overall Height

IMPERIAL

		IMPERIAL
CAPACITIES	Operating Weight	6510 lb
	Operating Capacity at 35% Tipping Load	1350 lb
	Operating Capacity At 50% Tipping Load	1929 lb
	Tipping capacity	3858 lb
WEIGHT AND DIMENSIONS	Overall Operating Height - Fully Raised	144 in
	Height to Hinge Pin - Fully Raised	110 in
	Dump angle at full height	40 °
	Overall Height to top of ROPS	76 in
	Overall length with bucket	121 in
	Overall Length without Bucket	93 in
	Specified Height	59 in
	Reach at Specified Height	30 in
	Dump angle at specified height	75 °
	Carry Position	6 in
	Maximum Rollback Angle at Carry Position	28 °
	Digging Position	0.71 in
	Angle of Departure with STD Counterweight	28 °
	Ground clearance	8 in
	Track gauge	45 in
	Track Shoe Width	12 in
	Crawler base	46 in
	Overall width less bucket	57 in
	Bucket Width	60 in
	Clearance Radius - Front with Bucket	76 in
	Track Type / Track Rollers / Roller Type	Rubber / 4 / Steel
PERFORMANCES	Ground Speed - Single Speed	6 mph
	Drawbar Pull/Ttractive Effort	7161 lb
	Bucket Breakout - Tilt Cylinder	3501 lb
	Bucket Breakout - Lift Cylinder	3730 lb
ENGINE	Engine brand	Yanmar
	Engine model	4TNV88
	Motor Type	Radial Piston
	Engine power (Hp)	46.60 Hp
	Engine power (kW)	33.20 kW
	Battery voltage	12 V
	Cold Cranking Amps at Temperature (CCA)	800 A
	Alternator - Voltage / Ampere	12 V / 100 A
HYDRAULICS	Standard flow - Auxiliary hydraulics	17 US gpm
	Oil Pan Capacity	2 US gal
TANK CAPACITIES	Hydraulic tank capacity	9 US gal
	Fuel	16 US gal
	Number of cylinders	4

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.


STAN

- Operator Restraint Bar
- All-Tach® Attachment Mounting System
- Hydraloc™ Safety System
- High-Back Adjustable Seat
- Swing-Out Cooler
- Auxiliary Hydraulics
- Hour meter
- Anti-Vandalism Protection
- Hand/Foot Controls
- Lift Arm Support Device
- ROPS/FOPS Level II Overhead Guard
- Back-Up Alarm
- Horn

OPTIONAL FEATURES

- Selectable Self-Leveling Hydraulic Lift Action
- Sound reduction Package
- Counterweight
- Rear camera with screen in cab
- Power-A-Tach® Attachment Mounting System
- Cab Enclosure
- Suspension Seat - Air Ride
- Engine Block Heater
- Cabin with Heat and Air Conditioning
- Back-Up Alarm
- Suspension Seat - Mechanical
- Strobe Light
- Bluetooth car radio



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT