



## B155 Specifications



<b>WEIGHTS</b>	
Shipping Weight	2700 lbs
Operating Weight (Full Ballast + Operator)	32100 lbs
<b>DIMENSIONS</b>	
Overall Length	77 in
Overall Height	62 in
Overall Width	40 in
Wheelbase	52.75 in
Curb Clearance	9.50 in
Wall Clearance	.875 in
<b>CAPACITIES</b>	
Fuel	3 gal
Hydraulic Fluid	4 qts
Engine Oil	1.6 pts
Water Tank	34 gal
<b>DRUMS</b>	
<i><b>FRONT</b></i>	
Overall Width	30 in
Diameter	20 in
Shell Thickness	.437 in
<i><b>REAR</b></i>	
Overall Width	37 in
Diameter	24 in
Shell Thickness	.500 in
<b>STEERING</b>	
Type	Hydraulic, Cylinder, Front Drum
Turning Radius	56 in
Oscillation	24 degree ttl
<b>DRIVE</b>	
Drive System	Hydrostatic, Internal Direct Drive, Rear Drum, Single Lever, Infinitely Variable Controls.
Travel Speed	0 - 6 mph
Engine	Kohler 18 HP OHC V-Twin Cylinder, Air Cooled, Electric Start, 12 Volt Battery.



## B155 Specifications

<b>VIBRATION SYSTEM – Rear Drum</b>	
Type	Hydraulic Direct Drive (Vibe Shaft and Motor in Drum).
Control	On-Off Switch on Control Lever
Frequency	2500 VPM
Centrifugal Force	4500 lbs. at 2500 VPM.
Total Applied Force	6550 lbs
<b>BRAKES</b>	
Service	Hydrostatic drive provides dynamic braking.
Secondary Parking	Failsafe, Spring applied Hydraulically released, manual switch on console.



## B155 Specifications

<b>DRUM SPRAY SYSTEM</b>	
Type	Pressurized water w/quick disconnect spray nozzles.
Tank	Polyethylene, 34 gal. capacity, 3" fill neck, cap w/safety chain, rear mount.
Drum Scrapers	Four adjustable, neoprene rubber.
Cocoa Mat	One each drum, pivoting.
<b>STANDARD EQUIPMENT</b>	
Instrumentation	Fuel Gauge, Hour meter, Voltmeter, Low Engine Oil Indicator Light.
Seat	High Back, Bucket Type, Adjustable.
Safety	Neutral Start Switch, Failsafe Hydraulic Brake.
Vandal Protection	Lockable fill caps for fuel and hydraulic fluid.