



# B200 Specifications



<b>WEIGHTS</b>	
Shipping Weight	2500 lbs
Operating Weight (Full Ballast + Operator)	4150 lbs
<b>DIMENSIONS</b>	
Overall Length	97 in.
Overall Height	65 in.
Overall Width	44 in.
Wheelbase	66.5 in.
Curb Clearance	11 in.
Wall Clearance	.875 in.
<b>CAPACITIES</b>	
Fuel	5 gal
Hydraulic Fluid	4 gal
Engine Oil	4 pts.
Water Tank	50 gal
<b>DRUMS</b>	
<b><i>FRONT</i></b>	
Type	Steel, Machined surface w/ ballast fill plug
Overall Width	30 in.
Diameter	24 in.
Shell Thickness	.500 in.
<b><i>REAR</i></b>	
Type	Steel, Machined surface w/ ballast fill plug
Overall Width	41 in.
Diameter	28 in.
Shell Thickness	.500 in.
<b>STEERING</b>	
Type	Automotive type, mechanical
Turning Radius	72 in.
Oscillation	24 degree ttl
<b>DRIVE</b>	
Drive System	Hydrostatic
Travel Speed	0-5 mph
Engine	Kohler 18 HP OHV Twin Cylinder, Electric Start, 12 Volt Battery
<b>BRAKES</b>	
Service	Hydrostatic drive provides dynamic braking
Secondary Parking	Mechanical band type parking brake on rear drum, adjustable brake lever.



# B200 Specifications

<b>DRUM SPRAY SYSTEM</b>	
Type	Gravity w/dual brass ball valves.
Tank	Polyethylene, 50 gal. capacity, 3" fill neck, cap w/safety chain, rear mount.
Drum Scrapers	Four adjustable, neoprene rubber.
Cocoa Mat	One each drum, pivoting
<b>STANDARD EQUIPMENT</b>	
Instrumentation	Hourmeter, Voltmeter, Low Engine Oil Indicator Light.
Seat	High Back, Bucket Type, Adjustable
Safety	Neutral Start Switch.
Transition By-Pass	Control within pump to "Freewheel unit".
Vandal Protection	Lockable fill caps for fuel and hydraulic fluid.
Tie Downs	6 for transporting