



### PURPOSE:

- Grade and rake soil and remove debris all with one attachment
- Heavy weeds, undergrowth, brush and small saplings up to 4" (102 mm) in diameter are easily cut down
- Prepare soil from rough grade to seed-ready in minutes rather than hours

### FEATURES:

- Direct drive motor with relief valve protection
- Carbide tip teeth for longer life in various soil conditions
- Motor is guarded against debris while allowing easy access for maintenance
- Manual angle provides a 25 degree angle in either direction
- Solid filled tires to eliminate costly interruptions from flats
- Comes complete with mount, hoses and flat faced couplers



### SPECIFICATION

Model	Weight (lbs/kg)	Hyd. Req. (gpm/lpm)	No. of Teeth	Angle (degrees)	Angled Path (in/mm)
PR72	1335 / 606	15-25 / 57-95	109	25	65 / 1659
PR90	1440 / 653	15-25 / 57-95	139	25	82 / 2070

### MACHINE COMPATIBILITY\*:

	Radial Skid Loaders							Vertical Skid Loaders			Track Loaders						Articulated Loaders		
	R105/ 1050R/ 1050 R	R135/ 1350R/ 1350 R	R150/ 1500R/ 1500 R	R165/ 1650R/ 1650 R	R190/ 1900R/ 1900 R	R220/ 2200R/ 2200 R	R260/ 2600R/ 2600 R	V270/ 2700V/ 2700 V	V330/ 3300V/ 3000 V	V420/ 4200V/ 4200 V	RT105/ 1050RT/ 1050 RT	RT135/ 1350RT/ 1350 RT	RT165/ 1650RT/ 1650 RT	RT185/ 1850RT/ 1850 RT	RT215/ 2150RT/ 2150 RT	RT255/ 2550RT/ 2550 RT	VT320/ 3200VT/ 3200 VT	650/ 608	750/ 708
PR72			x	x	x	x	x	x	x		x	x	x	x	x	x	x	x	x
PR90					x	x	x	x	x			x	x	x	x	x	x	x	x

\*Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment