

RT135

TRACK LOADER

GEHL®



KEY FEATURES

- ✓ Compact Dimensions
- ✓ Pilot Joystick Controls
- ✓ IdealTrax™ Automatic Track Tensioning
- ✓ All-Tach Attachment System (Universal Type)
- ✓ ROPS/FOPS Level II

KEY SPECIFICATIONS

- ✓ 1,350 lbs. (612 kg) Rated Operating Capacity (35%)
- ✓ 46.6 hp (34.3 kW) Yanmar Engine
- ✓ 110" (2794 mm) Height to Hinge Pin
- ✓ 57" (1448 mm) Overall Machine Width
- ✓ 76" (1930 mm) Overall Height

RT135 TRACK LOADER

SPECIFICATIONS

	IMPERIAL	METRIC	
DIMENSIONS	Overall Operating Height - Fully Raised	144.5"	3670 mm
	Height to Hinge Pin - Fully Raised	110"	2794 mm
	Dump Reach at Full Height	23.3"	592 mm
	Dump Angle at Full Height	40°	
	Dump Height - Fully Raised	83.6"	2123 mm
	Rollback Angle at Full Height	98°	
	Overall Height to Top of ROPS	76"	1930 mm
	Overall Length with Bucket (w/o Counterweight)	121.1"	3076 mm
	Overall Length without Bucket (w/o Counterweight)	92.9"	2360 mm
	Specified Height	58.8"	1494 mm
	Reach at Specified Height	20.3"	771 mm
	Dump Angle at Specified Height	75°	
	Maximum Rollback Angle at Ground	28°	
	Carry Position	6.5"	165 mm
	Maximum Rollback Angle at Carry Position	28°	
	Digging Position – Above Ground	+0.7"	18 mm
	Angle of Departure (w/o Counterweight)	28°	
	Ground Clearance to Chassis	8.4"	213 mm
	Crawler Base	46"	1168 mm
	Overall Width – Less Bucket - Narrow	57"	1448 mm
Bucket Width	60"	1524 mm	
Clearance Radius – Front with Bucket	75.5"	1918 mm	
Clearance Radius – Front without Bucket	46.1"	1171 mm	
Clearance Radius – Rear (w/o Counterweight)	56.7"	1440 mm	
CAPACITY	Operating Capacity at 35% Tipping Load	1,350 lbs.	612 kg
	Operating Capacity at 50% Tipping Load	1,929 lbs.	875 kg
	Tipping Load	3,857 lbs.	1,750 kg
	Operating Weight	6,510 lbs.	2953 kg
ENGINE	Make/Model	Yanmar/4TNV88C-KMS Tier IV	
	Type	4-Stroke Naturally Aspirated	
	Displacement/Cylinders	133.6 cu.in. / 4	2.2L / 4
	Gross Power @ 2500 rpm	46.6 hp	34.3 kW
	Oil Pump Capacity	6.8 qts.	6.4L
	Alternator Voltage / Amperage	12V / 100A	
TRACK DRIVES	Drawbar Pull/Tractive Effort	7,160 lbs.	3,248 kg
	Track Type / Track Rollers / Roller Type	Rubber/4/Steel	
	Track Gauge	45.2"	1148 mm
	Track Width	11.8"	300 mm
	Ground Pressure	6 psi	.41 bar
FORCES	Bucket Breakout – Tilt Cylinder	3,500 lbs.	1,588 kg
	Bucket Breakout – Lift Cylinder	3,730 lbs.	1692 kg
	Ground Speed – Single Speed	6.2 mph	10 km/h
VOLUME	Fuel Tank	15.7 gal.	59.4 L
	Hydraulic Reservoir Tank	9.2 gal.	34.8 L
	Coolant Capacity	2.1 gal.	7.9 L
HYDRAULICS	Auxiliary Hydraulic Flow – Rated Speed	16.8 gpm	63.6 L/min
	Hydrostatic Pump Transmission: Hydrostatic pumps with integral charge pumps - Direct drive off engine flywheel		
	Motor Type	Radial Piston	
BATTERY	Battery Volts	12 V	
	Cold Cranking Amps at @ 0° F	800 CCA @ 0° F (-18° C)	



STANDARD FEATURES

- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hourmeter
- Operator Restraint Bar with Armrests
- Induction hardened chrome plated cylinders
- ROPS/FOPS Level II Overhead Guard
- Top and Rear Windows
- High-Back Adjustable Seats
- Foot and Hand Throttles
- Hydraloc™ Safety System
- Audible Back-Up Alarm
- Lift Arm Support Device
- Operator Restraint Bar
- Horn



OPTIONAL FEATURES

- Air Conditioning
- Back-Up Alarm
- Cab Enclosure
- Bluetooth Radio
- Counterweight
- Engine Block Heater
- Heating
- Back-up Camera
- Strobe Light
- Power-A-Tach® Attachment Mounting System
- Selectable Self-Leveling Hydraulic Lift Action
- Suspension Seat - Air Ride
- Suspension Seat - Mechanical
- Sound Suppression Package

Gehl reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Gehl reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

One Gehl Way, West Bend, WI 53095

Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT



gehl.com