

The **UltraLift** represents the culmination of more than 50 years of design and manufacturing. Our unparalleled experience and professional engineering, combined with premium materials, allow us to proudly offer our “Flagship” **UltraLift**, the envy of the industry.

A UL unique feature is the patented **UltraGrip**<sup>™</sup> tank connection, which enables the **UltraLift** to be installed with all steel parts above the water.\* This innovation protects your boat life against rust and marine growth for years of convenient and carefree storage.

### UltraLift<sup>™</sup> Series 4,400-8,800



#### TECHNICAL SPECS

UL Series Specifications	Lifting Capacity	Min. Water Depth	Tanks	Tank Size	Min. Slip Width	Max. Slip Width
<b>4400 UL</b>	4,400 lbs	4 ft.	2	24" x 32" x 13'6"	8 ft.	18 ft.
<b>6600 UL</b>	6,600 lbs	5 ft.	2	32" x 32" x 13'6"	8 ft.	18 ft.
<b>6600 3T UL</b>	6,600 lbs	4 ft.	3	24" x 32" x 13'6"	10 ft.	18 ft.
<b>8800 UL</b>	8,800 lbs	5 ft.	2	32" x 32" x 17'6"	8 ft.	18 ft.

#### STANDARD FEATURES

- Custom-molded, high-impact polyethylene tanks
- All steel parts above the water\*
- Hot-dipped, zinc-galvanized structural steel frame/fasteners
- Heavy-duty 1/4" thick torsion bars and hull support system
- HydroGuard<sup>™</sup> to protect your boat in the dock
- Grade-8 pivot hardware
- All cast parts are (HSLA) High-Strength Low Alloy steel making them 40 percent stronger than fabricated steel

*\*Exceptions may be necessary for proper installation.*

#### RECOMMENDED FOR:


- Boats up to 8,800 lbs and up to 28' overall length
- Drive-in or back-in installations
- Floating docks with U-shaped slips
- Sailboat option



4400 UL



6600 UL



6600-3 Tank-UL



8800 UL

