



Eniac Energy LLC

BORN FOR GREEN ENERGY SOLUTIONS

info@uscharger.com  
www.USCarger.com  
West Palm Beach, FL, USA Phone: 561-693-7511

EVCP5

Level 2

Up to 2\*80A



## ONE CHARGER, TWO OUTPUT



### POWERFUL

Up to 2\*80A of charging capacity.



### FLEXIBLE

Cable management allows access from either side of the vehicle.



### DURABILITY

Type 3 and IK08 protection ratings, allowing for indoors or outdoors.



### INTERACTION

Visual 7" LCD screen with user friendly interface.



### CONNECTED

Complete with LAN connectivity (Wi-Fi or 4G optional), ensuring chargers are always online.



### OCPP

OCPP 1.6J help you connect EV charger to the cloud.



EVCP5 | Level 2 | Up to 2\*48A



Fast-charging 2 EVs simultaneously and charge up to 75-miles within an hour

7" touch screen make driver easy to use

Ideal for fleet deployment

TAILORED FOR  
FLEET CHARGING  
DEPLOYMENT

Model No.	EVCP5
Voltage	208-240Vac
Amperage/Power	80A+80A/19.2KW+19.2KW
AC Power Frequency	50-60Hz
Display	7" touch LCD
User Authentication	RFID ISO14443
Connectivity	LAN standard, 4G or Wi-Fi optional OCPP1.6J / Upgradable to OCPP2.0.1
Operating Temperature	-22°F to 122°F
IP Level	Type3
IK Rating	IK08
Cable Length	18ft
Net Weight	169lbs
Gross Weight	178.6lbs
Product Dimensions	81.6" x 22.7" x 11.2"
Package Dimensions	Top: 28.6" x 26.0" x 11.1" / Bottom: 64.2" x 21.0" x 15.3

# DATASHEET

Model No.	JNT-EVCP5
Input Voltage	208-240Vac
Frequency	50-60Hz
Amperage	2 x 80A
Max. Power Output	19.2kW+19.2kW

## Protection & Standard

Charging Interface	SAE J1772 Compliant, Type 1 Plug
Safety Compliance	UL2594, UL2231-1/-2
Multiple Protection	UVP, OVP, RCD (CCID 20), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection

## Environmental

Operating Temp.	-22°F to 122°F
Relative Humidity	Up to 95% non-condensing
Cable Length	18ft Standard