

Eniac Energy, LLC

USCharger.com



Eniac Energy, LLC.

BORN FOR GREEN ENERGY SOLUTIONS

info@uscharger.com
 www.uscharger.com
 1200 S. Flagler Dr. Suite 106, West Palm Beach, FL 33401 USA

EVCD1

Level 2

Up to 96A




ONE CHARGER, TWO OUTPUT

 POWERFUL Adjust power as needed, the maximum can be 48A+48A/11.5kW+11.5kW.	 SAFER Ground fault detection, protecting people from shock.	 CONVENIENT Automatic fault detection and repair, easier for maintenance.
 CONNECTED Complete with LAN or Wi-Fi connectivity (4G optional), ensuring chargers are always online.	 OCPP OCPP 1.6J help you connect EV charger to the cloud.	 DURABILITY IP65 and IK08 protection ratings, allowing for indoors or outdoors





- Tailored for commercial deployment
- Wall-mounted and integration design for easy installation
- Reduce the investment of power capacity to enjoy fast ROI

Model No.	EVCD1/64AC	
Voltage	208-240Vac	
Amperage/Power	32A+32A/7.6KW+7.6KW	48A+48A/11.5KW+11.5KW
AC Power Frequency	50-60Hz	
Display	4.3" LCD	
User Authentication	RFID (ISO14443)	
Connectivity	LAN+WiFi, standard, 4G optional OCPP1.6J / Upgradable to OCPP2.0.1	
Operating Temperature	-22°F to 122°F	
IP Level	Type3	
IK Rating	IK08	
Cable Length	18ft (25ft optional)	
Net Weight	30.09lbs	
Gross Weight	33.29lbs	
Product Dimensions	18.46" x 16.7" x 6.3"	
Package Dimensions	22" x 18.46" x 13.39"	

PAGE/14

DATASHEET

Model No.	JNT-EVCD1/96AC
Input Voltage	208-240Vac
Frequency	50-60Hz
Amperage	48A+48A
Max. Power Output	11.5kW+11.5kW
Product Dimensions	18.5" x 13.4" x 4.4"

Protection & Standard

Charging Interface	SAE J1772 Compliant, Type 1 Plug
Safety Compliance	UL2594, UL2231-1/-2
Multiple Protection	UVP, OVP, RCD (CCID 20), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection

Environmental

Operating Temp.	-22°F to 122°F
Relative Humidity	Up to 95% non-condensing
Cable Length	25ft Standard