



LINE-INTERACTIVE UPS

LT3-3000

KEY FEATURES

- Automatic Voltage Regulation (AVR)
- Single Boost Design/ Double Boost optional
- Auto-Restart/Auto-Charge
- LED/LCD Optional
- Generator Compatible
- Cold Start Function
- Off-Mode Charging
- Optional USB/RS232 Communication Port & RJ-11/RJ-45 Protection
- Metal Case

SPECIFICATION

Model Name	LT3-3000
Capacity	3000VA/1800W
Input	
Nominal Voltage	220-240Vac
Voltage Range	162-290Vac(Single boost) 140-300Vac(Double boost)
Frequency	50Hz/60Hz (Auto Sensing)
Output	
Nominal Voltage(Batt.mode)	220-240V
Frequency(Batt.mode)	50Hz/60Hz ±1%
Waveform (Batt.mode)	Simulated Sine Wave
Transfer Time	4ms typical
Overload Protection	Circuit breaker or inner firmware protection
Battery	
Battery Voltage	24V
Battery Type	12V/7Ah
Total Battery Quantity	4
Recharge Time(to 90%)	8H
Indicators	
Display	LED/LCD Optional
Alarm	Batt. Mode, low battery, overload, fault, etc.
Interface	
RS232	Optional
USB port	Optional
RJ45/RJ11	Optional
Management	
Auto Recharge	Yes
Auto Restart	Yes
Power Management Software	Yes
Physical	
Dimension(W x H x D)(mm)	151 x 225 x 394
Net Weight (kg)	18
Environment	
Operating Humidity	0-90% non-condensing
Operating Temperature	0-40°C