



BOTH TYPES OF GRADE RINGS
ARE AVAILABLE IN:
2" (50mm)
3" (75mm)
4" (100mm)
THICKNESSES



GENERAL NOTES

Precast concrete shall be exposure Class S and meet min compressive strength of 35MPA

Cement: Type GU
Air Category: 4.0% - 7.0%
Aggregate: CSA/CAN A23.4 Maximum
Size: 20mm
Admixtures: CSA/CAN A23.4
Reinforcing: Grade 400W CSA
G30.18-09
Inserts/Embeds: As noted in drawing
details

Manufacture of precast concrete units
shall be in accordance with specification
CSA A23.4

** LEKO PRECAST LTD SHALL NOT BE
RESPONSIBLE FOR ANY INSTALLATION
PRACTICES FOLLOWED ON-SITE UNLESS
PERFORMED BY LEKO PRECAST LTD **



CATCH BASIN GRADE RINGS

| | | | | |
|--|---------------|--------------------------|---------------------|-------------------|
| DRAWN BY: JA | CHECKED BY: | APPROVED BY: | DATE: April 2016 | |
| ASSEMBLY DWG. | PREVIOUS DWG. | DRAWING NO. R0300 | | REVISION 2 |
| SCALE: 1:20 ISOMETRIC: 1:20 | | | | |
| DO NOT SCALE THIS DRAWING | | | | |