



OPTIONAL FOOT

**GENERAL NOTES**  
 Precast concrete shall be exposure Class S and meet min compressive strength of 35MPa

Cement: Type GU  
 Air Category: 4.0% - 7.0%  
 Aggregate: CSA/CAN A23.4 Maximum Size: 20mm  
 Admixtures: CSA/CAN A23.4  
 Reinforcing: Grade 400W CSA G30.18-09  
 Inserts/Embeds: As noted in drawing details

Manufacture of precast concrete units shall be in accordance with specification CSA A23.4

**\*\* LEKO PRECAST LTD SHALL NOT BE RESPONSIBLE FOR ANY INSTALLATION PRACTICES FOLLOWED ON-SITE UNLESS PERFORMED BY LEKO PRECAST LTD \*\***

5,250Kg (11,500 LBS)  
 540Kg (1,200lbs) OPTIONAL FOOT



HEADWALL C/W OPENING UP TO 1400mm

DRAWN BY: JA	CHECKED BY:	APPROVED BY:	DATE: October 2020
ASSEMBLY DWG.	PREVIOUS DWG.	DRAWING NO. I1223	REVISION 4
SCALE: 1:50 ISOMETRIC: N/A			
DO NOT SCALE THIS DRAWING			