



GENERAL NOTES

Precast concrete shall be exposure Class HSe and meet min compressive strength of 30MPa @28d

Air Category: 4.0% - 7.0% (except where zero-slump concrete is used)

Aggregate: CSA/CAN A23.4 Maximum Size: 20mm

Admixtures: CSA/CAN A23.4

Reinforcing: Grade 400W CSA G30.18, 3x12 W2.5/W2.5

Inserts/Embeds: As noted in drawing details

Manufacture of precast concrete units shall be in accordance with specification CSA A23.4

** LEKO PRECAST LTD SHALL NOT BE RESPONSIBLE FOR ANY INSTALLATION PRACTICES FOLLOWED ON-SITE UNLESS PERFORMED BY LEKO PRECAST LTD **

1,925Kg (4,235 LBS)



MOTI Type 'C' Light Base

| | | | |
|---------------------------|-----------------|----------------------|---------------------|
| DRAWN BY: JA | CHECKED BY: | APPROVED BY: | DATE: April 2016 |
| ASSEMBLY DWG. | PREVIOUS DWG. | DRAWING NO. L1006 | REVISION 1 |
| SCALE: 1:20 | ISOMETRIC: 1:20 | | |
| DO NOT SCALE THIS DRAWING | | | |