



**GENERAL NOTES**

Precast manhole units shall be manufactured in accordance with CSA A257 and ASTM C478

Precast concrete shall be exposure Class HSe and meet min compressive strength of 30MPa @28d

Air Category: 4.0% – 7.0% (except where zero-slump concrete is used)

Aggregate: CSA/CAN A23.4 Maximum Size: 20mm

Admixtures: CSA/CAN A23.4

Reinforcing: Grade 400W CSA G30.18, 3x12 W2.5/W2.5

Inserts/Embeds: As noted in drawing details

Manufacture of precast concrete units shall be in accordance with specification CSA A23.4

**\*\* LEKO PRECAST LTD SHALL NOT BE RESPONSIBLE FOR ANY INSTALLATION PRACTICES FOLLOWED ON-SITE UNLESS PERFORMED BY LEKO PRECAST LTD \*\***

Meets H-20 loading

Requires 2-4t Starcon lift clutches

940Kg (2,065 LBS)

**48" x 3ft (1220mm x 915mm) DRYWELL MANHOLE BARREL**

DRAWN BY: JA		CHECKED BY:		APPROVED BY:		DATE: JANUARY 2023	
ASSEMBLY DWG.		PREVIOUS DWG.		DRAWING NO. M48100			REVISION 4
SCALE: 1:20		ISOMETRIC: 1:20					
DO NOT SCALE THIS DRAWING							

