



**GENERAL NOTES**

Precast concrete shall be exposure Class HSe and meet min compressive strength of 30MPa @28d

Air Category: 4.0% - 7.0% (except where zero-slump concrete is used)

Aggregate: CSA/CAN A23.4 Maximum Size: 20mm

Admixtures: CSA/CAN A23.4

Reinforcing: Grade 400W CSA G30.18, 3x12 W2.5/W2.5

Inserts/Embeds: As noted in drawing details

Manufacture of precast concrete units shall be in accordance with specification CSA A23.4

\*\* LEKO PRECAST LTD SHALL NOT BE RESPONSIBLE FOR ANY INSTALLATION PRACTICES FOLLOWED ON-SITE UNLESS PERFORMED BY LEKO PRECAST LTD \*\*

220Kg (485 LBS)



**HYDRO KIOSK BOLLARD**

|                           |                 |                 |                        |
|---------------------------|-----------------|-----------------|------------------------|
| DRAWN BY:<br>JA           | CHECKED BY:     | APPROVED BY:    | DATE:<br>FEBRUARY 2021 |
| ASSEMBLY DWG.             | PREVIOUS DWG.   | DRAWING NO.     | REVISION               |
| SCALE: 1:20               | ISOMETRIC: 1:20 | HYDRO BOLLARD 0 |                        |
| DO NOT SCALE THIS DRAWING |                 |                 |                        |