



3600



3600+

<p><b>1200A DC &amp; 1000A AC TRMS</b>  <b>3 1/2 Digit, 4000 Counts, 40 Segment Bargraph, Auto / Manual, PEAK HOLD, MAX / MIN, Δ ZERO, DATA HOLD, APO</b></p>	<p><b>1200A DC / 1000A AC TRMS</b>  <b>3 1/2 Digit, 4200 Counts, Auto Ranging, Frequency, Duty Cycle, MAX / MIN, Δ REL, DATA HOLD, APO</b></p>	<p>Accuracy ±(1.5%rdg + 5dgt) on 400Ω  ±(1.5%rdg + 3dgt) on 4kΩ~400kΩ  ±(2.0%rdg + 5dgt) on 4MΩ, 40MΩ</p>
<p><b>Ranges</b> <sup>TRMS</sup>  <b>AC Current</b> 400A, 1000A  Accuracy ±(1.75%rdg + 5dgt) (50~60Hz) upto 700A  (2.5%rdg + 5dgt) (50~60Hz) (700A~1000A)  ±(3.5%rdg + 5dgt) (40~500Hz)</p>	<p><b>Ranges</b> <sup>TRMS</sup>  <b>AC Current</b> 400A, 1000A  Accuracy ±(3.0%rdg + 8dgt) 50~60Hz  ±(3.5%rdg + 8dgt) 40Hz~1KHz</p>	<p><b>Capacitance</b> 4nF, 40nF, 400nF, 4μF, 40μF (Auto)  Accuracy ±(3%rdg + 10dgt) on all ranges except  ±(4%rdg + 40dgt) on 4nF  ±(4%rdg + 10dgt) on 40nF  Note : on 4nF (Use Δ REL)</p>
<p><b>Overload</b> <sup>TRMS</sup>  <b>AC Voltages</b> 400mV, 4V, 40V, 400V, 600V (Auto &amp; Manual)  Accuracy ±(0.75%rdg + 4dgt) (50~60Hz)  ±(2%rdg + 4dgt) (40~500Hz)  Note : 400mV AC for Reference only</p>	<p><b>Overload</b> 1200A DC/AC RMS max. 1 min.  <b>AC Voltages</b> 4V, 40V, 400V, 750V (Auto)  Accuracy ±(1.5%rdg + 5dgt) 50~60Hz  ±(2.0%rdg + 8dgt) 40Hz~1KHz</p>	<p><b>Frequency</b> 9.999, 99.99, 999.9Hz, 9.999, 99.99, 999.9KHz, 9.999MHz (Auto)  Accuracy ±(0.5%rdg + 4dgt)</p>
<p><b>DC Current</b> 400A, 1200A  Accuracy ±(1.5%rdg + 5dgt) (upto 700A)  ±(2%rdg + 5dgt) (700~1200A)</p>	<p><b>DC Current</b> 400A, 1200A  Accuracy ±(3.0%rdg+8dgt)  <b>Overload</b> 1200A DC/AC RMS max. 1 min.  <b>DC Voltage</b> 400mV, 4V, 40V, 400V, 1000V (Auto)  Accuracy ±(0.8%rdg + 5dgt)</p>	<p><b>Duty Cycle</b> 10~90%  Accuracy ±(0.5%rdg + 4dgt)</p>
<p><b>DC Voltage</b> 400mV, 4V, 40V, 400V, 600V (Auto &amp; Manual)  Accuracy ±(0.25%rdg + 4dgt)</p>	<p><b>DC Voltage</b> 400mV, 4V, 40V, 400V, 1000V (Auto)  Accuracy ±(0.8%rdg + 5dgt)</p>	<p><b>Temperature</b> -20°C ~ 750°C / -4°F ~ 1400°F  Accuracy ±(1.0%rdg + 5dgt) on -20°C ~ 400°C / -4°F ~ 650°F  +(1.5%rdg + 5dgt) on 401°C ~ 750°C / 651°F ~ 1400°F</p>
<p><b>Resistance</b> 400Ω, 4kΩ, 40kΩ, 400kΩ, 4MΩ, 40MΩ (Auto &amp; Manual)  Accuracy ±(0.3%rdg + 5dgt) on 400Ω  ±(0.3%rdg + 4dgt) on 4kΩ~400kΩ  ±(0.5%rdg + 4dgt) on 4MΩ  ±(2.0%rdg + 4dgt) on 40MΩ</p>	<p>Accuracy ±(0.1%rdg + 2dgt)  <b>Sp. Function</b> Audible Continuity, Diode Test function  One 9V Battery  <b>Battery Life</b> 150 hours (typical)  <b>Low Battery Protection</b> '⚡' is indicated.  600VDC or AC rms overload protection in DCV, ACV, Diode, Ohms, Hz, Continuity.</p>	<p><b>Sp. Function</b> Audible Continuity, Diode Test  <b>Power</b> Two 1.5V "AAA" Battery  <b>Battery Life</b> 150 hours (typical)  <b>Low Battery Protection</b> '⚡' is indicated.  600VDC or AC RMS overload protection in Capacitance, Diode, Ohms, Hz, Duty Cycle, Continuity, Temperature</p>
<p><b>Capacitance</b> 4nF, 40nF, 400nF, 4μF, 40μF (Auto &amp; Manual)  Accuracy ±(3%rdg + 20dgt) on 4nF (Use Δ ZERO)  ±(3%rdg + 4dgt) on 40nF to 20μF  ±(6%rdg + 4dgt) above 20μF</p>	<p><b>Dimension Weight</b> 250 x 100 x 46 mm (approx.)  386 gms Including Battery (approx.)  <b>Jaw Opening</b> Cable Dia 55mm max.</p>	<p><b>Dimensions Weight</b> 250 x 100 x 46 mm (approx.)  386 gms Including Battery (approx.)  <b>Jaw Opening</b> Cable Dia 55mm max.</p>
<p><b>Frequency</b> 4kHz, 40kHz</p>	<p><b>Accessories</b> One Pair of Test Leads, Carrying Case, Battery (installed) &amp; Inst. Manual</p>	<p><b>Accessories</b> One Pair of Test Leads, Carrying Case, Battery (installed), K Type Thermocouple (upto 260°C) &amp; Inst. Manual</p>