




KEW India Product Category	Product Category	Product Image	HS Code	Model Number	Short Description	KKIPL LP (in INR)	MRP (in INR)	Standard Certificate
L	Digital Multimeters		9030 3100	1018H	Digital Multimeter: <ul style="list-style-type: none"> Display : 4000 counts. Auto range. Diode test feature. Capacitance test feature. Continuity test. Inc. Accessories: LR44x 2, Instruction Manual, Hard Case 	3412	4162	Certificate of Conformity
L			9030 3100	1019R	Digital Multimeter: <ul style="list-style-type: none"> Elegant shiny-black finish Comes with user-friendly Hard case Large Display Accurate reading with True-RMS technology Electronic protection (no fuse!) on ohm and continuity ranges Safety Standard IEC 61010-1 / 61010-031 / 61010-2-033 CAT III 300V / CAT II 600V Inc. Accessories: 9188 (Hard case), CR2032 x 1, Instruction manual 	8044	9809	Certificate of Conformity
L			9030 3100	1009	Digital Multimeter: <ul style="list-style-type: none"> Display : 4000 counts. Auto range and manual range selector provided. (with range hold feature) Resistance range provides audible continuity test. Automatically turns power off in about 30 minutes to conserve battery life. Direct current measurement up to 10A AC and DC. With Holster. Inc. Accessories: 7066A (Test leads), 8919 (Ceramic fuse [10A/600V])x 1, 8923 (Fuse [0.5A/600V])x 1, R6x 2, Instruction Manual 	5850	7134	Certificate of Conformity
L			9030 3100	1021R	Digital Multimeter: <ul style="list-style-type: none"> Elegant and easy-to-use cabinet Large display with 6000 counts and Backlight Enhanced current measuring function using an external clamp sensor Two detachable holders, flat and wing type Accurate reading with True RMS Safety Standard IEC 61010-1 CAT IV 300V / CAT III 600V Inc. Accessories: Wing-type holder, Flat-type holder, 7066A (Test leads), 8919 (Ceramic fuse [10A/600V])x 1 (included), 9097 (Carrying case), R03 x 2, Instruction manual 	8775	10701	Certificate of Conformity
L			9030 3100	1051	Digital Multimeter: For Electrical and Electronic Troubleshooting High Accuracy, High Performance and Reliable Measurements <ul style="list-style-type: none"> 0.09% basic DC accuracy Large display with 6,000 counts True-RMS Measurements Low-pass filter for motor drive measurements User Test function Safety design for industrial use <ul style="list-style-type: none"> Complies with IEC 61010-1 CAT IV 600V, CAT III 1000V Terminal shutter to prevent incorrect test leads' insertion in current terminals Very wide operating temperature range from -10 to 55°C Inc. Accessories: 7220A (Test leads), R6x4, Instruction manual, 8926 (Fuse [440mA/1000V])x 1 (included), 8927 (Fuse [10A/1000V])x 1 (included) 	34690	42305	Test Certificate from KEW (A4 Size)
L	Digital Pen Type Multimeter		9030 3100	1030	Digital Pen Type Multimeter: <ul style="list-style-type: none"> Compact in Size, Light in Weight and Simple in Use. Double moulding provides comfortable and good feeling in hand. Penlight illuminates brightly the point to be measured, even in dark place. Backlight LCD is highly visible, even in darkness. Unique wrapping mechanism for test lead in the rear side compartment. Unique protection mechanism for the test prod for safety. All ranges including Ohm range are protected against overload voltage of 600V. Inc. Accessories: Carrving case, LR44 (1.5V) x 2, Instruction manual 	6581	8026	Certificate of Conformity


KYORITSU India Product Price List - 2022-23

KEW India Product Category	Product Category	Product Image	HS Code	Model Number	Short Description	KKIPL LP (in INR)	MRP (in INR)	Standard Certificate
L	AC Analog Clamp Meter		9030 3900	2608A	AC Analog Clamp Meter: <ul style="list-style-type: none"> DC voltage range is also available especially for checking emergency battery operated power supply. Can measure temperature using optional probe. Tear drop shaped transformer jaws for ease of use. Inc. Accessories: 7066A (Test leads), 8923 (Fuse [0.5A/600V]) x 2, 9097 (Carrying case), R6 (AA) x 1, Instruction Manual 	14381	17538	Certificate of Conformity
L	Digital AC Clamp Meters		9030 3900	2117R	Digital Clamp Meter: <ul style="list-style-type: none"> Fully Safety jaw Ergonomic over-molded body gives convenient one-hand operation Large easy-to-read display with 0.01A resolution Accurate reading with True RMS 60/600/1000A auto-ranging Long battery life Safety Standard IEC 61010-1 CAT IV 300V / CAT III 600V Inc. Accessories: 7066A (Test leads), 9079 (Carrying case), R03 (AAA) x 2, Instruction Manual 	11212	13674	Certificate of Conformity
L			9030 3900	200	Digital AC Clamp Meter: <ul style="list-style-type: none"> Measures Current up to 400A AC & Voltage up to 600V AC Resistance, Continuity buzzer Conductor Size #30mm Data hold memory function and Sleep feature Display: 4000 counts Complies to IEC61010-1 (CAT. III) UL3111 & VDE0411 300V Inc. Accessories: Test leads, Batteries, Instruction manual	6337	7729	Certificate of Conformity
L			9030 3900	2003A	Digital Clamp Meter: <ul style="list-style-type: none"> Equipped to measure both AC and DC current with transformer jaws of large diameter. Can measure AC and DC currents up to 2000A. Output terminal for connection to recorders. Inc. Accessories: 7107A (Test leads), 8201 (Output Plug), 9094 (Carrying Case), R6 (AA) x 2, Instruction Manual 	26325	32103	Certificate of Conformity
L	Digital AC/DC Clamp Meter		9030 3900	203	Digital Clamp Meter: <ul style="list-style-type: none"> Measures Current up to 400A AC/DC & Voltage up to 600V AC/DC Resistance, Continuity buzzer Conductor Size #30mm Data hold memory function and Sleep feature Display: 4000 counts Complies to IEC61010-1 (CAT. III) UL3111 & VDE0411 300V Inc. Accessories: Test leads, Batteries, Instruction manual	10031	12233	Certificate of Conformity
L			9030 3900	2055	Digital Clamp Meter: <ul style="list-style-type: none"> Designed to meet international safety standard IEC 61010-1 CAT IV 600V. CAT IV Clamp Meters can measure the Voltage and Current in both every low and high power circuits. Thus, very useful for power distribution companies, power utilities and maintenance fields. Inc. Accessories: 7290 (Test leads), 9198 (Soft Case), LR6(AA)x2, Instruction Manual 	19743	24077	Certificate of Conformity
L	Power Clamp Meter		9030 3300	2062	Power AC Clamp Meter: <ul style="list-style-type: none"> Conductor size φ55mm Current up to 1000A rms Voltage up to 1000V rms Harmonics up to 30th Phase rotation Inc. Accessories: 7290 (Test leads), 9198 (Soft Case), LR6(AA)x2, Instruction Manual 	73351	89453	Certificate of Conformity
L	Digital AC/DC Fork Current Tester		9030 3900	2300R	Fork Current Tester: <ul style="list-style-type: none"> True RMS reading is an essential feature for accurate measurement. “Non Contact” voltage function indicates the presence of AC voltage by warning the user with an audible signal. Set the DC current range to zero in one touch with the Zero Adjust function. Inc. Accessories: Carrying Case, R03 (AAA) x 2, Instruction Manual 	13894	16943	Certificate of Conformity
L	Digital AC Leakage Current Clamp Meter		9030 3900	2434	Leakage Clamp Meter <ul style="list-style-type: none"> Least affected by external stray magnetic field. 20mA AC max. in proximity to a 15mm-dia conductor carrying 100A AC Frequency Selector Switch to eliminate the effect of harmonics. Resolution 0.1mA. Inc. Accessories: 9097 Carrying Case, R03 x 2, Instruction Manual 	29006	35373	Test Certificate from KEW (B6 Size)

KEW India Product Category	Product Category	Product Image	HS Code	Model Number	Short Description	KKIPL LP (in INR)	MRP (in INR)	Standard Certificate
L	Insulation Tester Digital		9030 3900	3005A	Digital Insulation/Continuity Tester <ul style="list-style-type: none"> Bargraph to display insulation resistance. Displays the value of external AC voltage along with flashing symbol. Auto null function to automatically subtract the test lead resistance before displaying the real continuity resistance value. Live circuit warning beeper. Releasing the test button automatically discharges the charges stored in the circuit under test. 200mA continuity measuring current to IEC 61557. Minimum 1mA current on insulation tests to IEC 61557. Inc. Accessories: 7122B (Test leads) Pouch for test leads, 8923 (F500mA/600V fuse) x 2, R6 (AA) x 2, Shoulder Strap, Instruction Manual 	32183	39247	Test Certificate from KEW (A4 Size)
L			9030 3900	3552	Digital Insulation / Continuity Testers <ul style="list-style-type: none"> World's fastest measurement speed (0.5 sec.) Six ranges available for insulation resistance test (50/100/125/250/500/1000 V) Insulation measurement up to 40GΩ Diagnostic Insulation Test : PI, DAR KEW3552 : With memory function Incl. Accessories: 7260 (Test leads with remote control switch, 7261A (Test leads with alligator clip) , 8017A (Extension prod long) , 9173 (Carrying case) , 9121 (Shoulder strap) , LR6 (AA) (1.5V) x4, Instruction manual 	62275	75946	Certificate of Conformity
L			9030 3900	3125A	High Voltage Insulation Tester <ul style="list-style-type: none"> Insulation Resistance up to 1TΩ Short-Circuit Current up to 1.5mA Wide Test Voltage from 250V to 5000V Diagnosis Function of PI and DAR Newly-designed alligator clip It comes with a tough hard case Filter function reduces noise interference for obtaining stable measurement Large display with Bar Graph indication and backlight Live voltage warning Safety standard IEC 61010-1 CAT IV 300V / CAT III 600V Inc. Accessories: 7165A (Line probe: 3m), 7264 (Earth cord: 3m), 7265 (Guard cord: 3m), 8019 (Hook type prod), 9180 (3025A Hard case), 9181 (3125A Hard case), LR14 	100667	122765	Calibration Certificate from KEW (A4 Size)
L	Earth Tester Digital		9030 3320	4105A	Earth Resistance Tester <ul style="list-style-type: none"> Dust and drip proof (designed to IEC 529 IP54) In addition to the facility for precision measurement, test leads for simplified two wire measuring system also supplied as standard accessories. (unit can be hung from the neck for simplified measurement) Designed to meet IEC 61010-1 safety standard. Capable of measuring earth voltage. Automatic warning when resistance of auxiliary earth spikes is in excess of tolerance. Small and lightweight. Shock resistant new case material. 2mA measuring current permits earth resistance tests without tripping earth leakage current breakers in the circuit under test. Inc. Accessories: 7095A (Earth resistance test leads) x 1set (red-20m, yellow-10m, green-5m), 8032 (Auxiliary earth spikes) x 1set, 7127A (Simplified measurement probe) x 1set, R6 (AA) x 6, Neck strap, Instruction Manual 	29493	35968	Certificate of Conformity
L	RCD Tester		9030 3900	5406A	Digital RCD Tester <ul style="list-style-type: none"> Custom microprocessor controlled for highest accuracy and reliability. 3 LEDs for checking correct wiring status. 0 and 180 degree phase angle switch permits quick tests and consistent readings. Digital read-out of tripping time. Constant current source circuitry ensures that a fluctuating mains voltage does not affect the accuracy of readings. Large custom digital display readout. Visual indication of reversed phase and neutral wiring at socket. Designed to IP54 Rating. Complies with IEC 61557 Test of a large kind of RCD's: Standard, Selective, AC and A (DC sensitive breakers) Inc. Accessories: Molded plug test leads, Pouch for test leads, Shoulder Strap, Instruction Manual 	35317	43070	Test Certificate from KEW (A4 Size)
L	Phase Indicator		9030 3390	8031	Phase Indicator <ul style="list-style-type: none"> Digital Phase Indicator with open phase checker. Phase indicator designed to check the presence of open phase and also the phase sequence by LED and buzzer at the same time. Small, lightweight, and portable. Inc. Accessories: 9029 (Carrying Case), Instruction manual 	10481	12782	Certificate of Conformity