

Kyoritsu India Retail (L series) Product Price List - 2026-27

KEW India Product Category	Product Category	Product Image	HS Code	Model Number	Short Description	KKIPL LP (in INR)	MRP (in INR)	Standard Certificate
L	Digital Multimeters		9030 3100	1018H	Digital Multimeter: - Display : 4000 counts. - Auto range. - Diode test feature. - Capacitance test feature. - Continuity test. Inc. Accessories: 1 R44x 2, Instruction Manual, Hard Case. DC AC V Ω ••• → Hz DUTY DATA HOLD REL AUTOPOWER OFF			
L			9030 3100	1019R	Digital Multimeter: - Elegant shiny-black finish - Comes with user-friendly Hard case - Large Display - Accurate reading with True-RMS technology - Electronic protection (no fuse!) on ohm and continuity ranges - Safety Standard IEC 61010-1 / 61010-031 / 61010-2-033 CAT III 300V / CAT II 600V Inc. Accessories: 9188 (Hard case), CP2032 x 1, Instruction manual. TRUE RMS DC AC V Ω ••• → REL AUTOPOWER SAVE	10249	12499	Certificate of Conformity
L			9030 3100	1009	Digital Multimeter: - Display : 4000 counts. - Auto range and manual range selector provided. (with range hold feature) - Resistance range provides audible continuity test. - Automatically turns power off in about 30 minutes to conserve battery life. - Direct current measurement up to 10A AC and DC. - With Holster. Inc. Accessories: 7066A (Test leads), 8919 (Ceramic fuse [10A/600V])x 1, 8923 (Fuse [10A/600V])x 1, R6x 2, Instruction Manual. DC AC V DC AC A Ω ••• → Hz DUTY DATA HOLD REL AUTOPOWER OFF	7402	9027	Certificate of Conformity
L			9030 3100	1021R	Digital Multimeter: - Elegant and easy-to-use cabinet - Large display with 6000 counts and Backlight - Enhanced current measuring function using an external clamp sensor - Two detachable holders, flat and wing type - Accurate reading with True RMS - Safety Standard IEC 61010-1 CAT IV 300V / CAT III 600V Inc. Accessories: Wing-type holder, Flat-type holder, 7066A (Test leads), 8919 (Ceramic fuse [10A/600V]) x 1 (included), 9097 (Carrying case), R03 x 2, Instruction manual. TRUE RMS CAT IV 300V CAT III 600V DC AC V DC AC A Ω ••• → Hz DUTY ☀ DATA HOLD REL MAX/MIN AUTOPOWER SAVE	11957	14582	Certificate of Conformity
L			9030 3100	1051	Digital Multimeter: For Electrical and Electronic Troubleshootings High Accuracy, High Performance and Reliable Measurements 0.09% basic DC accuracy - Large display with 6,000 counts - True-RMS Measurements - Low-pass filter for motor drive measurements - User Test function Safety design for industrial use - Complies with IEC 61010-1 CAT IV 600V, CAT III 1000V - Terminal shutter to prevent incorrect test leads' insertion in current terminals - Very wide operating temperature range from -10 to 55°C Inc. Accessories: 7220A (Test leads), R6x4, Instruction manual, 8926 (Fuse [440mA/1000V])x1 (included), 9027 (Fuse [10A/600V])x1 (included). TRUE RMS CAT IV 600V DC AC V DC AC A Ω ••• → Hz °C ☀ DATA HOLD REL Filter AUTOPOWER OFF	48572	59234	Test Certificate from KEW (A4 Size)
L	Digital Pen Type Multimeter		9030 3100	1030	Digital Pen Type Multimeter: - Compact in Size, Light in Weight and Simple in Use. - Double moulding provides comfortable and good feeling in hand. - Penlight illuminates brightly the point to be measured, even in dark place. - Backlight LCD is highly visible, even in darkness. - Unique wrapping mechanism for test lead in the rear side compartment. - Unique protection mechanism for the test prod for safety. - All ranges including Ohm range are protected against overload voltage of 600V. Inc. Accessories: Carrying case, R44 (1.5A) x 2, Instruction manual. DC AC V Ω ••• → Hz DUTY ☀ DATA HOLD REL AUTOPOWER OFF	7971	9721	Certificate of Conformity

L	AC Analog Clamp Meter	 9030 3900	2608A	AC Analog Clamp Meter: - DC voltage range is also available especially for checking emergency battery operated power supply. - Can measure temperature using optional probe. - Tear drop shaped transformer jaws for ease of use. Inc. Accessories: 7066A (Test leads), 8923 (Fuse [0.5A/600V]) × 2, 9097 (Carrying case), R6 (AA) × 1. Instruction Manual				
L	Digital AC Clamp Meters	 9030 3900	2117R	Digital Clamp Meter: - Fully Safety jaw - Ergonomic over-molded body gives convenient one-hand operation - Large easy-to-read display with 0.01A resolution - Accurate reading with True RMS 60/600/1000A auto-ranging - Long battery life - Safety Standard IEC 61010-1 CAT IV 300V / CAT III 600V Inc. Accessories: 7066A (Test leads), 9079 (Carrying case), R03 (AAA) × 2, Instruction Manual	13950	17012	Certificate of Conformity	
L		 9030 3900	200	Digital AC Clamp Meter: - Measures Current up to 400A AC & Voltage up to 600V AC - Resistance, Continuity buzzer - Conductor Size *30mm - Data hold memory function and Sleep feature	7971	9721	Certificate of Conformity	
L		 9030 3900	2003A	Digital Clamp Meter: - Equipped to measure both AC and DC current with transformer jaws of large diameter. - Can measure AC and DC currents up to 2000A. - Output terminal for connection to recorders. Inc. Accessories: 7107A (Test leads), 8201 (Output Plug), 8094 (Carrying Case), R6 (AA)	33593	40968	Certificate of Conformity	
L	Digital AC/DC Clamp Meter	 9030 3900	203	Digital Clamp Meter: - Measures Current up to 400A AC/DC & Voltage up to 600V AC/DC - Resistance, Continuity buzzer - Conductor Size *30mm - Data hold memory function and Sleep feature	11960	14585	Certificate of Conformity	
L		 9030 3900	2055	Digital Clamp Meter: - Designed to meet international safety standard IEC 61010-1 CAT IV 600V. - CAT IV Clamp Meters can measure the Voltage and Current in both every low and high power circuits. - Thus, very useful for power distribution companies, power utilities and maintenance field. Inc.	24768	30205	Certificate of Conformity	
L	Power Clamp Meter	 9030 3300	2062	Power AC Clamp Meter: - Conductor size ϕ55mm - Current up to 1000A rms - Voltage up to 1000V rms - Harmonics up to 30th - Phase rotation Inc. Accessories: 7290 (Test leads), 9198 (Soft Case), LR6(AA)x2, Instruction Manual	90066	109836	Certificate of Conformity	
L	Digital AC/DC Fork Current Tester	 9030 3900	2300R	Fork Current Tester: - True RMS reading is an essential feature for accurate measurement. "Non Contact" voltage function indicates the presence of AC voltage by warning the user with an audible signal. - Set the DC current range to zero in one touch with the Zero Adjust function. Inc. Acces	17081	20831	Certificate of Conformity	
L	Digital AC Leakage Current Clamp Meter	 9030 3900	2434	Leakage Clamp Meter - Least affected by external stray magnetic field. 20mA AC max. in proximity to a 15mm-dia conductor carrying 100A AC - Frequency Selector Switch to eliminate the effect of harmonics. - Resolution 0.1mA. Inc. Accessories: 8003 (Test leads), 8004 (Soft Case), 8005 (Instruction Manual)	36440	44439	Test Certificate from KEW (B6 Size)	
L		 9030 3900	3005A	Digital Insulation/Continuity Tester - Bargraph to display insulation resistance. - Displays the value of external AC voltage along with flashing symbol. - Auto null function to automatically subtract the test lead resistance before displaying the real continuity resistance value. - Live circuit warning beeper. - Releasing the test button automatically discharges the charges stored in the circuit under test. 200mA continuity measuring current to IEC 61557. - Minimum 1mA current on insulation tests to IEC 61557. Inc. Accessories: 7122B (Test leads) Pouch for test leads, 8923 (F500mA/600V fuse) × 2, R6	40273	49114	Test Certificate from KEW (A4 Size)	

L	Insulation Tester Digital		9030 3900	3552	Digital Insulation / Continuity Testers - World's fastest measurement speed (0.5 sec.) - Six ranges available for insulation resistance test (50/100/125/250/500/1000 V) - Insulation measurement up to 40GΩ - Diagnostic Insulation Test : PI, DAR KEV3552 : With memory function Incl. Accessories : 7260 (Test leads with remote control switch, 7261A (Test leads with alligator clip) , 8017A (Extension prod long) , 9173 (Carrying case) , 9121 (Shoulder strap) , LR6 (AA) (1.5V) x4 Instruction manual   50V 100V 125V 250V 500V 1000V   	65902	80368	Certificate of Conformity	
L			9030 3900	3125A	High Voltage Insulation Tester - Insulation Resistance up to 1TΩ - Short-Circuit Current up to 1.5mA - Wide Test Voltage from 250V to 5000V - Diagnosis Function of PI and DAR - Newly-designed alligator clip - It comes with a tough hard case - Filter function reduces noise interference for obtaining stable measurement - Large display with Bar Graph indication and backlight - Live voltage warning - Safety standard IEC 61010-1 CAT IV 300V / CAT III 600V Incl. Accessories: 7165A (Line probe: 3m), 7264 (Earth cord: 3m), 7265 (Guard cord: 3m), 8019 (Hook type prod), 9180 (3025A Hard case), 9181 (3125A Hard case), LR14 (Alkaline battery size C) x 8, Instruction manual CAT IV 300V CAT III 600V   250V 500V 1000V  2500V 5000V	#N/A	#N/A	Test Certificate from KEW (A4 Size)	EOL Till India Stocks Last
L	Earth Tester Digital		9030 3320	4105A	Earth Resistance Tester - Dust and drip proof.(designed to IEC 529 IP54) - In addition to the facility for precision measurement, test leads for simplified two wire measuring system also supplied as standard accessories. (unit can be hung from the neck for simplified measurement) - Designed to meet IEC 61010-1 safety standard. - Capable of measuring earth voltage. - Automatic warning when resistance of auxiliary earth spikes is in excess of tolerance. - Small and lightweight. Shock resistant new case material. 2mA measuring current permits earth resistance tests without tripping earth leakage current breakers in the circuit under test. Incl. Accessories: 7095A (Earth resistance test leads) x 1set (red-20m, yellow-10m, green-5m), 8032 (Auxiliary earth spikes) x 1set, 7127A (Simplified measurement probe) x 1set, R6 (AA) x 6, Neck strap, Instruction Manual	40141	48953	Certificate of Conformity	
L	RCD Tester		9030 3900	5406A	Digital RCD Tester - Custom microprocessor controlled for highest accuracy and reliability. 3 LEDs for checking correct wiring status. 0 and 180 degree phase angle switch permits quick tests and consistent readings. - Digital read-out of tripping time.	45887	55960	Test Certificate from KEW (A4 Size)	
L	Phase Indicator		9030 3390	8031	Phase Indicator - Digital Phase Indicator with open phase checker. - Phase indicator designed to check the presence of open phase and also the phase sequence by LED and buzzer at the same time. - Small, lightweight, and portable.	12811	15623	Certificate of Conformity	
L	Insulation Tester Digital		9030 3900	3125B	High Voltage Insulation Tester (with reinforced Green Body) - Insulation Resistance up to 1TΩ - Short-Circuit Current up to 1.5mA - Wide Test Voltage from 250V to 5000V - Diagnosis Function of PI and DAR - Newly-designed alligator clip - It comes with a tough hard case - Filter function reduces noise interference for obtaining stable measurement - Large display with Bar Graph indication and backlight - Live voltage warning - Safety standard IEC 61010-1 CAT IV 300V / CAT III 600V Incl. Accessories: 7165A (Line probe), 7264 (Earth cord), 7265 (Guard cord), 8019 (Hook type prod), 9204 (Carrying case [Hard]), LR14 (Alkaline battery size C) x 8,	1,32,381	#####	Test Certificate from KEW (A4 Size)	
L	Voltage Tester		9030 3330	5711	VOLTAGE DETECTOR - Senses AC voltage through insulation - Buzzer sounds and tip glows upon AC voltage detection - Powerful flashlight - Dual range (Hi/Lo) sensitivity - Ready to use without power-on - Designed to meet IEC 61010-1 Incl. Accessories: LR03(AA) x 2, Instruction manual	4,882	5,953	NA	