

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
AC High Voltage Test Set		
	Please check annexure 'A' of the price list	
Acidity Testing Kit		
ATK	METRAVI Brand Acidity Testing Kit used to measure the Acidic content of Transformer Oil	1900
Analogue Clamp Meter		
M-300	Clamp Jaw Dia 34mm, AC/DC Voltage, AC Current up to 300A, Resistance & Temperature. Pointer Lock Facility, with temperature probe	2000
M-600	Clamp Jaw Dia 34mm, AC/DC Voltage, AC Current up to 600A, Resistance & Temperature. Pointer Lock	2300
M-1000	Clamp Jaw Dia 60mm, AC/DC Voltage, AC Current up to 1000A, Resistance.	4000
Analogue Multimeter		
250TR	Measures AC/DC Voltage, DC Current, Resistance, Battery Test and dB.	900
260TR	Measures AC/DC Voltage, DC Current, Resistance, Transistor Polarity Test, Audible Continuity	1600
2010BA	Measures AC/DC Voltage, up to 10A AC/DC, Resistance, Transistor and Audible Continuity	2000
5050E	Measures AC/DC Voltage up to 1000V, AC/DC Current up to 10A, Resistance up to 2000M.Ohms, Frequency up to 25kHz, Transistor Testing, Diode Testing and audible continuity testing	3100
6060	Measures AC / DC Voltage up to 2500V, AC/DC Current up to 10A, Resistance up to 10M.Ohms, Diode and continuity test facility	11500
Battery Impedance Tester		
TM-6002	Battery Impedance Tester to check Battery internal resistance, Voltage, Current and temperature, with 9999 memory, with PC Interface cable and software	72000
Bench Type Multimeter		
M-45	4-1/2 Digits, 19999 Counts Backlit LCD, Bench type Multimeter, Confirms to IEC610101-1 Degree , Mains and Battery Operated, AC/DC Voltage, AC/DC Current, Capacitance, Frequency, Temperature, Transistor & Diode Test Facility.	10600
45 T-RMS	4-1/2 Digits Bench type Multimeter	8500
55 TRMS NEW!!		44700
M-3511	6-1/2 Digits Bench type Multimeter AC/DC V, AC/DC Current, Resistance, Cap and Frequency	55400
M-3510A	6-1/2 Digits Bench type Multimeter AC/DC V, AC/DC Current, Resistance, Cap., Temp. and Frequency	69000
M-3500	6-1/2 Digits Bench type Multimeter with multiple options	89000
Cable Fault Locator		
CFL-01	Digital Cable Locator and Combined with Cable Fault locator	17500
PES-2000A	PES Brand Digital Cable Fault Locator for underground cable up to 5kms	
CFL-02	Digital Cable Fault Locator for Power, Control and Telecom Cables buried underground	60000

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Calibrator		
CAL-408	Bench type RTD Calibrator, Outputs available at -200, -100, -50, -25, 0, 25, 50, 100, 150, 200, 300, 400, 500, 600 °C	6400
CAL-400-3	Hand Held, 3-1/2 Digits, Battery Operated, 0 - 19.99/24mA, -199.9mV to 199.9mV source and current & power measurement	5000
CAL-400-4	Hand Held, 4-1/2 Digits, Battery Operated, 0 - 199.9mV / 0 - 19.999mA sourcing and measuring range	6500
CAL-402-4	Bench type, 230V AC 50Hz Operated, 0 - 199.99m / 1.9999 / 19.999V & 0 - 199.99u / 1.999m / 19.999mA Sourcing & Measuring	7100
CAL-500	Hand Held, 4 Digits Large LCD Display, Measures and Provides output for 20mV / 100mV / 15V DC, Current output up to 24mA, 24V Loop Power, and outputs for K, E, J, T, R, S, B and N types of thermocouples	20500
01+	5 Digits 0.5% Accuracy, Source for Volt, Resistance, Pt-100, Cu-50, Thermocouples R, S, B, E, K, J, T, N types.	23500
03+	5 Digits 0.5% Accuracy, Sources and Measures Resistance, PT-100 Sensor and Cu-50 Sensors	23500
05+	5 Digits, 0.5% Accuracy, Sources DC Current, Analogue Transducer & Loop Power and Measures DC Voltage, DC Current and Loop Current	27750
11+	6 Digits, 0.2% Accuracy, Sources R, S, B, E, K, J, T, N types of thermocouples, PT-100, Cu-50, DC Voltage, DC Current, Resistance, Analogue Transducer, Frequency, Pulse Output and LOOP Power.	69500
14+	6 Digits, 0.2% Accuracy, Sources and Measures DC Voltage, PT-100, Cu-50 Sensors and R, S, B, E, K, J, T & N types of Thermocouples.	69500
15+	6 Digits, 0.2% Accuracy, Sources and Measures DC Voltage, DC Current, Analogue Transducer and LOOP Power.	69500
16+ NEW!!	Simulates and measures Resistance, 14 types of RTD and 11 types of Thermocouples with an accuracy of 0.01%.	74000
25	50,000 Counts, 0.2% Universal Calibrator for DC Voltage, Current, Resistance, Frequency, all thermocouples and thermo-resistance and for pressure	250000
709H NEW!!	mA Loop Calibrator with HART COMMUNICATOR, Accuracy 0.01%	91000
709H-USB NEW!!	USB COMMUNICATION INTERFACE CABLE AND SOFTWARE	30000

Carbon Mono Oxide Meter		
CO-09	Detects Presence of Carbon Mono-Oxide. Range 0 to 1000PPM, Backlit LCD	11550
CO-10	Detects Presence of Carbon Mono-Oxide. Range 0 to 1000PPM, Backlit LCD, With Audio and Buzzer Alarm	14000

Clamp On Ground Resistance Tester		
CET-01	4 Digits LCD, 28mm Clamp Jaw Dia, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms	25000
CET-02	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms	25000
CET-03	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 20A.	29870
CET-04	4 Digits LCD, 28mm Clamp Jaw Dia, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms. With Leakage Current Measurement up to 20A.	28000
CET-05	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms	21200
CET-06	4 Digits LCD, 28 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms	21200
RS-232 Cable & S/W	RS-232 PC Interface cable and software for Clamp On Ground Resistance Tester	1750
CET-03 EX NEW!!	Explosion Proof Clamp On Ground Resistance Tester, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 20A.	27000

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Coatmeter		
CTG-01	Measures coating thickness on both ferrous and Non Ferrous materials	10600
CTG-02	Measures coating thickness on both ferrous and Non Ferrous materials with extended flexible cable with sensor	18886
Combustible Gas Leakage Detector		
GLD-01	16" Gooseneck detector for detecting Combustible Gas Leakage. With Audio and Visual Alarm	5200
Current Transducer		
CE-0102CT	Current Transducer, AC Current Input and DC output	3150
Data Logger for Sound Level		
DL-SL01	Sound Level Data logger to record sound, from 30 to 130 dB, with 129920 data Points	11400
Data Logger for Temperature & Humidity		
DL-TH01	Temperature and Humidity Data Logger with digital display and data logging up to 32700 points	4500
Data Logger for Voltage and Current		
DL-VI01	Data Logger for Voltage and Current with digital display and 100096 data points	13900
DC High Voltage Test Set		
	Please check annexure 'A' of the price list	
DC Regulated Power Supply		
RPS-3002	Single Output with Backlit LCD Display of Variable 0 - 30V / 0 - 2A DC	7130
RPS-3005	Single Output with Backlit LCD Display of Variable 0 - 30V / 0 - 5A DC	7130
RPS-6002	Single Output with Backlit LCD Display of Variable 0 - 60V / 0 - 2A DC	8700
RPS-6005	Single Output with Backlit LCD Display of Variable 0 - 60V / 0 - 5A DC	16380
RPS-3010	Single Output with LED Display of Variable 0 - 30V / 0 - 10A DC	16000
RPS-3020	Single Output with LED Display of Variable 0 - 30V / 0 - 20A DC	23000
RPS-3030	Single Output with LED Display of Variable 0 - 30V / 0 - 30A DC	49000
RPS-6010	Single Output with LED Display of Variable 0 - 60V / 0 - 10A DC	28500
RPS-6020	Single Output with LED Display of Variable 0 - 60V / 0 - 20A DC	58000
RPS-6030	Single Output with LED Display of Variable 0 - 60V / 0 - 30A DC	87000
RPS-3002-2	Dual Output with Backlit LCD Display of Variable 0 - 30V / 0 - 3A DC	12800
RPS-3005-2	Dual Output with Backlit LCD Display of Variable 0 - 30V / 0 - 5A DC	16400
RPS-3003-3	Triple Output with Backlit LCD Display, Dual 0 - 30V / 0 - 3A DC and Fixed 5V/3A	13500
RPS-3005-3	Triple Output with Backlit LCD Display, Dual 0 - 30V / 0 - 5A DC and Fixed 5V/3A	17500
DDS Function Generator		
DDS-1005	5 MHz DDS Function generator, 125MSa/s sampling rate	17400
DDS-1010	10 MHz DDS Function generator, 125MSa/s sampling rate	19250
DDS-1025	25 MHz DDS Function generator, 125MSa/s sampling rate	36000
DDS-1060	50 MHz DDS Function generator, 125MSa/s sampling rate	51800
DDS-1080 NEW!!	80MHz DDS Function generator, 320MSa/s sampling rate	65000
DDS-1120 NEW!!	120MHz DDS Function generator, 320MSa/s sampling rate	76000

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Digital AC/DC Clamp Meter		
DT-725	3-5/6-digit 5999 Count, Backlight LCD, T-RMS, Auto-Ranging, NCV, Flashlight, Relative Measurement, AC(750V)/DC(1000V) Voltage, 600A AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity. Square Wave Output, CAT-IV 600V	2500
DT-230	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 400A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test.	4500
DT-325	3-3/4 Digits 3999 Counts, Digital AC/DC Clamp Meter, Confirming to CAT-III 300V, Jaw Size 28 mm, Auto Power Off, Data Hold, AC/DC Voltage up to 600V, AC/DC Current up to 400A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test Facility	3300
DT-6250	3-3/4 Digits, LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Current up to 400A, Resistance, Frequency, Duty Cycle, Capacitance, Diode and Continuity Test.	5200
DT-1350	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A AC/DC Clamp Meter with AC/DC Voltage, Resistance, Diode and Continuity Check	2600
DT-1350A	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A AC/DC Clamp Meter with AC/DC Voltage, Resistance, Capacitance, Temperature and Frequency	3000
DT-3690	3-4/5 Digits 6000 Counts, LCD, Data Hold, T-RMS, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Frequency and Temperature & Continuity Test	3400
DT-425T	3-3/4 Digits 3999 Counts Backlit LCD, T-RMS AC/DC Clamp meter, Confirms to CAT-III 600V, Data Hold, MAX/MIN, Relative, In-Built Flash Light, Overload Protection, 30mm Clamp Jaw Dia, Auto Power Off, AC T-RMS / DC Current 600A, AC T-RMS / DC Voltage 600V, Resistance, Capacitance, Temperature, Frequency, Non Contact Voltage Detector, Diode and Continuity Test	4700
DT-3250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC Voltage, 1000A DC/AC Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	6400
DT-3600	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage, 1200A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	6750
DT-4250	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Duty Cycle, Diode & Continuity Test.	6750
DT-5250	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, T-RMS, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test.	7000
DT-8250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC Voltage, 2000A DC/AC Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	7000
DT-9250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage, 2000A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	8000

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
2003A NEW!!	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage, 2000A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	8000
METRACLAMP-15	3999 Counts, Backlit LCD, 52mm jaw Dia, Non Contact Voltage Detector, Auto Power Off, T-RMS, AC/DC Voltage, AC T-RMS/DC 1000A, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test, double Injection mould, CAT-IV 600V	7500
METRACLAMP-20	4-3/4 Digits, 40,000 Counts, Backlit, T-RMS, Autoranging, 52mm Jaw Dia, Non Contact Voltage Detector, Fully Protected, AC/DC Voltage, AC/DC Current up to 1500A, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Diode and Continuity Test	10500
SOLAR - 2 NEW!!	6000 Counts, Auto-Backlit LCD Display, 1000V DC/AC T-RMS, Specially designed for P-V Application to measure 2000V DC/1500V AC, DC/AC T-RMS 600A, Resistance up to 600k.Ohms, Temperature up to 400 Degree C, Capacitance up to 1000uF, Frequency up to 10kHz, Continuity and Diode Test, Optionally can connect to flexible clamp to measure up to 3000A AC. Designed to meet IEC/EN 61010-1, IEC/EN 61010-2-033 CAT IV 600V/CAT III 1000V, Max Conductor Dia 37mm, High Frequency Rejection, In-rush current measurement	26000

Digital Ammeter		
CE-0102A	3-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 48 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	850
CE-0102A 96	3-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 96 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	850
CE-0102A	3-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 48 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	975
CE-0102A 96	3-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 96 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	975
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size		
CE-0102A	4-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 48 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	1500
CE-0102A 96	4-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 96 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	1500
CE-0102A	4-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 48 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	1500
CE-0102A 96	4-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 96 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	1500

Digital Ammeter Controller		
CE-0102AC 1SP	Digital Ammeter with Single Set Point to control the current below a given set point. Size - 96 x 96 mm sq. With 1NO + 1NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	2700
CE-0102AC 2SP	Digital Ammeter with Two Set Point to control the current below a given pair of set points. Size - 96 x 96 mm sq. With 2NO + 2NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	2900

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Digital Anemometer		
AVM-01	4 Digits Backlit LCD Display, Data Hold, Max Record, Measures Air Velocity up to 30m/Sec, measures in km/hr, ft/min, knots, mph as well, Displays Air Temperature -10 to 50 Degree C, Shows windchill and also displays Beaufort Wind Scale	1550
AVM-02	Digital Thermo-Anemometer with facility to measure 40m/Sec and in ft/min also	3400
AVM-03	Digital Thermo-Anemometer with facility to measure 40m/Sec, with humidity, CMM, CFM, USB PC Interface	6050
AVM-04	Digital Thermo-Anemometer with facility to measure up to 45m/Sec and in ft/min also	5400
AVM-05	Digital Thermo-Anemometer with facility to measure wind flow (CFM / CMM)	6800
AVM-07	Digital Thermo-Anemometer to measure up to 30m/Sec with Metal Blades, Temp. -10 to 60°C / 14 to 140°F	4900
AVM-08	Digital Thermo-Anemometer with facility to measure wind flow (CFM / CMM) with built in infra-red Thermometer to measure from -50 to 260°C with 8:1 D:S Ratio and Emissivity Fixed at 0.95	11400
AVM-09	Digital Thermo-Anemometer with facility to measure wind flow (CFM/CMM) with built in Pressure Meter	17000
AVM-10	Digital Hot Wire Anemometer, Dual LCD, with RS-232 Interface, 0.1 to 20m/Sec and Temperature from -20 to 80°C / -5 to 175°F	13200
Digital Capacitance Meter		
DCM-1502	3-1/2 Digits, LCD, Zero Adjustment, up to 20mF Capacitance Measurement	2500
Digital Clamp Meter		
DT-625	3-3/4 Digits, LCD, Data Hold, Auto-Ranging, 33mm Jaw Size, AC/DC Voltage, AC Current up to 400A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test	2100
DT-115	6000 Counts, Backlit LCD, With Flashlight, Autoranging, Auto Power Off, T-RMS, Non Contact voltage detection, Flashlight, Data Hold, 40 mm Jaw Size, AC/DC Voltage, AC Current up to 600A T-RMS, Capacitance, Frquency, Temperture, Ressitance, Continuity & Diode test.	1625
DT-115A	6000 Counts Backlit LCD Display, Built-in Flashlight to access dark Areas, Non Contact Voltage Detection, Simple to use, Just provide the input and the instrument, detects the signal and displays the parameter, No Selection required, Just provide Input, Automatic Selection of AC/DC Voltage, Resistance, Capacitance, Diode Test, T-RMS, 600A T-RMS Measurements	2060
DT-369	3-4/5 Digits 6000 Counts, LCD, Data Hold, T-RMS, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance,Capacitance, Frequency and Temperature & Continuity Test	2200
DT-1150	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A Clamp Meter with AC/DC Voltage	1750
DT-1150A	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A Clamp Meter with AC/DC Voltage, Resistance, Capacitance, Temperature and Frequency	2150
DT-125	3-1/2 Digits, Data Hold, Max Hold, 23mm jaw Size, AC/DC Voltage, AC Current up to 400A, Resistance, Continuity & Diode Test	3000
DT-225	3-1/2 Digits, Backlit LCD, Data Hold, Max Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Temperature, Frequency, Diode and Continuity Test. 500V DC/AC Protection in all ranges.	2600
DT-1250	3-1/2 Digits, Backlit LCD, Data Hold, Max Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Diode and Continuity Test. 500V DC/AC Protection in all ranges.	2600
DT-2250	3-3/4 Digits, Backlit LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Duty Cycle, Diode and Continuity Test Facility. 500V DC/AC Protection in all ranges.	2900

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
DT-2255	3-1/2 Digits, LCD, Data Hold, Auto-ranging, 57mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test.	2900
DT-3150	3-3/4 Digits, Backlit LCD, Data Hold, 57mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Frequency, Duty Cycle, Diode and Continuity Test Facility. 1000V DC/AC Protection in all ranges.	3275
DT-7250	3-1/2 Digits, LCD, Data Hold, Auto-ranging, 57mm Jaw Size, AC/DC Voltage, AC Current up to 2000A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test.	5000
DT-525	3-1/2 Digits, LCD, Data Hold, Peak Hold, T-RMS, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity Test.	5400
METRACLAMP-10	3-3/4 Digits, Backlit LCD, CAT-IV 600V, Data Hold, Relative, 55mm Jaw Dia, AC/DC Voltage, AC Current up to 1000A, Resistance, Cap, Temp and Frequency with Diode and Continuity Test	4000

Digital Clamp Meter with Wireless PC Interface

DT-5250W	3-3/4 Digits, Backlit LCD, Peak & Data Hold, T-RMS, Wireless PC Interface, 30mm jaw size, AC/DC Voltage, AC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test	9000
----------	---	------

Digital Clamp On Power Meter

107F	10000 Counts Digital Clamp On Power Meter with 3000A Flexible Clamp, AC/DC Voltage and AC/DC Current Auto Detection, NCV, Jaw Dia 42mm, KW, PF, THD up to 25th Harmonics	24000
307	6000 Counts, Backlit LCD, Single Phase and Three Phase, Non Contact Voltage Detector, Data Hold, Peak Hold, Relative, Max/Min Reocrd, Single Phase KW, KVA, KVAr, PF, KWh and KW & PF for Three Phase. Clamp Jaw Size 56mm. AC Current up to 1500A AC.	14500
307N	4 Digits, Dual LCD, Single Phase and Three Phase, Max /Min / Peak Hold, 55mm Jaw Dia, T-RMS, AC Voltage, AC Current up to 1000A, KW, KVA, KVAR, Power Factor, Phase Angle, KWh, Frequency and Temperature. With Data Logging and PC Interface	8700
607	4 Digits, Dual LCD, Harmonic Analysis up to 50th Harmonic, PC Interface, Single Phase & Three Phase, Maximum Demand, KW, KVA, KVAR, KWh, KVAh, KVArH, Power Factor, Real time output of waveform, Power Parameters and Harmonics. Clamp Jaw Size - 55mm.	60000

Digital Distance Meter

DM-09	Digital Ultrasonic Distance Meter to measure up to 16m	1700
-------	--	------

Digital Earth Tester

ERT-1501	0 - 10 / 100 / 1000 Ohms, 4 Terminal with Testing Kit and Cables in hard carrying case	6750
ERT-1502	0 - 20 / 200 / 2000 Ohms, 4 Terminal with Testing Kit and Cables in hard carrying case	7500
	Rechargeable Battery and Battery Charger for above	4000

Digital Frequency Counter

FC-2700	8 Digits Green LED Frequency Counter up to 2.7GHz	5000
---------	---	------

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Digital Frequency Meter		
CE-500F 99.99Hz	4 Digits, Panel Flush Mounting, 96 X 48 mm sq, Input 10 - 500V, Measuring range 20 - 99.99 Hz.	890
CE-500F 96 x 96	4 Digits, Panel Flush Mounting, 96 X 96 mm sq, Input 10 - 500V, Measuring range 20 - 99.99 Hz.	890
CE-500F 999.9Hz	4 Digits, Panel Flush Mounting, 96 X 48 mm sq, Input 50 - 500V, Measuring range 0 - 999.9 Hz.	975
CE-500F 96 x 96	4 Digits, Panel Flush Mounting, 96 X 96 mm sq, Input 50 - 500V, Measuring range 0 - 999.9 Hz.	975
Digital IC Tester		
DICT-2040	40 Pin Digital IC Tester to test 54 / 74 series TTL and 4000 & 4500 series CMOS IC's, tests more than 2000 kinds of devices	29500
Digital Insulation Tester		
DIT-909	9999 Counts Backlit LCD, Low Battery Indication, Dat Hold, Timer Function up to 10mins, Comparator, 99 Data Records, USB PC Interface (optional) Test Voltage: 50V / 100V / 250V / 500V / 1000V, 200G.Ohms, AC Voltage T-RMS, DC Voltage, Freuqncy, Capacitance, Continuity Test, With Remote Probe, IP-54	19500
DIT-910	4 Digits, with GO NO-GO functions, 250V/500M.Ohms, 500V/1G.Ohms, 1000V/2G.Ohms	4200
DIT-912	4 Digits with Analog Bargraph, measures upto 2000M.Ohms at 250V / 500V / 1000V, measures 600V AC/DC, Low Resistance up to 4000 Ohms and Continuity test. Fully Protected on all ranges	9500
DIT-913	Digital Insulation Tester for 250V / 500V / 1000V / 2500V , 0-2000M(250V), 0-20G(500/1000/2500V)	5000
DIT-914	Battery cum Mains Operated, with facility to measure AC Voltage, Low Resistance, Continuity, 500V/2000M.Ohms, 1000V/2000M.Ohms, 2500V/20G.Ohms, 5000V/200G.Ohms	12000
DIT-915	Digital Insulation Tester for 1000V / 60G.Ohms, 2500V / 150G.Ohms, 5000V / 300G. Ohms and 10000V / 600G.Ohms	63000
DIT-916	Selectable testing voltages - one testing instrument for low and high voltage systems from 500/1000/2500 and 5000V, Insulation resistance measurement up to 1T Ω, User selectable programmable timer (10s to 30 min), Automatic discharge of test object after completion of measurement, Diagnostic tools, Polarization index (PI), Dielectric absorption ratio (DAR), USB PC Interface	29000
DIT-918		
DIT-921	Battery cum Mains Operated, with facility to measure, PI, DAR, AC Voltage, Low Resistance, Continuity, 500V/6G.Ohms, 1000V/6G.Ohms, 2500V/60G.Ohms, 5000V/60G.Ohms	27000
DIT-99A	Digital Battery Cum Mains Operated Insulation Tester for 100V / 200M.Ohms	2000
DIT-99B	Digital Battery Cum Mains Operated Insulation Tester for 250V / 200M.Ohms	2000
DIT-99C	Digital Battery Cum Mains Operated Insulation Tester for 500V / 1G.Ohms	2000
DIT-99D	Digital Battery Cum Mains Operated Insulation Tester for 1000V / 2G.Ohms	2000
DIT-321	Digital Insulation Resistance Tester with Buil-in Multimeter, 3-3/4 Digits 3999 Counts, Backlit LCD, Data Hold, Test Voltage: 250V / 500V / 1000V, upto 40G.Ohms, Measures AC/DC Voltage, AC/DC Current up to 400mA, Resistance, Capacitance, Frequency, Diode & Continuity Test Facility.	4100
DIT-322	Digital Insulation Resistance Tester with Buil-in Multimeter, 3-3/4 Digits 3999 Counts, Backlit LCD, Data Hold, Test Voltage: 500V / 1000V / 2500V, upto 40G.Ohms, Measures AC/DC Voltage, AC/DC Current up to 400mA, Resistance, Capacitance, Frequency, Diode & Continuity Test Facility.	5500
Digital VA Meter		
CE-0303VA	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	3500

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
CE-0304VA	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	3500
Digital VAR Meter		
CE-0303VAR	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	3500
CE-0304VAR	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	3500
Digital KWh Meter		
CE-0303EML	Digital KWh Meter with LCD Display for Three phase Three wire Two element loads	4100
CE-0304EML	Digital KWh Meter with LCD Display for Three Phase Four wire Three Element loads	4100
Digital LCR Meter		
LCR-360	3-1/2 Digits Hand Held Digital LCR Meter, Measures Inductance from 0.001mH to 20H, Capacitance from 0.001nF to 600uF and Resistance from 0.1 to 20M.Ohms, with diode test, transistor test and audible continuity test, CE Approved	3700
460	11,000 Counts Backlit LCD, Data Hold, MAX/MIN Record, RELATIVE, Inductance, Capacitance, Resistance, Diode & Continuity Test	5000
4070D	5 Digits, LCD, Dual Display, Inductance, Capacitance, Resistance, Impedance, D, ESR and Q Test Facility, Test Frequency of 100Hz, 120Hz, 1kHz, 10kHz and 100kHz	11200
Digital LCR Multimeter		
451	3-1/2 Digits, Backlit LCD, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Inductance, Frequency, Temperature, Diode, Transistor and Continuity Test	3000
506	3-3/4 Digits, Backlit, LCD Dual Display, T-RMS, RS-232 PC Interface, Internal Memory, Min, Max, Avg, Relative Modes, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Inductance, Duty Cycle, Temperature, dBm, Logic, Diode, Signal Output & Continuity Test	17500
Digital Leakage Current Meter		
DT-4671	3-3/4 Digits, Analogue Bargraph, LCD, Data Hold, MAX/MIN Record, 30mm Jaw Size, AC Voltage, AC Current, Resistance. Has Low Pass Filter to filter out noise.	5800
DT-4672	3-3/4 Digits, LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Leakage Current measurement, Capacitance, Resistance, Frequency, Duty Cycle, Diode & Continuity Test	6000
M-4673	3-1/2 Digits, LCD, T-RMS,. AC/DC Leakage Current Meter, Non contact voltage detector, Data Hold, Can be used for Variable Frequency Control Drives, Measures from 1mA, AC/DC Current up to 100A, AC/DC Voltage, Resistance, Capacitance, Diode and Continuity Test	5000
M-6054	3-1/2 Digits LCD, Data Hold, Max Hold, 30mm Jaw Dia, 0 - 200mA / 2A / 200A AC.	5200
MULTI-140	3-1/2 Digits, 3200 Counts LCD, Data Hold, 40mm jaw Dia, 0 - 30m/300m/30/300A AC	29850
PRO-468AC NEW!!	6000 Counts, Auto-Backlit LCD Display, Auto Power Off, as per IEC 61557-13: Class 2, 40mm Jaw Dia, IEC / EN 61010-1, IEC / EN 61010-2-032, CAT. III 600V, Pollution Degree 2, EN 61326-1 EN 61326-2-2, bandwidth up to 1kHz, 1% accuracy, 0 - 6mA / 60mA / 600mA / 6A / 60A, With resolution of 1uA, Bluetooth connection to connect it to freely available APP for recording data	29850

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Digital Lux Meter		
1300	4 Digits Backlit LCD Display, MAX / MIN Record, Data Hold, Digital Lux Meter, Can measure up to 200,000 Lux, Also measures in FC (Foot Candle), High Sampling Rate, Overload Indication, Auto Power Off, Low Battery Indication	1550
1310	4 Digits Backlit LCD Display, Data Hold, Hi/Lo Indication, Split Probe, Lux and Foot Candle Measurement, Auto Power Off, Lo-Battery Indication, Measures up to 199,900 Lux / Fc	2100
1330	Measures up to 50,000 Lux	2380
1331	Measures up to 50,000 Lux / Ft Candle with Max Hold and Data Hold	2900
1332	Measures up to 200,000 Lux / Ft Candle with Peak Hold and Data Hold	5200
1332A	Measures up to 200,000 Lux / Ft Candle with Max Hold and Data Hold	6600
1333	Measures up to 0 - 20 / 200 / 2000 / 200000 / 200,000 Lux / Ft Candle with Max Hold and Data Hold	4600
1334	Measures up to 400,000 Lux/40,000 Ft Candle, Data & Peak Hold, Max Min Record, USB PC Interface, Backlit LCD With Analogue Bargraph	6000

Digital Micro Ohms Meter		
53C	Digital Micro Ohms Meter to measure from 1uOhm to 2k.Ohms	5000
53C-II	Micro-Processor based, Digital Micro Ohms meter to measure from 1uOhms to 2kOhms, with digital selection of ranges	5500
UOT-10A	Digital Micro Ohms Meter with Test Current of 10A	55000
7272	60,000 Counts Backlit LCD Display, With USB PC Interface, 1000 Internal Memory, Data Hold, Pass / Fail Function, Four Wire measurement, Testing Current of 10A, Battery and Mains Operated, Measures from 1uOhms to 6k.Ohms.	44000
UONT-100A	Digital Micro Ohms Meter with Test Current of 100A	
UONT-200A	Digital Micro Ohms Meter with Test Current of 200A	

Digital Milli Ohms Meter		
52C	Hand Held, 0.1mOhms to 40 Ohms, 4 wire Kelvin type connection, also measures AC/DC Voltage, AC/DC Current, Resistance, Capacitance and continuity	8900

Digital Moisture Meter		
MM-1	Digital Moisture Meter for paper, wood and hardned material like plaster, concrete and mortar	3100
MM-2	Digital Moisture Meter for wood, bamboo, cotton, tobacco, paper, foodstuffs	1450
MM-3	Digital Moisture Meter for paper, carton, corporate and writing papers	3500
MM-5	Digital Wood Moisture Meter that can measure moisture in up to 150 different kinds of wood	5750
MM-10	Digital Pinless Moisture Meter, Range 0 - 100%, auto power off, backlit display, Min/Max function, Measure and Hold, works on most of the products	7500

Digital Multimeter		
XB-30	3-1/2 Digits, LCD, Data Hold, AC Voltage, DC Voltage, DC Current, Resistance, Diode & Transistor Test.	1300
XB-33CF	6000 Counts Backlit LCD, Flash Light, NCV, MAX/MIN Record, T-RMS, Measures AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Frequency, Diode and Continuity Test	1500
702	3-1/2 Digits, LCD, AC Voltage, DC Voltage, AC Current, DC Current, Resistance, Diode, Transistor and Continuity Test. 500V DC/AC Protection in Resistance, Diode and Continuity Test Range	1400
603	3-1/2 Digits, Backlit LCD, Data Hold, AC Voltage, DC Voltage, AC Current, DC Current, Resistance, Capacitance, Frequency, Temperature, Hot Wire, Diode, Transistor and Continuity Test.	1550

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
6030A	6000 Counts Backlit LCD, T-RMS Multimeter, Auto Power Off, Data Hold, MAX/MIN, AC / DC Voltage, AC/DC Current 20A, Resistance, Capacitance, Frequency, Temperature, Transistor Test, Diode and Continuity Test	1600
901-I	3-1/2 Digits, LCD, Auto-ranging, Max Hold and Data Hold, AC Voltage, DC Voltage, AC Current, DC Current, Resistance, Temperature, Diode & Continuity Test. 500V DC/AC Protection in Resistance, Temperature, Diode and Continuity Test.	2100
19	3-3/4 Digits, LCD, Auto-ranging, Relative, Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, 30MHz Frequency, Duty Cycle, Temperature, Diode, Transistor and Continuity Test.	1900
19-SUPER	6000 Counts LCD Display, NCV, T-RMS Multimeter, Measures AC/DC Voltage, AC/DC Current up to 20A, Resistance, Temperature, Frequency, Capacitance, Diode, Transistor Test and Continuity Test Facility	2000
901-II	3-3/4 Digits, Backlit LCD, Auto-ranging, Relative, Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity Test.	2700
901-III	3-5/6 Digits, 6000 Counts Backlit LCD, Autor-ranging, 600V AC/DC Protection, AC/DC Voltage, AC/DC Current, Resistance, 4mF capacitance, 20MHz Frequency, temperature diode and continuity	3800
901-IV	3-5/6 Digits, 6000 Counts Backlit LCD, Autor-ranging, T-RMS, 600V AC/DC Protection, AC/DC Voltage, AC/DC Current, Resistance, 4mF capacitance, 20MHz Frequency, temperature diode and continuity	4600
801	3-3/4 Digits, LCD, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Logic Test, Diode & Continuity Test. 500V DC/AC Protection in Resistance, Capacitance, Frequency, Logic, Diode & Continuity Test	2800
DT-19TB	3-3/4 Digits, Backlit LCD, Auto-ranging, Terminal Blocking Facility, Relative & Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Battery Test, Diode & Continuity Test. 500V AC/DC Protection in all ranges	3100
Metrasafe-10	6000 Counts Backlit LCD, T-RMS, Flashlight, Live-Neutral detectio, Non contact voltage detector, Audio and visual alarm for continuity, Transistor Test, AC/DC Voltage, AC/DC Current up to 20A, Resistance, Capacitance, Frequency, Temperature, Duty Cycle, Diode and Continuity Test.	2100
Metrasafe-13	3-3/4 Digits, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Relative, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Continuity and Battery Test. Confirms to CAT IV 600V	4050
Metrasafe-14	3-3/4 Digits, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Relative, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Continuity and Battery Test. Confirms to CAT IV 600V	4600
Metrasafe-15	3-3/4 Digits, Analogue Bargraph, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Max/Min, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test. Confirms to CAT IV 600V.	5600
Metrasafe-16	3-3/4 Digits, Analogue Bargraph, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Max/Min, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test. Confirms to CAT IV 600V.	6500
Metrasafe-18	4-3/4 Digits, Analogue Bargraph, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data & Peak Hold, Max/Min Record, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Non Contact type Infra Red Thermometer, Duty Cycle, Diode & Continuity Test. Confirms to CAT IV 600V.	13500
Metrasafe-19	4-3/4 Digits, Analogue Bargraph, Wireless PC Interface, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data & Peak Hold, Max/Min Record, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Non Contact type Infra Red Thermometer, Duty Cycle, Diode & Continuity Test. Confirms to CAT IV 600V.	15000

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Metrasafe-20	4-5/6 Digits, 60,000 Counts, T-RMS Multimeter, OLED Display, 100kHz Bandwidth, 0.025% Accuracy, Lo-Z measurement, AC/DC Voltage, AC/DC Current, Resistance, Process Measurement, Conductance, Capacitance, Frequency, Duty Cycle, Temperature, Diode and Continuity, Re-chargeable battery, Battery Charger, Misoperation Alarm, Data Logger. Optional Blue Tooth Interface	28500
23 T-RMS	4-1/2 Digits 19,999 Counts, T-RMS, Backlit LCD, NCV, Data Hold, Peak Hold, Relative, Auto Power Off, Dual Display to show Voltage & Current with Frequency on the same screen, AC/DC Voltage, AC/DC Current 10A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test both Audio and Visual.	3500
540	4-1/2 Digits, LCD, Data Hold, T-RMS, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Diode & Continuity Test.	5200
DM-454	22,000 Counts Backlit LCD Display, Peak Hold, Data Hold, Relative Measurement, T-RMS Multimeter, Confirms to CAT III 1000V, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Diode & Continuity Test, USB PC Interface.	6750
PRO-11	4000 Count Backlight LCD Display, Auto-Ranging, IP67 Dust and Waterproof, 600V AC/DC Voltage, 10A AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, UL 61010-1, CAT-III 600V, Class 2 Double Insulation, Built-in flashlight, Over range indication, Auto Power Off, Min/Max Data Hold. Hand-Held Waterproof and Dustproof, Digital Multimeter. Anything and Everything that you can possibly think about. A must for all technicians, double moulded injection body, a built-in flashlight to access dark areas,	4500
PRO-12B	4000 Count, Backlight LCD Display, TRMS, IP 67 Dust and Waterproof Digital Multimeter, 600V AC(TRMS)/DC Voltage, 10A AC(TRMS)/DC Current, LoZ, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity test, 50 to 400Hz AC Bandwidth, Bluetooth Smartphone interface, Free Smartphone App, Data Hold, MAX/MIN Record, Built-in Flashlight, Double-moulded injection body, Auto Power Off, Low battery indication, CAT-III 600V. Hand-Held Waterproof and Dustproof, Digital Multimeter. Anything and Everything that	5400
SOLAR - 1 NEW!!	6000 Counts, Auto-backlit LCD, confirming to EN 61010-1, EN 61010-2-033 for CAT III 1000V, CAT IV 600V, EN 61326-1, designed for Solar PV application, to measure 2000V DC and 1500V AC T-RMS, to measure DC/AC mV as well, AC/DC Current up to 10A, Resistance 40M.Ohms, Capacitance 10mF, Frequency 100kHz, Temperature 400 Degree C, Non Contact Voltage Detection, Diode and Continuity Test.	15000

Accessories to Digital Multimeter		
CA-01	Clamp On Current Adaptor to be used with any Multimeter with mV range, measures up to 200A AC	1150
CA-1000D	Clamp On Current Adaptor to be used with any Multimeter with mV range, measures up to 600A/1000A AC/DC	4300
TS-03	Infra Red Temperature Adaptor to measure from -30 to 550 Degree C, can be used with any Multimeter with mV range	3200
PD-28	High Voltage probe to measure 40kV DC and 28kV AC	7500
ATL-PV NEW!!	High Voltage Probe for P-V Multimeter SOLAR-1 and PV Clamp meter SOLAR-2	1400
TL-70 NEW!!	Right Angled shrouded termination to fit modern multimeters, fitted with a 4mm shrouded socket, CAT III 1000V / 20A Rating	160
TL-74 NEW!!	1m silicon single insulated test leads with right angle shrouded banana plugs, CAT IV 600V, CAT III 1000V with protective cap, banana plug termination, dia of test lead point 2mm	330
TL-75 NEW!!	1m silicon double insulated test leads with right angle shrouded banana plugs, CAT IV 600V, CAT III 1000V with protective cap, banana plug termination, dia of test lead point 2mm	400

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Digital Non Contact Infra Red Thermometer		
MT-2	3 Digits Backlit LCD with laser sighting used to measure temperature in the range of -30 to 260°C / -22 to 500°F, D:S Ratio 8:1, Fixed emissivity 0.95.	1750
MT-4	4 Digits Backlit LCD, adjustable emissivity from 0.10 to 1.00, D:S Ratio of 12:1, measures from -50 to 600°C / -58 to 1112°F, with double laser pointer to show the diameter of area whose temperature is being measured	4600
MT-5	4 Digits Backlit LCD, Dual Laser Pointer to show the diameter of the area whose temperature is being measured, emissivity adjustable from 0.10 to 1.00, D:S Ratio 12:1, measures -50 to 800°C / -58°F to 1472°F, Trigger Lock, Hi-Lo Alarm, Max Temp. Display	5500
MT-8	4 Digits Backlit LCD, Dual Laser Pointer to show the diameter of the area whose temperature is being measured, emissivity adjustable from 0.10 to 1.00, D:S Ratio 20:1, measures -50 to 1000°C / -58°F to 1832°F, Trigger Lock, Hi-Lo Alarm, Max Temp. Display	7100
MT-10	3-1/2 Digits Backlit LCD, fixed emissivity of 0.95, D:S Ratio of 50:1, measures from -50 to 1000°C / -58 to 1832°F, with laser pointer	13500
MT-13	Backlit LCD, Contact cum Non Contact type, measures from -18 to 1050 °C in Non Contact model and -50 to 1370 °C in Contact Mode, Emissivity adjustable from 0.10 to 1.0, D:S Ratio of 30:1, with wireless USB PC Interface and facility to calculate the emissivity of the surface	17500
MT-14	4 Digits Backlit LCD, Contact cum Non Contact type, measures -50 to 1300°C/-58 to 2372°F in non contact mode and contact mode. D:S Ratio 30:1, Emissivity Adjustable 0.10 to 1.00, mV output /°C, Trigger Lock, battery cum mains operated, Records 20 Data, Max/Min/Dif/Avg recording	12000
MT-16	4 Digits Backlit LCD, Contact cum Non Contact type, with USB PC Interface, adjustable emissivity from 0.10 ~ 1.0, D:S Ratio of 50:1, in non contact mode measures from -50 to 1800°C / -58 to 3272°F, with dual laser pointer to show the diameter of the area whose temperature is being measured and with Max./Min./Dif/AVG. Temp.	20500
MT-18	4 Digits Backlit LCD, Contact cum Non Contact type, with USB PC Interface, adjustable emissivity from 0.10 ~ 1.0, D:S Ratio of 50:1, in non contact mode measures from -50 to 2200°C / -58 to 3992°F, with dual laser pointer to show the diameter of the area whose temperature is being measured and with Max./Min./Dif/AVG. Temp.	28500
MT-20	4 digits LCD, adjustable emissivity from 0.10 to 1.00, telescopic sighting measures in the range of 500°C to 3000°C and in °F scale, distance to sighting ratio of 120:1, accuracy ±1%, with Max/Min/Ave/DT and High/Low alarm	170000
PRO-65 NEW!!	Precise Non Contact Measurement, Circular Laser to show the exact area whose temperature is being measured IP54 Rated for Dust / Water Proof, 2m Drop Tested, Automatic Data Hold, Non Contact and Contact Thermometer Combined, Contact temperature measurement using K type sensor, Adjustable Emissivity from 0.10 to 1.00, MAX / MIN / AVG / DIF Temperature display, Backlit LCD Display, Set High and Low Alarms, Distance to Sighting Ratio 16:1 (65Max) Battery Operated 2 x 1.5V AAA Batteries, CE Compliant with EMC, Tk Temperature: -50 to 1370°C, Resolution: 0.1°C < 1000; 1°C > 1000, Accuracy: ±0.5% of Reading ±1.5°C, IR Temperature Measurement: -50 to 800°C _{SEP} , Response Time: 150mS, Spectral Response: 8 – 14um	4000
PRO-65 MAX+ NEW!!	Precise Non Contact Measurement, Circular Laser to show the exact area whose temperature is being measured IP54 Rated for Dust / Water Proof, 2m Drop Tested, Automatic Data Hold, Non Contact and Contact Thermometer Combined, Contact temperature measurement using K type sensor, Adjustable Emissivity from 0.10 to 1.00, MAX / MIN / AVG / DIF Temperature display, Backlit LCD Display, Set High and Low Alarms, Distance to Sighting Ratio 20:1, Battery Operated 2 x 1.5V AAA Batteries, CE Compliant with EMC, Tk Temperature: -50 to 1370°C, Resolution: 0.1°C < 1000; 1°C > 1000, Accuracy: ±0.5% of Reading ±1.5°C, IR Temperature Measurement: -50 to 1000°C _{SEP} , Response Time: 150mS, Spectral Response: 8 – 14um	5000

CATEGORY / MODEL No.		DETAILS	LIST PRICE in Rs.
Digital Phase Angle Meter			
CE-0102D	Digital Phase Angle Meter, 96 x 96 mm sq, can measure Phase Angle between Voltage and Current		3000
Digital Power Analyzer			
CE-0102PA	Digital Ampere, Volt, PF and Watt meter combined in 96 x 96 mm sq for single phase loads		4000
Digital Power Factor Meter			
CE-0102PF	Microprocessor Based, 96 x 48 mm sq, For Single Phase, Red LED Display		2700
CE-0102PF 96 x 96 mm sq	Microprocessor Based, 96 x 96 mm sq, For Single Phase, Red LED Display		2700
CE-0303PF	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element , Red LED Display		3500
CE-0304PF	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display		3500
Digital Pressure Meter			
PM-01	Backlit LCD Display, measures up to 5 psi and in various other units of Pressure		6500
Digital Process Meter			
PM-29	3-3/4 Digits, Digital Multimeter Cum DC mV / Voltage / Frequency / Resistance / mA Calibrator and also provies output for all types of Thermocouples		40500
PM-39	5 Digits, Digital Multimeter combined with source for DC voltage, resistance, frequency, all kind of thermocouples, thermal resistance, and DC current. supply power to 24V circuits and meanwhile measure current; with built-in 250 Ω HART loop resistance		45000
Digital Process Clamp Meter			
771+ NEW!!	The Milliamp Process Clamp Meter is a hand-held battery-operated clamp meter that measures 4-20 mA DC without breaking the electrical circuit. DC mA measurement (4-20mA) using a remotely connected clamp via extension cable, Electronic zero, Percentage span (0-100%), Data Hold, Backlit Display, Measurement spotlight LED, Auto Power Off, 0mA... ±20.99mA, Resolution 0.01mA, Accuracy: 0.3% realding ±8 digits, Also measures ±21.0mA... ±99.9mA with Resolution of 0.1mA, Clamp Jaw 4.5mm, IP40, IEC 61010-1, 61010-2-032, CAT II 300V		20000
Digital SMT Component Tester			
SMT-01	SMT Component tester that can measure Capacitance and Resistance values of SMT components, it can also measure AC/DC Voltage, continuity and Diode test		3700
Digital Sound Level Meter			
SL-3010	4 Digital Backlit LCD, Sound Level Meter, Fast & Slow Response, Data Hold, MAX/MIN Record, A Weighting, Measures sound in the range of 30dB to 130dB with resolution of 0.1dB and accuracy of 1.5dB. With Over-range and Low Battery Indication		1600
SL-4010	3-1/2 Digits Backlit LCD, has A & C Weighting, measures in the range of 30 to 130 dB, with maximum hold		5400
SL-4005	3-1/2 Digits, has A & C Weighting, measures in the range of 35 to 130 dB, with data hold and maximum hold, with built in calibration check		6200
SL-4015	4 Digits, has A & C Weighting, measures in the range of 30 to 130 dB, USB PC Interface, with Max/Min Data Hold and Data Logging facility		10800

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Digital Storage Oscilloscope		
DSO-5025E	25MHz DSO with colored display, 250MSa/Sec sampling rate, with USB PC Interface cable and software	25000
DSO-5050E	50MHz DSO with colored display, 500MSa/Sec sampling rate, with USB PC Interface cable and software	27000
DSO-5070E	70MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host	33000
DSO-5100E	100MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host	34000
DSO-5150E	150MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host	67000
DSO-5200E	200MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host	72000
Accessories to Digital Storage Oscilloscope		
PD-20S	High Voltage Probe to be used with any oscilloscope (Analogue or Digital Storage) to measure High Voltage Waveform of 30kV DC and 20kV AC	8000
Digital Stroboscope		
DT-2350A	Digital Stroboscope, 50 to 12,000FPM, 230V Single Phase AC Operated	11500
DT-2350B	Digital Stroboscope, 50 to 40,000FPM, 230V Single Phase AC Operated	21000
Digital Tachometer		
DT-2235	Contact type Tachometer, measures up to 50,000RPM	2250
NCTM-500	Non Contact type Tachometer With Counter, Data Hold, Measures from 50mm to 200mm, RPM Up to 99999RPM, and Counts up to 99999 Counts	1600
NCTM-1000	Non Contact type Tachometer Cum Counter. Max / Min . Last Data Record, 2 to 99,999 RPM, 1 TO 99,999 Counts	3100
NCTM-2000	Contact cum Non Contact type Combined Tachometer, Max/Min, Last Record, 20,000RPM in contact mode and 99,999 RPM in non contact mode, measures Rotation speed, total revolution, frequency, surface speed and length	5550
Digital Temperature Controller		
DTC-200	Digital Temperature Controller 96 x 96 mm sq, with 1NO + 1NC, Single Set Point, for K, J, R, S, PT-100 (Any One)	1550
DTC-202	Digital Temperature Controller 96 x 96 mm sq, with 2NO + 2NC, Two Set Point, for K, J, R, S, PT-100 (Any One)	2100
METCAT 96	Digital Temperature Controller, 4 Digits Display, up to 1200 Degree C, 96 x 96 mm sq, with 1NO + 1NC, Single Set Point, for K, J, PT-100 (User Programmable)	1550
METCAT 72	Digital Temperature Controller, 4 Digits Display, up to 1200 Degree C, 72 x 72 mm sq, with 1NO + 1NC, Single Set Point, for K, J, PT-100 (User Programmable)	1550
Digital Temperature & Humidity Meter		
HT-305	3-1/2 Digits Backlit LCD Dual Display, Measures Temperature in Celsius and Fahrenheit scales in the range of -10 to 60 Degree C with resolution of 0.1 and accuracy of 1.0 Degree C, Relative Humidity from 0 to 100% RH with resolution of 0.1%RH and 5%RH accuracy, It has Data Hold, MAX/MIN Record Function, Auto Power Off	1600
HT-305A	Backlit LCD Dual Display, with split type Sensor for temperature and Humidity, Data Hold, MAX / MIN Record, Auto Power Off, Measure Tmperature from -10 to 60 Degree C, and Humidity Up to 100% RH	2000
HT-3004CT	Digital Thermo-Hygro Meter with in-built infra red thermometer. Has Backlit LCD Display	8300
HT-3005	Digital Thermo-Hygro Meter with K-type thermometer. Has Backlit LCD Display	3950
HT-3006	Digital Thermo-Hygro Meter with facility to measure wet bulb and dew point temperature	5800

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
HT-12	Digital Thermo-Hygro Meter with Jumbo Display, to measure Indoor and Outdoor Temperature measurement, with Humidity. Selectable scales, Alarm Clock and Comfort Level Indicator, Temperature range -10 to 50 Degree C and humidity from 20 to 95%	950
HT-13	Digital Thermo-Hygro Meter with Jumbo Display, to measure Temperature measurement, with Humidity. Selectable scales, Alarm Clock and Comfort Level Indicator, Temperature range -10 to 50 Degree C and humidity from 20 to 95%	900
HTC-01	Jumbo LCD Display, wall hanging, with time and alarm facility, -50 to 70 Degree C, 20% to 99%RH	650
TH-04	LCD Display, wall hanging, with time and alarm facility, calendar, climatic condition display, 0 to 50 Degree C, 10% to 90%RH	1000

Digital Temperature Indicator		
DTI-101	Digital Temperature Indicator 96 x 48 mm sq, for K, J, R, S, PT-100 (Any One)	1100
DTI-101	Digital Temperature Indicator 96 x 96 mm sq, for K, J, R, S, PT-100 (Any One)	1100
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size or 96 x 48 mm sq size		

Digital Thermometer		
DTM-900	3-1/2 Digits, Measures from -50 to 1300°C / -50 to 1999°F, Contact type, to be used with K type thermocouple, with backlit display and kelvin scale	3200
DTM-901	3-1/2 Digits, Dual Channel Input, Measures from -50 to 1300°C / -50 to 1999°F, Contact type, to be used with K type thermocouple. with backlit display and kelvin scale	5550
DTM-903	Wide Temperature Range, High Accuracy, Battery Operated, Selectable Thermocouple between K / J type, MAX / MIN / AVG Recording, Data Hold to Freeze Displayed Data, Backlit Display Measures Temperature from -50 to 1300°C using K-type Sensor and from -50 to 1200°C using J-type Sensor Accuracy: ±0.5%	1300
DTM-100	3-1/2 Digits, Hand Held 9V battery operated, for PT-100 Sensor up to 600 Degree C	1650
DTM-902	Pen Type, Auto Power Off, -40 to 250°C / -40 to 482°F	710
ST-9283B	Hand Held, With High Temperature Alarm Facility, Auto Power Off, Data Hold, -50 to 300°C / -58 to 572°F	600

Digital Three Phase Ammeter		
CE-03A	Microprocessor Based, 96 x 96 mm sq, with in built three phase selector switch, displays Current in three phases, CT Ratio programmable. Programmable up to 3000A AC	1600

Digital Three Phase Voltmeter		
CE-03V	Microprocessor Based, 96 x 96 mm sq, with in built three phase selector switch, displays Line to Line and Line to Neutral Voltage. Direct Operated and PT Ratio programmable	1600

Digital Time Interval Meter		
NTT-4D	4 Digits Digital Time Interval Meter for measuring in the range of 999.9mS, 9.999S, 99.99S	10500
3CH-NTT-4D	4 Digits 3 Channel Digital Time Interval Meter for measuring in the range of 99.99mS, 999.9mS, 9.999S	48000

Digital Voltage Controller		
CE-0102VC 1SP	Digital Voltmeter with Single Set Point to control the Voltage below a given set point. Size - 96 x 96 mm sq. With 1NO + 1NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	2700
CE-0102VC 2SP	Digital Voltmeter with Two Set Point to control the Voltage between a given set points. Size - 96 x 96 mm sq. With 2NO + 2NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	2900

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Digital Voltmeter		
CE-0102V	3-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	900
CE-0102V 96	3-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	900
CE-0102V	3-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	975
CE-0102V 96	3-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	975
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size		
CE-0102V	4-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1500
CE-0102V 96	4-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1500
CE-0102V	4-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1600
CE-0102V 96	4-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1600

Digital Wattmeter		
CE-0102W	Microprocessor Based, 96 x 48 mm sq, For Single Phase, Red LED Display	2700
CE-0102W 96 x 96	Microprocessor Based, 96 x 96 mm sq, For Single Phase, Red LED Display	2700
CE-0303W	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	3500
CE-0304W	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	3500

ELCB Tester		
1810D	Digital ELCB Tester with Current Rating up to 500mA, Trip Test, Fault Trip Time, Self Powered	5800
1811	Digital ELCB Tester with Current rating up to 500mA, Auto Ramp, Phase Switch, Reads Disconnection Time, Self-Powered	9700
1812	Digital ELCB Tester with Current rating up to 500mA, reads disconnection time also	10600
1813 NEW!!	Digital ELCB Tester with Current rating up to 1A, Trip Test, Fault Trip Time, 230V AC Operated	10200

Electrical Tester		
AC-1	Audio and Visual output on detecting voltage from 90V - 1000A AC with built in flash light	350
AC-4	Non Contact Voltage Detector by flashing light for 100 - 600V, with built-in flash light	650
AC-5	Non Contact Voltage Detector by flashing light and buzzer sound for 100 - 600V, with built-in flash light	750
AC-6	Socket Polarity & Earth Leakage Tester. Checks for No Earth / Line Neutral Reversal / No Neutral / Line Earth Reversal / No Line states.	1310
AC-7	Phase Rotation Indicator, No Batter Required, Nomical Voltage 40 - 690V, 15 to 400Hz.	3700
AC-8	Self Operated, phase rotation indicator along with voltage and frequency display	2500

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
EMF Tester		
EMF-823	Measures from 0.1 to 200mG / 1 to 2000mG & 0.01 to 20uT / 0.1 to 200uT, Frequency Response 30Hz to 400Hz, Max Hold and Data Hold	6750
Event Counter		
CTR-49	6 Digits Red LED Display, Event Counter, 1 to 999999 Counts, 96 x 48 mm sq	2200
N.B. - Please ask for the prices in case if you require this in 96 x 96 mm sq size		
Forehead Infra Red Thermometer		
FIR-1	Non Contact, infra red type, auto hold, auto power off, surface and forehead temperature, 90 to 109 Degree F, 0 to 60 Degree C	5200
FIR-2	Non Contact Infra Red Thermometer for body temperature	4000
Frequency Transducer		
CE-0102FT	Frequency Transducer with single Output	3500
N.B. - For Dual Output Rs.500/- shall be charged extra		
Function Generator		
FG-1000	1MHz Function Generator with TTL / CMOS output	10500
FG-2000	2MHz Function Generator with TTL / CMOS output	11500
FG-5000	5MHz Function Generator with TTL / CMOS output	13000
FG-10000	10MHz Function Generator with TTL / CMOS output	23000
FG-20000	20MHz Function Generator	25000
Gauss Meter		
GM-197 NEW!!	Gauss Meter for both static and electromagnets, DC and AC (40-500Hz), determines N/S polarity of Static Magnets, measures intensity of magnetic Field in Gauss and Tesla both, measures up to 0~3000mT(milli Tesla)/0~30000G(Gauss), Relative / Peak Hold / Real time Zero function, Auto Range, DATA HOLD, MAX/MIN hold, GO and NO-GO alarm and alarm value set up the function, Production testing, Manual 200 capacity records, Auto 6000 capacity data logging, interval is set up by PC, USB interface to send data + PC connection application software, real time function.	23000
High Voltage Detector		
277HP	Non Contact Type High Voltage Detector for presence of Voltage from 50V to 132kV with Buzzer and Light Indication	11500
275HP	Non Contact type, Light and Buzzer Indication, Detects Presence of High Voltage in AC Lines, 240V, 2KV, 6KV, 11KV, 22KV, 33KV, 132KV and 175KV Lines AC.	13000
276HD	Contact type, light and buzzer indication, detects presence of High Voltage in AC Lines, 354 to 1005mm length, detects 3kV to 24kV AC and 80 to 600V AC	14000
276SHD	Contact type, light and buzzer indication, detects presence of High Voltage in AC Lines, 230 to 880mm length, detects 3kV to 24kV AC and 80 to 600V AC	16000
290HD	Contact type, Light and Buzzer indication, detects presence of High Voltage in AC Lines, expandable from 1370mm to 2450mm, detects 3kV to 81.5kV AC	21000
Hot Line Indicator		
6.6kV	Hot Line Indicator, Neon Glow type for 6.6kV	7500
11kV	Hot Line Indicator, Neon Glow type for 11kV	9000
33kV	Hot Line Indicator, Neon Glow type for 33kV	11200
# Hot Line Indicator with Neon glow and audible buzzer both are also available. Please refer back for their price.		

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Hour Meter		
NE 045/7S DC	7 Digits, measures up to 99999.99 hours, 10 - 48V DC operated, 46 x 46 mm sq size panel cutout	720
NE 045/7	7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout	500
HM-01	7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout	450
Infra Red Temperature Calibrator		
BB-550	Black Body Source for Calibrating Infra Red Thermometer from 50 to 500 Degree C	67500
Insulation Tester		
IT-500	Test Voltage: 500V, Insulation Resistance Range: 0 - 1000M.Ohms, with AC Voltage Test Facility	1800
IT-1000	Test Voltage: 1000V, Insulation Resistance Range: 0 - 2000M.Ohms, with AC Voltage Test Facility	1900
Integrated Meter		
CE-0303IM	Three Phase Three Wire Two Element loads for energy and power measurement, measure each phase I, V, Hz, PF, KW, KVA, KVAh, KVAh, KVAh and MDI	5750
CE-0304IM	Three Phase Four Wire Three Element loads for energy and power measurement, measure each phase I, V, Hz, PF, KW, KVA, KVAh, KVAh, KVAh and MDI	5750
Kelvin Double Bridge		
KDBR	Oxford Brand Kelvin Double bridge, with spot reflecting galvanometer, High Current DC power supply and wooden stand for specimen	45000
Logic Probe Cum Pulser		
METRAVI CHY-625	Logic Probe Cum Pulser for maximum input of 50MHz	2200
Laser Distance Meter		
LDM-40H	Laser Distance Meter to measure up to 40m, with Area / Volume Calculations	4300
LDM-100H	Laser Distance Meter to measure up to 100m, with Area / Volume Calculations	5600
LDM-100	Laser Distance Meter to measure up to 50m, with Area / Volume Calculations	6750
Metal Detector		
MD-300	High Sensitive Metal Detector with a circular sensor, the detector vibrates and provides audible alarm on detecting metal	1400
SUPER-V	High Sensitive Metal Detector with a straight sensor, the detector vibrates, provides visual and audible warning on detecting metal	2400
Million MegOhms Meter		
MMM-1	Analogue Million MegOhms Meter for test voltage of 100, 200, 300, 400 and 500V, measures up to 10 Million MegOhms	
Mixed Signal Oscilloscope		
MSO-5062D	60MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate	64000
MSO-5102D	100MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate	69500
MSO0-5202D	200MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate	80000

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Motor Checker		
MC-22	Electric Motor Checker with analogue display	22000
MC-22D	Digital Motor Checker with insulation resistance test of 1000V	30000
MC-38D	Digital Motor Checker with insulation resistance test of 500 and 1000V	16000
Multifunction Environment Meter		
ET-2	Four-in-One Digital dB, Lux, temperature and Humidity meter with RS-232C PC Interface cable and software	5200
ET-3	Six-in-One Digital dB, Lux, Humidity, temperature, Multimeter and AC Voltage Detector	6400
Multi-point Temperature Indicator		
DTI-101M 6 CH	6 Channel Digital Multi-Point Temperature Indicate for K, J,R, S, PT-100 (Any One) type of sensor	3200
DTI-101M 12 CH	12 Channel Digital Multi-Point Temperature Indicate for K, J,R, S, PT-100 (Any One) type of sensor	3400
Non Contact Temperature Controller		
IT-91	Infra Red Temperature controller for -50 to 950 Degree C, 50:1 D:S Ratio, adjustable emissivity, relay output, controller cut out 72 x 72 mm sq	17500
Oil Test Set		
50-OTS	50kV Manually operated Oil Test Set	24000
50-MOTS	50kV Motor operated Oil Test Set	29500
60-OTS	60kV Manually operated Oil Test Set	24500
60-MOTS	60kV Motor operated Oil Test Set	30500
70-OTS	70kV Manually operated Oil Test Set	32000
70-MOTS	70kV Motor operated Oil Test Set	37500
75-OTS	75kV Manually operated Oil Test Set	33500
75-MOTS	75kV Motor operated Oil Test Set	40600
80-OTS	80kV Manually operated Oil Test Set	40600
80-MOTS	80kV Motor operated Oil Test Set	47000
90-OTS	90kV Manually operated Oil Test Set	45000
90-MOTS	90kV Motor operated Oil Test Set	51000
100-OTS	100kV Manually operated Oil Test Set	49700
100-MOTS	100kV Motor operated Oil Test Set	56000
120-OTS	120kV Manually operated Oil Test Set	71000
120-MOTS	120kV Motor operated Oil Test Set	85200
Digital Meters for above, extra to be paid		1000
Oscilloscopes		
OS-5010A	10MHz Single Channel, Cathode Ray Oscilloscope	14500
OS-5020	20MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with 1:1 and 10:1 probes	26500
OS-5020C	20MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with component test facility, comes complete with 1:1 and 10:1 probes	28520
OS-5030	30MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with 1:1 and 10:1 probes	28500
OS-5030C	30MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with component test facility, comes complete with 1:1 and 10:1 probes	20500
OS-5060	60MHz Dual Channel Four Trace Cathode Ray Oscilloscope with 1:1 and 10:1 Probes	62000
OS-5100	100MHz Dual Channel Four Trace Cathode Ray Oscilloscope with 1:1 and 10:1 Probes	70000

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Oscilloscope		
700S		58000
760	20MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software	97000
7100	100MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software, sampling rate 1GSa/Sec	257000
7200	200MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software, sampling rate 1GSa/Sec	330000
PC Based Oscilloscope		
DSO-2090	Dual Channel 40MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software	25000
DSO-2150	Dual Channel 60MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software	30000
DSO-2250	Dual Channel 100MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software	39000
PC Based Function Generator		
DDS-3005	5MHz PC Based Function generator with AM FM Modulation and TTL output along with sine, square, tri-angle, saw-tooth etc. with USB PC Interface cable and software	46000
PC Based Logic Analyzer		
LA-5034	34 Channel PC Based Logic Analyzer, with precision gripper, USB PC Interface cable and software	35000
Power Guard		
PG-01	Multifunction Power Meter, works on 6A, 230V, indicates, voltage, current, power factor, Power, KWh, Calculates CO2 emission, Calculates total time the equipment is under test and calculates the cost of electricity consumed accordingly. During load shedding the instrument memorizes the readings, ideal for analyzing power consumed for different kinds of loads	1900
Primary Current Injection Test Set		
	Please check ANNEXURE - 3	
Refrigerant Gas Leakage Detector		
RLD-01	16" Gooseneck sensor, detects all CFC Refrigerants such as R-22, R-124, R-11 and R-12 etc.	9500
Relay Test Set		
RNT-5	Relay Test Set, with current output upto 200A in various ranges	28400
RNT-5A	Relay Test Set with 200A in various ranges, Burden 1KVA, with AC/DC Voltage output	49000
RNT-33	Relay Test Set suitable for testing distance relay, 3 phase current / voltage output and Fixed DC Voltage output	175000
ZNT-34	Relay Test Set suitable for testing distance, over voltage relays etc., Variable three phase Voltage / Current and variable DC Voltage outputs	213000
Rotating Machine Tester		
RMT-01 NEW!!	One Single Meter that can test rotating machine, from insulation resistance to low resistance milli Ohms combined with a built-in T-RMS multimeters, Data logger, with Low pass Filter, Blue tooth Interface, Can measure AC/DC Voltage 1000V, DC/AC Current 10A, Resistance, Capacitance 5mF, Frequency 50Mhz, Temperature up to 1200 Degree C, Insulation Resistance can be measured up to 5000M.Ohms at test voltag of 50V / 100V / 250V / 500V / 1000V, with polarisation index and DAR, Low resistance from 1 m.Ohms to 2000 Ohms,	28500

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
RPM METER		
CTR-49	6 Digits Red LED Display, Event Counter, 1 to 999999 Counts, 96 x 48 mm sq	2200
Short Turn Indicator		
EFD	Electric Fault Detector, to be used with more than two identical windings like general motors and transformers	19000
Little Giant	9V Battery operated, to be used in single coils, simple insertion of coil on mandrill.	15000
Socket Polarity Tester		
ST-09	Socket Polarity Tester to be used for currents up to 6A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral.	675
ST-09A	Socket Polarity Tester to be used for currents up to 16A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral.	710
ST-09B	Socket Polarity Tester to be used for currents up to 6A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral. This can also be used for leakage test of up to 30mA	750
Sound Level Calibrator		
SC-05	Sound Level Calibrator provides signals of 94dB and 114dB	9250
Solar Power Meter		
207	Solar Power Meter, to measure the amount of sunlight falling on the solar panel or any surface exposed to sunlight	5550
Spectrum Analyzer		
AT-5010	1050MHz Spectrum Analyzer	89000
AT-5011	1050MHz Spectrum Analyzer With Marker Generator	139000
Static Charge Meter		
SC-291 NEW!!	Measuring range : 0~ +/- 20.000KV, Measuring distance : 2.54cm(1 inch), Warning alarm setting, DATA / PEAK hold. Backlight function, Auto power off with disable function, Zero function and low battery indicate, Manual data memory storing 99 data sets.	25000
Tachometer (Non Contact type) Calibrator		
CE-0102TMC	Calibrator for Non Contact Tachometer for up to 199,999RPM	12000
Transistor Tester		
TT-01	Transistor Tester for Testing and Checking Bias Current and other parameters of Transistors	4650
Tap Position Indicator		
CE-0102V	Digital type, Panel Mounting, Tap Position indicator, 96mm sq or 96x48 mm sq	1400
Time Totalizer		
TT-300	6 Digits LED Display, 96 x 48 mm sq, Auto range from 9999.99 to 999999Hrs.	1875
TT-302	6 Digits LED Display, 96 x 96 mm sq, Auto range from 9999.99 to 999999Hrs.	2000

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
Transformer Turns Ratio Set		
TTRS-100	Transformer Turns Ratio Set to measure ratio in the range of 0.800 to 2021 & for Phase Deviation Measurement	76000
Two Color Infra Red Thermometer		
ST-300A		310000
ST-300B		310000
ST-300C		337500
Ultrasonic Thickness Gauge		
UTG	Versatile Ultrasonic Thickness Gauge to measure thickness of high density material up to 200mm	11500
Vibration Meter		
VIB-30+	Digital Vibraton Meter, measures RMS velocity in the range of 0.1 to 199.9 mm/sec T-RMS & Peak	21500
AVD-80	Digital Vibration Meter, measures velocity, acceleration and displacement	29000
BCA-111	Bearing Condtion Analyzer, measures bearing test, vibration and has in-built tachometer.	124000
908	Measures velocity, acceleration and displacement along with the temperature, comes complete with the magnetic Base	17500
PVB-820	Pen Type Vibration Meter, it can measure accelleration, velocity and displacement	15000
VT-141 NEW!!	Dual Channel Vibration meter, Wide frequency range of 10Hz to 5KHz, Acceleration, velocity and displacement, Vibration sensor with magnetic adapter on 1.2M (47.2) cable, Frequency Lo range : 10Hz~1KHz meets ISO 2954 measurement, Hi range : 10Hz~5KHz, MAX record, Auto power off with disable function	73000
VT-141D NEW!!	Dual Channel Vibration meter, Wide frequency range of 10Hz to 5KHz, Acceleration, velocity and displacement, Vibration sensor with magnetic adapter on 1.2M (47.2) cable, Frequency Lo range : 10Hz~1KHz meets ISO 2954 measurement, Hi range : 10Hz~5KHz, MIN/MAX record and recall, Data logger with 9999 records capacity, USB interface, Auto power off with disable function	78000
Voltage Transducer		
CE-0102VT	Voltage Transducer with single Output	3200
Video IR Thermometer		
VIT-20	Dual Laser Pointer, Color Display, Video and Still picture recording, In-built Countact Thermometer, uSD Card & PC interface, -50 to 1850°C, Adjustable Emissivity, D:S 50:1	55000
Weather Station		
WH-1081PC	Weather station, for prediction of weather and recording of temperature, humidity, wind chill, dw point, rainfall, wind speed, air pressure and storm warning	30000
Wet Bulb Globe Temperature Meter		
WBGT-188 NEW!!	Quick-response capacitance sensor, accurate measurement for wet bulb globe temperature(WBGT), black globe temperature(TG), humidity(%RH), air temperature(TA), wet bulb(WET) and dew point(DEW). Max/Min and data hold, Low battery indication, LCD display with LED backlight, Viewing data records, Switch the temperature unit to °C or °F, Brass black ball in 50mm diameter, WBGT alarm setting, Auto power off with disable function	14500

CATEGORY / MODEL No.	DETAILS	LIST PRICE in Rs.
WBGT-188D NEW!!	Quick-response capacitance sensor, accurate measurement for wet bulb globe temperature(WBGT), black globe temperature(TG), humidity(%RH), air temperature(TA), wet bulb(WET) and dew point(DEW). Max/Min and data hold, Low battery indication, LCD display with LED backlight, Viewing data records, Switch the temperature unit to °C or °F, Brass black ball in 50mm diameter, WBGT alarm setting, Auto power off with disable function, Data logging capacity: 12000 records, USB PC serial interface, Sampling interval: Max 24 hours; Min 1 Second	22000

Wheatstone Bridge		
WSB	OXFORD Brand Wheatstone Bridge	15200

TERMS & CONDITIONS	
VALIDITY:	PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE
PRICES:	NETT, EX GODOWN KOLKATA
PACKING:	PRICES INCLUSIVE OF PACKING CHARGES
FREIGHT:	PRICES INCLUSIVE OF FREIGHT CHARGES, THROUGH OUR NOMINATED COURIER, BY SURFACE MODE ONLY, INCASE IF GOODS ARE REQUIRED BY ANY OTHER COURIER, OTHER THAN OUR NOMINATED COURIER ANY BY AIR, THEN THE FREIGHT SHALL BE CHARGED
DELIVERY:	READY STOCK SUBJECT TO PRIOR SALES, FOR HIGH VOLTAGE EQUIPMENTS 8-12 WEEKS DELIVERIES WILL BE MADE ONLY AFTER THE PAYMENT IS CREDITED TO OUR ACCOUNT
INSURANCE:	TO BE CONVERED BY THE BUYER THE GOODS WOULD BE PACKED SECURELY WITH OUR BEST INTENT TO PROTECT IT AGIANST ANY KIND OF DAMAGE, HOWEVER, IN CASE IF THE GOODS GETS DAMAGED IN TRANSIT THE BUYER WILL HAVE TO COVER ITS RISK
PAYMENT:	100% AGAINST PERFORMA INVOICE / DOD / THROUGH BANK 'ALTERNATIVELY' IF IT'S A TAILOR MADE PRODUCT 25% ADVANCE WITH THE ORDER BALANCE AGAINST PERFORMA INVOICE / DOD / THROUGH BANK
SHIPMENT:	SHALL TAKE PLACE WITHIN 48 HOURS OF RECEIPT OF PAYMENT
GOODS & SERVICE TAXES:	GST SHALL BE CHARGED EXTRA @18%. THIS SHALL ALSO BE CHARGED ON THE FREIGHT
ORDERING VALUE:	FOR ORDER VALUE LESS THAN RS.3000/- (RUPEES THREE THOUSAND) A CHARGE RS. TWO HUNDRED AS HANDLING CHARGES WILL BE LEVIED
DISCLAIMER:	WE TRY OUR BEST TO USE THE BEST OF COURIERS POSSIBLE FOR EARLIEST DELIVERY TIME BUT HAVE NO CONTROL OVER THE DELIVERIES BY THE COURIER. YOU MAY SUGGEST THE COURIER OF YOUR CHOICE AND WE SHALL SHIP THE GOODS THROUGH THEM, IF POSSIBLE. HOWEVER IN EITHER CASE, WE ARE NOT BE HELD RESPONSIBLE, UNDER ANY CIRCUMSTANCES, IF THE COURIER DELAYS THE DELIVERY FOR WHATSOEVER REASON.
JURISDICTION:	SUBJECT TO KOLKATA JURISDICTION ONLY

THIS SUPERCEDES ALL PREVIOUS PRCE LISTS

BANK DETAILS:	
Bank Name	HDFC BANK LTD
Account Name	METRAVI INSTRUMENT PVT. LTD.
Type of Account	CURRENT ACCOUNT
Address of Bank:	31, G. C. AVENUE, KOLKATA - 700013
Account Number:	50200007518712
NEFT Code	HDFC0000382