

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---------------------------------|--|----------------|----------|
| AC High Voltage Test Set | | | |
| ACHV | On Request | | |
| Acidity Testing Kit | | | |
| ATK | Testing Kit used to measure the Acidic content of Transformer Oil | 2043 | 90308990 |
| AC Power Supply | | | |
| APS-6003 NEW!! | | 33271 | |
| APS-6006 NEW!! | | 43323 | |
| APS-60031 NEW!! | | 38297 | |
| APS-4002 NEW!! | | 56244 | |
| APS-4003 NEW!! | | 71595 | |
| APS-4005 NEW!! | | 81700 | |
| APS-7002 NEW!! | | 71595 | |
| APS-7004 NEW!! | | 83850 | |
| APS-7008 NEW!! | | 142975 | |
| APS-51005 NEW!! | | | |
| APS-51008 NEW!! | | | |
| APS-51010 NEW!! | | | |
| APS-51015 NEW!! | | | |
| APS-51020 NEW!! | | | |
| APS-51030 NEW!! | | 913750 | |
| APS-51050 NEW!! | | | |
| APS-51075 NEW!! | | | |
| APS-51100 NEW!! | | | |
| Analogue Clamp Meter | | | |
| M-300 | Clamp Jaw Dia 34mm, AC/DC Voltage, AC Current up to 300A, Resistance & Temperature. Pointer Lock Facility, with temperature probe | 2795 | 90303100 |
| M-600 | Clamp Jaw Dia 34mm, AC/DC Voltage, AC Current up to 600A, Resistance & Temperature. Pointer Lock | 3118 | 90303100 |
| M-1000 | Clamp Jaw Dia 48mm, AC Voltage up to 600V, DC Voltage up to 300V, AC Current in the range of 0-50/250/500/1000A AC, Resistance up to 2000K. Ohms, Temperature, Audible continuity Test | 4838 | 90303100 |
| Analogue Multimeter | | | |
| 250TR | Measures AC/DC Voltage, DC Current, Resistance, Battery Test and dB. | 1064 | 90303100 |
| 260TR | Measurs AC/DC Voltage, DC Current, Resistance, Transistor Polarity Test, Audible Continuity | 1720 | 90303100 |
| 2010BA | Measures AC/DC Voltage, up to 10A AC/DC, Resistance, Transistor and Audible Continuity | 2526 | 90308990 |
| 5050E | Measures AC/DC Voltage up to 1000V, AC/DC Current up to 10A, Resistance up to 2000M.Ohms, Frequency up to 25kHz, Transistor Testing, Diode Testing and audible continuity testing | 3655 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|------------------------------|--|----------------|----------|
| 6060 | Measures AC / DC Voltage up to 2500V, AC/DC Current up to 10A, Resistance up to 10M.Ohms, Diode and continuity test facility | 13438 | 90308990 |
| Battery Impedance | | | |
| TM-6002 | Battery Impedance Tester to check Battery internal resistance, Voltage, Current and temperature, with 9999 memory, with PC Interface cable and software | 87075 | 90308990 |
| Bench Type Multimeter | | | |
| 45 T-RMS | 4-1/2 Digits Bench type Multimeter | 10266 | 90308990 |
| 55 TRMS NEW!! | | 54825 | 90308990 |
| M-3511 | 6-1/2 Digits Bench type Multimeter AC/DC V, AC/DC Current, Resistance, Cap and Frequency | 72025 | 90308990 |
| M-3510A NEW!! | 6-1/2 Digits Bench type Multimeter AC/DC V, AC/DC Current, Resistance, Cap., Temp. and Frequency | 89225 | 90308990 |
| M-3500A | 6-1/2 Digits Bench type Multimeter with multiple options | 117954 | 90308990 |
| Cable Fault Locator | | | |
| CFL-01 | Digital Cable Locator and Combined with Cable Fault locator | 19888 | 90308990 |
| CFL-02 | Digital Cable Fault Locator for Power, Control and Telecom Cables burries underground | 69875 | 90308990 |
| Calibrator | | | |
| CAL-408 | Bench type RTD Calibrator , Outputs available at -200, -100, -50, -25, 0, 25, 50, 100, 150, 200, 300, 400, 500, 600 °C | 8063 | 90308990 |
| CAL-400-3 | Hand Held, 3-1/2 Digits, Battery Operated, 0 - 19.99 /24mA, -199.9mV to 199.9mV source and current & power measurement | 5913 | 90308990 |
| CAL-400-4 | Hand Held, 4-1/2 Digits, Battery Operated, 0 - 199.9 mV / 0 - 19.999mA sourcing and measuring range | 8600 | 90308990 |
| CAL-402-4 | Bench type, 230V AC 50Hz Operated, 0 - 199.99m/ 1.9999 / 19.999V & 0 - 199.99u/1.999m / 19.999mA Sourcing & Measuring | 9675 | 90308990 |
| CAL-500 | Hand Held, 4 Digits Large LCD Display, Measures and Provides output for 20mV / 100mV / 15V DC, Current output up to 24mA, 24V Loop Power, and outputs for K, E, J, T, R, S, B and N types of thermocouples | 25800 | 90308990 |
| 01+ | 5 Digits 0.5% Accuracy, Source for Volt, Resistance, Pt-100, Cu-50, Thermocouples R, S, B, E, K, J, T, N types. | 26338 | 90308990 |
| 03+ | 5 Digits 0.5% Accuracy, Sources and Measures Resistance, PT-100 Sensor and Cu-50 Sensors | 26338 | 90308990 |
| 05+ | 5 Digits, 0.5% Accuracy, Sources DC Current, Analogue Transducer & Loop Power and Measures DC Voltage, DC Current and Loop Current | 30100 | 90308990 |
| 11+ | 6 Digits, 0.2% Accuracy, Sources R, S, B, E, K, J, T, N types of thermocouples, PT-100, Cu-50, DC Voltage, DC Current, Resistance, Analogue Transducer, Frequency, Pulse Output and LOOP Power. | 77400 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|--|--|----------------|----------|
| 14+ | 6 Digits, 0.2% Accuracy, Sources and Measures DC Voltage, PT-100, Cu-50 Sensors and R, S, B, E, K, J, T & N types of Thermocouples. | 77400 | 90308990 |
| 15+ | 6 Digits, 0.2% Accuracy, Sources and Measures DC Voltage, DC Current, Analogue Transducer and LOOP Power. | 77400 | 90308990 |
| 25 NEW!! | 50,000 Counts, 0.2% Universal Calibrator for DC Voltage, Current, Resistance, Frequency, all thermocouples and thermo-resistance and for | 268750 | 90308990 |
| 709H | mA Loop Calibrator with HART COMMUNICATOR, Accuracy 0.01% | 102125 | 90308990 |
| 709H-USB | USB COMMUNICATION INTERFACE CABLE AND SOFTWARE for 709H | 43000 | 90308990 |
| VIB-CAL-01 NEW!! | Vibration Calibrator | 219300 | 90308990 |
| CAL-ER NEW!! | Earth Resistance Tester Calibrator | 34400 | |
| | | | |
| Carbon Mono Oxide Meter | | | |
| CO-05 NEW!! | | 15319 | |
| CO-09 | Detects Presence of Carbon Mono-Oxide. Range 0 to 1000PPM, Backlit LCD | 15050 | 90308990 |
| CO-10 | Detects Presence of Carbon Mono-Oxide. Range 0 to 1000PPM, Backlit LCD, With Audio and Buzzer Alarm | 16125 | 90308990 |
| CO-110 NEW!! | Compact Carbon Monoxide Detector with audio & visual alarms | 16125 | |
| | | | |
| | | | |
| Clamp On Ground Resistance Tester | | | |
| | | | |
| CET-01 | 4 Digits LCD, 28mm Clamp Jaw Dia, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms | 27950 | 90308990 |
| CET-02 | 4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms | 27950 | 90308990 |
| CET-03 | 4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 20A. | 34400 | 90308990 |
| CET-04 | 4 Digits LCD, 28mm Clamp Jaw Dia, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms. With Leakage Current Measurement up to 20A. | 37195 | 90308990 |
| CET-05 | 4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms | 24725 | 90308990 |
| CET-06 | 4 Digits LCD, 28 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms | 24725 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|---|----------------|----------|
| CET-02EX | Explosion Proof Clamp On Ground Resistance Tester, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 20A. | 38593 | 90308990 |
| CET-09 NEW!! | | 59125 | |
| Coatmeter | | | |
| CTG-01 | Measures coating thickness on both ferrous and Non Ferrous materials | 11395 | 90318000 |
| CTG-02 | Measures coating thickness on both ferrous and Non Ferrous materials with extended flexible cable with sensor | 21446 | 90308990 |
| CTG-03 NEW!! | Coating Thickness Gauge with USB Interface. Single probe for coating measurements, for both ferrous and non-ferrous metal substrates. | 12900 | |
| Combustible Gas Leakage Detector | | | |
| GLD-01 | 16" Gooseneck detector for detecting Combustible Gas Leakage. With Audio and Visual Alarm | 5870 | 90308990 |
| Current Transducer | | | |
| CE-0102CT | Current Transducer, AC Current Input and DC output | 3601 | 90308990 |
| Data Logger for Sound Level | | | |
| DL-SL01 | Sound Level Data logger to record sound, from 30 to 130 dB, with 129920 data Points | 12911 | 90308990 |
| Data Logger for Temperature & Humidity | | | |
| DL-TH-01 | Temperature and Humidity Data Logger with digital display and data logging up to 32700 points | 5053 | 90308990 |
| DL-TH-02 | Dry Ice Data Logger for to -80~70°C(-112~158°F), 17280 records, USB interface and IP67 protection | 7525 | 90308990 |
| Data Logger for Voltage and Current | | | |
| DL-VL-01 | Data Logger for Voltage and Current with digital display and 100096 data points | 15803 | 90308990 |
| DC High Voltage Test Set | | | |
| DCHV | On Request | | 90308990 |
| DC Regulated Power Supply | | | |
| RPS-3002 | Single Output with Backlit LCD Display of Variable 0 - 30V / 0 - 2A DC | 8546 | 90308990 |
| RPS-3005 | Single Output with Backlit LCD Display of Variable 0 - 30V / 0 - 5A DC | 8546 | 90308990 |
| RPS-6005 | Single Output with Backlit LCD Display of Variable 0 - 60V / 0 - 5A DC | 20963 | 90308990 |
| RPS-3010 | Single Output with LED Display of Variable 0 - 30V / 0 - 10A DC | 20909 | 90308990 |
| RPS-3020 | Single Output with LED Display of Variable 0 - 30V / 0 - 20A DC | 30100 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|----------------------------------|--|----------------|----------|
| RPS-3030 | Single Output with LED Display of Variable 0 - 30V / 0 - 30A DC | 66650 | 90308990 |
| RPS-6010 | Single Output with LED Display of Variable 0 - 60V / 0 - 10A DC | 39399 | 90308990 |
| RPS-6030 | Single Output with LED Display of Variable 0 - 60V / 0 - 30A DC | 120400 | 90308990 |
| RPS-3002-2 | Dual Output with Backlit LCD Display of Variable 0 - 30V / 0 - 3A DC | 16663 | 90308990 |
| RPS-3005-2 | Dual Output with Backlit LCD Display of Variable 0 - 30V / 0 - 5A DC | 20855 | 90308990 |
| RPS-3003-3 | Triple Output with Backlit LCD Display, Dual 0 - 30V / 0 - 3A DC and Fixed 5V/3A | 16448 | 90308990 |
| RPS-3005-3 | Triple Output with Backlit LCD Display, Dual 0 - 30V / 0 - 5A DC and Fixed 5V/3A | 20855 | 90308990 |
| RPS-3010-2 NEW!! | Dual Output with Backlit LCD Display, Dual 0 - 30V / 0 - 10A DC | 50616 | 90308990 |
| RPS-10003 NEW!! | Single Output with LED Display of Variable 0 - 100V / 0 - 03A DC | 29563 | 90308990 |
| RPS-20002 NEW!! | Single Output with LED Display of Variable 0 - 200V / 0 - 02A DC | 34400 | 90308990 |
| | | | |
| | | | |
| DDS Function Generator | | | |
| DDS-30 NEW!! | 5 MHz DDS Function generator, 125MSa/s sampling rate | 22038 | 90308990 |
| DDS-60 NEW!! | 5 MHz DDS Function generator, 125MSa/s sampling rate | 27413 | 90308990 |
| DDS-1010 | 10 MHz DDS Function generator, 125MSa/s sampling rate | 23650 | 90308990 |
| DDS-1025 | 25 MHz DDS Function generator, 125MSa/s sampling rate | 43323 | 90308990 |
| DDS-1060 | 50 MHz DDS Function generator, 125MSa/s sampling rate | 64500 | 90308990 |
| DDS-1080 NEW!! | 80MHz DDS Function generator, 320MSa/s sampling rate | 113950 | 90308990 |
| DDS-1120 NEW!! | 120MHz DDS Function generator, 320MSa/s sampling rate | 146200 | 90308990 |
| | | | |
| Digital AC/DC Clamp Meter | | | |
| DT-725 | 3-5/6-digit 5999 Count, Backlight LCD, T-RMS, Auto-Ranging, NCV, Flashlight, Relative Measurement, AC (750V)/DC(1000V) Voltage, 600A AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity. Square Wave Output, CAT-IV 600V | 2956 | 90303100 |
| DT-230 | 3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 400A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test. | 5106 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|------------------------|---|----------------|----------|
| DT-325 | 3-3/4 Digits 3999 Counts, Digital AC/DC Clamp Meter, Confirming to CAT-III 300V, Jaw Size 28 mm, Auto Power Off, Data Hold, AC/DC Voltage up to 600V, AC/DC Current up to 400A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test Facility | 3720 | 90308990 |
| DT-6250 | 3-3/4 Digits, LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Current up to 400A, Resistance, Frequency, Duty Cycle, Capacitance, Diode and Continuity Test. | 5913 | 90308990 |
| DT-1350 | 3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A AC/DC Clamp Meter with AC/DC Voltage, Resistance, Diode and Continuity Check | 2903 | 90303100 |
| DT-1350A | 3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A AC/DC Clamp Meter with AC/DC Voltage, Resistance, Capacitance, Temperature and Frequency | 3333 | 90303100 |
| DT-1350AT NEW!! | 3-5/6 digit, 6000 Counts, backlit LCD, Measure TRMS AC/DC Current & Voltage, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity. Protected in all ranges. | 3440 | 90303100 |
| DT-3690 | 3-4/5 Digits 6000 Counts, LCD, Data Hold,T-RMS, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 1000A, Resistance,Capacitance, Frequency and Temperature & Continuity Test | 3978 | 90303100 |
| DT-425T | 3-3/4 Digits 3999 Counts Backlit LCD, T-RMS AC/DC Clamp meter, Confirms to CAT-III 600V, Data Hold, MAX/MIN, Relative, In-Built Flash Light, Overload Protection, 30mm Clamp Jaw Dia, Auto Power Off, AC T-RMS / DC Current 600A, AC T-RMS / DC Voltage 600V, Resistance, Capacitance, Temperature, Frequency, Non Contact Voltage Detector, Diode and Cotinuity Test | 5913 | 90308990 |
| DT-3250 | 3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC Voltage, 1000A DC/AC Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V | 7203 | 90308990 |
| DT-3600 | 3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage,1200A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V | 7418 | 90308990 |
| DT-4250 | 3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Duty Cycle, Diode & Continuity Test. | 7418 | 90303100 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|----------------------|---|----------------|----------|
| DT-5250 | 3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, T-RMS, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test. | 7740 | 90303100 |
| DT-8250 | 3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC Voltage, 2000A DC/AC Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V | 7955 | 90308990 |
| DT-9250 | 3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage, 2000A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V | 9138 | 90308990 |
| 2003A NEW!! | 3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage, 2000A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V | 9138 | 90303100 |
| METRACLAMP-15 | 3999 Counts, Backlit LCD, 52mm jaw Dia, Non Contact Voltage Detector, Auto Power Off, T-RMS, AC/DC Voltage, AC T-RMS/DC 1000A, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test, double Injection mould, CAT-IV 600V | 8493 | 90308990 |
| METRACLAMP-20 | 4-3/4 Digits, 40,000 Counts, Backlit, T-RMS, Autoranging, 52mm Jaw Dia, Non Contact Voltage Detector, Fully Protected, AC/DC Voltage, AC/DC Current up to 1500A, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Diode and Continuity Test | 12900 | 90308990 |
| PRO Solar-2 | 6000 Counts, Auto-Backlit LCD Display, 1000V DC/AC T-RMS, Specially designed for PV Application to measure 2000V DC/1500V AC, DC/AC T-RMS 600A, Resistance up to 600k Ω , Temperature up to 400°C, Capacitance up to 1000 μ F, Frequency up to 10kHz, Continuity and Diode Test, Optionally can connect to flexible clamp to measure up to 3000A AC. Designed to meet IEC/EN 61010-1, IEC/EN 61010-2-033 CAT IV 600V/CAT III 1000V, Max Conductor Dia 37mm, High Frequency Rejection, In-rush current measurement. | 29778 | 90303100 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|--|----------------|----------|
| PRO 474 | 6000 counts, digital AC/DC T-RMS clamp meter, TFT LCD display, Bluetooth, 1000V AC T-RMS /DC, 1000A AC T-RMS/DC, 34mm Jaw, 10" Flexible Clamp adaptor for upto 3000A AC, AC+DC Voltage, Inrush Current, VFD AC T-RMS Voltage, Lo-Z Voltage, NCV, Capacitance, Resistance, Frequency, Temperature, Continuity and Duty Cycle, Free APP, Datalogging, Trend Capture on device and APP simultaneously | 24188 | 90303100 |
| PRO 419 | 3-3/4 Digit Professional T-RMS AC/DC Clamp Meter, 4000 Count, 1000V AC T-RMS/DC, 1000A AC T-RMS/DC, Auto Power Off, Non Contact Voltage Detector, Flashlight, Data Hold, MAX-MIN Record, Relative Measurement, 100mF Capacitance, 100kHz Frequency, 40MOhms Resistance, 1000°C Temperature measurement using K type sensor, Continuity. | 7203 | 90303100 |
| PRO 421 NEW!! | 3 5/6 Digits TRMS Clamp Meter, 6000 Counts, 1000V AC/DC, 1000A AC/DC with LoZ, Inrush, Peak, VFD, Capacitance, Frequency, Resistance, Temperature, Continuity Test, NCV | 7955 | 90303100 |
| PRO Solar-3 NEW!! | Professional T-RMS Industrial AC/DC Clamp Meter with TFT Colour Display with Bluetooth and IP65. High accuracy & 1500V DC for Solar & Photovoltaic Applications. In-rush current and VFD measurement for all Motor Applications. | 20963 | 90303100 |
| | | | |
| Digital Ammeter | same | | |
| CE-0102A 96x48 | 3-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 48 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A | 1075 | 90303310 |
| CE-0102A 96x96 | 3-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 96 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A | 1075 | 90303310 |
| CE-0102A 96x48 | 3-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 48 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A | 1183 | 90303310 |
| CE-0102A 96x96 | 3-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 96 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A | 1183 | 90303310 |
| N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size | | | |
| | | | |
| CE-0102A 96x48 | 4-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 48 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A | 2365 | 90303310 |
| CE-0102A 96x96 | 4-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 96 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A | 2365 | 90303310 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|-----------------------------------|---|----------------|----------|
| CE-0102A 96x48 | 4-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 48 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A | 2365 | 90303310 |
| CE-0102A 96x96 | 4-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 96 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A | 2365 | 90303310 |
| Digital Ammeter Controller | | | |
| CE-0102AC 1SP | Digital Ammeter with Single Set Point to control the current below a given set point. Size - 96 x 96 mm sq. With 1NO + 1NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One) | 3763 | 85359030 |
| CE-0102AC 2SP | Digital Ammeter with Two Set Point to control the current below a given pair of set points. Size - 96 x 96 mm sq. With 2NO + 2NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One) | 4193 | 85359030 |
| Digital Anemometer | | | |
| AVM-01 | 4 Digits Backlit LCD Display, Data Hold, Max Record, Measures Air Velocity up to 30m/Sec, measures in km/hr, ft/min, knots, mph as well, Displays Air Temperature -10 to 50 Degree C, Shows windchill and also displays Beaufort Wind Scale | 1881 | 90268090 |
| AVM-03 | Digital Thermo-Anemometer with facility to measure 40m/Sec, with humidity, CMM, CFM, USB PC Interface | 5375 | 90268090 |
| AVM-04 | Digital Thermo-Anemometer with facility to measure up to 45m/Sec and in ft/min also | 6128 | 90268090 |
| AVM-05 | Digital Thermo-Anemometer with facility to measure wind flow (CFM / CMM) | 7659 | 90268090 |
| AVM-07 | Digital Thermo-Anemometer to measure up to 30m/Sec with Metal Blades, Temp. -10 to 60°C / 14 to 140°F | 5483 | 90268090 |
| AVM-08 | Digital Thermo-Anemometer with facility to measure wind flow (CFM / CMM) with built in infra-red Thermometer to measure from -50 to 260°C with 8:1 D:S Ratio and Emissivity Fixed at 0.95 | 12868 | 90268090 |
| AVM-09 | Digital Thermo-Anemometer with facility to measure wind flow (CFM/CMM) with built in Pressure Meter | 19350 | 90268090 |
| AVM-10 | Digital Hot Wire Anemometer, Dual LCD, with RS-232 Interface, 0.1 to 20m/Sec and Temperature from -20 to 80°C / -5 to 175°F | 15050 | 90268090 |
| Digital Capacitance Meter | | | |
| DCM-1502 | 3-1/2 Digits, LCD, Zero Adjustment, up to 20mF Capacitance Measurement | 2849 | 90308990 |
| Digital Clamp Meter | | | |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|---|----------------|----------|
| DT-115 | 6000 Counts, Backlit LCD, With Flashlight, Autoranging, Auto Power Off, T-RMS, Non Contact voltage detection, Flashlight, Data Hold, 40 mm Jaw Size, AC/DC Voltage, AC Current up to 600A T-RMS, Capacitance, Frqueueency, Temperture, Ressitance, Continuity & Diode test. | 1914 | 90303100 |
| DT-115A | 6000 Counts Backlit LCD Display, Built-in Flashlight to access dark Areas, Non Contact Voltage Detection, Simple to use, Just provide the input and the instrument, detects the signal and displays the parameter, No Selection required, Just provide Input, Automatic Selection of AC/DC Voltage, Resistance, Capacitance, Diode Test, T-RMS, 600A T-RMS Measurements | 2338 | 90303100 |
| DT-369 | 3-4/5 Digits 6000 Counts, LCD, Data Hold, T-RMS, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance,Capacitance, Frequency and Temperature & Continuity Test | 2419 | 90303100 |
| DT-1150 | 3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A Clamp Meter with AC/DC Voltage | 1989 | 90303100 |
| DT-1150A | 3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A Clamp Meter with AC/DC Voltage, Resistance, Capacitance, Temperature and Frequency | 2419 | 90303100 |
| DT-225 | 3-1/2 Digits, Backlit LCD, Data Hold, Max Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Temperature, Frequency, Diode and Continuity Test. 500V DC/AC Protection in all ranges. | 3010 | 90308990 |
| DT-1250 | 3-1/2 Digits, Backlit LCD, Data Hold, Max Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Diode and Continuity Test. 500V DC/AC Protection in all ranges. | 3118 | 90308990 |
| DT-2250 | metra clamp | 3655 | 90308990 |
| DT-2255 | 3-1/2 Digits, LCD, Data Hold, Auto-ranging, 57mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test. | 3655 | 90308990 |
| DT-3150 | 3-3/4 Digits, Backlit LCD, Data Hold, 57mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Frequency, Duty Cycle, Diode and Continuity Test Facility. 1000V DC/AC Protection in all ranges. | 3763 | 90308990 |
| DT-7250 | 3-1/2 Digits, LCD, Data Hold, Auto-ranging, 57mm Jaw Size, AC/DC Voltage, AC Current up to 2000A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test. | 5913 | 90308990 |
| Digital Clamp Meter with Wireless PC Interface | | | |
| DT-5250W | 3-3/4 Digits, Backlit LCD, Peak & Data Hold, T-RMS, Wireless PC Interface, 30mm jaw size, AC/DC Voltage, AC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test | 10213 | 90308990 |
| Digital Clamp On Power Meter | | | |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|--|--|----------------|----------|
| 107F | 10000 Counts Digital Clamp On Power Meter, AC/DC Voltage and AC/DC Current Auto Detection, NCV, Jaw Dia 42mm, KW, PF, THD up to 25th Harmonics | 26338 | 90308990 |
| 307 | 6000 Counts, Backlit LCD, Single Phase and Three Phase, Non Contact Voltage Detector, Data Hold, Peak Hold, Relative, Max/Min Reocrd, Single Phase KW, KVA, KVA, PF, KWh and KW & PF for Three Phase. Clamp Jaw Size 56mm. AC Current up to1500A AC. | 16448 | 90308990 |
| 307N | 4 Digits, Dual LCD, Single Phase and Three Phase, Max /Min / Peak Hold, 55mm Jaw Dia, T-RMS, AC Voltage, AC Current up to 1000A, KW, KVA, KVAR, Power Factor, Phase Angle, KWh, Frequency and Temperature. With Data Logging and PC Interface | 9890 | 90308990 |
| 607 | 4 Digits, Dual LCD, Harmonic Analysis up to 50th Harmonic, PC Interface, Single Phase & Three Phase, Maximum Demand, KW, KVA, KVAR, KWh, KVAh, KVAh, Power Factor, Real time output of waveform, Power Parameters and Harmonics. Clamp Jaw Size - 55mm. | 76594 | 90308990 |
| Digital Distance Meter | | | |
| DM-09 | Digital Ultrasonic Distance Meter to measure up to 16m | 1881 | 90308990 |
| Digital Earth Resistance Tester | | | |
| ERT-1501 | 0 - 10 / 100 / 1000 Ohms, 4 Terminal with Testing Kit and Cables in hard carrying case | 7686 | 90303900 |
| ERT-1502 | 0 - 10 / 100 / 2000 Ohms, 4 Terminal with Testing Kit and Cables in hard carrying case | 8600 | 90303900 |
| | Rechargeable Battery and Battery Charger for above | 4730 | |
| PRO ERT-1635 NEW!! | Double Clamp, Multi-function, Earth and Grounding Resistance Tester for on-site measurement of grounding resistance, soil resistivity, grounding voltage, grounding line leakage current, AC current and DC resistance. Offers precision 4-wire method, 3-wire method and simple 2-wire method, selection method, double-clamp method to measure grounding resistance. | 83313 | 90303390 |
| PRO ERT-1602 NEW!! | Precision 4-wire, 3-wire and simple 2-wire measurement for Earth Resistance, Soil Resistivity, Earth Voltage and AC Voltage. Complete kit in hard carrying case. | 34938 | 90303390 |
| Digital Frequency Counter | | | |
| FC-2700 | 8 Digits Green LED Frequency Counter up to 2.7GHz | 9847 | 90308990 |
| Digital Frequency Meter | | | |
| CE-500F 99.99Hz | 4 Digits, Panel Flush Mounting, 96 X 48 mm sq, Input 10 - 500V, Measuring range 20 - 99.99 Hz. | 1322 | 90303310 |
| CE-500F 96 x 96 | 4 Digits, Panel Flush Mounting, 96 X 96 mm sq, Input 10 - 500V, Measuring range 20 - 99.99 Hz. | 1322 | 90303310 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|----------------------------------|--|----------------|----------|
| CE-500F 999.9Hz | 4 Digits, Panel Flush Mounting, 96 X 48 mm sq, Input 50 - 500V, Measuring range 0 - 999.9 Hz. | 1451 | 90303310 |
| CE-500F 96 x 96 | 4 Digits, Panel Flush Mounting, 96 X 96 mm sq, Input 50 - 500V, Measuring range 0 - 999.9 Hz. | 1451 | 90303310 |
| Digital IC Tester | | | |
| DICT-2040 | 40 Pin Digital IC Tester to test 54 / 74 series TTL and 4000 & 4500 series CMOS IC's, tests more than 2000 kinds of devices | 33701 | 90308200 |
| Digital Insulation Tester | | | |
| DIT-909 | 9999 Counts Backlit LCD, Low Battery Indication, Dat Hold, Timer Function up to 10mins, Comparator, 99 Data Records, USB PC Interface (optional) Test Voltage: 50V / 100V / 250V / 500V / 1000V, 200G. Ohms, AC Voltage T-RMS, DC Voltage, Freuqnecy, Capacitance, Continuity Test, With Remote Probe, IP-54 | 29133 | 90308990 |
| DIT-910 NEW!! | 4 Digits, with GO NO-GO functions, 250V/500M.Ohms, 500V/1G.Ohms, 1000V/2G.Ohms | 4730 | 90308990 |
| DIT-912 | 4 Digits with Analog Bargraph, measures upto 2000M. Ohms at 250V / 500V / 1000V, measures 600V AC/DC, Low Resistance up to 4000 Ohms and Continuity test. Fully Protected on all ranges | 10723 | 90308990 |
| DIT-913 | Digital Insulation Tester for 250V / 500V / 1000V / 2500V , 0-2000M(250V), 0-20G(500/1000/2500V) | 6128 | 90308990 |
| DIT-914 | Battery cum Mains Operated, with facility to measure AC Voltage, Low Resistance, Continuity, 500V/2000M. Ohms, 1000V/2000M.Ohms, 2500V/20G.Ohms, 5000V/200G.Ohms | 16985 | 90308990 |
| DIT-916 | Selectable testing voltages - one testing instrument for low and high voltage systems from 500/1000/2500 and 5000V, Insulation resistance measurement up to 1T Ω , User selectable programmable timer (10s to 30 min), Automatic discharge of test object after completion of measurement, Diagnostic tools, Polarization index (PI), Dielectric absorption ratio (DAR), USB PC Interface | 31175 | 90308990 |
| DIT-921 | Battery cum Mains Operated, with facility to measure, PI, DAR, AC Voltage, Low Resistance, Continuity, 500V/6G.Ohms, 1000V/6G.Ohms, 2500V/60G.Ohms, 5000V/60G.Ohms | 29025 | 90308990 |
| DIT-99A | Digital Battery Cum Mains Operated Insulation Tester for 100V / 200M.Ohms | 3064 | 90308990 |
| DIT-99B | Digital Battery Cum Mains Operated Insulation Tester for 250V / 200M.Ohms | 3064 | 90308990 |
| DIT-99C | Digital Battery Cum Mains Operated Insulation Tester for 500V / 1G.Ohms | 3064 | 90308990 |
| DIT-99D | Digital Battery Cum Mains Operated Insulation Tester for 1000V / 2G.Ohms | 3064 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|-------------------------|--|----------------|----------|
| DIT-321 | Digital Insulation Resistance Tester with Built-in Multimeter, 3-3/4 Digits 3999 Counts, Backlit LCD, Data Hold, Test Voltage: 250V / 500V / 1000V, upto 40G.Ohms, Measures AC/DC Voltage, AC/DC Current up to 400mA, Resistance, Capacitance, Frequency, Diode & Continuity Test Facility. | 4838 | 90308990 |
| DIT-322 | Digital Insulation Resistance Tester with Built-in Multimeter, 3-3/4 Digits 3999 Counts, Backlit LCD, Data Hold, Test Voltage: 500V / 1000V / 2500V, upto 40G.Ohms, Measures AC/DC Voltage, AC/DC Current up to 400mA, Resistance, Capacitance, Frequency, Diode & Continuity Test Facility. | 6450 | 90303100 |
| DIT-925 NEW!! | 5kV Insulation Resistance Tester featuring Insulation Resistance measurement (IR); Polarisation Index measurement (PI); Absorption Ratio (DAR); Ramp Test mode (RAMP) ; Filtered Resistance test (FR), Voltage measurement (V); Current measurement (nA). With touchscreen display. | 59125 | 90303900 |
| DIT-927 NEW!! | 10kV Insulation Resistance Tester featuring Insulation Resistance measurement (IR); Polarisation Index measurement (PI); Absorption Ratio (DAR); Ramp Test mode (RAMP) ; Filtered Resistance test (FR), Voltage measurement (V); Current measurement (nA). With touchscreen display | 65575 | 90303900 |
| DIT-930 NEW!! | Megohmmeter/ high-voltage insulation resistance tester, used for insulation resistance tests upto 5KV and 0.01MΩ ~ 10TΩ. Functions: Insulation resistance test, voltage test, current test, capacitance test. | 83850 | 90303900 |
| DIT-930E NEW!! | Megohmmeter/ high-voltage insulation resistance tester, used for insulation resistance tests upto 10KV and 0.01MΩ ~ 35TΩ. Functions: Insulation resistance test, voltage test, current test, capacitance test. | 91375 | 90303900 |
| DIT-930F NEW!! | Megohmmeter/ high-voltage insulation resistance tester, used for insulation resistance tests upto 15KV and 0.01MΩ ~ 50TΩ. Functions: Insulation resistance test, voltage test, current test, capacitance test. | 129000 | 90303900 |
| DIT-950 NEW!! | High Precision IR Tester 10kΩ to 50TΩ, used for rapid measurements on IR properties of electronic parts and components, dielectric materials, equipments, cables, etc. | 392375 | 90303900 |
| DIT-951 NEW!! | High Precision IR Tester 10kΩ to 100TΩ, used for rapid measurements on IR properties of electronic parts and components, dielectric materials, equipments, cables, etc. | 294550 | 90303900 |
| Digital VA Meter | | | |
| CE-0303VA | Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display | 4515 | 90303310 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|--------------------------------------|--|----------------|----------|
| CE-0304VA | Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display | 4515 | 90303310 |
| Digital VAR Meter | | | |
| CE-0303VAR | Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display | 4515 | 90303310 |
| CE-0304VAR | Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display | 4515 | 90303310 |
| Digital KWh Meter | | | |
| CE-0303EML | Digital KWh Meter with LCD Display for Three phase Three wire Two element loads | 5321 | 90283090 |
| CE-0304EML | Digital KWh Meter with LCD Display for Three Phase Four wire Three Element loads | 5321 | 90283090 |
| CE-0102EML NEW!! | | 4300 | 90283090 |
| Digital LCR Meter | | | |
| 360 | 3-1/2 Digits Hand Held Digital LCR Meter, Measures Inductance from 0.001mH to 20H, Capacitance from 0.001nF to 600uF and Resistance from 0.1 to 20M. Ohms, with diode test, transistor test and audible continuity test, CE Approved | 4945 | 90308990 |
| 460 | 11,000 Counts Backlit LCD, Data Hold, MAX/MIN Record, RELATIVE, Inductance, Capacitance, Resistance, Diode & Continuity Test | 5698 | 90308990 |
| 4070D | 5 Digits, LCD, Dual Display, Inductance, Capacitance, Resistance, Impedance, D, ESR and Q Test Facility, Test Frequency of 100Hz, 120Hz, 1kHz, 10kHz and 100kHz | 12900 | 90308990 |
| 4090D NEW!! | | 33325 | |
| Digital LCR Multimeter | | | |
| 451 | 3-1/2 Digits, Backlit LCD, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Inductance, Frequency, Temperature, Diode, Transistor and Continuity Test | 4053 | 90303100 |
| 506 | 3-3/4 Digits, Backlit, LCD Dual Display, T-RMS, RS-232 PC Interface, Internal Memory, Min, Max, Avg, Relative Modes, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Inductance, Duty Cycle, Temperature, dBm, Logic, Diode, Signal Output & Continuity Test | 22038 | 90303100 |
| Digital Leakage Current Meter | | | |
| DT-4671 | 3-3/4 Digits, Analogue Bargraph, LCD, Data Hold, MAX/MIN Record, 30mm Jaw Size, AC Voltage, AC Current, Resistance. Has Low Pass Filter to filter out noise. | 6558 | 90308990 |
| DT-4672 | 3-3/4 Digits, LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Leakage Current measurement, Capacitance, Resistance, Frequency, Duty Cycle, Diode & Continuity Test | 6880 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---------------------------------|--|----------------|----------|
| DT-4673 | 3-1/2 Digits, LCD, T-RMS,. AC/DC Leakage Current Meter, Non contact voltage detector, Data Hold, Can be used for Variable Frequency Control Drives, Measures from 1mA, AC/DC Current up to 100A, AC/DC Voltage, Resistance, Capacitance, Diode and Continuity Test | 5698 | 90308990 |
| DT-6054 | 3-1/2 Digits LCD, Data Hold, Max Hold, 30mm Jaw Dia, 0 - 200mA / 2A / 200A AC. | 5590 | 90308990 |
| MULTI-140 | 3-1/2 Digits, 3200 Counts LCD, Data Hold, 40mm jaw Dia, 0 - 30m/300m/30/300A AC | 32788 | 90308990 |
| PRO-468AC | 6000 Counts, Auto-Backlit LCD Display, Auto Power Off, as per IEC 61557-13: Class 2, 40mm Jaw Dia, IEC / EN 61010-1, IEC / EN 61010-2-032, CAT. III 600V, Pollution Degree 2, EN 61326-1 EN 61326-2-2, bandwidth up to 1kHz, 1% accuracy, 0 - 6mA / 60mA / 600mA / 6A / 60A, With resolution of 1uA, Bluetooth | 33540 | 90308990 |
| PRO 2010 NEW!! | AC/DC Auto-ranging Leakage Current Clamp Meter, 0.1mA resolution, 5000 counts, Backlit LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Leakage Current, Resistance, Continuity Test | 26875 | |
| Digital Lux Meter | | | |
| 1300 | 4 Digits Backlit LCD Display, MAX / MIN Record, Data Hold, Digital Lux Meter, Can measure up to 200,000 Lux, Also measures in FC (Foot Candle), High Sampling Rate, Overload Indication, Auto Power Off, Low Battery Indication | 1860 | 90278090 |
| 1310 | 4 Digits Backlit LCD Display, Data Hold, Hi/Lo Indication, Split Probe, Lux and Foot Candle Measurement, Auto Power Off, Lo-Battery Indication, Measures up to 199,900 Lux / Fc | 2903 | 90278090 |
| 1330 | Measures up to 50,000 Lux | 2688 | 90278090 |
| 1331 | Measures up to 50,000 Lux / Ft Candle with Max Hold and Data Hold | 3225 | 90278090 |
| 1332 | Measures up to 200,000 Lux / Ft Candle with Peak Hold and Data Hold | 5913 | 90278090 |
| 1332A | Measures up to 200,000 Lux / Ft Candle with Max Hold and Data Hold | 7848 | 90278090 |
| 1333 | Measures up to 0 - 20 / 200 / 2000 / 200000 / 200,000 Lux / Ft Candle with Max Hold and Data Hold | 5268 | 90278090 |
| 1334 | Measures up to 400,000 Lux/40,000 Ft Candle, Data & Peak Hold, Max Min Record, USB PC Interface, Backlit LCD With Analogue Bargraph | 6558 | 90278090 |
| 1335 NEW!! | Measures visible light up to 400000 Lux from luminaries equipped with white light LED, fluorescent, metal halide, high-pressure sodium and incandescent sources. | 8493 | 90278090 |
| Digital Micro Ohms Meter | | | |
| 53C | Digital Micro Ohms Meter to measure from 1uOhm to 2k.Ohms | 6343 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---------------------------------|---|----------------|----------|
| 53C-II | Micro-Processor based, Digital Micro Ohms meter to measure from 1uOhms to 2kOhms, with digital selection of ranges | 6773 | 90308990 |
| UOT-10A | Digital Micro Ohms Meter with Test Current of 10A | 82775 | 90308990 |
| 7272A NEW!! | 10A Micro Ohms Meter with backlit LCD display, USB PC Interface, 500 Internal Memory, Four Wire measurement, Testing Current of 10A, Battery Operated, Measures from 10.0uΩ-50.00KΩ with accuracy of ±0.2%FS±10 dgt. | 60200 | 90308990 |
| UONT-100A | Digital Micro Ohms Meter with Test Current of 100A | 96750 | 90308990 |
| UONT-200A | Digital Micro Ohms Meter with Test Current of 200A | 188125 | 90308990 |
| Digital Milli Ohms Meter | | | |
| 52C | Hand Held, 0.1mOhms to 40 Ohms, 4 wire Kelvin type connection, also measures AC/DC Voltage, AC/DC Current, Resistance, Capacitance and continuity | 10213 | 90308990 |
| Digital Moisture Meter | | | |
| MM-1 | Digital Moisture Meter for paper, wood and hardned material like plaster, concrete and mortar | 3548 | 90308990 |
| MM-2 | Digital Moisture Meter for wood, bamboo, cotton, tobacco, paper, foodstuffs | 1720 | 90308990 |
| MM-5 | Digital Wood Moisture Meter that can measure moisture in up to 150 different kinds of wood | 6558 | 90308990 |
| MM-10 | Digital Pinless Moisture Meter, Range 0 - 100%, auto power off, backlit display, Min/Max function, Measure and Hold, works on most of the products | 8600 | 90308990 |
| Digital Multimeter | | | |
| XB-30 | 3-1/2 Digits, LCD, Data Hold, AC Voltage, DC Voltage, DC Current, Resistance, Diode & Transistor Test. | 1478 | 90308990 |
| XB-33CF | 6000 Counts Backlit LCD, Flash Light, NCV, MAX/MIN Record, T-RMS, Measures AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Frequency, Diode and Continuity Test | 1720 | 90303100 |
| 603 | 3-1/2 Digits, Backlit LCD, Data Hold, AC Voltage, DC Voltage, AC Current, DC Current, Resistance, Capacitance, Frequency, Temperature, Hot Wire, Diode, Transistor and Continuity Test. | 2043 | 90303100 |
| 6030A+ | 6000 Counts Backlit LCD, T-RMS Multimeter, Auto Power Off, Data Hold, MAX/MIN, AC / DC Voltage, AC/DC Current 20A, Resitance, Capacitance, Frequency, Temperature, Transistor Test, Diode and Continuity Test | 2096 | 90303100 |
| 901-I | 3-1/2 Digits, LCD, Auto-ranging, Max Hold and Data Hold, AC Voltage, DC Voltage, AC Current, DC Current, Resistance, Temperature, Diode & Continuity Test. 500V DC/AC Protection in Resistance, Temperature, Diode and Continuity Test. | 2365 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---------------------|--|----------------|----------|
| 19 | 3-3/4 Digits, LCD, Auto-ranging, Relative, Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, 30MHz Frequency, Duty Cycle, Temperature, Diode, Transistor and Continuity Test. | 2258 | 90303100 |
| 19-SUPER | 6000 Counts LCD Display, NCV, T-RMS Multimeter, Measures AC/DC Voltage, AC/DC Current up to 20A, Resistance, Temperature, Frequency, Capacitance, Diode, Transistor Test and Continuity Test Facility | 2419 | 90303100 |
| 901-II | 3-3/4 Digits, Backlit LCD, Auto-ranging, Relative, Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity Test. | 3118 | 90308990 |
| 901-III | 3-5/6 Digits, 6000 Counts Backlit LCD, Autor-ranging, 600V AC/DC Protection, AC/DC Voltage, AC/DC Current, Resistance, 4mF capacitance, 20MHz Frequency, temperature diode and continuity | 4408 | 90308990 |
| 901-IV | 3-5/6 Digits, 6000 Counts Backlit LCD, Autor-ranging, T-RMS, 600V AC/DC Protection, AC/DC Voltage, AC/DC Current, Resistance, 4mF capacitance, 20MHz Frequency, temperature diode and continuity | 5268 | 90308990 |
| 801 | 3-3/4 Digits, LCD, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Logic Test, Diode & Continuity Test. 500V DC/AC Protection in Resistance, Capacitance, Frequency, Logic, Diode & Continuity Test | 3171 | 90308990 |
| DT-19TB | 3-3/4 Digits, Backlit LCD, Auto-ranging, Terminal Blocking Facility, Relative & Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Battery Test, Diode & Continuity Test. 500V AC/DC Protection in all ranges | 3548 | 90308990 |
| Metrasafe-10 | 6000 Counts Backlit LCD, T-RMS, Flashlight, Live-Neutral detectio, Non contact voltage detector, Audio and visual alarm for continuity, Transistor Test, AC/DC Voltage, AC/DC Current up to 20A, Resistance, Capacitance, Frequency, Temperature, Duty Cycle, Diode and Continuity Test. | 2580 | 90303100 |
| Metrasafe-13 | 3-3/4 Digits, Backlit LCD, Autoranging,FULLY PROTECTED, Data Hold, Relative, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Continuity and Battery Test. Confirms to CAT IV 600V | 4596 | 90308990 |
| Metrasafe-14 | 3-3/4 Digits, Backlit LCD, Autoranging,FULLY PROTECTED, Data Hold, Relative, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Continuity and Battery Test. Confirms to CAT IV 600V | 5268 | 90308990 |
| Metrasafe-15 | 3-3/4 Digits, Analogue Bargraph, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Max/Min, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test. Confirms to CAT IV 600V. | 6343 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---------------------|---|----------------|----------|
| Metrasafe-16 | 3-3/4 Digits, Analogue Bargraph, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Max/Min, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test. Confirms to CAT IV 600V. | 7310 | 90308990 |
| Metrasafe-18 | 4-3/4 Digits, Analogue Bargraph, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data & Peak Hold, Max/Min Record, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Non Contact type Infra Red Thermometer, Duty Cycle, Diode & Continuity Test. Confirms to CAT IV 600V. | 15265 | 90308990 |
| Metrasafe-19 | 4-3/4 Digits, Analogue Bargraph, Wireless PC Interface, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data & Peak Hold, Max/Min Record, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Non Contact type Infra Red Thermometer, Duty Cycle, Diode & Continuity Test. Confirms to CAT IV 600V. | 17093 | 90308990 |
| Metrasafe-20 | 4-5/6 Digits, 60,000 Counts, T-RMS Multimeter, OLED Display, 100kHz Bandwidth, 0.025% Accuracy, Lo-Z measurement, AC/DC Voltage, AC/DC Current, Resistance, Process Measurement, Conductance, Capacitance, Frequency, Duty Cycle, Temperature, Diode and Continuity, Re-chargeable battery, Battery Charger, Misoperation Alarm, Data Logger. Optional Blue Tooth Interface | 34400 | 90308990 |
| 23S-TRMS | 4-1/2 Digits 19,999 Counts, T-RMS, Backlit LCD, NCV, Data Hold, Peak Hold, Relative, Auto Power Off, Dual Display to show Voltage & Current with Frequency on the same screen, AC/DC Voltage, AC/ DC Current 10A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test both Audio and Visual. | 3978 | 90308990 |
| 540 | 4-1/2 Digits, LCD, Data Hold, T-RMS, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Diode & Continuity Test. | 4838 | 90308990 |
| DM-454 NEW!! | 22,000 Counts LCD Display, Peak Hold, Data Hold, Relative Measurement, T-RMS Multimeter, Confirms to CAT III 1000V, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Diode & Continuity Test, USB PC Interface. | 10723 | 90303100 |
| PRO-11 | 4000 Count Backlight LCD Display, Auto-Ranging, IP67 Dust and Waterproof, 600V AC/DC Voltage, 10A AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, UL 61010-1, CAT-III 600V, Class 2 Double Insulation, Built-in flashlight, Over range indication, Auto Power Off, Min/Max Data Hold. Hand-Held Waterproof and Dustproof, Digital Multimeter. Anything and Everything that you can possibly think about. A must for all technicians, double moulded injection body, a built-in flashlight to access dark areas, | 4596 | 90303100 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---------------------------|--|----------------|----------|
| PRO-12B | 4000 Count, Backlight LCD Display, TRMS, IP 67 Dust and Waterproof Digital Multimeter, 600V AC(TRMS) /DC Voltage, 10A AC(TRMS)/DC Current, LoZ, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity test, 50 to 400Hz AC Bandwidth, Bluetooth Smartphone interface, Free Smartphone App, Data Hold, MAX/MIN Record, Built-in Flashlight, Double-moulded injection body, Auto Power Off, Low battery indication, CAT-III 600V. Hand-Held Waterproof and Dustproof, Digital Multimeter. Anything and Everything that you can possibly think about. A must for all technicians. | 5375 | 90303100 |
| PRO SOLAR-1 NEW!! | 6000 Counts, Auto-backlit LCD, confirming to EN 61010-1, EN 61010-2-033 for CAT III 1000V, CAT IV 600V, EN 61326-1, designed for Solar PV applicaton, to measure 2000V DC and 1500V AC T-RMS, to measure DC/AC mV as well, AC/DC Current up to 10A, Resistance 40M.Ohms, Capacitance 10mF, Frequency 100kHz, Temperature 400 Degree C, Non Contact Voltage Detection, Diode and Continuity Test. | 17200 | 90303100 |
| PRO SOLAR-1A NEW!! | 1500VDC, 1000VAC, 6000 counts backlit LCD display, TRMS, Auto-ranging, Heavy Duty, Industrial-grade Digital Multimeter with VFD Measurement. IP67 & 2 metres drop/shock-proof. Perfect for Solar & PV Applications. | 6988 | 90303100 |
| PRO 587 NEW!! | 6,000 /60,000 Counts user selectable, Backlit LCD Display, Bargraph, T-RMS Multimeter, 1000V AC/DC Current, 10A AC/DC Current, 100kHz AC Response, Resistance, Capacitance, Electrical and Electronic Frequency, Temperature, Duty Cycle, Low Pass Filter, 4-20mA measurement, Continuity and Diode testing. | 13438 | 90303100 |
| PRO 589 NEW!! | Professional True RMS Industrial Digital Multimeter and TFT color LCD display, providing fast A/D converting sampling time, high accuracy, built-in data logging, and Trend Capture features. AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency (electrical & electronic), Duty Cycle, Diode Test, Insulation Test, and Continuity plus Thermocouple Temperature. It can store and recall data. It features a waterproof, rugged design for heavy duty use. | 22038 | 90303100 |
| PRO 21 NEW!! | 6000 counts backlit LCD display, TRMS, Auto-ranging, Heavy Duty, Industrial-grade Digital Multimeter with VFD Measurement. IP67 dust and water proof as well as 2 metres drop/shock-proof! | 5913 | 90303100 |
| PRO 27 NEW!! | 6000 counts backlit LCD display, Auto-Ranging T-RMS Multimeter with VFD, LoZ, 61 Segment Analogue Bargraph and IP67- best fit for all applications regarding electrical motors. | 6665 | 90303100 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|--|--|----------------|----------|
| XB-33A NEW!! | 6000 Counts, Auto-ranging, T-RMS Digital multimeter with backlit LCD display. Can measure AC T-RMS Voltage and Current, DC Current / Voltage, Frequency, Resistance, Capacitance, Temperature, Diode and Continuity Test and Non-contact Voltage Detection, along with overload protection. | 1613 | |
| PRO 7 NEW!! | | 3677 | |
| Accessories to Digital Multimeter | | | |
| CA-01 | Clamp On Current Adaptor to be used with any Multimeter with mV range, measures up to 200A AC | 1290 | 90308990 |
| CA-1000D | Clamp On Current Adaptor to be used with any Multimeter with mV range, measures up to 600A/1000A AC/DC | 5698 | 90308990 |
| TS-03 | Infra Red Temperature Adaptor to measure from -30 to 550 Degree C, can be used with any Multimeter with mV range | 3655 | 90308990 |
| PD-28 | High Voltage probe to measure 40kV DC and 28kV AC | 8869 | 90308990 |
| ATL-PV NEW!! | High Voltage Probe for P-V Multimeter SOLAR-1 and PV Clamp meter SOLAR-2 | 3225 | 90308990 |
| TL-70 | Right Angled shrouded termination to fit modern multimeters, fitted with a 4mm shrouded socket, CAT III 1000V / 20A Rating | 215 | 90308990 |
| TL-74 | 1m silicon single insulated test leads with right angle shrouded banana plugs, CAT IV 600V, CAT III 1000V with protective cap, banana plug termination, dia of test lead point 2mm | 376 | 9030 |
| TL-75 | 1m silicon double insulated test leads with right angle shrouded banana plugs, CAT IV 600V, CAT III 1000V with protective cap, banana plug termination, dia of test lead point 2mm | 538 | 90303100 |
| Flexi Clamp NEW!! | For PRO 27 and Solar-3 | 6450 | |
| Flexi Clamp NEW!! | For Solar-2 and 107F | 7525 | |
| Digital Non Contact Infra Red Thermometer | | | |
| MT-2 | 3 Digits Backlit LCD with laser sighting used to measure temperature in the range of -30 to 260°C / -22 to 500°F, D:S Ratio 8:1, Fixed emissivity 0.95. | 2258 | 90251920 |
| PRO-65 MAX | Precise Non Contact Measurement, Circular Laser to show the exact area whose temperature is being measured IP54 Rated for Dust / Water Proof, 2m Drop Tested, Automatic Data Hold, Non Contact and Contact Thermometer Combined, Contact temperature measurement using K type sensor, Adjustable Emissivity from 0.10 to 1.00, MAX / MIN / AVG / DIF Temperature display, Backlit LCD Display, Set High and Low Alarms, Distance to Sighting Ratio 16:1 (65Max) Battery Operated 2 x 1.5V AAA Batteries, CE Compliant with EMC, Tk Temperature: -50 to 1370°C, Resolution: 0.1°C < 1000; 1°C > 1000, Accuracy: ±0.5% of Reading ±1.5°C, IR Temperature Measurement: -50 to 800°C Response Time: 150mS, Spectral Response: 8 – 14um | 4730 | 90251920 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|--------------------|---|----------------|----------|
| PRO-65 MAX+ | Precise Non Contact Measurement, Circular Laser to show the exact area whose temperature is being measured IP54 Rated for Dust / Water Proof, 2m Drop Tested, Automatic Data Hold, Non Contact and Contact Thermometer Combined, Contact temperature measurement using K type sensor, Adjustable Emissivity from 0.10 to 1.00, MAX / MIN / AVG / DIF Temperature display, Backlit LCD Display, Set High and Low Alarms, Distance to Sighting Ratio 20:1, Battery Operated 2 x 1.5V AAA Batteries, CE Compliant with EMC, Tk Temperature: -50 to 1370°C, Resolution: 0.1°C < 1000; 1°C > 1000, Accuracy: ±0.5% of Reading ±1.5°C, IR Temperature Measurement: -50 to 1000°C, Response Time: 150ms, Spectral Response: 8 – 14um | 5913 | 90251920 |
| MT-10 | 3-1/2 Digits Backlit LCD, fixed emissivity of 0.95, D:S Ratio of 50:1, measures from -50 to 1000°C / -58 to 1832°F, with laser pointer | 15265 | 90308990 |
| MT-13 | Backlit LCD, Contact cum Non Contact type, measures from -18 to 1050 °C in Non Contact model and -50 to 1370 °C in Contact Mode, Emissivity adjustable from 0.10 to 1.0, D:S Ratio of 30:1, with wireless USB PC Interface and facility to calculate the emissivity of the surface | 19673 | 90251990 |
| MT-14 | 4 Digits Backlit LCD, Contact cum Non Contact type, measures -50 to 1300°C/-58 to 2372°F in non contact mode and contact mode. D:S Ratio 30:1, Emissivity Adjustable 0.10 to 1.00, mV output /°C, Trigger Lock, battery cum mains operated, Records 20 Data, Max/Min/Dif/Avg recording | 13438 | 90251990 |
| MT-15 NEW!! | Measures from -50 to 1200°C / -58 to 2192°F with dual laser pointer, contact cum non-contact type, with USB PC Interface and with Max./Min./Dif/AVG., 4 Digits Backlit LCD, adjustable emissivity from 0.10 ~ 1.0, D:S Ratio of 50:1, in non contact mode | 19350 | 90251920 |
| MT-16 | 4 Digits Backlit LCD, Contact cum Non Contact type, with USB PC Interface, adjustable emissivity from 0.10 ~ 1.0, D:S Ratio of 50:1, in non contact mode measures from -50 to 1800°C / -58 to 3272°F, with dual laser pointer to show the diameter of the area whose temperature is being measured and with Max. /Min./Dif/AVG. Temp. | 23650 | 90308990 |
| MT-18 | 4 Digits Backlit LCD, Contact cum Non Contact type, with USB PC Interface, adjustable emissivity from 0.10 ~ 1.0, D:S Ratio of 50:1, in non contact mode measures from -50 to 2200°C / -58 to 3992°F, with dual laser pointer to show the diameter of the area whose temperature is being measured and with Max. /Min./Dif/AVG. Temp. | 30100 | 90251990 |
| MT-19 | | 31713 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|------------------------------------|---|----------------|----------|
| MT-20 | 4 digits LCD, adjustable emissivity from 0.10 to 1.00, telescopic sighting measures in the range of 500°C to 3000°C and in °F scale, distance to sighting ratio of 120:1, accuracy ±1%, with Max/Min/Ave/DT and High/Low alarm | 268750 | 90308990 |
| Digital Phase Angle Meter | | | |
| CE-0102D | Digital Phase Angle Meter, 96 x 96 mm sq, can measure Phase Angle between Voltage and Current | 3870 | 90303310 |
| Digital Power Analyzer | | | |
| CE-0102PA | Digital Ampere, Volt, PF and Watt meter combined in 96 x 96 mm sq for single phase loads | 4838 | 90303310 |
| Digital Power Factor Meter | | | |
| CE-0102PF 96x48 | Microprocessor Based, 96 x 48 mm sq, For Single Phase, Red LED Display | 3548 | 90303310 |
| CE-0102PF 96 x 96 mm sq | Microprocessor Based, 96 x 96 mm sq, For Single Phase, Red LED Display | 3548 | 90303310 |
| CE-0303PF | Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element , Red LED Display | 4515 | 90303310 |
| CE-0304PF | Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display | 4515 | 90303310 |
| Digital Pressure Meter | | | |
| PM-01 | Backlit LCD Display, measures up to 5 psi and in various other units of Pressure | 13975 | 90308990 |
| Digital Process Meter | | | |
| PM-29 | 3-3/4 Digits, Digital Multimeter Cum DC mV / Voltage / Frequency / Resistance / mA Calibrator and also provides output for all types of Thermocouples | 43753 | 90308990 |
| PM-39 | 5 Digits, Digital Multimeter combined with source for DC voltage, resistance, frequency, all kind of thermocouples, thermal resistance, and DC current. supply power to 24V circuits and meanwhile measure current; with built-in 250 Ω HART loop resistance | 50525 | 90303100 |
| Digital Process Clamp Meter | | | |
| 771+ | The Milliamp Process Clamp Meter is a hand-held battery-operated clamp meter that measures 4-20 mA DC without breaking the electrical circuit. DC mA measurement (4-20mA) using a remotely connected clamp via extension cable, Electronic zero, Percentage span (0-100%), Data Hold, Backlit Display, Measurement spotlight LED, Auto Power Off, 0mA... ±20.99mA, Resolution 0.01mA, Accuracy: 0.3% reading ±8 digits, Also measures ±21.0mA... ±99.9mA with Resolution of 0.1mA, Clamp Jaw 4.5mm, IP40, IEC 61010-1, 61010-2-032, CAT II 300V | 22575 | 90303100 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|--|---|----------------|----------|
| Digital SMT Component Tester | | | |
| SMT-01 | SMT Component tester that can measure Capacitance and Resistance values of SMT components, it can also measure AC/DC Voltage, continuity and Diode test | 4300 | 90308990 |
| Digital Sound Level Meter | | | |
| SL-3010 | 4 Digital Backlit LCD, Sound Level Meter, Fast & Slow Response, Data Hold, MAX/MIN Record, A Weighting, Measures sound in the range of 30dB to 130dB with resolution of 0.1dB and accuracy of 1.5dB. With Over-range and Low Battery Indication | 1881 | 90278090 |
| SL-4010 | 3-1/2 Digits Backlit LCD, has A & C Weighting, measures in the range of 30 to 130 dB, with maximum hold | 6128 | 90278090 |
| SL-4005 | 3-1/2 Digits, has A & C Weighting, measures in the range of 35 to 130 dB, with data hold and maximum hold, with built in calibration check | 7095 | 90278090 |
| SL-4015 | 4 Digits, has A & C Weighting, measures in the range of 30 to 130 dB, USB PC Interface, with Max/Min Data Hold and Data Logging facility | 12255 | 90278090 |
| Digital Storage Oscilloscope | | | |
| DSO-5025E | 25MHz DSO with colored display, 250MSa/Sec sampling rate, with USB PC Interface cable and software | 30638 | 90302000 |
| DSO-5050E | 50MHz DSO with colored display, 500MSa/Sec sampling rate, with USB PC Interface cable and software | 31713 | 90302000 |
| DSO-5074E NEW!! | | 76325 | 90302000 |
| DSO-5100E | 100MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host | 37088 | 90302000 |
| DSO-5104E NEW!! | | 80625 | 90302000 |
| DSO-5150E | 150MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host | 40850 | 90302000 |
| DSO-5200E | 200MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host | 44075 | 90302000 |
| Accessories to Digital Storage Oscilloscope | | | |
| PD-20S | High Voltage Probe to be used with any oscilloscope (Analogue or Digital Storage) to measure High Voltage Waveform of 30kV DC and 20kV AC | 9460 | 90308990 |
| OP-60 NEW!! | OP-60 is a x 1 / x 10 attenuation modular probe designed to be used with 60MHz oscilloscopes with an input impedance of 1MΩ. | 753 | 90308990 |
| OP-100 NEW!! | OP-100 is a x 1 / x 10 attenuation modular probe designed to be used with 100MHz oscilloscopes with an input impedance of 1MΩ. | 1075 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|--|----------------|----------|
| OP-250 NEW!! | OP-250 is a x 100 attenuation modular probe designed to be used with 250MHz oscilloscopes with an input impedance of 100MΩ. | 6235 | 90308990 |
| Digital Stroboscope | | | |
| DT-2350A | Digital Stroboscope, 50 to 12,000FPM, 230V Single Phase AC Operated | 12911 | 90308990 |
| DT-2350B | Digital Stroboscope, 50 to 40,000FPM, 230V Single Phase AC Operated | 22978 | 90308990 |
| DT-720 | LED Stroboscope | 9675 | 90308990 |
| DT-720-2 | LED Stroboscope | 11825 | 90308990 |
| Digital Tachometer | | | |
| DT-2235 | Contact type Tachometer, measures up to 50,000RPM | 2795 | 90292090 |
| NCTM-500 | Non Contact type Tachometer With Counter, Data Hold, Measures from 50mm to 200mm, RPM Up to 99999RPM, and Counts up to 99999 Counts | 1881 | 90308990 |
| NCTM-1000 | Non Contact type Tachometer Cum Counter. Max / Min . Last Data Record, 2 to 99,999 RPM, 1 TO 99,999 Counts | 3548 | 90308990 |
| NCTM-2000 | Contact cum Non Contact type Combined Tachometer, Max/Min, Last Record, 20,000RPM in contact mode and 99,999 RPM in non contact mode, measures Rotation speed, total revolution, frequency, surface speed and length | 6450 | 90308990 |
| NCTM-3000 NEW!! | Contact and Non Contact type Combined Tachometer with non-contact laser sighting for measuring from up to 12 feet distance. 20,000 RPM in contact mode and 200,000 RPM in non-contact mode. | 7310 | 90308990 |
| Digital Temperature Controller | | | |
| DTC-200 | Digital Temperature Controller 96 x 96 mm sq, with 1NO + 1NC, Single Set Point, for K, J, R, S, PT-100 (Any One) | 2338 | 84779000 |
| DTC-202 | Digital Temperature Controller 96 x 96 mm sq, with 2NO + 2NC, Two Set Point, for K, J, R, S, PT-100 (Any One) | 2849 | 84779000 |
| METCAT 96 | Digital Temperature Controller, 4 Digits Display, up to 1200 Degree C, 96 x 96 mm sq, with 1NO + 1NC, Single Set Point, for K, J, PT-100 (User Programmable) | 1935 | 84779000 |
| METCAT 72 | Digital Temperature Controller, 4 Digits Display, up to 1200 Degree C, 72 x 72 mm sq, with 1NO + 1NC, Single Set Point, for K, J, PT-100 (User Programmable) | 1935 | 84779000 |
| Digital Temperature & Humidity Meter | | | |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|---|----------------|----------|
| HT-305 | 3-1/2 Digits Backlit LCD Dual Display, Measures Temperature in Celsius and Fahrenheit scales in the range of -10 to 60 Degree C with resolution of 0.1 and accuracy of 1.0 Degree C, Relative Humidity from 0 to 100% RH with resolution of 0.1%RH and 5%RH accuracy, It has Data Hold, MAX/MIN Record Function, Auto Power Off | 2150 | 90258090 |
| HT-305A | Backlit LCD Dual Display, with split type Sensor for temperature and Humidity, Data Hold, MAX / MIN Record, Auto Power Off, Measure Temperature from -10 to 60 Degree C, and Humidity Up to 100% RH | 2688 | 90308990 |
| HT-3004CT | Digital Thermo-Hygro Meter with in-built infra red thermometer. Has Backlit LCD Display | 9353 | 90308990 |
| HT-3005 | Digital Thermo-Hygro Meter with K-type thermometer. Has Backlit LCD Display | 4515 | 90258090 |
| HT-3006 | Digital Thermo-Hygro Meter with facility to measure wet bulb and dew point temperature | 6450 | 90258090 |
| HT-12 | Digital Thermo-Hygro Meter with Jumbo Display, to measure Indoor and Outdoor Temperature measurement, with Humidity. Selectable scales, Alarm Clock and Comfort Level Indicator, Temperature range -10 to 50 Degree C and humidity from 20 to 95% | 1398 | 90258090 |
| HT-13 | Digital Thermo-Hygro Meter with Jumbo Display, to measure Temperature measurement, with Humidity. Selectable scales, Alarm Clock and Comfort Level Indicator, Temperature range -10 to 50 Degree C and humidity from 20 to 95% | 1290 | 90258090 |
| HTC-01 | Jumbo LCD Display, wall hanging, with time and alarm facility, -50 to 70 Degree C, 20% to 99%RH | 699 | 90258090 |
| TH-04 | LCD Display, wall hanging, with time and alarm facility, calendar, climatic condition display, 0 to 50 Degree C, 10% to 90%RH | 1290 | 90308990 |
| Digital Temperature Indicator | | | |
| DTI-101 48 | Digital Temperature Indicator 96 x 48 mm sq, for K, J, R, S, PT-100 (Any One) | 1451 | 90308990 |
| DTI-101 96 | Digital Temperature Indicator 96 x 96 mm sq, for K, J, R, S, PT-100 (Any One) | 1451 | 90308990 |
| N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size or 96 x 48 mm sq size | | | |
| Digital Thermometer | | | |
| DTM-900 | 3-1/2 Digits, Measures from -50 to 1300°C / -50 to 1999°F, Contact type, to be used with K type thermocouple , with backlit display and kelvin scale | 3655 | 90251990 |
| DTM-901 NEW!! | 3-1/2 Digits, Dual Channel Input, Measures from -50 to 1300°C / -50 to 1999°F, Contact type, to be used with K type thermocouple. with backlit display and kelvin scale | 4193 | 90251990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|--------------------------------------|--|----------------|----------|
| DTM-903 | Wide Temperature Range, High Accuracy, Battery Operated, Selectable Thermocouple between K / J type, MAX / MIN / AVG Recording, Data Hold to Freeze Displayed Data, Backlit Display Measures Temperature from -50 to 1300°C using K-type Sensor and from -50 to 1200°C using J-type Sensor Accuracy: ±0.5% | 1720 | 90251990 |
| DTM-100 | 3-1/2 Digits, Hand Held 9V battery operated, for PT-100 Sensor up to 600 Degree C | 2016 | 90251990 |
| DTM-902 | Pen Type, Auto Power Off, -40 to 250°C / -40 to 482°F | 806 | 90251990 |
| DTM-925 | | 3763 | 90251990 |
| ST-9283B | Hand Held, With High Temperature Alarm Facility, Auto Power Off, Data Hold, -50 to 300°C / -58 to 572°F | 806 | 90251910 |
| Digital Three Phase Ammeter | | | |
| CE-03A | Microprocessor Based, 96 x 96 mm sq, with in built three phase selector switch, displays Current in three phases, CT Ratio programmable. Programmable up to 3000A AC | 2258 | 90303310 |
| Digital Three Phase Voltmeter | | | |
| CE-03V | Microprocessor Based, 96 x 96 mm sq, with in built three phase selector switch, displays Line to Line and Line to Neutral Voltage. Direct Operated and PT Ratio programmable | 2258 | 90303310 |
| Digital Time Interval Meter | | | |
| NTT-4D | 4 Digits Digital Time Interval Meter for measuring in the range of 999.9mS, 9.999S, 99.99S | 17200 | 90318000 |
| 3CH-NTT-4D | 4 Digits 3 Channel Digital Time Interval Meter for measuring in the range of 99.99mS, 999.9mS, 9.999S | 74175 | 90318000 |
| Digital Voltage Controller | | | |
| CE-0102VC 1SP | Digital Voltmeter with Single Set Point to control the Voltage below a given set point.Size - 96 x 96 mm sq. With 1NO + 1NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One) | 3601 | 90303310 |
| CE-0102VC 2SP | Digital Voltmeter with Two Set Point to control the Voltage between a given set points.Size - 96 x 96 mm sq. With 2NO + 2NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One) | 4300 | 90303310 |
| Digital Voltmeter | | | |
| CE-0102V | 3-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range) | 1371 | 90303310 |
| CE-0102V 96 | 3-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range) | 1371 | 90303310 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|--|----------------|----------|
| CE-0102V | 3-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range) | 1371 | 90303310 |
| CE-0102V 96 | 3-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range) | 1371 | 90303310 |
| N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size | | | |
| CE-0102V 4-1/2 Digits | 4-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range) | 2688 | 90303310 |
| CE-0102V 96 4-1/2 Digits | 4-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range) | 2688 | 90303310 |
| CE-0102V 4-1/2 Digits | 4-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range) | 2688 | 90303310 |
| CE-0102V 96 4-1/2 Digits | 4-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range) | 2688 | 90303310 |
| Digital Wattmeter | | | |
| CE-0102W | Microprocessor Based, 96 x 48 mm sq, For Single Phase, Red LED Display | 3655 | 90309090 |
| CE-0102W 96 x 96 | Microprocessor Based, 96 x 96 mm sq, For Single Phase, Red LED Display | 3655 | 90309090 |
| CE-0303W | Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display | 4515 | 90309090 |
| CE-0304W | Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display | 4515 | 90309090 |
| Discharge Rod | | | |
| DR 11-33kV NEW!! | | 4300 | |
| DR 33-66kV NEW!! | | 6450 | |
| DR 66-132kV NEW!! | | 10428 | |
| DR 132-220kV NEW!! | | 12900 | |
| DR 400kV NEW!! | | 16125 | |
| ELCB Tester | | | |
| 1810D | Digital ELCB Tester with Current Rating up to 500mA, Trip Test, Fault Trip Time, Self Powered | 6558 | 90308990 |
| 1811 | Digital ELCB Tester with Current rating up to 500mA, Auto Ramp, Phase Switch, Reads Disconnection Time, Self-Powered | 12900 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|---|----------------|----------|
| 1813 | Digital ELCB Tester with Current rating up to 1A, Trip Test, Fault Trip Time, 230V AC Operated | 11825 | 90308990 |
| Electrical Tester | | | |
| AC-1 | Audio and Visual output on detecting voltage from 90V - 1000A AC with built in flash light | 403 | 90308990 |
| AC-4 | Non Contact Voltage Detector by flashing light for 100 - 600V, with built-in flash light | 753 | 90308990 |
| AC-5 | Non Contact Voltage Detector by flashing light and buzzer sound for 100 - 600V, with built-in flash light | 860 | 90308990 |
| AC-6 | Socket Polarity & Earth Leakage Tester. Checks for No Earth / Line Neutral Reversal / No Neutral / Line Earth Reversal / No Line states. | 1505 | 90308990 |
| AC-7 | Phase Rotation Indicator, No Batter Required, Nomical Voltage 40 - 690V, 15 to 400Hz. | 4193 | 90308990 |
| AC-8 | Self Operated, phase rotation indicator along with voltage and frequency display | 2688 | 90308990 |
| PRO ELEC+ NEW!! | Two-pole Voltage Tester with LCD display and LED signalling. Features Audible Continuity and RCD tripping test. Built-in LED flashlight, IP67 dust and splash proof, over-voltage protection with CAT III 1000V / CAT IV 600V. | 6343 | 90303900 |
| EMF Tester | | | |
| EMF-823 | Measures from 0.1 to 200mG / 1 to 2000mG & 0.01 to 20uT / 0.1 to 200uT, Frequency Response 30Hz to 400Hz, Max Hold and Data Hold | 8063 | 90308990 |
| Event Counter | | | |
| CTR-49 | 6 Digits Red LED Display, Event Counter, 1 to 999999 Counts, 96 x 48 mm sq | 2419 | 90292090 |
| N.B. - Please ask for the prices in case if you require this in 96 x 96 mm sq size | | | |
| Forehead Infra Red Thermometer | | | |
| FIR-2 | Non Contact Infra Red Thermometer for body temperature | 3010 | 90308990 |
| PIR-I | "A non-touch Infrared Thermometer to measure human body temperature via the hand wrist & palm. The PIR-1 is a non-touch Infrared Thermometer to measure human body temperature via the hand wrist, palm or even forehead. You just need to put your hand or your wrist over the sensor at a 2-8 cms distance and you will get the body temperature instantly. The PIR-1 uses 2 sensors – a distance sensor and a temperature sensor, to get accurate temperature measurements quickly and safely. When used at any Entry/Exits, people can walk through the check-points quickly without any crowding or queuing. The PIR-1 is mountable on almost any surface and comes with a multi-angle adjustment. It is the ideal solution for enabling safe access control so as to prevent spread of COVID-19." | 37625 | 90230090 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|--|----------------|----------|
| Frequency Transducer | | | |
| CE-0102FT | Frequency Transducer with single Output | 6773 | 85045090 |
| N.B. - For Dual Output Rs.500/- shall be charged extra | | | |
| Function Generator | | | |
| FG-1000 | 1MHz Function Generator with TTL / CMOS output | 10105 | 90308990 |
| FG-2000 | 2MHz Function Generator with TTL / CMOS output | 10965 | 90308990 |
| FG-5000 | 5MHz Function Generator with TTL / CMOS output | 13975 | 90308990 |
| FG-10000 | 10MHz Function Generator with TTL / CMOS output | 23650 | 90308990 |
| FG-20000 | 20MHz Function Generator | 26875 | 90308990 |
| Gauss Meter | | | |
| GM-197 | Gauss Meter for both static and electromagnets, DC and AC (40-500Hz), determines N/S polarity of Static Magnets, measures intensity of magnetic Field in Gauss and Tesla both, measures up to 0~3000mT(milli Tesla)/0~30000G(Gauss), Relative / Peak Hold / Real time Zero function, Auto Range, DATA HOLD, MAX/MIN hold, GO and NO-GO alarm and alarm value set up the function, Production testing, Manual 200 capacity records, Auto 6000 capacity data logging, interval is set up by PC, USB interface to send data + PC connection application software, real time function. | 27413 | 90303100 |
| Gas Detectors | | | |
| GD-09-4M NEW!! | 4-in-1 Multi Gas Detector for O2, CO, H2S and Explosive/Combustible Gas. Features IP65 protection and audio/visual alarms. | 19350 | |
| GD-09-02 NEW!! | Portable and world's smallest Oxygen Gas Detector with audio & visual alarms. Detects Oxygen in the air. | 15319 | |
| High Voltage Detector | | | |
| 277HP | Non Contact Type High Voltage Detector for presence of Voltage from 50V to 132kV with Buzzer and Light Indication | 13438 | 90308990 |
| 275HP | Non Contact type, Light and Buzzer Indication, Detects Presence of High Voltage in AC Lines, 240V, 2KV, 6KV, 11KV, 22KV, 33KV, 132KV and 175KV Lines AC. | 17200 | 90308990 |
| 275HP1 NEW!! | High Voltage Detectors (Electroscope) for electrical testing on high voltage transmission lines upto 275kV, with audible buzzer and visual light alarms. | 7955 | 90308990 |
| 275HP2 NEW!! | High Voltage Detectors (Electroscope) for electrical testing on high voltage transmission lines upto 500kV, with audible buzzer and visual light alarms. | 7955 | 90308990 |
| 276HD | Contact type, light and buzzer indication, detects presence of High Voltage in AC Lines, 354 to 1005mm length, detects 3kV to 24kV AC and 80 to 600V AC | 17953 | 90308990 |
| 276SHD | Contact type, light and buzzer indication, detects presence of High Voltage in AC Lines, 230 to 880mm length, detects 3kV to 24kV AC and 80 to 600V AC | 17953 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|---|----------------|----------|
| 290HD | 7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout | 22575 | 90292090 |
| WT500 NEW!! | A handy, wearable (wrist-type), close-range, non-contact, high voltage detector, featuring sound & light alarms when an operator wearing it gets close to a high voltage charged body upto 500kV. | 4112 | 90303390 |
| AT500 NEW!! | A handy, wearable (arm-type), close-range non-contact high voltage detector, featuring sound & light alarms when an operator wearing it gets close to a high voltage charged body upto 500kV. | 4193 | 90303390 |
| Hot Line Indicator | | | |
| 6.6kV | Hot Line Indicator, Neon Glow type for 6.6kV | 11503 | 90308990 |
| 11kV | Hot Line Indicator, Neon Glow type for 11kV | 17200 | 90308990 |
| 33kV | Hot Line Indicator, Neon Glow type for 33kV | 29025 | 90308990 |
| # Hot Line Indicator with Neon glow and audible buzzer both are also available. Please refer back for their price. | | | |
| Hour Meter | | | |
| NE 045/7S DC | 7 Digits, measures up to 99999.99 hours, 10 - 48V DC operated, 46 x 46 mm sq size panel cutout | 1183 | 90292090 |
| NE 045/7 | 7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout | 645 | 90292090 |
| HM-01 NEW!! | 7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout | 538 | |
| Infrared Temperature Calibrator | | | |
| BB-500 | Black Body Source for Calibrating Infra Red Thermometer from 50 to 500 Degree C | 76325 | 90308990 |
| Insulation Tester | | | |
| IT-500 | Test Voltage: 500V, Insulation Resistance Range: 0 - 1000M.Ohms, with AC Voltage Test Facility | 2043 | 90308990 |
| IT-1000 | Test Voltage: 1000V, Insulation Resistance Range: 0 - 2000M.Ohms, with AC Voltage Test Facility | 2150 | 90308990 |
| Integrated Meter | | | |
| CE-0303IM | Three Phase Three Wire Two Element loads for energy and power measurement, measure each phase I, V, Hz, PF, KW, KVA, KVAh, KVArh and MDI | 8063 | |
| CE-0304IM | Three Phase Four Wire Three Element loads for energy and power measurement, measure each phase I, V, Hz, PF, KW, KVA, KVAh, KVArh and MDI | 8063 | |
| Kelvin Double Bridge | | | |
| KDBR | Oxford Brand Kelvin Double bridge, with spot reflecting galvanometer, High Current DC power supply and wooden stand for specimen | 77400 | 90230090 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|--|---|----------------|----------|
| Laser Distance Meter | | | |
| LDM-40H | Laser Distance Meter to measure up to 40m, with Area / Volume Calculations | 4623 | 90308990 |
| LDM-100H | Laser Distance Meter to measure up to 100m, with Area / Volume Calculations | 6450 | 90303100 |
| Metal Detector | | | |
| MD-300 | High Sensitive Metal Detector with a circular sensor, the detector vibrates and provides audible alarm on detecting metal | 1935 | 90308990 |
| SUPER-V | High Sensitive Metal Detector with a straight sensor, the detector vibrates, provides visual and audible warning on detecting metal | 3225 | 90308990 |
| Million MegOhms Meter | | | |
| MMM-1 | Analogue Million MegOhms Meter for test voltage of 100, 200, 300, 400 and 500V, measures up to 10 Million MegOhms | 18275 | 90308990 |
| Mini Environmental Meters | | | |
| ET-99A | Digital Anemometer | 1935 | 90303100 |
| ET-99L | Digital Lux Meter | 1720 | 90303100 |
| ET-99SL | Digital Sound Level Meter | 1935 | 90303390 |
| ET-99TH | Digital Temperature & Humidity Meter | 1935 | 90258090 |
| ET-99M | Digital Moisture Meter | 1935 | 90308990 |
| ET-99IR | Digital Infrared Thermometer | 2096 | |
| ET-99P | Digital Manometer | 4623 | 90268090 |
| ET-99HT | Digital HCHO and TVOC Meter | 6450 | |
| Mixed Signal Oscilloscope | | | |
| MSO-5062D | 60MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate | 75680 | 90302000 |
| MSO-5102D | 100MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate | 82184 | 90302000 |
| MSO-5202D | 200MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate | 94600 | 90302000 |
| Motor Checker | | | |
| MC-22 | Electric Motor Checker with analogue display | 27950 | 90308990 |
| MC-22D | Digital Motor Checker with insulation resistance test of 1000V | 34400 | 90308990 |
| MC-38D | Digital Motor Checker with insulation resistance test of 500 and 1000V | 18813 | 90308990 |
| Multifunction Environment Meter | | | |
| ET-2 | Four-in-One Digital dB, Lux, temperature and Humidity meter with RS-232C PC Interface cable and software | 7740 | 90278090 |
| ET-3 | Six-in-One Digital dB, Lux, Humidity, temperature, Multimeter and AC Voltage Detector | 8278 | 90278090 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|---|----------------|----------|
| Multi-point Temperature Indicator | | | |
| DTI-101M 6 CH | 6 Channel Digital Multi-Point Temperature Indicate for K, J,R, S, PT-100 (Any One) type of sensor | 4031 | 90308990 |
| DTI-101M 12 CH | 12 Channel Digital Multi-Point Temperature Indicate for K, J,R, S, PT-100 (Any One) type of sensor | 4838 | 90308990 |
| Non Contact Temperature Controller | | | |
| IT-91 | Infra Red Temperature controller for -50 to 950 Degree C, 50:1 D:S Ratio, adjustable emissivity, relay output, controller cut out 72 x 72 mm sq | 20425 | 84779000 |
| Oil Test Set | | | |
| 50-OTS | 50kV Manually operated Oil Test Set | 33325 | 84212900 |
| 50-MOTS | 50kV Motor operated Oil Test Set | 42463 | 84212900 |
| 60-OTS | 60kV Manually operated Oil Test Set | 37088 | 84212900 |
| 60-MOTS | 60kV Motor operated Oil Test Set | 46225 | 84212900 |
| 70-OTS | 70kV Manually operated Oil Test Set | 44075 | 84212900 |
| 70-MOTS | 70kV Motor operated Oil Test Set | 52675 | 84212900 |
| 75-OTS | 75kV Manually operated Oil Test Set | 47300 | 84212900 |
| 75-MOTS | 75kV Motor operated Oil Test Set | 56438 | 84212900 |
| 80-OTS | 80kV Manually operated Oil Test Set | 52998 | 84212900 |
| 80-MOTS | 80kV Motor operated Oil Test Set | 62350 | 84212900 |
| 90-OTS | 90kV Manually operated Oil Test Set | 58050 | 84212900 |
| 90-MOTS | 90kV Motor operated Oil Test Set | 66650 | 84212900 |
| 100-OTS | 100kV Manually operated Oil Test Set | 62350 | 84212900 |
| 100-MOTS | 100kV Motor operated Oil Test Set | 74175 | 84212900 |
| 120-OTS | 120kV Manually operated Oil Test Set | 84925 | 84212900 |
| 120-MOTS | 120kV Motor operated Oil Test Set | 106425 | 84212900 |
| Digital Meters for above, extra to be paid | | | |
| Oscilloscopes | | | |
| OS-5010A | 10MHz Single Channel, Cathode Ray Oscilloscope | 19673 | 90302000 |
| OS-5020 | 20MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with 1:1 and 10:1 probes | 32143 | 90302000 |
| OS-5020C | 20MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with component test facility, comes complete with 1:1 and 10:1 probes | 33863 | 90302000 |
| OS-5030 | 30MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with 1:1 and 10:1 probes | 34400 | 90302000 |
| OS-5030C | 30MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with component test facility, comes complete with 1:1 and 10:1 probes | 36765 | 90302000 |
| OS-5060 | 60MHz Dual Channel Four Trace Cathode Ray Oscilloscope with 1:1 and 10:1 Probes | 74175 | 90302000 |
| OS-5100 | 100MHz Dual Channel Four Trace Cathode Ray Oscilloscope with 1:1 and 10:1 Probes | 88688 | 90302000 |
| Oscillometer | | | |
| 700S | | 68585 | 90302000 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|------------------------------------|---|----------------|----------|
| 760 | 20MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software | 114703 | 90302000 |
| 7100 | 100MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software, sampling rate 1GSa/Sec | 303903 | 90302000 |
| 7200 | 200MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software, sampling rate 1GSa/Sec | 390225 | 90302000 |
| Power Meter | | | |
| PM-10 | Bench-top high-precision Power Meter up to 900W | 17200 | |
| PM-10B | Bench-top high-precision Power Meter up to 3000W | 55900 | |
| Power Quality Analyser | | | |
| PRO 531 NEW!! | A comprehensive test instrument carefully developed and specially designed for field test of three phases, multi-functional and intelligent, concise man-machine operation. | 188125 | |
| Set of 4 Clamps 10A Max NEW!! | Optional set of Clamps for the PRO 531 for 10A | 21500 | |
| Set of 4 Clamps 100A Max NEW!! | Optional set of Clamps for the PRO 531 for 100A | 24725 | |
| Set of 4 Clamps 1000A Max NEW!! | Optional set of Clamps for the PRO 531 for 1000A | 44075 | |
| Set of 4 Clamps 6000A Max NEW!! | Optional set of Clamps for the PRO 531 for 6000A | 76325 | |
| PC Based Oscilloscope | | | |
| DSO-2090 | Dual Channel 40MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software | 29563 | 90302000 |
| DSO-2150 | Dual Channel 60MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software | 35475 | 90302000 |
| DSO-2250 | Dual Channel 100MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software | 46118 | 90302000 |
| PC Based Function Generator | | | |
| DDS-3005 | 5MHz PC Based Function generator with AM FM Modulation and TTL output along with sine, square, tri-angle, saw-tooth etc. with USB PC Interface cable and software | 54395 | 90308990 |
| PC Based Logic Analyzer | | | |
| LA-5034 | 34 Channel PC Based Logic Analyzer, with precision gripper, USB PC Interface cable and software | 41388 | 90308990 |
| pH Meter | | | |
| PH-600 | High-precision pH Meter with glass bulb electrode for measuring 0.00-14.00pH | 591 | 90308990 |
| Power Guard | | | |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|--|----------------|----------|
| PG-01 | Multifunction Power Meter, works on 6A, 230V, indicates, voltage, current, power factor, Power, KWh, Calculates CO2 emission, Calculates total time the equipment is under test and calculates the cost of electricity consumed accordingly. During load shedding the instrument memorizes the readings, ideal for analyzing power consumed for different kinds of loads | 2096 | 90308990 |
| Power Meter | | | |
| PM-10 NEW!! | Power Meter | 17200 | |
| PM-10B NEW!! | Power Meter | 55900 | |
| Primary Current Injection Test Set | | | |
| PCIT | On Request | | 90303390 |
| Programmable DC Power Supply | | | |
| PRPS-3005 NEW!! | Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 30V / 0– 5A DC | 12040 | 90308990 |
| PRPS-3003-2 NEW!! | Programmable DC Regulated Power Supply with Dual Output and Backlit LCD Display of Variable 0 – 30V / 0– 3A DC | 33863 | 90308990 |
| PRPS-3003-3 NEW!! | Programmable DC Regulated Power Supply with Triple Output and Backlit LCD Display of Variable 0 – 30V / 0– 3A DC | 38270 | 90308990 |
| PRPS-3005-2 NEW!! | Programmable DC Regulated Power Supply with Dual Output and Backlit LCD Display of Variable 0 – 30V / 0– 5A DC | 38270 | 90308990 |
| PRPS-3005-3 NEW!! | Programmable DC Regulated Power Supply with Triple Output and Backlit LCD Display of Variable 0 – 30V / 0– 5A DC | 38270 | 90308990 |
| PRPS-3005-4 NEW!! | Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 30V / 0– 5A DC | 161411 | 90308990 |
| PRPS-3010-4 NEW!! | Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 30V / 0– 10A DC | 0 | 90308990 |
| PRPS-3020 NEW!! | Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 30V / 0– 20A DC | 70950 | 90308990 |
| PRPS-3030 NEW!! | Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 30V / 0– 30A DC | 84925 | 90308990 |
| PRPS-6003-4 NEW!! | Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 60V / 0– 3A DC | 0 | 90308990 |
| PRPS-6005-4 NEW!! | Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 60V / 0– 5A DC | 0 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|--|----------------|----------|
| PRPS-6010 NEW!! | Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 60V / 0– 10A DC | 70950 | 90308990 |
| Refrigerant Gas Leakage Detector | | | |
| RLD-01 | 16" Gooseneck sensor, detects all CFC Refrigerants such as R-22, R-124, R-11 and R-12 etc. | 9675 | 90308990 |
| Relay Test Set | | | |
| RNT-5 | Relay Test Set, with current output upto 200A in various ranges | 46225 | 90318000 |
| RNT-5A | Relay Test Set with 200A in various ranges, Burden 1KVA, with AC/DC Voltage output | 66650 | 90318000 |
| RNT-33 | Relay Test Set suitable for testing distance relay, 3 phase current / voltage output and Fixed DC Voltage output | 268750 | 90318000 |
| ZNT-34 | Relay Test Set suitable for testing distance, over voltage relays etc., Variable three phase Voltage / Current and variable DC Voltage outputs | 290250 | 90318000 |
| Rotating Machine Tester | | | |
| RMT-10 NEW!! | One Single Meter that can test rotating machine, from insulation resistance to low resistance milli Ohms combined with a built-in T-RMS multimeters, Data logger, with Low pass Filter, Blue tooth Interface, Can measure AC/DC Voltage 1000V, DC/AC Current 10A, Resistance, Capacitance 5mF, Frequency 50Mhz, Temperature up to 1200 Degree C, Insulation Resistance can be measured up to 5000M.Ohms at test voltag of 50V / 100V / 250V / 500V / 1000V, with polarisation index and DAR, Low resistance from 1 m. Ohms to 2000 Ohms, | 32465 | 90303900 |
| RMTi-1 NEW!! | Rotating Machine Tester with Thermal Imager | 80625 | 90303900 |
| RPM METER | | | |
| CTR-49 | 6 Digits Red LED Display, Event Counter, 1 to 999999 Counts, 96 x 48 mm sq | 2419 | 90292090 |
| Short Turn Indicator | | | |
| EFD | Electric Fault Detector, to be used with more than two identical windings like general motors and transformers | 22468 | 90308990 |
| Little Giant | 9V Battery operated, to be used in single coils, simple insertion of coil on mandrill. | 17738 | 90308990 |
| Socket Polarity Tester | | | |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|---|----------------|----------|
| ST-09 | Socket Polarity Tester to be used for currents up to 6A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral. | 774 | 90308990 |
| ST-09A | Socket Polarity Tester to be used for currents up to 16A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral. | 817 | 90308990 |
| ST-09B | Socket Polarity Tester to be used for currents up to 6A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral. This can also be used for leakage test of up to 30mA | 925 | 90308990 |
| Sound Level Calibrator | | | |
| SC-05 | Sound Level Calibrator provides signals of 94dB and 114dB | 10535 | 90308990 |
| Solar Power Meter | | | |
| 207 | Solar Power Meter, to measure the amount of sunlight falling on the solar panel or any surface exposed to sunlight | 6343 | 90308990 |
| Spectrum Analyzer | | | |
| AT-5010 | 1050MHz Spectrum Analyzer | 105243 | 90308990 |
| AT-5011 | 1050MHz Spectrum Analyzer With Marker Generator | 164368 | 90308990 |
| Static Charge Meter | | | |
| SC-291 NEW!! | Measuring range : 0~ + / - 20.000KV, Measuring distance : 2.54cm(1 inch), Warning alarm setting, DATA / PEAK hold. Backlight function, Auto power off with disable function, Zero function and low battery indicate, Manual data memory storing 99 data sets. | 29563 | 90303100 |
| Tachometer (Non Contact type) Calibrator | | | |
| CE-0102TMC | Calibrator for Non Contact Tachometer for up to 199,999RPM | 13975 | 90308990 |
| Thermal Imagers | | | |
| PRO TI-10P NEW!! | Handheld, pocket-sized Thermal Imager for upto 500° C with storage for images and videos, Wi-Fi and USB interfaces, 8 Colour Palettes and Digital Zoom. | 54288 | 90251990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|--|---|----------------|----------|
| PRO TI-25 NEW!! | Handheld Thermal Imager for upto 550°C with 256×192 pixels resolution. Images & video recording along with touchscreen TFT LCD display, Wi-Fi, USB and free App. | 84925 | 90251990 |
| PRO TI-50 NEW!! | Handheld Thermal Imager for upto 650°C with 384×288 pixels resolution. Images & video recording along with touchscreen TFT LCD display, Auto-Fusion, Wi-Fi, USB and free App. | 196725 | 90251990 |
| Transistor Tester | | | |
| TT-01 | Transistor Tester for Testing and Checking Bias Current and other parameters of Transistors | 4999 | 90312000 |
| Tap Position Indicator | | | |
| CE-0102V | Digital type, Panel Mounting, Tap Position indicator, 96mm sq or 96x48 mm sq | 2580 | 85049010 |
| Time Totalizer | | | |
| TT-300 | 6 Digits LED Display, 96 x 48 mm sq, Auto range from 9999.99 to 999999Hrs. | 2419 | 90292090 |
| TT-302 | 6 Digits LED Display, 96 x 96 mm sq, Auto range from 9999.99 to 999999Hrs. | 2688 | 90292090 |
| Transformer Turns Ratio Set | | | |
| TTRS-100 | Transformer Turns Ratio Set to measure ratio in the range of 0.800 to 2021 & for Phase Deviation Measurement | 129000 | 90303900 |
| Two Color Infra Red Thermometer | | | |
| ST-300A | | 367650 | 90308990 |
| ST-300B | | 367650 | 90308990 |
| ST-300C | | 397750 | 90308990 |
| Ultrasonic Thickness Gauge | | | |
| UTG-01 | Versatile Ultrasonic Thickness Gauge to measure thickness of high density material up to 200mm | 12900 | 90308990 |
| Vibration Meter | | | |
| VIB-30+ | Digital Vibraton Meter, measures RMS velocity in the range of 0.1 to 199.9 mm/sec T-RMS & Peak | 31175 | 90301000 |
| AVD-80 | Digital Vibration Meter, measures velocity, acceleration and displacement | 39775 | 90308990 |
| BCA-111 | Bearing Condtion Analyzer, measures bearing test, vibration and has in-built tachometer. | 145125 | 90308990 |
| 908 | Measures velocity, acceleration and displacement along with the temperature, comes complete with the magnetic Base | 18813 | 90308990 |
| 908T NEW!! | | 91053 | 90308990 |
| PVB-820 | Pen Type Vibration Meter, it can measure accelleration, velocity and displacement | 18275 | 90308990 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|---|----------------|----------|
| VT-141 NEW!! | Dual Channel Vibration meter, Wide frequency range of 10Hz to 5KHz, Acceleration, velocity and displacement, Vibration sensor with magnetic adapter on 1.2M (47.2) cable, Frequency Lo range : 10Hz~1KHz meets ISO 2954 measurement, Hi range : 10Hz~5KHz, MAX record, Auto power off with disable function | 87075 | 90308990 |
| VT-141D NEW!! | Dual Channel Vibration meter, Wide frequency range of 10Hz to 5KHz, Acceleration, velocity and displacement, Vibration sensor with magnetic adapter on 1.2M (47.2) cable, Frequency Lo range : 10Hz~1KHz meets ISO 2954 measurement, Hi range : 10Hz~5KHz, MIN/MAX record and recall, Data logger with 9999 records capacity, USB interface, Auto power off with disable function | 94600 | 90308990 |
| Voltage Transducer | | | |
| CE-0102VT | Voltage Transducer with single Output | 3655 | 85045090 |
| Video IR Thermometer | | | |
| VIT-20 | Dual Laser Pointer, Color Display, Video and Still picture recording, In-built Contact Thermometer, uSD Card & PC interface, -50 to 1850°C, Adjustable Emissivity, D:S 50:1 | 59125 | 90251990 |
| Weather Station | | | |
| WH-1081PC | Weather station, for prediction of weather and recording of temperature, humidity, wind chill, dew point, rainfall, wind speed, air pressure and storm warning | 17738 | 90308990 |
| WP-1050 | | | |
| Wet Bulb Globe Temperature Meter | | | |
| WBGT-188 NEW!! | Quick-response capacitance sensor, accurate measurement for wet bulb globe temperature (WBGT), black globe temperature (TG), humidity (% RH), air temperature (TA), wet bulb (WET) and dew point (DEW). Max/Min and data hold, Low battery indication, LCD display with LED backlight, Viewing data records, Switch the temperature unit to °C or °F, Brass black ball in 50mm diameter, WBGT alarm setting, Auto power off with disable function | 17738 | 90318000 |
| WBGT-188D NEW!! | Quick-response capacitance sensor, accurate measurement for wet bulb globe temperature (WBGT), black globe temperature (TG), humidity (% RH), air temperature (TA), wet bulb (WET) and dew point (DEW). Max/Min and data hold, Low battery indication, LCD display with LED backlight, Viewing data records, Switch the temperature unit to °C or °F, Brass black ball in 50mm diameter, WBGT alarm setting, Auto power off with disable function, Data logging capacity: 12000 records, USB PC serial interface, Sampling interval: Max 24 hours; Min 1 Second | 24725 | 90318000 |

This is a temporary Price List as on 11th July 2022
and supercedes all earlier price lists.
Final Price List with updated models descriptions will be shared soon.

| ITEM | DETAILS | NEW LIST PRICE | HSN |
|---|---|----------------|----------|
| Wheatstone Bridge | | | |
| WSB | OXFORD Brand Wheatstone Bridge | 16663 | 90230090 |
| TERMS & CONDITIONS | | | |
| VALIDITY: | PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE | | |
| PRICES: | NETT, EX GODOWN KOLKATA | | |
| PACKING: | PRICES INCLUSIVE OF PACKING CHARGES | | |
| FREIGHT: | PRICES EXCLUSIVE OF FREIGHT CHARGES. IN CASE IF GOODS ARE REQUIRED BY ANY OTHER COURIER, OTHER THAN OUR NOMINATED COURIER ANY BY AIR, THEN THE FREIGHT SHALL BE CHARGED EXTRA AT ACTUALS | | |
| DELIVERY: | READY STOCK SUBJECT TO PRIOR SALES, FOR HIGH VOLTAGE EQUIPMENTS 8-12 WEEKS DELIVERIES WILL BE MADE ONLY AFTER THE PAYMENT IS CREDITED TO OUR ACCOUNT | | |
| INSURANCE: | TO BE COVERED BY THE BUYER THE GOODS WOULD BE PACKED SECURELY WITH OUR BEST INTENT TO PROTECT IT AGAINST ANY KIND OF TRANSIT DAMAGE. HOWEVER, IN CASE IF THE GOODS GET DAMAGED IN TRANSIT, THE BUYER WILL HAVE TO COVER ITS RISK | | |
| PAYMENT: | 100% AGAINST PROFORMA INVOICE / DOD / THROUGH BANK. 'ALTERNATIVELY' IF IT'S A TAILOR-MADE PRODUCT, 25% ADVANCE WITH THE ORDER BALANCE AGAINST PROFORMA INVOICE / DOD / THROUGH BANK | | |
| SHIPMENT: | SHALL TAKE PLACE WITHIN 48 HOURS OF RECEIPT OF PAYMENT | | |
| GOODS & SERVICE TAXES: | GST SHALL BE CHARGED EXTRA @18%. GST IS ALSO APPLICABLE ON FREIGHT CHARGES | | |
| ORDERING VALUE: | FOR ORDER VALUE LESS THAN RS.3000/- (RUPEES THREE THOUSAND) A CHARGE RS. TWO HUNDRED AS HANDLING CHARGES WILL BE LEVIED | | |
| DISCLAIMER: | WE TRY OUR BEST TO USE THE BEST OF COURIERS POSSIBLE FOR EARLIEST DELIVERY TIME BUT HAVE NO CONTROL OVER THE DELIVERIES BY THE COURIER. YOU MAY SUGGEST THE COURIER OF YOUR CHOICE AND WE SHALL SHIP THE GOODS THROUGH THEM, IF POSSIBLE. HOWEVER IN EITHER CASE, WE WILL NOT BE HELD RESPONSIBLE, UNDER ANY CIRCUMSTANCES, IF THE COURIER DELAYS THE DELIVERY FOR ANY REASON WHATSOEVER. | | |
| JURISDICTION: | SUBJECT TO KOLKATA JURISDICTION ONLY | | |
| THIS SUPERCEDES ALL PREVIOUS PRICE LISTS | | | |