

ITEM	DETAILS	LIST PRICE	HSN
AC High Voltage Test Set			
ACHV	Please check ACHV Tab or Click Here		
Acidity Testing Kit			
ATK	Testing Kit used to measure the Acidic content of Transformer Oil	1900	90308990
AC Power Supply			
APS-6003 NEW!!		30950	
APS-6006 NEW!!		40300	
APS-6003I NEW!!		35625	
APS-4002 NEW!!		52320	
APS-4003 NEW!!		66600	
APS-4005 NEW!!		76000	
APS-7002 NEW!!		66600	
APS-7004 NEW!!		78000	
APS-7008 NEW!!		133000	
Analogue Clamp Meter			
M-300	Clamp Jaw Dia 34mm, AC/DC Voltage, AC Current up to 300A, Resistance & Temperature. Pointer Lock Facility, with temperature probe	2600	90303100
M-600	Clamp Jaw Dia 34mm, AC/DC Voltage, AC Current up to 600A, Resistance & Temperature. Pointer Lock	2900	90303100
M-1000	Clamp Jaw Dia 48mm, AC Voltage up to 600V, DC Voltage up to 300V, AC Current in the range of 0-50/250/500/1000A AC, Resistance up to 2000K. Ohms, Temperature, Audible continuity Test	4500	90303100
Analogue Multimeter			
250TR	Measures AC/DC Voltage, DC Current, Resistance, Battery Test and dB.	990	90303100
260TR	Measures AC/DC Voltage, DC Current, Resistance, Transistor Polarity Test, Audible Continuity	1600	90303100
2010BA	Measures AC/DC Voltage, up to 10A AC/DC, Resistance, Transistor and Audible Continuity	2350	90308990
5050E	Measures AC/DC Voltage up to 1000V, AC/DC Current up to 10A, Resistance up to 2000M.Ohms, Frequency up to 25kHz, Transistor Testing, Diode Testing and audible continuity testing	3400	90308990
6060	Measures AC / DC Voltage up to 2500V, AC/DC Current up to 10A, Resistance up to 10M.Ohms, Diode and continuity test facility	12500	90308990
Battery Impedance			
TM-6002	Battery Impedance Tester to check Battery internal resistance, Voltage, Current and temperature, with 9999 memory, with PC Interface cable and software	81000	90308990
Bench Type Multimeter			

ITEM	DETAILS	LIST PRICE	HSN
45 T-RMS	4-1/2 Digits Bench type Multimeter	9550	90308990
55 TRMS NEW!!		51000	90308990
M-3511	6-1/2 Digits Bench type Multimeter AC/DC V, AC/DC Current, Resistance, Cap and Frequency	67000	90308990
M-3510A NEW!!	6-1/2 Digits Bench type Multimeter AC/DC V, AC/DC Current, Resistance, Cap., Temp. and Frequency	83000	90308990
M-3500A	6-1/2 Digits Bench type Multimeter with multiple options	109725	90308990
Cable Fault Locator			
CFL-01	Digital Cable Locator and Combined with Cable Fault locator	18500	90308990
CFL-02	Digital Cable Fault Locator for Power, Control and Telecom Cables burries underground	65000	90308990
Calibrator			
CAL-408	Bench type RTD Calibrator , Outputs availble at -200, -100, -50, -25, 0, 25, 50, 100, 150, 200, 300, 400, 500, 600 °C	7500	90308990
CAL-400-3	Hand Held, 3-1/2 Digits, Battery Operated, 0 - 19.99 /24mA, -199.9mV to 199.9mV source and current & power measurement	5500	90308990
CAL-400-4	Hand Held, 4-1/2 Digits, Battery Operated, 0 - 199.9 mV / 0 - 19.999mA sourcing and measuring range	8000	90308990
CAL-402-4	Bench type, 230V AC 50Hz Operated, 0 - 199.99m/ 1.9999 / 19.999V & 0 - 199.99u/1.999m / 19.999mA Sourcing & Measuring	9000	90308990
CAL-500	Hand Held, 4 Digits Large LCD Display, Measures and Provides output for 20mV / 100mV / 15V DC, Current output up to 24mA, 24V Loop Power, and outputs for K, E, J, T, R, S, B and N types of thermocouples	24000	90308990
01+	5 Digits 0.5% Accuracy, Source for Volt, Resistance, Pt-100, Cu-50, Thermocouples R, S, B, E, K, J, T, N types.	24500	90308990
03+	5 Digits 0.5% Accuarcy, Sources and Measures Resistance, PT-100 Sensor and Cu-50 Sensors	24500	90308990
05+	5 Digits, 0.5% Accuracy, Sources DC Current, Analogue Transducer & Loop Power and Measures DC Voltage, DC Current and Loop Current	28000	90308990
11+	6 Digits, 0.2% Accuracy, Sources R, S, B, E, K, J, T, N types of thermocouples, PT-100, Cu-50, DC Voltage, DC Current, Resistance, Analogue Transducer, Frequency, Pulse Output and LOOP Power.	72000	90308990
14+	6 Digits, 0.2% Accuracy, Sources and Measures DC Voltage, PT-100, Cu-50 Sensors and R, S, B, E, K, J, T & N types of Thermocouples.	72000	90308990
15+	6 Digits, 0.2% Accuracy, Sources and Measures DC Voltage, DC Current, Analogue Transducer and LOOP Power.	72000	90308990

ITEM	DETAILS	LIST PRICE	HSN
25 NEW!!	50,000 Counts, 0.2% Universal Calibrator for DC Voltage, Current, Resistance, Frequency, all thermocouples and thermo-resistance and for	250000	90308990
709H	mA Loop Calibrator with HART COMMUNICATOR, Accuracy 0.01%	95000	90308990
709H-USB	USB COMMUNICATION INTERFACE CABLE AND SOFTWARE for 709H	40000	90308990
VIB-CAL-01 NEW!!	Vibration Calibrator	204000	90308990
CAL-ER NEW!!	Earth Resistance Tester Calibrator	32000	

Carbon Mono Oxide Meter

CO-05 NEW!!		14250	
CO-09	Detects Presence of Carbon Mono-Oxide. Range 0 to 1000PPM, Backlit LCD	14000	90308990
CO-10	Detects Presence of Carbon Mono-Oxide. Range 0 to 1000PPM, Backlit LCD, With Audio and Buzzer Alarm	15000	90308990
CO-110 NEW!!	Wearable/compact	15000	

Clamp On Ground Resistance Tester

CET-01	4 Digits LCD, 28mm Clamp Jaw Dia, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms	26000	90308990
CET-02	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms	26000	90308990
CET-03	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 20A.	32000	90308990
CET-04	4 Digits LCD, 28mm Clamp Jaw Dia, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms. With Leakage Current Measurement up to 20A.	34600	90308990
CET-05	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms	23000	90308990
CET-06	4 Digits LCD, 28 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms	23000	90308990
CET-02EX	Explosion Proof Clamp On Ground Resistance Tester, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 20A.	35900	90308990
CET-09 NEW!!		55000	

Coatmeter

ITEM	DETAILS	LIST PRICE	HSN
CTG-01	Measures coating thickness on both ferrous and Non Ferrous materials	10600	90318000
CTG-02	Measures coating thickness on both ferrous and Non Ferrous materials with extended flexible cable with sensor	19950	90308990
CTG-03 NEW!!		12000	
Combustible Gas Leakage Detector			
GLD-01	16" Gooseneck detector for detecting Combustible Gas Leakage. With Audio and Visual Alarm	5460	90308990
Current Transducer			
CE-0102CT	Current Transducer, AC Current Input and DC output	3350	90308990
Data Logger for Sound Level			
DL-SL01	Sound Level Data logger to record sound, from 30 to 130 dB, with 129920 data Points	12010	90308990
Data Logger for Temperature & Humidity			
DL-TH-01	Temperature and Humidity Data Logger with digital display and data logging up to 32700 points	4700	90308990
Data Logger for Voltage and Current			
DL-VL-01	Data Logger for Voltage and Current with digital display and 100096 data points	14700	90308990
DC High Voltage Test Set			
DCHV	Please check tab DCHV or click here		90308990
DC Regulated Power Supply			
RPS-3002	Single Output with Backlit LCD Display of Variable 0 - 30V / 0 - 2A DC	7950	90308990
RPS-3005	Single Output with Backlit LCD Display of Variable 0 - 30V / 0 - 5A DC	7950	90308990
RPS-6005	Single Output with Backlit LCD Display of Variable 0 - 60V / 0 - 5A DC	19500	90308990
RPS-3010	Single Output with LED Display of Variable 0 - 30V / 0 - 10A DC	19450	90308990
RPS-3020	Single Output with LED Display of Variable 0 - 30V / 0 - 20A DC	28000	90308990
RPS-3030	Single Output with LED Display of Variable 0 - 30V / 0 - 30A DC	62000	90308990
RPS-6010	Single Output with LED Display of Variable 0 - 60V / 0 - 10A DC	36650	90308990
RPS-6030	Single Output with LED Display of Variable 0 - 60V / 0 - 30A DC	112000	90308990
RPS-3002-2	Dual Output with Backlit LCD Display of Variable 0 - 30V / 0 - 3A DC	15500	90308990
RPS-3005-2	Dual Output with Backlit LCD Display of Variable 0 - 30V / 0 - 5A DC	19400	90308990

ITEM	DETAILS	LIST PRICE	HSN
RPS-3003-3	Triple Output with Backlit LCD Display, Dual 0 - 30V / 0 - 3A DC and Fixed 5V/3A	15300	90308990
RPS-3005-3	Triple Output with Backlit LCD Display, Dual 0 - 30V / 0 - 5A DC and Fixed 5V/3A	19400	90308990
RPS-10003 NEW!!		27500	
RPS-20002 NEW!!		32000	
DDS Function Generator			
DDS-30 NEW!!	5 MHz DDS Function generator, 125MSa/s sampling rate	20500	90308990
DDS-60 NEW!!	5 MHz DDS Function generator, 125MSa/s sampling rate	25500	90308990
DDS-1010	10 MHz DDS Function generator, 125MSa/s sampling rate	22000	90308990
DDS-1025	25 MHz DDS Function generator, 125MSa/s sampling rate	40300	90308990
DDS-1060	50 MHz DDS Function generator, 125MSa/s sampling rate	60000	90308990
DDS-1080 NEW!!	80MHz DDS Function generator, 320MSa/s sampling rate	106000	90308990
DDS-1120 NEW!!	120MHz DDS Function generator, 320MSa/s sampling rate	136000	90308990
Digital AC/DC Clamp Meter			
DT-725	3-5/6-digit 5999 Count, Backlight LCD, T-RMS, Auto-Ranging, NCV, Flashlight, Relative Measurement, AC (750V)/DC(1000V) Voltage, 600A AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity. Square Wave Output, CAT-IV 600V	2750	90303100
DT-230	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 400A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test.	4750	90308990
DT-325	3-3/4 Digits 3999 Counts, Digital AC/DC Clamp Meter, Confirming to CAT-III 300V, Jaw Size 28 mm, Auto Power Off, Data Hold, AC/DC Voltage up to 600V, AC/DC Current up to 400A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test Facility	3460	90308990
DT-6250	3-3/4 Digits, LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Current up to 400A, Resistance, Frequency, Duty Cycle, Capacitance, Diode and Continuity Test.	5500	90308990
DT-1350	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A AC/DC Clamp Meter with AC/DC Voltage, Resistance, Diode and Continuity Check	2700	90303100
DT-1350A	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A AC/DC Clamp Meter with AC/DC Voltage, Resistance, Capacitance, Temperature and Frequency	3100	90303100

ITEM	DETAILS	LIST PRICE	HSN
DT-3690	3-4/5 Digits 6000 Counts, LCD, Data Hold,T-RMS, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 1000A, Resistance,Capacitance, Frequency and Temperature & Continuity Test	3700	90303100
DT-425T	3-3/4 Digits 3999 Counts Backlit LCD, T-RMS AC/DC Clamp meter, Confirms to CAT-III 600V, Data Hold, MAX/MIN, Relative, In-Built Flash Light, Overload Protection, 30mm Clamp Jaw Dia, Auto Power Off, AC T-RMS / DC Current 600A, AC T-RMS / DC Voltage 600V, Resistance, Capacitance, Temperature, Frequency, Non Contact Voltage Detector, Diode and Cotinuity Test	5500	90308990
DT-3250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC Voltage, 1000A DC/AC Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	6700	90308990
DT-3600	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage,1200A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	6900	90308990
DT-4250	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Duty Cycle, Diode & Continuity Test.	6900	90303100
DT-5250	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, T-RMS, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test.	7200	90303100
DT-8250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC Voltage, 2000A DC/AC Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	7400	90308990
DT-9250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage,2000A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	8500	90308990

ITEM	DETAILS	LIST PRICE	HSN
2003A NEW!!	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage,2000A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	8500	90303100
METRACLAMP-15	3999 Counts, Backlit LCD, 52mm jaw Dia, Non Contact Voltage Detector, Auto Power Off, T-RMS, AC/DC Voltage, AC T-RMS/DC 1000A, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test, double Injection mould, CAT-IV 600V	7900	90308990
METRACLAMP-20	4-3/4 Digits, 40,000 Counts, Backlit, T-RMS, Autoranging, 52mm Jaw Dia, Non Contact Voltage Detector, Fully Protected, AC/DC Voltage, AC/DC Current up to 1500A, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Diode and Continuity Test	12000	90308990
SOLAR - 2	6000 Counts, Auto-Backlit LCD Display, 1000V DC/AC T-RMS, Specially designed for P-V Application to measure 2000V DC/1500V AC, DC/AC T-RMS 600A, Resistance up to 600k.Ohms, Tempeature up to 400 Degree C, Capacitance up to 1000uF, Frequency up to 10kHz, Continuity and Diode Test, Optionally can connect to flexible clamp to measure up to 3000A AC. Designed to meet IEC/EN 61010-1, IEC/EN 61010-2-033 CAT IV 600V/CAT III 1000V, Max Conductor Dia 37mm, High Frequency Rejection, In-rush current measurement	27700	90303100
PRO 474	6000 counts, digital AC/DC T-RMS clamp meter, TFT LCD display, Bluetooth, 1000V AC T-RMS /DC, 1000A AC T-RMS/DC, 34mm Jaw, 10" Flexible Clamp adaptor for upto 3000A AC, AC+DC Voltage, Inrush Current, VFD AC T-RMS Voltage, Lo-Z Voltage, NCV, Capacitance, Resistance, Frequency, Temperature, Continuity and Duty Cycle, Free APP, Datalogging, Trend Capture on device and APP simultaneously	22500	90303100
PRO 419	3-3/4 Digit Professional T-RMS AC/DC Clamp Meter, 4000 Count, 1000V AC T-RMS/DC, 1000A AC T-RMS/DC, Auto Power Off, Non Contact Voltage Detector, Flash light, Data Hold, MAX-MIN Record, Relative Measurement, 100mF Capacitance, 100kHz Frequency, 40MOhms Resistance, 1000°C Temperature measurement using K type sensor, Continuity.	6700	90303100
PRO 421 NEW!!		7400	90303100
PRO Solar-3 NEW!!		19500	90303100
DT-1350AT		3200	

ITEM	DETAILS	LIST PRICE	HSN
Digital Ammeter			
	same		
CE-0102A 96x48	3-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 48 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	1000	90303310
CE-0102A 96x96	3-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 96 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	1000	90303310
CE-0102A 96x48	3-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 48 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	1100	90303310
CE-0102A 96x96	3-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 96 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	1100	90303310
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size			
CE-0102A 96x48	4-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 48 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	2200	90303310
CE-0102A 96x96	4-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 96 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	2200	90303310
CE-0102A 96x48	4-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 48 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	2200	90303310
CE-0102A 96x96	4-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 96 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	2200	90303310
Digital Ammeter Controller			
CE-0102AC 1SP	Digital Ammeter with Single Set Point to control the current below a given set point. Size - 96 x 96 mm sq. With 1NO + 1NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	3500	85359030
CE-0102AC 2SP	Digital Ammeter with Two Set Point to control the current below a given pair of set points. Size - 96 x 96 mm sq. With 2NO + 2NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	3900	85359030
Digital Anemometer			

ITEM	DETAILS	LIST PRICE	HSN
AVM-01	4 Digits Backlit LCD Display, Data Hold, Max Record, Measures Air Velocity up to 30m/Sec, measures in km/hr, ft/min, knots, mph as well, Displays Air Temperature -10 to 50 Degree C, Shows windchill and also displays Beaufort Wind Scale	1750	90268090
AVM-03	Digital Thermo-Anemometer with facility to measure 40m/Sec, with humidity, CMM, CFM, USB PC Interface	5000	90268090
AVM-04	Digital Thermo-Anemometer with facility to measure up to 45m/Sec and in ft/min also	5700	90268090
AVM-05	Digital Thermo-Anemometer with facility to measure wind flow (CFM / CMM)	7125	90268090
AVM-07	Digital Thermo-Anemometer to measure up to 30m/Sec with Metal Blades, Temp. -10 to 60°C / 14 to 140°F	5100	90268090
AVM-08	Digital Thermo-Anemometer with facility to measure wind flow (CFM / CMM) with built in infra-red Thermometer to measure from -50 to 260°C with 8:1 D:S Ratio and Emissivity Fixed at 0.95	11970	90268090
AVM-09	Digital Thermo-Anemometer with facility to measure wind flow (CFM/CMM) with built in Pressure Meter	18000	90268090
AVM-10	Digital Hot Wire Anemometer, Dual LCD, with RS-232 Interface, 0.1 to 20m/Sec and Temperature from -20 to 80°C / -5 to 175°F	14000	90268090

Digital Capacitance Meter

DCM-1502	3-1/2 Digits, LCD, Zero Adjustment, up to 20mF Capacitance Measurement	2650	90308990
-----------------	--	-------------	----------

Digital Clamp Meter

DT-115	6000 Counts, Backlit LCD, With Flashlight, Autoranging, Auto Power Off, T-RMS, Non Contact voltage detection, Flashlight, Data Hold, 40 mm Jaw Size, AC/DC Voltage, AC Current up to 600A T-RMS, Capacitance, Frquency, Temperture, Ressitance, Continuity & Diode test.	1780	90303100
DT-115A	6000 Counts Backlit LCD Display, Built-in Flashlight to access dark Areas, Non Contact Voltage Detection, Simple to use, Just provide the input and the instrument, detects the signal and displays the parameter, No Selection required, Just provide Input, Automatic Selection of AC/DC Voltage, Resistance, Capacitance, Diode Test, T-RMS, 600A T-RMS Measurements	2175	90303100
DT-369	3-4/5 Digits 6000 Counts, LCD, Data Hold, T-RMS, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance,Capacitance, Frequency and Temperature & Continuity Test	2250	90303100
DT-1150	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A Clamp Meter with AC/DC Voltage	1850	90303100

ITEM	DETAILS	LIST PRICE	HSN
DT-1150A	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A Clamp Meter with AC/DC Voltage, Resistance, Capacitance, Temperature and Frequency	2250	90303100
DT-225	3-1/2 Digits, Backlit LCD, Data Hold, Max Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Temperature, Frequency, Diode and Continuity Test. 500V DC/AC Protection in all ranges.	2800	90308990
DT-1250	3-1/2 Digits, Backlit LCD, Data Hold, Max Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Diode and Continuity Test. 500V DC/AC Protection in all ranges.	2900	90308990
DT-2250	metra clamp	3400	90308990
DT-2255	3-1/2 Digits, LCD, Data Hold, Auto-ranging, 57mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test.	3400	90308990
DT-3150	3-3/4 Digits, Backlit LCD, Data Hold, 57mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Frequency, Duty Cycle, Diode and Continuity Test Facility. 1000V DC/AC Protection in all ranges.	3500	90308990
DT-7250	3-1/2 Digits, LCD, Data Hold, Auto-ranging, 57mm Jaw Size, AC/DC Voltage, AC Current up to 2000A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test.	5500	90308990

Digital Clamp Meter with Wireless PC Interface

DT-5250W	3-3/4 Digits, Backlit LCD, Peak & Data Hold, T-RMS, Wireless PC Interface, 30mm jaw size, AC/DC Voltage, AC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test	9500	90308990
----------	---	------	----------

Digital Clamp On Power Meter

107F	10000 Counts Digital Clamp On Power Meter, AC/DC Voltage and AC/DC Current Auto Detection, NCV, Jaw Dia 42mm, KW, PF, THD up to 25th Harmonics	24500	90308990
307	6000 Counts, Backlit LCD, Single Phase and Three Phase, Non Contact Voltage Detector, Data Hold, Peak Hold, Relative, Max/Min Reocrd, Single Phase KW, KVA, KVAr, PF, kWh and KW & PF for Three Phase. Clamp Jaw Size 56mm. AC Current up to 1500A AC.	15300	90308990
307N	4 Digits, Dual LCD, Single Phase and Three Phase, Max /Min / Peak Hold, 55mm Jaw Dia, T-RMS, AC Voltage, AC Current up to 1000A, KW, KVA, KVAR, Power Factor, Phase Angle, kWh, Frequency and Temperature. With Data Logging and PC Interface	9200	90308990

ITEM	DETAILS	LIST PRICE	HSN
607	4 Digits, Dual LCD, Harmonic Analysis up to 50th Harmonic, PC Interface, Single Phase & Three Phase, Maximum Demand, KW, KVA, KVAR, KWh, KVAh, KVARh, Power Factor, Real time output of waveform, Power Parameters and Harmonics. Clamp Jaw Size - 55mm.	71250	90308990
Digital Distance Meter			
DM-09	Digital Ultrasonic Distance Meter to measure up to 16m	1750	90308990
Digital Earth Tester			
ERT-1501	0 - 10 / 100 / 1000 Ohms, 4 Terminal with Testing Kit and Cables in hard carrying case	7150	90303900
ERT-1502	Rechargeable Battery and Battery Charger for above	8000 4400	90303900
PRO ERT-1635 NEW!!		77500	90303390
PRO ERT-1602 NEW!!		32500	90303390
Digital Frequency Counter			
FC-2700	8 Digits Green LED Frequency Counter up to 2.7GHz	9160	90308990
Digital Frequency Meter			
CE-500F 99.99Hz	4 Digits, Panel Flush Mounting, 96 X 48 mm sq, Input 10 - 500V, Measuring range 20 - 99.99 Hz.	1230	90303310
CE-500F 96 x 96	4 Digits, Panel Flush Mounting, 96 X 96 mm sq, Input 10 - 500V, Measuring range 20 - 99.99 Hz.	1230	90303310
CE-500F 999.9Hz	4 Digits, Panel Flush Mounting, 96 X 48 mm sq, Input 50 - 500V, Measuring range 0 - 999.9 Hz.	1350	90303310
CE-500F 96 x 96	4 Digits, Panel Flush Mounting, 96 X 96 mm sq, Input 50 - 500V, Measuring range 0 - 999.9 Hz.	1350	90303310
Digital IC Tester			
DICT-2040	40 Pin Digital IC Tester to test 54 / 74 series TTL and 4000 & 4500 series CMOS IC's, tests more than 2000 kinds of devices	31350	90308200
Digital Insulation Tester			
DIT-909	9999 Counts Backlit LCD, Low Battery Indication, Dat Hold, Timer Function up to 10mins, Comparator, 99 Data Records, USB PC Interface (optional) Test Voltage: 50V / 100V / 250V / 500V / 1000V, 200G. Ohms, AC Voltage T-RMS, DC Voltage, Freuqncy, Capacitance, Continuity Test, With Remote Probe, IP-54	27100	90308990
DIT-910 NEW!!	4 Digits, with GO NO-GO functions, 250V/500M. Ohms, 500V/1G.Ohms, 1000V/2G.Ohms	4400	90308990

ITEM	DETAILS	LIST PRICE	HSN
DIT-912	4 Digits with Analog Bargraph, measures upto 2000M.Ohms at 250V / 500V / 1000V, measures 600V AC/DC, Low Resistance up to 4000 Ohms and Continuity test. Fully Protected on all ranges	9975	90308990
DIT-913	Digital Insulation Tester for 250V / 500V / 1000V / 2500V , 0-2000M(250V), 0-20G(500/1000/2500V)	5700	90308990
DIT-914	Battery cum Mains Operated, with facility to measure AC Voltage, Low Resistance, Continuity, 500V/2000M.Ohms, 1000V/2000M.Ohms, 2500V/20G.Ohms, 5000V/200G.Ohms	15800	90308990
DIT-916	Selectable testing voltages - one testing instrument for low and high voltage systems from 500/1000/2500 and 5000V, Insulation resistance measurement up to 1T Ω , User selectable programmable timer (10s to 30 min), Automatic discharge of test object after completion of measurement, Diagnostic tools, Polarization index (PI), Dielectric absorption ratio (DAR), USB PC Interface	29000	90308990
DIT-921	Battery cum Mains Operated, with facility to measure, PI, DAR, AC Voltage, Low Resistance, Continuity, 500V/6G.Ohms, 1000V/6G.Ohms, 2500V/60G.Ohms, 5000V/60G.Ohms	27000	90308990
DIT-99A	Digital Battery Cum Mains Operated Insulation Tester for 100V / 200M.Ohms	2850	90308990
DIT-99B	Digital Battery Cum Mains Operated Insulation Tester for 250V / 200M.Ohms	2850	90308990
DIT-99C	Digital Battery Cum Mains Operated Insulation Tester for 500V / 1G.Ohms	2850	90308990
DIT-99D	Digital Battery Cum Mains Operated Insulation Tester for 1000V / 2G.Ohms	2850	90308990
DIT-321	Digital Insulation Resistance Tester with Built-in Multimeter, 3-3/4 Digits 3999 Counts, Backlit LCD, Data Hold, Test Voltage: 250V / 500V / 1000V, upto 40G.Ohms, Measures AC/DC Voltage, AC/DC Current up to 400mA, Resistance, Capacitance, Frequency, Diode & Continuity Test Facility.	4500	90308990
DIT-322	Digital Insulation Resistance Tester with Built-in Multimeter, 3-3/4 Digits 3999 Counts, Backlit LCD, Data Hold, Test Voltage: 500V / 1000V / 2500V, upto 40G.Ohms, Measures AC/DC Voltage, AC/DC Current up to 400mA, Resistance, Capacitance, Frequency, Diode & Continuity Test Facility.	6000	90303100
DIT-925 NEW!!		55000	90303900
DIT-927 NEW!!		61000	90303900
DIT-930 NEW!!		78000	90303900
DIT-930E NEW!!		85000	90303900
DIT-930F NEW!!		120000	90303900
DIT-950 NEW!!		365000	
DIT-951 NEW!!		274000	

ITEM	DETAILS	LIST PRICE	HSN
Digital VA Meter			
CE-0303VA	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	4200	90303310
CE-0304VA	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	4200	90303310
Digital VAR Meter			
CE-0303VAR	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	4200	90303310
CE-0304VAR	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	4200	90303310
Digital KWh Meter			
CE-0303EML	Digital KWh Meter with LCD Display for Three phase Three wire Two element loads	4950	90283090
CE-0304EML	Digital KWh Meter with LCD Display for Three Phase Four wire Three Element loads	4950	90283090
CE-0102EML NEW!!		4000	90283090
Digital LCR Meter			
360	3-1/2 Digits Hand Held Digital LCR Meter, Measures Inductance from 0.001mH to 20H, Capacitance from 0.001nF to 600uF and Resistance from 0.1 to 20M. Ohms, with diode test, transistor test and audible continuity test, CE Approved	4600	90308990
460	11,000 Counts Backlit LCD, Data Hold, MAX/MIN Record, RELATIVE, Inductance, Capacitance, Resistance, Diode & Continuity Test	5300	90308990
4070D	5 Digits, LCD, Dual Display, Inductance, Capacitance, Resistance, Impedance, D, ESR and Q Test Facility, Test Frequency of 100Hz, 120Hz, 1kHz, 10kHz and 100kHz	12000	90308990
4090D NEW!!		31000	
Digital LCR Multimeter			
451	3-1/2 Digits, Backlit LCD, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Inductance, Frequency, Temperature, Diode, Transistor and Continuity Test	3770	90303100
506	3-3/4 Digits, Backlit, LCD Dual Display, T-RMS, RS-232 PC Interface, Internal Memory, Min, Max, Avg, Relative Modes, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Inductance, Duty Cycle, Temperature, dBm, Logic, Diode, Signal Output & Continuity Test	20500	90303100
Digital Leakage Current Meter			

ITEM	DETAILS	LIST PRICE	HSN
DT-4671	3-3/4 Digits, Analogue Bargraph, LCD, Data Hold, MAX/MIN Record, 30mm Jaw Size, AC Voltage, AC Current, Resistance. Has Low Pass Filter to filter out noise.	6100	90308990
DT-4672	3-3/4 Digits, LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Leakage Current measurement, Capacitance, Resistance, Frequency, Duty Cycle, Diode & Continuity Test	6400	90308990
DT-4673	3-1/2 Digits, LCD, T-RMS,. AC/DC Leakage Current Meter, Non contact voltage detector, Data Hold, Can be used for Variable Frequency Control Drives, Measures from 1mA, AC/DC Current up to 100A, AC/DC Voltage, Resistance, Capacitance, Diode and Continuity Test	5300	90308990
DT-6054	3-1/2 Digits LCD, Data Hold, Max Hold, 30mm Jaw Dia, 0 - 200mA / 2A / 200A AC.	5200	90308990
MULTI-140	3-1/2 Digits, 3200 Counts LCD, Data Hold, 40mm jaw Dia, 0 - 30m/300m/30/300A AC	30500	90308990
PRO-468AC	6000 Counts, Auto-Backlit LCD Display, Auto Power Off, as per IEC 61557-13: Class 2, 40mm Jaw Dia, IEC / EN 61010-1, IEC / EN 61010-2-032, CAT. III 600V, Pollution Degree 2, EN 61326-1 EN 61326-2-2, bandwidth up to 1kHz, 1% accuracy, 0 - 6mA / 60mA / 600mA / 6A / 60A, With resolution of 1uA,	31200	90308990
PRO 2010 NEW!!		25000	
Digital Lux Meter			
1300	4 Digits Backlit LCD Display, MAX / MIN Record, Data Hold, Digital Lux Meter, Can measure up to 200,000 Lux, Also measures in FC (Foot Candle), High Sampling Rate, Overload Indication, Auto Power Off, Low Battery Indication	1730	90278090
1310	4 Digits Backlit LCD Display, Data Hold, Hi/Lo Indication, Split Probe, Lux and Foot Candle Measurement, Auto Power Off, Lo-Battery Indication, Measures up to 199,900 Lux / Fc	2700	90278090
1330	Measures up to 50,000 Lux	2500	90278090
1331	Measures up to 50,000 Lux / Ft Candle with Max Hold and Data Hold	3000	90278090
1332	Measures up to 200,000 Lux / Ft Candle with Peak Hold and Data Hold	5500	90278090
1332A	Measures up to 200,000 Lux / Ft Candle with Max Hold and Data Hold	7300	90278090
1333	Measures up to 0 - 20 / 200 / 2000 / 200000 / 200,000 Lux / Ft Candle with Max Hold and Data Hold	4900	90278090
1334	Measures up to 400,000 Lux/40,000 Ft Candle, Data & Peak Hold, Max Min Record, USB PC Interface, Backlit LCD With Analogue Bargraph	6100	90278090
1335 NEW!!	LED	7900	

ITEM	DETAILS	LIST PRICE	HSN
Digital Micro Ohms Meter			
53C	Digital Micro Ohms Meter to measure from 1uOhm to 2k.Ohms	5900	90308990
53C-II	Micro-Processor based, Digital Micro Ohms meter to measure from 1uOhms to 2kOhms, with digital selection of ranges	6300	90308990
UOT-10A	Digital Micro Ohms Meter with Test Current of 10A	77000	90308990
7272A NEW!!		56000	90308990
UONT-100A	Digital Micro Ohms Meter with Test Current of 100A	90000	90308990
UONT-200A	Digital Micro Ohms Meter with Test Current of 200A	175000	90308990
Digital Milli Ohms Meter			
52C	Hand Held, 0.1mOhms to 40 Ohms, 4 wire Kelvin type connection, also measures AC/DC Voltage, AC/DC Current, Resistance, Capacitance and continuity	9500	90308990
Digital Moisture Meter			
MM-1	Digital Moisture Meter for paper, wood and hardned material like plaster, concrete and mortar	3300	90308990
MM-2	Digital Moisture Meter for wood, bamboo, cotton, tobacco, paper, foodstuffs	1600	90308990
MM-5	Digital Wood Moisture Meter that can measure moisture in up to 150 different kinds of wood	6100	90308990
MM-10	Digital Pinless Moisture Meter, Range 0 - 100%, auto power off, backlit display, Min/Max function, Measure and Hold, works on most of the products	8000	90308990
Digital Multimeter			
XB-30	3-1/2 Digits, LCD, Data Hold, AC Voltage, DC Voltage, DC Current, Resistance, Diode & Transistor Test.	1375	90308990
XB-33CF	6000 Counts Backlit LCD, Flash Light, NCV, MAX/MIN Record, T-RMS, Measures AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Frequency, Diode and Continuity Test	1600	90303100
603	3-1/2 Digits, Backlit LCD, Data Hold, AC Voltage, DC Voltage, AC Current, DC Current, Resistance, Capacitance, Frequency, Temperature, Hot Wire, Diode, Transistor and Continuity Test.	1900	90303100
6030A+	6000 Counts Backlit LCD, T-RMS Multimeter, Auto Power Off, Data Hold, MAX/MIN, AC / DC Voltage, AC/DC Current 20A, Resitance, Capacitance, Frequency, Temperature, Transistor Test, Diode and Continuity Test	1950	90303100
901-I	3-1/2 Digits, LCD, Auto-ranging, Max Hold and Data Hold, AC Voltage, DC Voltage, AC Current, DC Current, Resistance, Temperature, Diode & Continuity Test. 500V DC/AC Protection in Resistance, Temperature, Diode and Continuity Test.	2200	90308990

ITEM	DETAILS	LIST PRICE	HSN
19	3-3/4 Digits, LCD, Auto-ranging, Relative, Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, 30MHz Frequency, Duty Cycle, Temperature, Diode, Transistor and Continuity Test.	2100	90303100
19-SUPER	6000 Counts LCD Display, NCV, T-RMS Multimeter, Measures AC/DC Voltage, AC/DC Current up to 20A, Resistance, Temperature, Frequency, Capacitance, Diode, Transistor Test and Continuity Test Facility	2250	90303100
901-II	3-3/4 Digits, Backlit LCD, Auto-ranging, Relative, Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity Test.	2900	90308990
901-III	3-5/6 Digits, 6000 Counts Backlit LCD, Autor-ranging, 600V AC/DC Protection, AC/DC Voltage, AC/DC Current, Resistance, 4mF capacitance, 20MHz Frequency, temperature diode and continuity	4100	90308990
901-IV	3-5/6 Digits, 6000 Counts Backlit LCD, Autor-ranging, T-RMS, 600V AC/DC Protection, AC/DC Voltage, AC/DC Current, Resistance, 4mF capacitance, 20MHz Frequency, temperature diode and continuity	4900	90308990
801	3-3/4 Digits, LCD, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Logic Test, Diode & Continuity Test. 500V DC/AC Protection in Resistance, Capacitance, Frequency, Logic, Diode & Continuity Test	2950	90308990
DT-19TB	3-3/4 Digits, Backlit LCD, Auto-ranging, Terminal Blocking Facility, Relative & Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Battery Test, Diode & Continuity Test. 500V AC/DC Protection in all ranges	3300	90308990
Metrasafe-10	6000 Counts Backlit LCD, T-RMS, Flashlight, Live-Neutral detectio, Non contact voltage detector, Audio and visual alarm for continuity, Transistor Test, AC/DC Voltage, AC/DC Current up to 20A, Resistance, Capacitance, Frequency, Temperature, Duty Cycle, Diode and Continuity Test.	2400	90303100
Metrasafe-13	3-3/4 Digits, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Relative, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Continuity and Battery Test. Confirms to CAT IV 600V	4275	90308990
Metrasafe-14	3-3/4 Digits, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Relative, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Continuity and Battery Test. Confirms to CAT IV 600V	4900	90308990
Metrasafe-15	3-3/4 Digits, Analogue Bargraph, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Max/Min, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test. Confirms to CAT IV 600V.	5900	90308990

ITEM	DETAILS	LIST PRICE	HSN
Metrasafe-16	3-3/4 Digits, Analogue Bargraph, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Max/Min, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test. Confirms to CAT IV 600V.	6800	90308990
Metrasafe-18	4-3/4 Digits, Analogue Bargraph, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data & Peak Hold, Max/Min Record, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Non Contact type Infra Red Thermometer, Duty Cycle, Diode & Continuity Test. Confirms to CAT IV 600V.	9400	90308990
Metrasafe-19	4-3/4 Digits, Analogue Bargraph, Wireless PC Interface, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data & Peak Hold, Max/Min Record, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Non Contact type Infra Red Thermometer, Duty Cycle, Diode & Continuity Test. Confirms to CAT IV 600V.	15900	90308990
Metrasafe-20	4-5/6 Digits, 60,000 Counts, T-RMS Multimeter, OLED Display, 100kHz Bandwidth, 0.025% Accuracy, Lo-Z measurement, AC/DC Voltage, AC/DC Current, Resistance, Process Measurement, Conductance, Capacitance, Frequency, Duty Cycle, Temperature, Diode and Continuity, Re-chargeable battery, Battery Charger, Misoperation Alarm, Data Logger. Optional Blue Tooth Interface	32000	90308990
23S-TRMS	4-1/2 Digits 19,999 Counts, T-RMS, Backlit LCD, NCV, Data Hold, Peak Hold, Relative, Auto Power Off, Dual Display to show Voltage & Current with Frequency on the same screen, AC/DC Voltage, AC/ DC Current 10A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test both Audio and Visual.	3700	90308990
540	4-1/2 Digits, LCD, Data Hold, T-RMS, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Diode & Continuity Test.	4500	90308990
DM-454 NEW!!	22,000 Counts LCD Display, Peak Hold, Data Hold, Relative Measurement, T-RMS Multimeter, Confirms to CAT III 1000V, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Diode & Continuity Test, USB PC Interface.	9975	90303100
PRO-11	4000 Count Backlight LCD Display, Auto-Ranging, IP67 Dust and Waterproof, 600V AC/DC Voltage, 10A AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, UL 61010-1, CAT-III 600V, Class 2 Double Insulation, Built-in flashlight, Over range indication, Auto Power Off, Min/Max Data Hold. Hand-Held Waterproof and Dustproof, Digital Multimeter. Anything and Everything that you can possibly think about. A must for all technicians, double moulded injection body, a built-in flashlight to access dark areas,	4275	90303100

ITEM	DETAILS	LIST PRICE	HSN
PRO-12B	4000 Count, Backlight LCD Display, TRMS, IP 67 Dust and Waterproof Digital Multimeter, 600V AC(TRMS) /DC Voltage, 10A AC(TRMS)/DC Current, LoZ, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity test, 50 to 400Hz AC Bandwidth, Bluetooth Smartphone interface, Free Smartphone App, Data Hold, MAX/MIN Record, Built-in Flashlight, Double-moulded injection body, Auto Power Off, Low battery indication, CAT-III 600V. Hand-Held Waterproof and Dustproof, Digital Multimeter. Anything and Everything that you can possibly think about. A must for all technicians.	5000	90303100
SOLAR - 1 NEW!!	6000 Counts, Auto-backlit LCD, confirming to EN 61010-1, EN 61010-2-033 for CAT III 1000V, CAT IV 600V, EN 61326-1, designed for Solar PV applicaton, to measure 2000V DC and 1500V AC T-RMS, to measure DC/AC mV as well, AC/DC Current up to 10A, Resistance 40M.Ohms, Capacitance 10mF, Frequency 100kHz, Temperature 400 Degree C, Non Contact Voltage Detection, Diode and Continuity Test.	18300	90303100
SOLAR - 1A NEW!!		6500	90303100
PRO 587 NEW!!		12500	90303100
PRO 589 NEW!!		20500	90303100
PRO 21 NEW!!		5500	90303100
PRO 27 NEW!!		6200	90303100
XB-33A NEW!!		1500	
PRO 7		3420	

Accessories to Digital Multimeter

CA-01	Clamp On Current Adaptor to be used with any Multimeter with mV range, measures up to 200A AC	1200	90308990
CA-1000D	Clamp On Current Adaptor to be used with any Multimeter with mV range, measures up to 600A/1000A AC/DC	5300	90308990
TS-03	Infra Red Temperature Adaptor to measure from -30 to 550 Degree C, can be used with any Multimeter with mV range	3400	90308990
PD-28	High Voltage probe to measure 40kV DC and 28kV AC	8250	90308990
ATL-PV NEW!!	High Voltage Probe for P-V Multimeter SOLAR-1 and PV Clamp meter SOLAR-2	3000	90308990
TL-70	Right Angled shrouded termination to fit modern multimeters, fitted with a 4mm shrouded socket, CAT III 1000V / 20A Rating	200	90308990
TL-74	1m silicon single insulated test leads with right angle shrouded banana plugs, CAT IV 600V, CAT III 1000V with protective cap, banana plug termination, dia of test lead point 2mm	350	9030

ITEM	DETAILS	LIST PRICE	HSN
TL-75	1m silicon double insulated test leads with right angle shrouded banana plugs, CAT IV 600V, CAT III 1000V with protective cap, banana plug termination, dia of test lead point 2mm	500	90303100
Flexi Clamp NEW!!	For PRO 27 and Solar-3	6000	
Digital Non Contact Infra Red Thermometer			
MT-2	3 Digits Backlit LCD with laser sighting used to measure temperature in the range of -30 to 260°C / -22 to 500°F, D:S Ratio 8:1, Fixed emissivity 0.95.	2100	90251920
MT-10	3-1/2 Digits Backlit LCD, fixed emissivity of 0.95, D:S Ratio of 50:1, measures from -50 to 1000°C / -58 to 1832°F, with laser pointer	14200	90308990
MT-13	Backlit LCD, Contact cum Non Contact type, measures from -18 to 1050 °C in Non Contact model and -50 to 1370 °C in Contact Mode, Emissivity adjustable from 0.10 to 1.0, D:S Ratio of 30:1, with wireless USB PC Interface and facility to calculate the emissivity of the surface	18300	90251990
MT-14	4 Digits Backlit LCD, Contact cum Non Contact type, measures -50 to 1300°C/-58 to 2372°F in non contact mode and contact mode. D:S Ratio 30:1, Emissivity Adjustable 0.10 to 1.00, mV output /°C, Trigger Lock, battery cum mains operated, Records 20 Data, Max/Min/Dif/Avg recording	12500	90251990
MT-16	4 Digits Backlit LCD, Contact cum Non Contact type, with USB PC Interface, adjustable emissivity from 0.10 ~ 1.0, D:S Ratio of 50:1, in non contact mode measures from -50 to 1800°C / -58 to 3272°F, with dual laser pointer to show the diameter of the area whose temperature is being measured and with Max./Min./Dif/AVG. Temp.	22000	90308990
MT-18	4 Digits Backlit LCD, Contact cum Non Contact type, with USB PC Interface, adjustable emissivity from 0.10 ~ 1.0, D:S Ratio of 50:1, in non contact mode measures from -50 to 2200°C / -58 to 3992°F, with dual laser pointer to show the diameter of the area whose temperature is being measured and with Max./Min./Dif/AVG. Temp.	28000	90251990
MT-19		29500	90308990
MT-20	4 digits LCD, adjustable emissivity from 0.10 to 1.00, telescopic sighting measures in the range of 500°C to 3000°C and in °F scale, distance to sighting ratio of 120:1, accuracy ±1%, with Max/Min/Ave/DT and High/Low alarm	250000	90308990

ITEM	DETAILS	LIST PRICE	HSN
PRO-65 MAX	Precise Non Contact Measurement, Circular Laser to show the exact area whose temperature is being measured IP54 Rated for Dust / Water Proof, 2m Drop Tested, Automatic Data Hold, Non Contact and Contact Thermometer Combined, Contact temperature measurement using K type sensor, Adjustable Emissivity from 0.10 to 1.00, MAX / MIN / AVG / DIF Temperature display, Backlit LCD Display, Set High and Low Alarms, Distance to Sighting Ratio 16:1 (65Max) Battery Operated 2 x 1.5V AAA Batteries, CE Compliant with EMC, Tk Temperature: -50 to 1370°C, Resolution: 0.1°C < 1000; 1°C > 1000, Accuracy: ±0.5% of Reading ±1.5°C, IR Temperature Measurement: -50 to 800°C Response Time: 150mS, Spectral Response: 8 – 14um	4400	90251920
PRO-65 MAX+	Precise Non Contact Measurement, Circular Laser to show the exact area whose temperature is being measured IP54 Rated for Dust / Water Proof, 2m Drop Tested, Automatic Data Hold, Non Contact and Contact Thermometer Combined, Contact temperature measurement using K type sensor, Adjustable Emissivity from 0.10 to 1.00, MAX / MIN / AVG / DIF Temperature display, Backlit LCD Display, Set High and Low Alarms, Distance to Sighting Ratio 20:1 , Battery Operated 2 x 1.5V AAA Batteries, CE Compliant with EMC, Tk Temperature: -50 to 1370°C, Resolution: 0.1°C < 1000; 1°C > 1000, Accuracy: ±0.5% of Reading ±1.5°C, IR Temperature Measurement: -50 to 1000°C, Response Time: 150mS, Spectral Response: 8 – 14um	5500	90251920
MT-15 NEW!!	75:1 1200°C	18000	
Digital Phase Angle Meter			
CE-0102D	Digital Phase Angle Meter, 96 x 96 mm sq, can measure Phase Angle between Voltage and Current	3600	90303310
Digital Power Analyzer			
CE-0102PA	Digital Ampere, Volt, PF and Watt meter combined in 96 x 96 mm sq for single phase loads	4500	90303310
Digital Power Factor Meter			
CE-0102PF 96x48	Microprocessor Based, 96 x 48 mm sq, For Single Phase, Red LED Display	3300	90303310
CE-0102PF 96 x 96 mm sq	Microprocessor Based, 96 x 96 mm sq, For Single Phase, Red LED Display	3300	90303310
CE-0303PF	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element , Red LED Display	4200	90303310
CE-0304PF	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	4200	90303310
Digital Pressure Meter			

ITEM	DETAILS	LIST PRICE	HSN
PM-01	Backlit LCD Display, measures up to 5 psi and in various other units of Pressure	13000	90308990
Digital Process Meter			
PM-29	3-3/4 Digits, Digital Multimeter Cum DC mV / Voltage / Frequency / Resistance / mA Calibrator and also provies output for all types of Thermocouples	40700	90308990
PM-39	5 Digits, Digital Multimeter combined with source for DC voltage, resistance, frequency, all kind of thermocouples, thermal resistance, and DC current. supply power to 24V circuits and meanwhile measure current; with built-in250 Ω HART loop resistance	47000	90303100
Digital Process Clamp Meter			
771+	The Milliamp Process Clamp Meter is a hand-held battery-operated clamp meter that measures 4-20 mA DC without breaking the electrical circuit. DC mA measurement (4-20mA) using a remotely connected clamp via extension cable, Electronic zero, Percentage span (0-100%), Data Hold, Backlit Display, Measurement spotlight LED, Auto Power Off, 0mA... ±20.99mA, Resolution 0.01mA, Accuracy: 0.3% realding ±8 digits, Also measures ±21.0mA... ±99.9mA with Resolution of 0.1mA, Clamp Jaw 4.5 mm, IP40, IEC 61010-1, 61010-2-032, CAT II 300V	21000	90303100
Digital SMT Component Tester			
SMT-01	SMT Component tester that can measure Capacitance and Resistance values of SMT components, it can also measure AC/DC Voltage, continuity and Diode test	4000	90308990
Digital Sound Level Meter			
SL-3010	4 Digital Backlit LCD, Sound Level Meter, Fast & Slow Response, Data Hold, MAX/MIN Record, A Weighting, Measures sound in the range of 30dB to 130dB with resolution of 0.1dB and accuracy of 1.5 dB. With Over-range and Low Battery Indication	1750	90278090
SL-4010	3-1/2 Digits Backlit LCD, has A & C Weighting, measures in the range of 30 to 130 dB, with maximum hold	5700	90278090
SL-4005	3-1/2 Digits, has A & C Weighting, measures in the range of 35 to 130 dB, with data hold and maximum hold, with built in calibration check	6600	90278090
SL-4015	4 Digits, has A & C Weighting, measures in the range of 30 to 130 dB, USB PC Interface, with Max/Min Data Hold and Data Logging facility	11400	90278090
Digital Storage Oscilloscope			

ITEM	DETAILS	LIST PRICE	HSN
DSO-5025E	25MHz DSO with colored display, 250MSa/Sec sampling rate, with USB PC Interface cable and software	28500	90302000
DSO-5050E	50MHz DSO with colored display, 500MSa/Sec sampling rate, with USB PC Interface cable and software	29500	90302000
DSO-5074E NEW!!		71000	90302000
DSO-5100E	100MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host	34500	90302000
DSO-5104E NEW!!		75000	90302000
DSO-5150E	150MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host	38000	90302000
DSO-5200E	200MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host	41000	90302000
Accessories to Digital Storage Oscilloscope			
PD-20S	High Voltage Probe to be used with any oscilloscope (Analogue or Digital Storage) to measure High Voltage Waveform of 30kV DC and 20kV AC	8800	90308990
OP-60 NEW!!	OP-60 is a x 1 / x 10 attenuation modular probe designed to be used with 60MHz oscilloscopes with an input impedance of 1MΩ.	700	90308990
OP-100 NEW!!	OP-100 is a x 1 / x 10 attenuation modular probe designed to be used with 100MHz oscilloscopes with an input impedance of 1MΩ.	1000	90308990
OP-250 NEW!!	OP-250 is a x 100 attenuation modular probe designed to be used with 250MHz oscilloscopes with an input impedance of 100MΩ.	5800	90308990
Digital Stroboscope			
DT-2350A	Digital Stroboscope, 50 to 12,000FPM, 230V Single Phase AC Operated	12010	90308990
DT-2350B	Digital Stroboscope, 50 to 40,000FPM, 230V Single Phase AC Operated	21375	90308990
DT-720	LED Stroboscope	9000	90308990
DT-720-2	LED Stroboscope	11000	90308990
Digital Tachometer			
DT-2235	Contact type Tachometer, measures up to 50,000 RPM	2600	90292090
NCTM-500	Non Contact type Tachometer With Counter, Data Hold, Measures from 50mm to 200mm, RPM Up to 99999RPM, and Counts up to 99999 Counts	1750	90308990
NCTM-1000	Non Contact type Tachometer Cum Counter. Max / Min . Last Data Record, 2 to 99,999 RPM, 1 TO 99,999 Counts	3300	90308990

ITEM	DETAILS	LIST PRICE	HSN
NCTM-2000	Contact cum Non Contact type Combined Tachometer, Max/Min, Last Record, 20,000RPM in contact mode and 99,999 RPM in non contact mode, measures Rotation speed, total revolution, frequency, surface speed and length	6000	90308990
NCTM-3000 NEW!!		6800	90308990
Digital Temperature Controller			
DTC-200	Digital Temperature Controller 96 x 96 mm sq, with 1NO + 1NC, Single Set Point, for K, J, R, S, PT-100 (Any One)	2175	84779000
DTC-202	Digital Temperature Controller 96 x 96 mm sq, with 2NO + 2NC, Two Set Point, for K, J, R, S, PT-100 (Any One)	2650	84779000
METCAT 96	Digital Temperature Controller, 4 Digits Display, up to 1200 Degree C, 96 x 96 mm sq, with 1NO + 1NC, Single Set Point, for K, J, PT-100 (User Programmable)	1800	84779000
METCAT 72	Digital Temperature Controller, 4 Digits Display, up to 1200 Degree C, 72 x 72 mm sq, with 1NO + 1NC, Single Set Point, for K, J, PT-100 (User Programmable)	1800	84779000
Digital Temperature & Humidity Meter			
HT-305	3-1/2 Digits Backlit LCD Dual Display, Measures Temperature in Celsius and Fahrenheit scales in the range of -10 to 60 Degree C with resolution of 0.1 and accuracy of 1.0 Degree C, Relative Humidity from 0 to 100% RH with resolution of 0.1%RH and 5%RH accuracy, It has Data Hold, MAX/MIN Record Function, Auto Power Off	2000	90258090
HT-305A	Backlit LCD Dual Display, with split type Sensor for temperature and Humidity, Data Hold, MAX / MIN Record, Auto Power Off, Measure Temperature from -10 to 60 Degree C, and Humidity Up to 100% RH	2500	90308990
HT-3004CT	Digital Thermo-Hygro Meter with in-built infra red thermometer. Has Backlit LCD Display	8700	90308990
HT-3005	Digital Thermo-Hygro Meter with K-type thermometer. Has Backlit LCD Display	4200	90258090
HT-3006	Digital Thermo-Hygro Meter with facility to measure wet bulb and dew point temperature	6000	90258090
HT-12	Digital Thermo-Hygro Meter with Jumbo Display, to measure Indoor and Outdoor Temperature measurement, with Humidity. Selectable scales, Alarm Clock and Comfort Level Indicator, Temperature range -10 to 50 Degree C and humidity from 20 to 95%	1300	90258090

ITEM	DETAILS	LIST PRICE	HSN
HT-13	Digital Thermo-Hygro Meter with Jumbo Display, to measure Temperature measurement, with Humidity. Selectable scales, Alarm Clock and Comfort Level Indicator, Temperature range -10 to 50 Degree C and humidity from 20 to 95%	1200	90258090
HTC-01	Jumbo LCD Display, wall hanging, with time and alarm facility, -50 to 70 Degree C, 20% to 99%RH	650	90258090
TH-04	LCD Display, wall hanging, with time and alarm facility, calander, climatic condition display, 0 to 50 Degree C, 10% to 90%RH	1200	90308990

Digital Temperature Indicator

DTI-101 48	Digital Temperature Indicator 96 x 48 mm sq, for K, J, R, S, PT-100 (Any One)	1350	90308990
DTI-101 96	Digital Temperature Indicator 96 x 96 mm sq, for K, J, R, S, PT-100 (Any One)	1350	90308990

N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size or 96 x 48 mm sq size

Digital Thermometer

DTM-900	3-1/2 Digits, Measures from -50 to 1300°C / -50 to 1999°F, Contact type, to be used with K type thermocouple , with backlit display and kelvin scale	3400	90251990
DTM-901 NEW!!	3-1/2 Digits, Dual Channel Input, Measures from -50 to 1300°C / -50 to 1999°F, Contact type, to be used with K type thermocouple. with backlit display and kelvin scale	3900	90251990
DTM-903	Wide Temperature Range, High Accuracy, Battery Operated, Selectable Thermocouple between K / J type, MAX / MIN / AVG Recording, Data Hold to Freeze Displayed Data, Backlit Display Measures Temperature from -50 to 1300°C using K-type Sensor and from -50 to 1200°C using J-type Sensor Accuracy: ±0.5%	1600	90251990
DTM-100	3-1/2 Digits, Hand Held 9V battery operated, for PT-100 Sensor up to 600 Degree C	1875	90251990
DTM-902	Pen Type, Auto Power Off, -40 to 250°C / -40 to 482° F	750	90251990
DTM-925		3500	90251990
ST-9283B	Hand Held, With High Temperature Alarm Facility, Auto Power Off, Data Hold, -50 to 300°C / -58 to 572°F	750	90251910

Digital Three Phase Ammeter

CE-03A	Microprocessor Based, 96 x 96 mm sq, with in built three phase selector switch, displays Current in three phases, CT Ratio programmable. Programmable up to 3000A AC	2100	90303310
--------	---	------	----------

Digital Three Phase Voltmeter

ITEM	DETAILS	LIST PRICE	HSN
CE-03V	Microprocessor Based, 96 x 96 mm sq, with in built three phase selector switch, displays Line to Line and Line to Neutral Voltage. Direct Operated and PT Ratio programmable	2100	90303310
Digital Time Interval Meter			
NTT-4D	4 Digits Digital Time Interval Meter for measuring in the range of 999.9mS, 9.999S, 99.99S	16000	90318000
3CH-NTT-4D	4 Digits 3 Channel Digital Time Interval Meter for measuring in the range of 99.99mS, 999.9mS, 9.999S	69000	90318000
Digital Voltage Controller			
CE-0102VC 1SP	Digital Voltmeter with Single Set Point to control the Voltage below a given set point.Size - 96 x 96 mm sq. With 1NO + 1NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	3350	90303310
CE-0102VC 2SP	Digital Voltmeter with Two Set Point to control the Voltage between a given set points.Size - 96 x 96 mm sq. With 2NO + 2NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	4000	90303310
Digital Voltmeter			
CE-0102V	3-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1275	90303310
CE-0102V 96	3-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1275	90303310
CE-0102V	3-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1275	90303310
CE-0102V 96	3-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1275	90303310
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size			
CE-0102V 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2500	90303310
CE-0102V 96 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2500	90303310
CE-0102V 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2500	90303310

ITEM	DETAILS	LIST PRICE	HSN
CE-0102V 96 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2500	90303310
Digital Wattmeter			
CE-0102W	Microprocessor Based, 96 x 48 mm sq, For Single Phase, Red LED Display	3400	90309090
CE-0102W 96 x 96	Microprocessor Based, 96 x 96 mm sq, For Single Phase, Red LED Display	3400	90309090
CE-0303W	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	4200	90309090
CE-0304W	Microprocessor Based, 96 x 96 mm sq, For Thre Phase Four Wire Three Element, Red LED Display	4200	90309090
Discharge Rod			
DR 11-33kV NEW!!		4000	
DR 33-66kV NEW!!		6000	
DR 66-132kV NEW!!		9700	
DR 132-220kV NEW!!		12000	
DR 400kV NEW!!		15000	
ELCB Tester			
1810D	Digital ELCB Tester with Current Rating up to 500mA, Trip Test, Fault Trip Time, Self Powered	6100	90308990
1811	Digital ELCB Tester with Current rating up to 500mA, Auto Ramp, Phase Switch, Reads Disconnection Time, Self-Powered	12000	90308990
1813	Digital ELCB Tester with Current rating up to 1A, Trip Test, Fault Trip Time, 230V AC Operated	11000	90308990
Electrical Tester			
AC-1	Audio and Visual output on detecting voltage from 90V - 1000A AC with built in flash light	375	90308990
AC-4	Non Contact Voltage Detector by flashing light for 100 - 600V, with built-in flash light	700	90308990
AC-5	Non Contact Voltage Detector by flashing light and buzzer sound for 100 - 600V, with built-in flash light	800	90308990
AC-6	Socket Polarity & Earth Leakage Tester. Checks for No Earth / Line Neutral Reversal / No Neutral / Line Earth Reversal / No Line states.	1400	90308990
AC-7	Phase Rotation Indicator, No Batter Required, Nomical Voltage 40 - 690V, 15 to 400Hz.	3900	90308990
AC-8	Self Operated, phase rotation indicator along with voltage and frequency display	2500	90308990
PRO ELEC+ NEW!!		5900	90303900
EMF Tester			

ITEM	DETAILS	LIST PRICE	HSN
EMF-823	Measures from 0.1 to 200mG / 1 to 2000mG & 0.01 to 20uT / 0.1 to 200uT, Frequency Response 30Hz to 400Hz, Max Hold and Data Hold	7500	90308990

Event Counter

CTR-49	6 Digits Red LED Display, Event Counter, 1 to 999999 Counts, 96 x 48 mm sq	2250	90292090
---------------	--	-------------	----------

N.B. - Please ask for the prices in case if you require this in 96 x 96 mm sq size

Forehead Infra Red Thermometer

FIR-2	Non Contact Infra Red Thermometer for body temperature	2800	90308990
PIR-I	"A non-touch Infrared Thermometer to measure human body temperature via the hand wrist & palm. The PIR-1 is a non-touch Infrared Thermometer to measure human body temperature via the hand wrist, palm or even forehead. You just need to put your hand or your wrist over the sensor at a 2-8 cms distance and you will get the body temperature instantly. The PIR-1 uses 2 sensors – a distance sensor and a temperature sensor, to get accurate temperature measurements quickly and safely. When used at any Entry/Exits, people can walk through the check-points quickly without any crowding or queuing. The PIR-1 is mountable on almost any surface and comes with a multi-angle adjustment. It is the ideal solution for enabling safe access control so as to prevent spread of COVID-19."	35000	90230090

Frequency Transducer

CE-0102FT	Frequency Transducer with single Output	6300	85045090
------------------	---	-------------	----------

N.B. - For Dual Output Rs.500/- shall be charged extra

Function Generator

FG-1000	1MHz Function Generator with TTL / CMOS output	9400	90308990
FG-2000	2MHz Function Generator with TTL / CMOS output	10200	90308990
FG-5000	5MHz Function Generator with TTL / CMOS output	12000	90308990
FG-10000	10MHz Function Generator with TTL / CMOS output	22000	90308990
FG-20000	20MHz Function Generator	25000	90308990

Gauss Meter

ITEM	DETAILS	LIST PRICE	HSN
GM-197	Gauss Meter for both static and electromagnets, DC and AC (40-500Hz), determines N/S polarity of Static Magnets, measures intensity of magnetic Field in Gauss and Tesla both, measures up to 0~3000mT (milli Tesla)/0~30000G(Gauss), Relative / Peak Hold / Real time Zero function, Auto Range, DATA HOLD, MAX/MIN hold, GO and NO-GO alarm and alarm value set up the function, Production testing, Manual 200 capacity records, Auto 6000 capacity data logging, interval is set up by PC, USB interface to send data + PC connection application software, real time function.	25500	90303100
High Voltage Detector			
277HP	Non Contact Type High Voltage Detector for presence of Voltage from 50V to 132kV with Buzzer and Light Indication	12500	90308990
275HP	Non Contact type, Light and Buzzer Indication, Detects Presence of High Voltage in AC Lines, 240V, 2KV, 6KV, 11KV, 22KV, 33KV, 132KV and 175KV Lines AC.	16000	90308990
275HP1 NEW!!		7400	
275HP2 NEW!!		7400	
276HD	Contact type, light and buzzer indication, detects presence of High Voltage in AC Lines, 354 to 1005mm length, detects 3kV to 24kV AC and 80 to 600V AC	16700	90308990
276SHD	Contact type, light and buzzer indication, detects presence of High Voltage in AC Lines, 230 to 880mm length, detects 3kV to 24kV AC and 80 to 600V AC	16700	90308990
290HD	7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout	21000	90292090
WT500 NEW!!		3750	90303390
AT500 NEW!!		3750	90303390
Hot Line Indicator			
6.6kV	Hot Line Indicator, Neon Glow type for 6.6kV	10700	90308990
11kV	Hot Line Indicator, Neon Glow type for 11kV	16000	90308990
33kV	Hot Line Indicator, Neon Glow type for 33kV	27000	90308990
# Hot Line Indicator with Neon glow and audible buzzer both are also available. Please refer back for their price.			
Hour Meter			
NE 045/7S DC	7 Digits, measures up to 99999.99 hours, 10 - 48V DC operated, 46 x 46 mm sq size panel cutout	1100	90292090
NE 045/7	7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout	600	90292090
HM-01 NEW!!		500	

ITEM	DETAILS	LIST PRICE	HSN
Infra Red Temperature Calibrator			
BB-550	Black Body Source for Calibrating Infra Red Thermometer from 50 to 500 Degree C	71000	90308990
Insulation Tester			
IT-500	Test Voltage: 500V, Insulation Resistance Range: 0 - 1000M.Ohms, with AC Voltage Test Facility	1900	90308990
IT-1000	Test Voltage: 1000V, Insulation Resistance Range: 0 - 2000M.Ohms, with AC Voltage Test Facility	2000	90308990
Integrated Meter			
CE-0303IM	Three Phase Three Wire Two Element loads for energy and power measurement, measure each phase I, V, Hz, PF, KW, KVA, KVAh, KVAh, KVAh and MDI	7500	
CE-0304IM	Three Phase Four Wire Three Element loads for energy and power measurement, measure each phase I, V, Hz, PF, KW, KVA, KVAh, KVAh, KVAh and MDI	7500	
Kelvin Double Bridge			
KDBR	Oxford Brand Kelvin Double bridge, with spot reflecting galvanometer, High Current DC power supply and wooden stand for specimen	72000	90230090
Laser Distance Meter			
LDM-40H	Laser Distance Meter to measure up to 40m, with Area / Volume Calculations	4300	90308990
LDM-100H	Laser Distance Meter to measure up to 100m, with Area / Volume Calculations	6000	90303100
Metal Detector			
MD-300	High Sensitive Metal Detector with a circular sensor, the detector vibrates and provides audible alarm on detecting metal	1800	90308990
SUPER-V	High Sensitive Metal Detector with a straight sensor, the detector vibrates, provides visual and audible warning on detecting metal	3000	90308990
Million MegOhms Meter			
MMM-1	Analogue Million MegOhms Meter for test voltage of 100, 200, 300, 400 and 500V, measures up to 10 Million MegOhms	17000	90308990
Mixed Signal Oscilloscope			
MSO-5062D	60MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate	70400	90302000
MSO-5102D	100MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate	76450	90302000
MSO-5202D	200MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate	88000	90302000

ITEM	DETAILS	LIST PRICE	HSN
Motor Checker			
MC-22	Electric Motor Checker with analogue display	26000	90308990
MC-22D	Digital Motor Checker with insulation resistance test of 1000V	32000	90308990
MC-38D	Digital Motor Checker with insulation resistance test of 500 and 1000V	17500	90308990
Multifunction Environment Meter			
ET-2	Four-in-One Digital dB, Lux, temperature and Humidity meter with RS-232C PC Interface cable and software	7200	90278090
ET-3	Six-in-One Digital dB, Lux, Humidity, temperature, Multimeter and AC Voltage Detector	7700	90278090
Multi-point Temperature Indicator			
DTI-101M 6 CH	6 Channel Digital Multi-Point Temperature Indicate for K, J,R, S, PT-100 (Any One) type of sensor	3750	90308990
DTI-101M 12 CH	12 Channel Digital Multi-Point Temperature Indicate for K, J,R, S, PT-100 (Any One) type of sensor	4500	90308990
Non Contact Temperature Controller			
IT-91	Infra Red Temperature controller for -50 to 950 Degree C, 50:1 D:S Ratio, adjustable emissivity, relay output, controller cut out 72 x 72 mm sq	19000	84779000
Oil Test Set			
50-OTS	50kV Manually operated Oil Test Set	31000	84212900
50-MOTS	50kV Motor operated Oil Test Set	39500	84212900
60-OTS	60kV Manually operated Oil Test Set	34500	84212900
60-MOTS	60kV Motor operated Oil Test Set	43000	84212900
70-OTS	70kV Manually operated Oil Test Set	41000	84212900
70-MOTS	70kV Motor operated Oil Test Set	49000	84212900
75-OTS	75kV Manually operated Oil Test Set	44000	84212900
75-MOTS	75kV Motor operated Oil Test Set	52500	84212900
80-OTS	80kV Manually operated Oil Test Set	49300	84212900
80-MOTS	80kV Motor operated Oil Test Set	58000	84212900
90-OTS	90kV Manually operated Oil Test Set	54000	84212900
90-MOTS	90kV Motor operated Oil Test Set	62000	84212900
100-OTS	100kV Manually operated Oil Test Set	58000	84212900
100-MOTS	100kV Motor operated Oil Test Set	69000	84212900
120-OTS	120kV Manually operated Oil Test Set	79000	84212900
120-MOTS	120kV Motor operated Oil Test Set	99000	84212900
Digital Meters for above, extra to be paid		5000	
Oscilloscopes			
OS-5010A	10MHz Single Channel, Cathode Ray Oscilloscope	18300	90302000
OS-5020	20MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with 1:1 and 10:1 probes	29900	90302000

ITEM	DETAILS	LIST PRICE	HSN
OS-5020C	20MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with component test facility, comes complete with 1:1 and 10:1 probes	31500	90302000
OS-5030	30MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with 1:1 and 10:1 probes	32000	90302000
OS-5030C	30MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with component test facility, comes complete with 1:1 and 10:1 probes	34200	90302000
OS-5060	60MHz Dual Channel Four Trace Cathode Ray Oscilloscope with 1:1 and 10:1 Probes	69000	90302000
OS-5100	100MHz Dual Channel Four Trace Cathode Ray Oscilloscope with 1:1 and 10:1 Probes	82500	90302000
Oxygen Meter			
O2-09 NEW!!		14250	
Oscilloscope			
700S		63800	90302000
760	20MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software	106700	90302000
7100	100MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software, sampling rate 1GSa/Sec	282700	90302000
7200	200MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software, sampling rate 1GSa/Sec	363000	90302000
PC Based Oscilloscope			
DSO-2090	Dual Channel 40MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software	27500	90302000
DSO-2150	Dual Channel 60MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software	33000	90302000
DSO-2250	Dual Channel 100MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software	42900	90302000
PC Based Function Generator			
DDS-3005	5MHz PC Based Function generator with AM FM Modulation and TTL output along with sine, square, tri-angle, saw-tooth etc. with USB PC Interface cable and software	50600	90308990
PC Based Logic Analyzer			
LA-5034	34 Channel PC Based Logic Analyzer, with precision gripper, USB PC Interface cable and software	38500	90308990

ITEM	DETAILS	LIST PRICE	HSN
Power Guard			
PG-01	Multifunction Power Meter, works on 6A, 230V, indicates, voltage, current, power factor, Power, KWh, Calculates CO2 emission, Calculates total time the equipment is under test and calculates the cost of electricity consumed accordingly. During load shedding the instrument memorizes the readings, ideal for analyzing power consumed for different kinds of loads	1950	90308990
Primary Current Injection Test Set			
PCIT	Please check PCIT Tab or click here		90303390
Refrigerant Gas Leakage Detector			
RLD-01	16" Gooseneck sensor, detects all CFC Refrigerants such as R-22, R-124, R-11 and R-12 etc.	9000	90308990
Relay Test Set			
RNT-5	Relay Test Set, with current output upto 200A in various ranges	43000	90318000
RNT-5A	Relay Test Set with 200A in various ranges, Burden 1KVA, with AC/DC Voltage output	62000	90318000
RNT-33	Relay Test Set suitable for testing distance relay, 3 phase current / voltage output and Fixed DC Voltage output	250000	90318000
ZNT-34	Relay Test Set suitable for testing distance, over voltage relays etc., Variable three phase Voltage / Current and variable DC Voltage outputs	270000	90318000
Rotating Machine Tester			
RMT-10 NEW!!	One Single Meter that can test rotating machine, from insulation resistance to low resistance milli Ohms combined with a built-in T-RMS multimeters, Data logger, with Low pass Filter, Blue tooth Interface, Can measure AC/DC Voltage 1000V, DC/AC Current 10A, Resistance, Capacitance 5mF, Frequency 50Mhz, Temperature up to 1200 Degree C, Insulation Resistance can be measured up to 5000M.Ohms at test voltag of 50V / 100V / 250V / 500V / 1000V, with polarisation index and DAR, Low resistance from 1 m.Ohms to 2000 Ohms,	30200	90303900
RMTi-1 NEW!!	Rotating Machine Tester with Thermal Imager	75000	90303900
RPM METER			
CTR-49	6 Digits Red LED Display, Event Counter, 1 to 999999 Counts, 96 x 48 mm sq	2250	90292090
Short Turn Indicator			

ITEM	DETAILS	LIST PRICE	HSN
EFD	Electric Fault Detector, to be used with more than two identical windings like general motors and transformers	20900	90308990
Little Giant	9V Battery operated, to be used in single coils, simple insertion of coil on mandrill.	16500	90308990
Socket Polarity Tester			
ST-09	Socket Polarity Tester to be used for currents up to 6A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral.	720	90308990
ST-09A	Socket Polarity Tester to be used for currents up to 16A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral.	760	90308990
ST-09B	Socket Polarity Tester to be used for currents up to 6A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral. This can also be used for leakage test of up to 30mA	860	90308990
Sound Level Calibrator			
SC-05	Sound Level Calibrator provides signals of 94dB and 114dB	9800	90308990
Solar Power Meter			
207	Solar Power Meter, to measure the amount of sunlight falling on the solar panel or any surface exposed to sunlight	5900	90308990
Spectrum Analyzer			
AT-5010	1050MHz Spectrum Analyzer	97900	90308990
AT-5011	1050MHz Spectrum Analyzer With Marker Generator	152900	90308990
Static Charge Meter			
SC-291 NEW!!	Measuring range : 0~ + / - 20.000KV, Measuring distance : 2.54cm(1 inch), Warning alarm setting, DATA / PEAK hold. Backlight function, Auto power off with disable function, Zero function and low battery indicate, Manual data memory storing 99 data sets.	27500	90303100
Tachometer (Non Contact type) Calibrator			

ITEM	DETAILS	LIST PRICE	HSN
CE-0102TMC	Calibrator for Non Contact Tachometer for up to 199,999RPM	13000	90308990
Thermal Imagers			
PRO TI-10P NEW!!	Pocket Thermal Imager	50500	
PRO TI-25 NEW!!	Handheld Thermal Imager	79000	
PRO TI-50 NEW!!	Handheld Thermal Imager	183000	
Transistor Tester			
TT-01	Transistor Tester for Testing and Checking Bias Current and other parameters of Transistors	4650	90312000
Tap Position Indicator			
CE-0102V	Digital type, Panel Mounting, Tap Position indicator, 96mm sq or 96x48 mm sq	2400	85049010
Time Totalizer			
TT-300	6 Digits LED Display, 96 x 48 mm sq, Auto range from 9999.99 to 999999Hrs.	2250	90292090
TT-302	6 Digits LED Display, 96 x 96 mm sq, Auto range from 9999.99 to 999999Hrs.	2500	90292090
Transformer Turns Ratio Set			
TTRS-100	Transformer Turns Ratio Set to measure ratio in the range of 0.800 to 2021 & for Phase Deviation Measurement	120000	90303900
Two Color Infra Red Thermometer			
ST-300A		342000	90308990
ST-300B		342000	90308990
ST-300C		370000	90308990
Ultrasonic Thickness Gauge			
UTG-01	Versatile Ultrasonic Thickness Gauge to measure thickness of high density material up to 200mm	12000	90308990
Vibration Meter			
VIB-30+	Digital Vibraiton Meter, measures RMS velocity in the range of 0.1 to 199.9 mm/sec T-RMS & Peak	29000	90301000
AVD-80	Digital Vibration Meter, measures velocity, acceleration and displacement	37000	90308990
BCA-111	Bearing Condtion Analyzer, measures bearing test, vibration and has in-built tachometer.	135000	90308990
908	Measures velocity, acceleration and displacement along with the temperature, comes complete with the magnetic Base	17500	90308990
908T NEW!!		84700	90308990

ITEM	DETAILS	LIST PRICE	HSN
PVB-820	Pen Type Vibration Meter, it can measure acceleration, velocity and displacement	17000	90308990
VT-141 NEW!!	Dual Channel Vibration meter, Wide frequency range of 10Hz to 5KHz, Acceleration, velocity and displacement, Vibration sensor with magnetic adapter on 1.2M (47.2) cable, Frequency Lo range : 10Hz~1KHz meets ISO 2954 measurement, Hi range : 10Hz~5KHz, MAX record, Auto power off with disable function	81000	90308990
VT-141D NEW!!	Dual Channel Vibration meter, Wide frequency range of 10Hz to 5KHz, Acceleration, velocity and displacement, Vibration sensor with magnetic adapter on 1.2M (47.2) cable, Frequency Lo range : 10Hz~1KHz meets ISO 2954 measurement, Hi range : 10Hz~5KHz, MIN/MAX record and recall, Data logger with 9999 records capacity, USB interface, Auto power off with disable function	88000	90308990
Voltage Transducer			
CE-0102VT	Voltage Transducer with single Output	3400	85045090
Video IR Thermometer			
VIT-20	Dual Laser Pointer, Color Display, Video and Still picture recording, In-built Contact Thermometer, uSD Card & PC interface, -50 to 1850°C, Adjustable Emissivity, D:S 50:1	55000	90251990
Weather Station			
WH-1081PC	Weather station, for prediction of weather and recording of temperature, humidity, wind chill, dew point, rainfall, wind speed, air pressure and storm warning	16500	90308990
WP-1050			
Wet Bulb Globe Temperature Meter			
WBGT-188 NEW!!	Quick-response capacitance sensor, accurate measurement for wet bulb globe temperature (WBGT), black globe temperature (TG), humidity (% RH), air temperature (TA), wet bulb (WET) and dew point (DEW). Max/Min and data hold, Low battery indication, LCD display with LED backlight, Viewing data records, Switch the temperature unit to °C or °F, Brass black ball in 50mm diameter, WBGT alarm setting, Auto power off with disable function	16500	90318000

ITEM	DETAILS	LIST PRICE	HSN
WBGT-188D NEW!!	Quick-response capacitance sensor, accurate measurement for wet bulb globe temperature (WBGT), black globe temperature(TG), humidity(% RH), air temperature(TA), wet bulb(WET) and dew point(DEW). Max/Min and data hold, Low battery indication, LCD display with LED backlight, Viewing data records, Switch the temperature unit to °C or °F, Brass black ball in 50mm diameter, WBGT alarm setting, Auto power off with disable function, Data logging capacity: 12000 records, USB PC serial interface, Sampling interval: Max 24 hours; Min 1 Second	23000	90318000

Wheatstone Bridge

WSB	OXFORD Brand Wheatstone Bridge	15500	90230090
------------	--------------------------------	--------------	----------

TERMS & CONDITIONS

VALIDITY:	PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE
PRICES:	NETT, EX GODOWN KOLKATA
PACKING:	PRICES INCLUSIVE OF PACKING CHARGES
FREIGHT:	PRICES EXCLUSIVE OF FREIGHT CHARGES. IN CASE IF GOODS ARE REQUIRED BY ANY OTHER COURIER, OTHER THAN OUR NOMINATED COURIER ANY BY AIR, THEN THE FREIGHT SHALL BE CHARGED EXTRA AT ACTUALS
DELIVERY:	READY STOCK SUBJECT TO PRIOR SALES, FOR HIGH VOLTAGE EQUIPMENTS 8-12 WEEKS DELIVERIES WILL BE MADE ONLY AFTER THE PAYMENT IS CREDITED TO OUR ACCOUNT
INSURANCE:	TO BE COVERED BY THE BUYER THE GOODS WOULD BE PACKED SECURELY WITH OUR BEST INTENT TO PROTECT IT AGAINST ANY KIND OF TRANSIT DAMAGE. HOWEVER, IN CASE IF THE GOODS GET DAMAGED IN TRANSIT, THE BUYER WILL HAVE TO COVER ITS RISK
PAYMENT:	100% AGAINST PROFORMA INVOICE / DOD / THROUGH BANK. 'ALTERNATIVELY' IF IT'S A TAILOR-MADE PRODUCT, 25% ADVANCE WITH THE ORDER BALANCE AGAINST PROFORMA INVOICE / DOD / THROUGH BANK
SHIPMENT:	SHALL TAKE PLACE WITHIN 48 HOURS OF RECEIPT OF PAYMENT
GOODS & SERVICE TAXES:	GST SHALL BE CHARGED EXTRA @18%. GST IS ALSO APPLICABLE ON FREIGHT CHARGES
ORDERING VALUE:	<u>FOR ORDER VALUE LESS THAN RS.3000/- (RUPEES THREE THOUSAND) A CHARGE RS. TWO HUNDRED AS HANDLING CHARGES WILL BE LEVIED</u>
DISCLAIMER:	WE TRY OUR BEST TO USE THE BEST OF COURIERS POSSIBLE FOR EARLIEST DELIVERY TIME BUT HAVE NO CONTROL OVER THE DELIVERIES BY THE COURIER. YOU MAY SUGGEST THE COURIER OF YOUR CHOICE AND WE SHALL SHIP THE GOODS THROUGH THEM, IF POSSIBLE. HOWEVER IN EITHER CASE, WE WILL NOT BE HELD RESPONSIBLE, UNDER ANY CIRCUMSTANCES, IF THE COURIER DELAYS THE DELIVERY FOR NAY REASON WHATSOEVER.
JURISDICTION:	SUBJECT TO KOLKATA JURISDICTION ONLY

THIS SUPERCEDES ALL PREVIOUS PRICE LISTS

ACHV PRICES UPDATED 01.01.2022										
Output Voltage KV	10mA	20mA	30mA	50mA	60mA	100mA	150mA	200mA	250mA	300mA
0-2.5						26299.35	35065.80	50844.20		
0-3										61363.94
0-5				26299.35		35065.80	54350.78	64870.52		
0-10	43831.04	47337.62		52597.49		71883.68	85910.00	96429.74	113962.64	127988.96
0-15	54350.78	56104.07		66623.81		78896.84	91169.87	112209.35	126235.67	149027.23
0-20	59610.65	64870.52		77143.55		92923.16	113962.64	133247.62	149027.23	170066.71
0-25	66623.81	71883.68		89416.58		113962.64	131494.33	149027.23	166560.13	198119.35
0-30	77143.55	89416.58		105196.19		135000.91	152533.81	191106.19	222664.20	306820.91
0-35	85910.00	91169.87		120975.80		163053.55	194612.77	229677.36	254223.42	275262.90
0-40	92923.16	101689.61		131494.33		177079.87	212145.67	229677.36	254223.42	287535.93
0-50	112209.35	126235.67		149027.23		198119.35	219157.62	240197.10	264743.16	299808.96
0-60	131494.33	142014.07		175326.58		219157.62	233183.94	254223.42	271756.32	310327.49
0-70	149027.23	163053.55		182339.74		236690.52	254223.42	273509.61	303314.33	343640.00
0-75	156040.39	164806.84		198119.35		254223.42	275262.90	294549.09	333120.26	368186.06
0-80				240197.10		275262.90	299808.96	334873.55	369939.35	422536.84
0-100				275262.90		334873.55	369939.35	545265.93	615396.32	755657.10

OUTPUT								
DCHV PRICES UPDATED 01.01.2022								
VOLTAGE	3mA/5mA	10mA	20mA	30mA	50mA	100mA	130mA	200mA
KV								
0-3	15954.71	18409.29	20863.86	25773.00	30682.14	42955.00		
0-5	19636.57	22091.14	25773.00	30682.14	41727.71			
0-10	30682.14	35591.29	38045.86	42955.00	60137.00	94501.00		
0-15	38045.86	42955.00	47864.14	55227.86	79773.57			
0-20	50318.71	55227.86	60137.00	69955.29	99410.14			
0-25	62591.57	67500.71	74864.43	89591.86	114137.57			
0-30	66273.43	74864.43	89591.86	104319.29	138683.29	234411.57		357140.14
0-35	79773.57	87137.29	96955.57	116592.14	168138.14			
0-40	92046.43	104319.29	119046.71	141137.86	209865.86			
0-50	114137.57	143592.43	160774.43	182865.57	234411.57	332594.43		
0-60	128865.00	148501.57	177956.43	202502.14	282275.71			
0-70	153410.71	168138.14	185320.14	234411.57	328912.57			
0-75	160774.43	177956.43	192683.86	239320.71	360085.63	430777.29	528960.14	
0-80	177956.43	184092.86	197593.00		369413.00			
0-100	209865.86	234411.57	308048.71		516687.29			
0-130	406231.57	443050.14	614870.14					

PCIT PRICES UPDATED AS ON 01.01.2022

CURRENT OUTPUT	CAPACITY	No OF RANGES	
100A	3V	2 RANGE	30682.14
100A	5V	3 RANGE	36818.57
200A	1KVA	3 RANGE	38045.86
200A	1.2KVA	3 RANGE	45409.57
200A	4.0KVA	3 RANGE	112910.29
250A	1.25KV	3 RANGE	42955.00
300A	1.2KVA	3 RANGE	47864.14
300A	2.0KVA	1 RANGE	60137.00
300A	2.0KVA	2 RANGE	62591.57
300A	2.0KVA	3 RANGE	65046.14
400A	1.2KVA	3 RANGE	55227.86
400A	2.0KVA	2 RANGE	65046.14
400A	2.0KVA	3 RANGE	69955.29
500A	1.0KVA	3 RANGE	65046.14
500A	2.0KVA	3 RANGE	94501.00
500A	2.5KVA	3 RANGE	104319.29
600A	3.0KVA	1 RANGE	111683.00
600A	3.0KVA	2 RANGE	114137.57
600A	3.0KVA	3 RANGE	119046.71
800A	3.2KVA	1RANGE	112910.29
800A	4.0KVA	3 RANGE	137456.00
1000A	2.5KVA	3 RANGE	104319.29
1000A	3KVA	3 RANGE	117819.43
1000A	4.0KVA	3 RANGE	137456.00
1000A	5.0KVA	1 RANGE	119046.71
1000A	5.0KVA	2 RANGE	132546.86
1000A	5.0KVA	3 RANGE	153410.71
1000A	6.0KVA	3 RANGE	166910.86
1000A	10.0KVA	3 RANGE	306821.43
1200A	12.0KVA	3RANGE	233184.29
1500A	3.0KVA	3 RANGE	137456.00

This is a temporary Price List as on date.
Final Price List with updated descriptions will be shared soon.

PCIT PRICES UPDATED AS ON 01.01.2022

CURRENT OUTPUT	CAPACITY	No OF RANGES	
1500A	5.0KVA	3 RANGE	177956.43
1500A	6.0KVA	2 RANGE	177956.43
1500A	7.5KVA	3 RANGE	211093.14
1500A	7.5KVA	2 RANGE	185320.14
1500A	7.5KVA	1 RANGE	168138.14
1500A	30 KVA	3 RANGE	773190.00
1600A	4.0KVA	3 RANGE	159547.14
1600A	4.8KVA	3 RANGE	177956.43
1600A	6.4KVA	3 RANGE	184092.86
1600A	8.0KVA	3 RANGE	241775.29
2000A	4.0KVA	3 RANGE	177956.43
2000A	5.0KVA	3 RANGE	190229.29
2000A	6.0KVA	3 RANGE	217229.57
2000A	8.0KVA	3 RANGE	240548.00
2000A	10.0KVA	1 RANGE	208638.57
2000A	10.0KVA	2 RANGE	233184.29
2000A	10.0KVA	3 RANGE	257730.00
2000A	12.0KVA	3 RANGE	283503.00
2000A	15.0KVA	3 RANGE	306821.43
2000A	20.0KVA	3 RANGE	405004.29
3000A	7.5KVA	3 RANGE	217229.57
3000A	9.0KVA	3 RANGE	258957.29
3000A	10.5KVA	3 RANGE	282275.71
3000A	12.0KVA	3 RANGE	308048.71
3000A	15.0KVA	3 RANGE	357140.14
3000A	22KVA	3 RANGE	479868.71
4000A	8.0KVA	3 RANGE	258957.29
4000A	10.0KVA	3 RANGE	295775.86
4000A	12.0KVA	3 RANGE	344867.29
4000A	16.0KVA	3 RANGE	429550.00
4000A	40.0KVA	3 RANGE	860327.29