

ITEM	DETAILS	NEW LIST PRICE	HSN
AC High Voltage Test Set			
ACHV		On Request	
Acidity Testing Kit			
ATK	Testing Kit used to measure the Acidic content of Transformer Oil	2043	90308990
Acoustic Imager			
AI-09	Industrial Acoustic Imager for gas leakage, partial discharge and other accidents with 128 MEMS microphones, multi-gas detection, IP56 and free software with reports as per ISO-50001 and data analysis.	On Request	90275090
AI-09EX	Explosion-proof Industrial Acoustic Imager for gas leakage, partial discharge and other accidents with 128 MEMS microphones, multi-gas detection and free software with reports as per ISO-50001 and data analysis. With ATEX Certification. For use in hazardous environments.	On Request	90275090
AC Power Supply			
APS-6003 NEW!!		33271	
APS-6006 NEW!!		43323	
APS-60031 NEW!!		38297	
APS-4002 NEW!!		56244	
APS-4003 NEW!!		71595	
APS-4005 NEW!!		81700	
APS-7002 NEW!!		71595	
APS-7004 NEW!!		83850	
APS-7008 NEW!!		142975	
APS-51005 NEW!!		On Request	
APS-51008 NEW!!		On Request	
APS-51010 NEW!!		On Request	
APS-51015 NEW!!		On Request	
APS-51020 NEW!!		On Request	
APS-51030 NEW!!		913750	
APS-51050 NEW!!		On Request	
APS-51075 NEW!!		On Request	
APS-51100 NEW!!		On Request	
Analogue Clamp Meter			
M-300	Clamp Jaw Dia 34mm, AC/DC Voltage, AC Current up to 300A, Resistance & Temperature. Pointer Lock Facility, with temperature probe	2795	90303100
M-600	Clamp Jaw Dia 34mm, AC/DC Voltage, AC Current up to 600A, Resistance & Temperature. Pointer Lock	3118	90303100
M-1000	Clamp Jaw Dia 48mm, AC Voltage up to 600V, DC Voltage up to 300V, AC Current in the range of 0-50/250/500/1000A AC, Resistance up to 2000K. Ohms, Temperature, Audible continuity Test	4838	90303100

ITEM	DETAILS	NEW LIST PRICE	HSN
Analogue Multimeter			
250TR	Measures AC/DC Voltage, DC Current, Resistance, Battery Test and dB.	1064	90303100
260TR	Measures AC/DC Voltage, DC Current, Resistance, Transistor Polarity Test, Audible Continuity	1720	90303100
2010BA	Measures AC/DC Voltage, up to 10A AC/DC, Resistance, Transistor and Audible Continuity	2526	90308990
5050E	Measures AC/DC Voltage up to 1000V, AC/DC Current up to 10A, Resistance up to 2000M.Ohms, Frequency up to 25kHz, Transistor Testing, Diode Testing and audible continuity testing	3655	90308990
6060	Measures AC / DC Voltage up to 2500V, AC/DC Current up to 10A, Resistance up to 10M.Ohms, Diode and continuity test facility	13438	90308990
Battery Impedance			
TM-6002	Battery Impedance Tester to check Battery internal resistance, Voltage, Current and temperature, with 9999 memory, with PC Interface cable and software	87075	90308990
Bench Type Multimeter			
45 T-RMS	4-1/2 Digits Bench type Multimeter	10266	90308990
55 TRMS NEW!!		54825	90308990
M-3511	6-1/2 Digits Bench type Multimeter AC/DC V, AC/DC Current, Resistance, Cap and Frequency	72025	90308990
M-3510A NEW!!	6-1/2 Digits Bench type Multimeter AC/DC V, AC/DC Current, Resistance, Cap., Temp. and Frequency	89225	90308990
M-3500A	6-1/2 Digits Bench type Multimeter with multiple options	117954	90308990
Cable Fault Locator			
CFL-01	Digital Cable Locator and Combined with Cable Fault locator	19888	90318000
CFL-02	Digital Cable Fault Locator for Power, Control and Telecom Cables buried underground	69875	90318000
TDRL-912	Cable Fault Locator for Telecom Cables	145000	90318000
Cable Locator			
CL-2160A	Cable and Pipe Route Tracer for underground cables	400000	90318000
Calibrator			
CAL-408	Bench type RTD Calibrator , Outputs available at -200, -100, -50, -25, 0, 25, 50, 100, 150, 200, 300, 400, 500, 600 °C	8063	90308990
CAL-400-3	Hand Held, 3-1/2 Digits, Battery Operated, 0 - 19.99/24mA, -199.9mV to 199.9mV source and current & power measurement	5913	90308990
CAL-400-4	Hand Held, 4-1/2 Digits, Battery Operated, 0 - 199.9mV / 0 - 19.999mA sourcing and measuring range	8600	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
CAL-402-4	Bench type, 230V AC 50Hz Operated, 0 - 199.99m/1.9999 / 19.999V & 0 - 199.99u/1.999m / 19.999mA Sourcing & Measuring	9675	90308990
CAL-500	Hand Held, 4 Digits Large LCD Display, Measures and Provides output for 20mV / 100mV / 15V DC, Current output up to 24mA, 24V Loop Power, and outputs for K, E, J, T, R, S, B and N types of thermocouples	25800	90308990
01+	5 Digits 0.5% Accuracy, Source for Volt, Resistance, Pt-100, Cu-50, Thermocouples R, S, B, E, K, J, T, N types.	26338	90308990
03+	5 Digits 0.5% Accuracy, Sources and Measures Resistance, PT-100 Sensor and Cu-50 Sensors	26338	90308990
05+	5 Digits, 0.5% Accuracy, Sources DC Current, Analogue Transducer & Loop Power and Measures DC Voltage, DC Current and Loop Current	30100	90308990
11+	6 Digits, 0.2% Accuracy, Sources R, S, B, E, K, J, T, N types of thermocouples, PT-100, Cu-50, DC Voltage, DC Current, Resistance, Analogue Transducer, Frequency, Pulse Output and LOOP Power.	77400	90308990
14+	6 Digits, 0.2% Accuracy, Sources and Measures DC Voltage, PT-100, Cu-50 Sensors and R, S, B, E, K, J, T & N types of Thermocouples.	77400	90308990
15+	6 Digits, 0.2% Accuracy, Sources and Measures DC Voltage, DC Current, Analogue Transducer and LOOP Power.	77400	90308990
25 NEW!!	50,000 Counts, 0.2% Universal Calibrator for DC Voltage, Current, Resistance, Frequency, all thermocouples and thermo-resistance and for	268750	90308990
709H	mA Loop Calibrator with HART COMMUNICATOR , Accuracy 0.01%	102125	90308990
709H-USB	USB COMMUNICATION INTERFACE CABLE AND SOFTWARE for 709H	43000	90308990
VIB-CAL-01 NEW!!	Vibration Calibrator	219300	90308990
CAL-ER NEW!!	Earth Resistance Tester Calibrator	34400	90308990
PM-S Series	Pressure Calibration Modules for 15+	On Request	90308990
Carbon Mono Oxide Meter			
CO-05 NEW!!		15319	90308990
CO-09	Detects Presence of Carbon Mono-Oxide. Range 0 to 1000PPM, Backlit LCD	15050	90308990
CO-10	Detects Presence of Carbon Mono-Oxide. Range 0 to 1000PPM, Backlit LCD, With Audio and Buzzer Alarm	16125	90308990
CO-110 NEW!!	Compact Carbon Monoxide Detector with audio & visual alarms	16125	90308990
Clamp On Ground Resistance Tester			
CET-01	4 Digits LCD, 28mm Clamp Jaw Dia, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms	21825	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
CET-02	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms	21825	90308990
CET-03	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 20A.	26100	90308990
CET-04	4 Digits LCD, 28mm Clamp Jaw Dia, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms. With Leakage Current Measurement up to 20A.	26100	90308990
CET-05	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms	20250	90308990
CET-06	4 Digits LCD, 28 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms	20250	90308990
CET-02EX	Explosion Proof Clamp On Ground Resistance Tester, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 20A.	39600	90308990
CET-09 NEW!!	4 Digits LCD, 35 mm Elliptical Clamp Jaw, Range 0.01Ω to 1500Ω, Max Resolution 0.001Ω, Data Hold, Open Clamp Jaw Indication. With USB Interface & Rechargeable Battery – features Ground Resistance, Loop Resistance, Leakage Current measurements as well as judges Ground Faults.	60075	90308990
Coatmeter			
CTG-01	Measures coating thickness on both ferrous and Non Ferrous materials	11395	90303900
CTG-02	Measures coating thickness on both ferrous and Non Ferrous materials with extended flexible cable with sensor	22050	90303900
CTG-03 NEW!!	Coating Thickness Gauge with USB Interface. Single probe for coating measurements, for both ferrous and non-ferrous metal substrates.	13050	90303900
Combustible Gas Leakage Detector			
GLD-01	16" Gooseneck detector for detecting Combustible Gas Leakage. With Audio and Visual Alarm	5870	90308990
Current Transducer			
CE-0102CT	Current Transducer, AC Current Input and DC output	3601	90308990
Data Logger for Sound Level			
DL-SL-01	Sound Level Data logger to record sound, from 30 to 130 dB, with 129920 data Points	12911	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
Data Logger for Temperature & Humidity			
DL-TH-01	Temperature and Humidity Data Logger with digital display and data logging up to 32700 points	5053	90308990
DL-TH-02 NEW!!	Dry Ice Data Logger for to -80~70°C(-112~158°F), 17280 records, USB interface and IP67 protection	7525	90308990
Data Logger for Voltage and Current			
DL-VL-01	Data Logger for Voltage and Current with digital display and 100096 data points	15803	90258090
Data Logger Multi-Channel			
TP-700 NEW!!	Multi-channel Data Logger with IoT	200000	90258090
DC High Voltage Test Set			
DCHV		On Request	90308990
DC Regulated Power Supply			
RPS-3002	Single Output with Backlit LCD Display of Variable 0 - 30V / 0 - 2A DC	8546	90308990
RPS-3005	Single Output with Backlit LCD Display of Variable 0 - 30V / 0 - 5A DC	8546	90308990
RPS-6005	Single Output with Backlit LCD Display of Variable 0 - 60V / 0 - 5A DC	20963	90308990
RPS-3010	Single Output with LED Display of Variable 0 - 30V / 0 - 10A DC	20909	90308990
RPS-3020	Single Output with LED Display of Variable 0 - 30V / 0 - 20A DC	30100	90308990
RPS-3030	Single Output with LED Display of Variable 0 - 30V / 0 - 30A DC	66650	90308990
RPS-6010	Single Output with LED Display of Variable 0 - 60V / 0 - 10A DC	39399	90308990
RPS-6030	Single Output with LED Display of Variable 0 - 60V / 0 - 30A DC	120400	90308990
RPS-3002-2	Dual Output with Backlit LCD Display of Variable 0 - 30V / 0 - 3A DC	16663	90308990
RPS-3005-2	Dual Output with Backlit LCD Display of Variable 0 - 30V / 0 - 5A DC	20855	90308990
RPS-3003-3	Triple Output with Backlit LCD Display, Dual 0 - 30V / 0 - 3A DC and Fixed 5V/3A	16448	90308990
RPS-3005-3	Triple Output with Backlit LCD Display, Dual 0 - 30V / 0 - 5A DC and Fixed 5V/3A	20855	90308990
RPS-3010-2 NEW!!	Dual Output with Backlit LCD Display, Dual 0 - 30V / 0 - 10A DC	50616	90308990
RPS-10003 NEW!!	Single Output with LED Display of Variable 0 - 100V / 0 - 03A DC	29563	90308990
RPS-20002 NEW!!	Single Output with LED Display of Variable 0 - 200V / 0 - 02A DC	34400	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
DDS Function Generator			
DDS-30 NEW!!	30MHz DDS Function Generator with full-band resolution of 1µHz, 200MSa/s sampling rate and USB interface.	22038	90308990
DDS-60 NEW!!	60MHz DDS Function Generator with full-band resolution of 1µHz, 200MSa/s sampling rate and USB interface.	27413	90308990
DDS-1010	10 MHz DDS Function generator, 125MSa/s sampling rate	23650	90308990
DDS-1025	25 MHz DDS Function generator, 125MSa/s sampling rate	43323	90308990
DDS-1060	50 MHz DDS Function generator, 125MSa/s sampling rate	64500	90308990
DDS-1080 NEW!!	80MHz DDS Function generator, 320MSa/s sampling rate	113950	90308990
DDS-1120 NEW!!	120MHz DDS Function generator, 320MSa/s sampling rate	146200	90308990
Digital AC/DC Clamp Meter			
DT-725	3-5/6-digit 5999 Count, Backlight LCD, T-RMS, Auto-Ranging, NCV, Flashlight, Relative Measurement, AC(750V)/DC(1000V) Voltage, 600A AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity. Square Wave Output, CAT-IV 600V	2956	90303100
DT-230	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 400A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test.	5106	90308990
DT-325	3-3/4 Digits 3999 Counts, Digital AC/DC Clamp Meter, Confirming to CAT-III 300V, Jaw Size 28 mm, Auto Power Off, Data Hold, AC/DC Voltage up to 600V, AC/DC Current up to 400A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test Facility	3720	90308990
DT-6250	3-3/4 Digits, LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Current up to 400A, Resistance, Frequency, Duty Cycle, Capacitance, Diode and Continuity Test.	5913	90308990
DT-1350	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A AC/DC Clamp Meter with AC/DC Voltage, Resistance, Diode and Continuity Check	2903	90303100
DT-1350A	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A AC/DC Clamp Meter with AC/DC Voltage, Resistance, Capacitance, Temperature and Frequency	3333	90303100
DT-1350AT NEW!!	3-5/6 digit, 6000 Counts, backlit LCD, Measure TRMS AC/DC Current & Voltage, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity. Protected in all ranges.	3440	90303100

ITEM	DETAILS	NEW LIST PRICE	HSN
DT-3690	3-4/5 Digits 6000 Counts, LCD, Data Hold,T-RMS, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 1000A, Resistance,Capacitance, Frequency and Temperature & Continuity Test	3978	90303100
DT-425T	3-3/4 Digits 3999 Counts Backlit LCD, T-RMS AC/DC Clamp meter, Confirms to CAT-III 600V, Data Hold, MAX/MIN, Relative, In-Built Flash Light, Overload Protection, 30mm Clamp Jaw Dia, Auto Power Off, AC T-RMS / DC Current 600A, AC T-RMS / DC Voltage 600V, Resistance, Capacitance, Temperature, Frequency, Non Contact Voltage Detector, Diode and Cotinuity Test	5913	90308990
DT-3250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC Voltage,1000A DC/AC Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	7203	90308990
DT-3600	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage,1200A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	7418	90308990
DT-4250	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Duty Cycle, Diode & Continuity Test.	7418	90303100
DT-5250	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, T-RMS, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test.	7740	90303100
DT-8250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC Voltage,2000A DC/AC Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	7955	90308990
DT-9250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage,2000A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	9138	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
2003A	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage, 2000A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	9138	90303100
METRACLAMP-15	3999 Counts, Backlit LCD, 52mm jaw Dia, Non Contact Voltage Detector, Auto Power Off, T-RMS, AC/DC Voltage, AC T-RMS/DC 1000A, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test, double Injection mould, CAT-IV 600V	8493	90308990
METRACLAMP-20	4-3/4 Digits, 40,000 Counts, Backlit, T-RMS, Autoranging, 52mm Jaw Dia, Non Contact Voltage Detector, Fully Protected, AC/DC Voltage, AC/DC Current up to 1500A, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Diode and Continuity Test	12900	90308990
PRO Solar-2	6000 Counts, Auto-Backlit LCD Display, 1000V DC/AC T-RMS, Specially designed for PV Application to measure 2000V DC/1500V AC, DC/AC T-RMS 600A, Resistance up to 600kΩ, Temperature up to 400°C, Capacitance up to 1000uF, Frequency up to 10kHz, Continuity and Diode Test, Optionally can connect to flexible clamp to measure up to 3000A AC. Designed to meet IEC/EN 61010-1, IEC/EN 61010-2-033 CAT IV 600V/CAT III 1000V, Max Conductor Dia 37mm, High Frequency Rejection, In-rush current measurement.	29778	90303100
PRO 474	6000 counts, digital AC/DC T-RMS clamp meter, TFT LCD display, Bluetooth, 1000V AC T-RMS /DC, 1000A AC T-RMS/DC, 34mm Jaw, 10" Flexible Clamp adaptor for upto 3000A AC, AC+DC Voltage, Inrush Current, VFD AC T-RMS Voltage, Lo-Z Voltage, NCV, Capacitance, Resistance, Frequency, Temperature, Continuity and Duty Cycle, Free APP, Datalogging, Trend Capture on device and APP simultaneously	24188	90303100
PRO 419	3-3/4 Digit Professional T-RMS AC/DC Clamp Meter, 4000 Count, 1000V AC T-RMS/DC, 1000A AC T-RMS/DC, Auto Power Off, Non Contact Voltage Detector, Flashlight, Data Hold, MAX-MIN Record, Relative Measurement, 100mF Capacitance, 100kHz Frequency, 40MOhms Resistance, 1000°C Temperature measurement using K type sensor, Continuity.	7203	90303100
PRO 421	3 5/6 Digits TRMS Clamp Meter, 6000 Counts, 1000V AC/DC, 1000A AC/DC with LoZ, Inrush, Peak, VFD, Capacitance, Frequency, Resistance, Temperature, Continuity Test, NCV	7955	90303100

ITEM	DETAILS	NEW LIST PRICE	HSN
PRO Solar-3 with Flexibvle Clamp NEW!!	Professional T-RMS Industrial AC/DC Clamp Meter with 3000A Flexible Clamp, TFT Colour Display with Bluetooth and IP65. High accuracy & 1500V DC for Solar & Photovoltaic Applications. In-rush current and VFD measurement for all Motor Applications.	23500	90303100
PRO Solar-3 NEW!!	Professional T-RMS Industrial AC/DC Clamp Meter with TFT Colour Display with Bluetooth and IP65. High accuracy & 1500V DC for Solar & Photovoltaic Applications. In-rush current and VFD measurement for all Motor Applications.	21000	90303100
Pro Solar-2A NEW!!	3-3/4 digits (4000 counts) backlit LCD, TRMS, PV Voltage upto 1500V DC, AC Voltage, AC/DC Current. Peak Current, Resistance, Capacitance, Frequency, Diode & Continuity, Temperature, Auto-range, 52mm Jaw, Data Hold, Auto Power-off, over-range protection, CAT III 1000V, CAT IV 600V	7850	90303100
PRO EV-CL-01 NEW!!	3-3/4 digits, backlit LCD, T-RMS, wide AC/DC Ampere range (4.000 to 1000A), bar graph, high resolution, best accuracy, one-touch zero, Inrush current, Low Pass filter, non-contact Frequency and Voltage detection, data hold, auto power-off.	15750	90303100
Digital Ammeter	same		
CE-0102A 96x48	3-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 48 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	1075	90303310
CE-0102A 96x96	3-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 96 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	1075	90303310
CE-0102A 96x48	3-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 48 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	1183	90303310
CE-0102A 96x96	3-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 96 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	1183	90303310
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size			
CE-0102A 96x48	4-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 48 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	2365	90303310
CE-0102A 96x96	4-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 96 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	2365	90303310
CE-0102A 96x48	4-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 48 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	2365	90303310

ITEM	DETAILS	NEW LIST PRICE	HSN
CE-0102A 96x96	4-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 96 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	2365	90303310
Digital Ammeter Controller			
CE-0102AC 1SP	Digital Ammeter with Single Set Point to control the current below a given set point. Size - 96 x 96 mm sq. With 1NO + 1NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	3763	85359030
CE-0102AC 2SP	Digital Ammeter with Two Set Point to control the current below a given pair of set points. Size - 96 x 96 mm sq. With 2NO + 2NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	4193	85359030
Digital Anemometer			
AVM-01	4 Digits Backlit LCD Display, Data Hold, Max Record, Measures Air Velocity up to 30m/Sec, measures in km/hr, ft/min, knots, mph as well, Displays Air Temperature -10 to 50 Degree C, Shows windchill and also displays Beaufort Wind Scale	1881	90268090
AVM-03	Digital Thermo-Anemometer with facility to measure 40m/Sec, with humidity, CMM, CFM, USB PC Interface	5375	90268090
AVM-04	Digital Thermo-Anemometer with facility to measure up to 45m/Sec and in ft/min also	6128	90268090
AVM-05	Digital Thermo-Anemometer with facility to measure wind flow (CFM / CMM)	7659	90268090
AVM-07	Digital Thermo-Anemometer to measure up to 30m/Sec with Metal Blades, Temp. -10 to 60°C / 14 to 140°F	5483	90268090
AVM-08	Digital Thermo-Anemometer with facility to measure wind flow (CFM / CMM) with built in infra-red Thermometer to measure from -50 to 260°C with 8:1 D:S Ratio and Emissivity Fixed at 0.95	12868	90268090
AVM-09	Digital Thermo-Anemometer with facility to measure wind flow (CFM/CMM) with built in Pressure Meter	19350	90268090
AVM-10	Digital Hot Wire Anemometer, Dual LCD, with RS-232 Interface, 0.1 to 20m/Sec and Temperature from -20 to 80°C / -5 to 175°F	15050	90268090
Digital Capacitance Meter			
DCM-1502	3-1/2 Digits, LCD, Zero Adjustment, up to 20mF Capacitance Measurement	2849	90308990
Digital Clamp Meter			
DT-115	6000 Counts, Backlit LCD, With Flashlight, Autoranging, Auto Power Off, T-RMS, Non Contact voltage detection, Flashlight, Data Hold, 40 mm Jaw Size, AC/DC Voltage, AC Current up to 600A T-RMS, Capacitance, Frquency, Temperture, Ressitance, Continuity & Diode test.	1914	90303100

ITEM	DETAILS	NEW LIST PRICE	HSN
DT-115A	6000 Counts Backlit LCD Display, Built-in Flashlight to access dark Areas, Non Contact Voltage Detection, Simple to use, Just provide the input and the instrument, detects the signal and displays the parameter, No Selection required, Just provide Input, Automatic Selection of AC/DC Voltage, Resistance, Capacitance, Diode Test, T-RMS, 600A T-RMS Measurements	2338	90303100
DT-369	3-4/5 Digits 6000 Counts, LCD, Data Hold, T-RMS, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Frequency and Temperature & Continuity Test	2419	90303100
DT-1150	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A Clamp Meter with AC/DC Voltage	1989	90303100
DT-1150A	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A Clamp Meter with AC/DC Voltage, Resistance, Capacitance, Temperature and Frequency	2419	90303100
DT-225	3-3/4 Digits, Backlit LCD, Data Hold, Max Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 400A, Resistance, Temperature, Frequency, Diode and Continuity Test. 500V DC/AC Protection in all ranges.	3010	90308990
DT-1250	3-1/2 Digits, Backlit LCD, Data Hold, Max Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Diode and Continuity Test. 500V DC/AC Protection in all ranges.	3118	90308990
DT-2250	3-3/4 Digits, Backlit LCD, Data Hold, 30mm Jaw size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Duty Cycle, Diode and Continuity Test Facility.	3655	90308990
DT-2255	3-1/2 Digits, LCD, Data Hold, Auto-ranging, 57mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test.	3655	90308990
DT-3150	3-3/4 Digits, Backlit LCD, Data Hold, 57mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Frequency, Duty Cycle, Diode and Continuity Test Facility. 1000V DC/AC Protection in all ranges.	3763	90308990
DT-7250	3-1/2 Digits, LCD, Data Hold, Auto-ranging, 57mm Jaw Size, AC/DC Voltage, AC Current up to 2000A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test.	5913	90308990
Digital Clamp Meter with Wireless PC Interface			
DT-5250W	3-3/4 Digits, Backlit LCD, Peak & Data Hold, T-RMS, Wireless PC Interface, 30mm jaw size, AC/DC Voltage, AC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test	10213	90308990
Digital Clamp On Power Meter			
107F	10000 Counts Digital Clamp On Power Meter, AC/DC Voltage and AC/DC Current Auto Detection, NCV, Jaw Dia 42mm, KW, PF, THD up to 25th Harmonics	26338	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
307	6000 Counts, Backlit LCD, Single Phase and Three Phase, Non Contact Voltage Detector, Data Hold, Peak Hold, Relative, Max/Min Reocrd, Single Phase KW, KVA, KVA, PF, KWh and KW & PF for Three Phase. Clamp Jaw Size 56mm. AC Current up to 1500A AC.	16448	90308990
307N	4 Digits, Dual LCD, Single Phase and Three Phase, Max /Min / Peak Hold, 55mm Jaw Dia, T-RMS, AC Voltage, AC Current up to 1000A, KW, KVA, KVAR, Power Factor, Phase Angle, KWh, Frequency and Temperature. With Data Logging and PC Interface	9890	90308990
607	4 Digits, Dual LCD, Harmonic Analysis up to 50th Harmonic, PC Interface, Single Phase & Three Phase, Maximum Demand, KW, KVA, KVAR, KWh, KVAh, KVAh, Power Factor, Real time output of waveform, Power Parameters and Harmonics. Clamp Jaw Size - 55mm.	76594	90308990
Digital Distance Meter			
DM-09	Digital Ultrasonic Distance Meter to measure up to 16m	1881	90308990
Digital Earth Resistance Tester			
ERT-1501	0 - 10 / 100 / 1000 Ohms, 4 Terminal with Testing Kit and Cables in hard carrying case	7686	90303900
ERT-1502	0 - 10 / 100 / 2000 Ohms, 4 Terminal with Testing Kit and Cables in hard carrying case	8600	90303900
ERT-1501R	0 - 10 / 100 / 1000 Ohms, 4 Terminal with Testing Kit and Cables in hard carrying case as above with Rechargeable Battery and Battery Charger	12416	90303900
ERT-1502R	0 - 10 / 100 / 2000 Ohms, 4 Terminal with Testing Kit and Cables in hard carrying case as above with Rechargeable Battery and Battery Charger	13330	90303900
PRO ERT-1635 NEW!!	Double Clamp, Multi-function, Earth and Grounding Resistance Tester for on-site measurement of grounding resistance, soil resistivity, grounding voltage, grounding line leakage current, AC current and DC resistance. Offers precision 4-wire method, 3-wire method and simple 2-wire method, selection method, double-clamp method to measure grounding resistance.	83313	90303390
PRO ERT-1602 NEW!!	Precision 4-wire, 3-wire and simple 2-wire measurement for Earth Resistance, Soil Resistivity, Earth Voltage and AC Voltage. Complete kit in hard carrying case.	34938	90303390
Digital Frequency Counter			
FC-2700	8 Digits Green LED Frequency Counter up to 2.7GHz	9847	90308990
Digital Frequency Meter			
CE-500F 99.99Hz	4 Digits, Panel Flush Mounting, 96 X 48 mm sq, Input 10 - 500V, Measuring range 20 - 99.99 Hz.	1322	90303310

ITEM	DETAILS	NEW LIST PRICE	HSN
CE-500F 96 x 96	4 Digits, Panel Flush Mounting, 96 X 96 mm sq, Input 10 - 500V, Measuring range 20 - 99.99 Hz.	1322	90303310
CE-500F 999.9Hz	4 Digits, Panel Flush Mounting, 96 X 48 mm sq, Input 50 - 500V, Measuring range 0 - 999.9 Hz.	1451	90303310
CE-500F 96 x 96	4 Digits, Panel Flush Mounting, 96 X 96 mm sq, Input 50 - 500V, Measuring range 0 - 999.9 Hz.	1451	90303310
Digital IC Tester			
DICT-2040	40 Pin Digital IC Tester to test 54 / 74 series TTL and 4000 & 4500 series CMOS IC's, tests more than 2000 kinds of devices	33701	90308200
Digital Insulation Tester			
DIT-909	9999 Counts Backlit LCD, Low Battery Indication, Dat Hold, Timer Function up to 10mins, Comparator, 99 Data Records, USB PC Interface (optional) Test Voltage: 50V / 100V / 250V / 500V / 1000V, 200G.Ohms, AC Voltage T-RMS, DC Voltage, Freuqncy, Capacitance, Continuity Test, With Remote Probe, IP-54	29133	90308990
DIT-910 NEW!!	4 Digits, with GO NO-GO functions, 250V/500M.Ohms, 500V/1G.Ohms, 1000V/2G.Ohms	4730	90308990
DIT-912	4 Digits with Analog Bargraph, measures upto 2000M.Ohms at 250V / 500V / 1000V, measures 600V AC/DC, Low Resistance up to 4000 Ohms and Continuity test. Fully Protected on all ranges	10723	90308990
DIT-913	Digital Insulation Tester for 250V / 500V / 1000V / 2500V , 0-2000M(250V), 0-20G(500/1000/2500V)	6128	90308990
DIT-914	Battery cum Mains Operated, with facility to measure AC Voltage, Low Resistance, Continuity, 500V/2000M.Ohms, 1000V/2000M.Ohms, 2500V/20G.Ohms, 5000V/200G.Ohms	16985	90308990
DIT-916	Selectable testing voltages - one testing instrument for low and high voltage systems from 500/1000/2500 and 5000V, Insulation resistance measurement up to 1T Ω , User selectable programmable timer (10s to 30 min), Automatic discharge of test object after completion of measurement, Diagnostic tools, Polarization index (PI), Dielectric absorption ratio (DAR), USB PC Interface	31175	90308990
DIT-921	Battery cum Mains Operated, with facility to measure, PI, DAR, AC Voltage, Low Resistance, Continuity, 500V/6G.Ohms, 1000V/6G.Ohms, 2500V/60G.Ohms, 5000V/60G.Ohms	29025	90308990
DIT-99A	Digital Battery Cum Mains Operated Insulation Tester for 100V / 200M.Ohms	3064	90308990
DIT-99B	Digital Battery Cum Mains Operated Insulation Tester for 250V / 200M.Ohms	3064	90308990
DIT-99C	Digital Battery Cum Mains Operated Insulation Tester for 500V / 1G.Ohms	3064	90308990
DIT-99D	Digital Battery Cum Mains Operated Insulation Tester for 1000V / 2G.Ohms	3064	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
DIT-321	Digital Insulation Resistance Tester with Built-in Multimeter, 3-3/4 Digits 3999 Counts, Backlit LCD, Data Hold, Test Voltage: 250V / 500V / 1000V, upto 40G.Ohms, Measures AC/DC Voltage, AC/DC Current up to 400mA, Resistance, Capacitance, Frequency, Diode & Continuity Test Facility.	4838	90308990
DIT-322	Digital Insulation Resistance Tester with Built-in Multimeter, 3-3/4 Digits 3999 Counts, Backlit LCD, Data Hold, Test Voltage: 500V / 1000V / 2500V, upto 40G.Ohms, Measures AC/DC Voltage, AC/DC Current up to 400mA, Resistance, Capacitance, Frequency, Diode & Continuity Test Facility.	6450	90303100
PRO DIT-925 NEW!!	5kV Insulation Resistance Tester featuring Insulation Resistance measurement (IR); Polarisation Index measurement (PI); Absorption Ratio (DAR); Ramp Test mode (RAMP) ; Filtered Resistance test (FR), Voltage measurement (V); Current measurement (nA). With touchscreen display.	59125	90303900
PRO DIT-927 NEW!!	10kV Insulation Resistance Tester featuring Insulation Resistance measurement (IR); Polarisation Index measurement (PI); Absorption Ratio (DAR); Ramp Test mode (RAMP) ; Filtered Resistance test (FR), Voltage measurement (V); Current measurement (nA). With touchscreen display	65575	90303900
DIT-930 NEW!!	Megohmmeter/ high-voltage insulation resistance tester, used for insulation resistance tests upto 5KV and 0.01MΩ ~ 10TΩ. Functions: Insulation resistance test, voltage test, current test, capacitance test.	83850	90303900
DIT-930E NEW!!	Megohmmeter/ high-voltage insulation resistance tester, used for insulation resistance tests upto 10KV and 0.01MΩ ~ 35TΩ. Functions: Insulation resistance test, voltage test, current test, capacitance test.	91375	90303900
DIT-930F NEW!!	Megohmmeter/ high-voltage insulation resistance tester, used for insulation resistance tests upto 15KV and 0.01MΩ ~ 50TΩ. Functions: Insulation resistance test, voltage test, current test, capacitance test.	129000	90303900
DIT-931 NEW!!	5kV Insulation Resistance Tester featuring Insulation Resistance measurement (IR); Polarisation Index measurement (PI); Absorption Ratio (DAR); Ramp Test mode (RAMP) ; Filtered Resistance test (FR), Voltage measurement (V); Current measurement (nA). With touchscreen display.	99500	90303900
DIT-931E NEW!!	10kV Insulation Resistance Tester featuring Insulation Resistance measurement (IR); Polarisation Index measurement (PI); Absorption Ratio (DAR); Ramp Test mode (RAMP) ; Filtered Resistance test (FR), Voltage measurement (V); Current measurement (nA). With touchscreen display.	120000	90303900

ITEM	DETAILS	NEW LIST PRICE	HSN
DIT-931F NEW!!	15kV Insulation Resistance Tester featuring Insulation Resistance measurement (IR); Polarisation Index measurement (PI); Absorption Ratio (DAR); Ramp Test mode (RAMP) ; Filtered Resistance test (FR), Voltage measurement (V); Current measurement (nA). With touchscreen display.	144000	90303900
DIT-950 NEW!!	High Precision IR Tester 10kΩ to 50TΩ, used for rapid measurements on IR properties of electronic parts and components, dielectric materials, equipments, cables, etc.	392375	90303900
DIT-951 NEW!!	High Precision IR Tester 10kΩ to 100TΩ, used for rapid measurements on IR properties of electronic parts and components, dielectric materials, equipments, cables, etc.	294550	90303900
Digital VA Meter			
CE-0303VA	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	4515	90303310
CE-0304VA	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	4515	90303310
Digital VAR Meter			
CE-0303VAR	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	4515	90303310
CE-0304VAR	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	4515	90303310
Digital KWh Meter			
CE-0303EML	Digital KWh Meter with LCD Display for Three phase Three wire Two element loads	5321	90283090
CE-0304EML	Digital KWh Meter with LCD Display for Three Phase Four wire Three Element loads	5321	90283090
CE-0102EML NEW!!		4300	90283090
Digital LCR Meter			
460	11,000 Counts Backlit LCD, Data Hold, MAX/MIN Record, RELATIVE, Inductance, Capacitance, Resistance, Diode & Continuity Test	5698	90308990
4070D	5 Digits, LCD, Dual Display, Inductance, Capacitance, Resistance, Impedance, D, ESR and Q Test Facility, Test Frequency of 100Hz, 120Hz, 1kHz, 10kHz and 100kHz	12900	90308990
4090D NEW!!	LCR Meter	33325	
Digital LCR Multimeter			
451	3-1/2 Digits, Backlit LCD, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Inductance, Frequency, Temperature, Diode, Transistor and Continuity Test	4053	90303100

ITEM	DETAILS	NEW LIST PRICE	HSN
506	3-3/4 Digits, Backlit, LCD Dual Display, T-RMS, RS-232 PC Interface, Internal Memory, Min, Max, Avg, Relative Modes, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Inductance, Duty Cycle, Temperature, dBm, Logic, Diode, Signal Output & Continuity Test	22038	90303100
Digital Leakage Current Meter			
DT-4671	3-3/4 Digits, Analogue Bargraph, LCD, Data Hold, MAX/MIN Record, 30mm Jaw Size, AC Voltage, AC Current, Resistance. Has Low Pass Filter to filter out noise.	6558	90308990
DT-4672	3-3/4 Digits, LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Leakage Current measurement, Capacitance, Resistance, Frequency, Duty Cycle, Diode & Continuity Test	6880	90303100
DT-4673	3-1/2 Digits, LCD, T-RMS, AC/DC Leakage Current Meter, Non contact voltage detector, Data Hold, Can be used for Variable Frequency Control Drives, Measures from 1mA, AC/DC Current up to 100A, AC/DC Voltage, Resistance, Capacitance, Diode and Continuity Test	5698	90303100
DT-6054	3-1/2 Digits LCD, Data Hold, Max Hold, 30mm Jaw Dia, 0 - 200mA / 2A / 200A AC.	5590	90303100
MULTI-140	3-1/2 Digits, 3200 Counts LCD, Data Hold, 40mm jaw Dia, 0 - 30m/300m/30/300A AC	32788	90303100
PRO-468AC	6000 Counts, Auto-Backlit LCD Display, Auto Power Off, as per IEC 61557-13: Class 2, 40mm Jaw Dia, IEC / EN 61010-1, IEC / EN 61010-2-032, CAT. III 600V, Pollution Degree 2, EN 61326-1 EN 61326-2-2, bandwidth up to 1kHz, 1% accuracy, 0 - 6mA / 60mA / 600mA / 6A / 60A, With resolution of 1uA,	33540	90303100
PRO 2010 NEW!!	AC/DC Auto-ranging Leakage Current Clamp Meter, 0.1mA resolution, 5000 counts, Backlit LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Leakage Current, Resistance, Continuity Test	26875	90303100
Digital Lux Meter			
1300	4 Digits Backlit LCD Display, MAX / MIN Record, Data Hold, Digital Lux Meter, Can measure up to 200,000 Lux, Also measures in FC (Foot Candle), High Sampling Rate, Overload Indication, Auto Power Off, Low Battery Indication	1860	90278090
1310	4 Digits Backlit LCD Display, Data Hold, Hi/Lo Indication, Split Probe, Lux and Foot Candle Measurement, Auto Power Off, Lo-Battery Indication, Measures up to 199,900 Lux / Fc	2903	90278090
1330	Measures up to 50,000 Lux	2688	90278090
1331	Measures up to 50,000 Lux / Ft Candle with Max Hold and Data Hold	3225	90278090
1332	Measures up to 200,000 Lux / Ft Candle with Peak Hold and Data Hold	5913	90278090

ITEM	DETAILS	NEW LIST PRICE	HSN
1332A	Measures up to 200,000 Lux / Ft Candle with Max Hold and Data Hold	7848	90278090
1333	Measures up to 0 - 20 / 200 / 2000 / 200000 / 200,000 Lux / Ft Candle with Max Hold and Data Hold	5268	90278090
1334	Measures up to 400,000 Lux/40,000 Ft Candle, Data & Peak Hold, Max Min Record, USB PC Interface, Backlit LCD With Analogue Bargraph	6558	90278090
1335 NEW!!	Measures visible light up to 400000 Lux from luminaries equipped with white light LED, fluorescent, metal halide, high-pressure sodium and incandescent sources.	8493	90278090
Digital Micro Ohms Meter			
53C	Digital Micro Ohms Meter to measure from 1uOhm to 2k.Ohms	6343	90308990
53C-II	Micro-Processor based, Digital Micro Ohms meter to measure from 1uOhms to 2kOhms, with digital selection of ranges	6773	90308990
UOT-10A	Digital Micro Ohms Meter with Test Current of 10A	82775	90308990
7272A NEW!!	10A Micro Ohms Meter with backlit LCD display, USB PC Interface, 500 Internal Memory, Four Wire measurement, Testing Current of 10A, Battery Operated, Measures from 10.0uΩ-50.00KΩ with accuracy of ±0.2%FS±10 dgt.	60200	90308990
PRO 7275 NEW!!	10A Digital Microohms Meter	64575	90308990
PRO 7275A NEW!!	20A Digital Microohms Meter	85500	90308990
UONT-100A	Digital Micro Ohms Meter with Test Current of 100A	96750	90308990
UONT-200A	Digital Micro Ohms Meter with Test Current of 200A	188125	90308990
Digital Milli Ohms Meter			
52C	Hand Held, 0.1mOhms to 40 Ohms, 4 wire Kelvin type connection, also measures AC/DC Voltage, AC/DC Current, Resistance, Capacitance and continuity	10213	90308990
Digital Moisture Meter			
MM-1	Digital Moisture Meter for paper, wood and hardned material like plaster, concrete and mortar	3548	90308990
MM-2	Digital Moisture Meter for wood, bamboo, cotton, tobacco, paper, foodstuffs	1720	90308990
MM-5	Digital Wood Moisture Meter that can measure moisture in up to 150 different kinds of wood	6558	90308990
MM-10	Digital Pinless Moisture Meter, Range 0 - 100%, auto power off, backlit display, Min/Max function, Measure and Hold, works on most of the products	8600	90308990
Digital Multimeter			
XB-30	3-1/2 Digits, LCD, Data Hold, AC Voltage, DC Voltage, DC Current, Resistance, Diode & Transistor Test.	1478	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
XB-33CF	6000 Counts Backlit LCD, Flash Light, NCV, MAX/MIN Record, T-RMS, Measures AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Frequency, Diode and Continuity Test	1720	90303100
603	3-1/2 Digits, Backlit LCD, Data Hold, AC Voltage, DC Voltage, AC Current, DC Current, Resistance, Capacitance, Frequency, Temperature, Hot Wire, Diode, Transistor and Continuity Test.	1760	90303100
6030A+	6000 Counts Backlit LCD, T-RMS Multimeter, Auto Power Off, Data Hold, MAX/MIN, AC / DC Voltage, AC/DC Current 20A, Resistance, Capacitance, Frequency, Temperature, Transistor Test, Diode and Continuity Test	2096	90303100
901-I	3-1/2 Digits, LCD, Auto-ranging, Max Hold and Data Hold, AC Voltage, DC Voltage, AC Current, DC Current, Resistance, Temperature, Diode & Continuity Test. 500V DC/AC Protection in Resistance, Temperature, Diode and Continuity Test.	2365	90308990
19	3-3/4 Digits, LCD, Auto-ranging, Relative, Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, 30MHz Frequency, Duty Cycle, Temperature, Diode, Transistor and Continuity Test.	2258	90303100
19-SUPER	6000 Counts LCD Display, NCV, T-RMS Multimeter, Measures AC/DC Voltage, AC/DC Current up to 20A, Resistance, Temperature, Frequency, Capacitance, Diode, Transistor Test and Continuity Test Facility	2419	90303100
901-II	3-3/4 Digits, Backlit LCD, Auto-ranging, Relative, Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity Test.	3118	90303100
901-III	3-5/6 Digits, 6000 Counts Backlit LCD, Autor-ranging, 600V AC/DC Protection, AC/DC Voltage, AC/DC Current, Resistance, 4mF capacitance, 20MHz Frequency, temperature diode and continuity	4408	90303100
901-IV	3-5/6 Digits, 6000 Counts Backlit LCD, Autor-ranging, T-RMS, 600V AC/DC Protection, AC/DC Voltage, AC/DC Current, Resistance, 4mF capacitance, 20MHz Frequency, temperature diode and continuity	5268	90303100
801	3-3/4 Digits, LCD, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Logic Test, Diode & Continuity Test. 500V DC/AC Protection in Resistance, Capacitance, Frequency, Logic, Diode & Continuity Test	3171	90303100
DT-19TB	3-3/4 Digits, Backlit LCD, Auto-ranging, Terminal Blocking Facility, Relative & Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Battery Test, Diode & Continuity Test. 500V AC/DC Protection in all ranges	3548	90303100

ITEM	DETAILS	NEW LIST PRICE	HSN
Metrasafe-10	6000 Counts Backlit LCD, T-RMS, Flashlight, Live-Neutral detectio, Non contact voltage detector, Audio and visual alarm for continuity, Transistor Test, AC/DC Voltage, AC/DC Current up to 20A, Resistance, Capacitance, Frequency, Temperature, Duty Cycle, Diode and Continuity Test.	2580	90303100
Metrasafe-13	3-3/4 Digits, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Relative, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Continuity and Battery Test. Confirms to CAT IV 600V	4596	90303100
Metrasafe-14	3-3/4 Digits, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Relative, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Continuity and Battery Test. Confirms to CAT IV 600V	5268	90303100
Metrasafe-15	3-3/4 Digits, Analogue Bargraph, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Max/Min, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test. Confirms to CAT IV 600V.	6343	90303100
Metrasafe-16	3-3/4 Digits, Analogue Bargraph, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Max/Min, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test. Confirms to CAT IV 600V.	7310	90303100
Metrasafe-18	4-3/4 Digits, Analogue Bargraph, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data & Peak Hold, Max/Min Record, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Non Contact type Infrared Thermometer, Duty Cycle, Diode & Continuity Test. Confirms to CAT IV 600V.	15265	90303100
Metrasafe-19	4-3/4 Digits, Analogue Bargraph, Wireless PC Interface, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data & Peak Hold, Max/Min Record, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Non Contact type Infrared Thermometer, Duty Cycle, Diode & Continuity Test. Confirms to CAT IV 600V.	17093	90303100
Metrasafe-20	4-5/6 Digits, 60,000 Counts, T-RMS Multimeter, OLED Display, 100kHz Bandwidth, 0.025% Accuracy, Lo-Z measurement, AC/DC Voltage, AC/DC Current, Resistance, Process Measurement, Conductance, Capacitance, Frequency, Duty Cycle, Temperature, Diode and Continuity, Re-chargeable battery, Battery Charger, Misoperation Alarm, Data Logger. Optional Blue Tooth Interface	34400	90303100

ITEM	DETAILS	NEW LIST PRICE	HSN
23S-TRMS	4-1/2 Digits 19,999 Counts, T-RMS, Backlit LCD, NCV, Data Hold, Peak Hold, Relative, Auto Power Off, Dual Display to show Voltage & Current with Frequency on the same screen, AC/DC Voltage, AC/ DC Current 10A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test both Audio and Visual.	3978	90303100
540	4-1/2 Digits, LCD, Data Hold, T-RMS, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Diode & Continuity Test.	4838	90303100
DM-454	22,000 Counts LCD Display, Peak Hold, Data Hold, Relative Measurement, T-RMS Multimeter, Confirms to CAT III 1000V, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Diode & Continuity Test, USB PC Interface.	10723	90303100
PRO-11	4000 Count Backlight LCD Display, Auto-Ranging, IP67 Dust and Waterproof, 600V AC/DC Voltage, 10A AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, UL 61010-1, CAT-III 600V, Class 2 Double Insulation, Built-in flashlight, Over range indication, Auto Power Off, Min/Max Data Hold. Hand-Held Waterproof and Dustproof, Digital Multimeter. Anything and Everything that you can possibly think about. A must for all technicians, double moulded injection body, a built-in flashlight to access dark areas,	4596	90303100
PRO-12B	4000 Count, Backlight LCD Display, TRMS, IP 67 Dust and Waterproof Digital Multimeter, 600V AC(TRMS)/DC Voltage, 10A AC(TRMS)/DC Current, LoZ, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity test, 50 to 400Hz AC Bandwidth, Bluetooth Smartphone interface, Free Smartphone App, Data Hold, MAX/MIN Record, Built-in Flashlight, Double-moulded injection body, Auto Power Off, Low battery indication, CAT-III 600V. Hand-Held Waterproof and Dustproof, Digital Multimeter. Anything and Everything that you can possibly think about. A must for all technicians.	5375	90303100
PRO SOLAR-1 NEW!!	6000 Counts, Auto-backlit LCD, confirming to EN 61010-1, EN 61010-2-033 for CAT III 1000V, CAT IV 600V, EN 61326-1, designed for Solar PV applicaton, to measure 2000V DC and 1500V AC T-RMS, to measure DC/AC mV as well, AC/DC Current up to 10A, Resistance 40M.Ohms, Capacitance 10mF, Frequency 100kHz, Temperature 400 Degree C, Non Contact Voltage Detection, Diode and Continuity Test.	17200	90303100
PRO SOLAR-1A NEW!!	1500VDC, 1000VAC, 6000 counts backlit LCD display, TRMS, Auto-ranging, Heavy Duty, Industrial-grade Digital Multimeter with VFD Measurement. IP67 & 2 metres drop/shock-proof. Perfect for Solar & PV Applications.	6988	90303100

ITEM	DETAILS	NEW LIST PRICE	HSN
PRO 587 NEW!!	6,000 /60,000 Counts user selectable, Backlit LCD Display, Bargraph, T-RMS Multimeter, 1000V AC/DC Current, 10A AC/DC Current, 100kHz AC Response, Resistance, Capacitance, Electrical and Electronic Frequency, Temperature, Duty Cycle, Low Pass Filter, 4-20mA measurement, Continuity and Diode testing.	13438	90303100
PRO 589 NEW!!	Professional True RMS Industrial Digital Multimeter and TFT color LCD display, providing fast A/D converting sampling time, high accuracy, built-in data logging, and Trend Capture features. AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency (electrical & electronic), Duty Cycle, Diode Test, Insulation Test, and Continuity plus Thermocouple Temperature. It can store and recall data. It features a waterproof, rugged design for heavy duty use.	22038	90303100
PRO 21 NEW!!	6000 counts backlit LCD display, TRMS, Auto-ranging, Heavy Duty, Industrial-grade Digital Multimeter with VFD Measurement. IP67 dust and water proof as well as 2 metres drop/shock-proof!	5913	90303100
PRO 27 NEW!!	6000 counts backlit LCD display, Auto-Ranging T-RMS Multimeter with VFD, LoZ, 61 Segment Analogue Bar-graph and IP67- best fit for all applications regarding electrical motors.	6665	90303100
XB-33A NEW!!	6000 Counts, Auto-ranging, T-RMS Digital multimeter with backlit LCD display. Can measure AC T-RMS Voltage and Current, DC Current / Voltage, Frequency, Resistance, Capacitance, Temperature, Diode and Continuity Test and Non-contact Voltage Detection, along with overload protection.	1613	90303100
PRO 7 NEW!!	Digital TRMS auto-ranging multimeter with backlit display, backlit switch as well as backlit ranges. AC/DC Voltage, VFD Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Duty Cycle, Diode & Continuity Test, NCV detection, Live Line test & Square Wave Output. Heavy-duty, rugged design with double-injection moulding. Built-in Flashlight. Confirms to CATIII 600V. Data Hold, MAX/MIN, Auto Power Off.	3677	90303100
Accessories to Digital Multimeter			
CA-01	Clamp On Current Adaptor to be used with any Multimeter with mV range, measures up to 200A AC	1290	90308990
CA-1000D	Clamp On Current Adaptor to be used with any Multimeter with mV range, measures up to 600A/1000A AC/DC	5698	90308990
TS-03	Infra Red Temperature Adaptor to measure from -30 to 550 Degree C, can be used with any Multimeter with mV range	3655	90308990
PD-28	High Voltage probe to measure 40kV DC and 28kV AC	8869	90308990
ATL-PV NEW!!	High Voltage Probe for P-V Multimeter SOLAR-1 and PV Clamp meter SOLAR-2	3225	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
TL-70	Right Angled shrouded termination to fit modern multimeters, fitted with a 4mm shrouded socket, CAT III 1000V / 20A Rating	215	90308990
TL-74	1m silicon single insulated test leads with right angle shrouded banana plugs, CAT IV 600V, CAT III 1000V with protective cap, banana plug termination, dia of test lead point 2mm	376	90308990
TL-75	1m silicon double insulated test leads with right angle shrouded banana plugs, CAT IV 600V, CAT III 1000V with protective cap, banana plug termination, dia of test lead point 2mm	538	90303100
Flex Clamp NEW!!	For PRO 27 and PRO Solar-3	4000	90303100
Flex Clamp NEW!!	For Solar-2 and 107F	7525	90303100
Digital Non Contact Infrared Thermometer			
MT-2	Digits Backlit LCD with laser sighting used to measure temperature in the range of -50°C to 550°C / -58°F ~ 1022°F, D:S Ratio 12:1, Fixed emissivity 0.95.	2258	90251920
PRO-65 MAX	Precise Non Contact Measurement, Circular Laser to show the exact area whose temperature is being measured IP54 Rated for Dust / Water Proof, 2m Drop Tested, Automatic Data Hold, Non Contact and Contact Thermometer Combined, Contact temperature measurement using K type sensor, Adjustable Emissivity from 0.10 to 1.00, MAX / MIN / AVG / DIF Temperature display, Backlit LCD Display, Set High and Low Alarms, Distance to Sighting Ratio 16:1 (65Max) Battery Operated 2 x 1.5V AAA Batteries, CE Compliant with EMC, Tk Temperature: -50 to 1370°C, Resolution: 0.1°C < 1000; 1°C > 1000, Accuracy: ±0.5% of Reading ±1.5°C, IR Temperature Measurement: -50 to 800°C Response Time: 150mS, Spectral Response: 8 – 14um	4730	90251920
PRO-65 MAX+	Precise Non Contact Measurement, Circular Laser to show the exact area whose temperature is being measured IP54 Rated for Dust / Water Proof, 2m Drop Tested, Automatic Data Hold, Non Contact and Contact Thermometer Combined, Contact temperature measurement using K type sensor, Adjustable Emissivity from 0.10 to 1.00, MAX / MIN / AVG / DIF Temperature display, Backlit LCD Display, Set High and Low Alarms, Distance to Sighting Ratio 20:1, Battery Operated 2 x 1.5V AAA Batteries, CE Compliant with EMC, Tk Temperature: -50 to 1370°C, Resolution: 0.1°C < 1000; 1°C > 1000, Accuracy: ±0.5% of Reading ±1.5°C, IR Temperature Measurement: -50 to 1000°C, Response Time: 150mS, Spectral Response: 8 – 14um	5913	90251920
MT-10	3-1/2 Digits Backlit LCD, fixed emissivity of 0.95, D:S Ratio of 50:1, measures from -50 to 1000°C / -58 to 1832°F, with laser pointer	15265	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
MT-13	Backlit LCD, Contact cum Non Contact type, measures from -18 to 1050 °C in Non Contact model and -50 to 1370 °C in Contact Mode, Emissivity adjustable from 0.10 to 1.0, D:S Ratio of 30:1, with wireless USB PC Interface and facility to calculate the emissivity of the surface	19673	90251990
MT-14	4 Digits Backlit LCD, Contact cum Non Contact type, measures -50 to 1300°C/-58 to 2372°F in non contact mode and contact mode. D:S Ratio 30:1, Emissivity Adjustable 0.10 to 1.00, mV output /°C, Trigger Lock, battery cum mains operated, Records 20 Data, Max/Min/Dif/Avg recording	13438	90251990
MT-15 NEW!!	Measures from -50 to 1200°C / -58 to 2192°F with dual laser pointer, contact cum non-contact type, with USB PC Interface and with Max./Min./Dif/AVG., 4 Digits Backlit LCD, adjustable emissivity from 0.10 ~ 1.0, D:S Ratio of 50:1, in non contact mode	19350	90251920
MT-16 NEW!!	4 Digits Backlit LCD, Contact cum Non Contact type, with USB PC Interface, adjustable emissivity from 0.10 ~ 1.0, D:S Ratio of 50:1, in non contact mode measures from -50 to 1800°C / -58 to 3272°F, with dual laser pointer to show the diameter of the area whose temperature is being measured and with Max./Min./Dif/AVG. Temp.	23650	90308990
MT-18	4 Digits Backlit LCD, Contact cum Non Contact type, with USB PC Interface, adjustable emissivity from 0.10 ~ 1.0, D:S Ratio of 50:1, in non contact mode measures from -50 to 2200°C / -58 to 3992°F, with dual laser pointer to show the diameter of the area whose temperature is being measured and with Max./Min./Dif/AVG. Temp.	30100	90251990
MT-19 NEW!!	Non-contact Infrared Thermometer for -50° to 2200°C with D:S Ratio of 75:1. Features Dot Matrix Backlit LCD, Bluetooth, up to 32000 data points, adjustable emissivity with dual laser pointer and Max./Min./Dif/AVG. Temp.	31713	90251990
MT-20	4 digits LCD, adjustable emissivity from 0.10 to 1.00, telescopic sighting measures in the range of 500°C to 3000°C and in °F scale, distance to sighting ratio of 120:1, accuracy ±1%, with Max/Min/Ave/DT and High/Low alarm	268750	90251990
ST-201A	Fixed Online Infrared Thermometer 300°C~1300°C. Spectral Response 2.6 µm	120000	90251990
ST-201AK	Fixed Online Infrared Thermometer 500°C~1400°C. Spectral Response 2.6 µm	140000	90251990
ST-201B	Fixed Online Infrared Thermometer 600°C~1600°C. Spectral Response 1.7 µm	138200	90251990
Digital Phase Angle Meter			
CE-0102D	Digital Phase Angle Meter, 96 x 96 mm sq, can measure Phase Angle between Voltage and Current	3870	90303310

ITEM	DETAILS	NEW LIST PRICE	HSN
Digital Power Analyser			
CE-0102PA	Digital Ampere, Volt,PF and Watt meter combined in 96 x 96 mm sq for single phase loads	4838	90303310
Digital Power Factor Meter			
CE-0102PF 96x48	Microprocessor Based, 96 x 48 mm sq, For Single Phase, Red LED Display	3548	90303310
CE-0102PF 96 x 96 mm sq	Microprocessor Based, 96 x 96 mm sq, For Single Phase, Red LED Display	3548	90303310
CE-0303PF	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element , Red LED Display	4515	90303310
CE-0304PF	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	4515	90303310
Digital Pressure Meter			
PM-01	Backlit LCD Display, measures up to 5 psi and in various other units of Pressure	13975	90318000
PM-05	Differential Pressure Manometer measures negative, positive and differential pressure. Option for 11 measurement units: bar, ozin ² , psi, mbar, mmHg, cmH ₂ O, ftH ₂ O, kgcm ² and kPa.	4500	90318000
Digital Process Meter			
PM-29	3-3/4 Digits, Digital Multimeter Cum DC mV / Voltage / Frequency / Resistance / mA Calibrator and also provies output for all types of Thermocouples	43753	90308990
PM-39	5 Digits, Digital Multimeter combined with source for DC voltage, resistance, frequency, all kind of thermocouples, thermal resistance, and DC current. supply power to 24V circuits and meanwhile measure current; with built-in 250 Ω HART loop resistance	50525	90303100
Digital Process Clamp Meter			
771+	The Milliamp Process Clamp Meter is a hand-held battery-operated clamp meter that measures 4-20 mA DC without breaking the electrical circuit. DC mA measurement (4-20mA) using a remotely connected clamp via extension cable, Electronic zero, Percentage span (0-100%), Data Hold, Backlit Display, Measurement spotlight LED, Auto Power Off, 0mA... ±20.99mA, Resolution 0.01mA, Accuracy: 0.3% realding ±8 digits, Also measures ±21.0mA... ±99.9mA with Resolution of 0.1mA, Clamp Jaw 4.5mm, IP40, IEC 61010-1, 61010-2-032, CAT II 300V	22575	90303100
Digital SMT Component Tester			
SMT-01	SMT Component tester that can measure Capacitance and Resistance values of SMT components, it can also measure AC/DC Voltage, continuity and Diode test	4300	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
Digital Sound Level Meter			
SL-3010	4 Digital Backlit LCD, Sound Level Meter, Fast & Slow Response, Data Hold, MAX/MIN Record, A Weighting, Measures sound in the range of 30dB to 130dB with resolution of 0.1dB and accuracy of 1.5dB. With Over-range and Low Battery Indication	1881	90278090
SL-4010	3-1/2 Digits Backlit LCD, has A & C Weighting, measures in the range of 30 to 130 dB, with maximum hold	6128	90278090
SL-4005	3-1/2 Digits, has A & C Weighting, measures in the range of 35 to 130 dB, with data hold and maximum hold, with built in calibration check	7095	90278090
SL-4015	4 Digits, has A & C Weighting, measures in the range of 30 to 130 dB, USB PC Interface, with Max/Min Data Hold and Data Logging facility	12255	90278090
Digital Storage Oscilloscope			
DSO-5025E	25MHz DSO with colored display, 250MSa/Sec sampling rate, with USB PC Interface cable and software	30638	90302000
DSO-5050E	50MHz DSO with colored display, 500MSa/Sec sampling rate, with USB PC Interface cable and software	31713	90302000
DSO-5074E NEW!!		76325	90302000
DSO-5100E	100MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host	37088	90302000
DSO-5104E NEW!!		80625	90302000
DSO-5150E	150MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host	40850	90302000
DSO-5200E	200MHz DSO with colored display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device&host	44075	90302000
Accessories to Digital Storage Oscilloscope			
PD-20S	High Voltage Probe to be used with any oscilloscope (Analogue or Digital Storage) to measure High Voltage Waveform of 30kV DC and 20kV AC	9460	90308990
OP-60 NEW!!	OP-60 is a x 1 / x 10 attenuation modular probe designed to be used with 60MHz oscilloscopes with an input impedance of 1MΩ.	753	90308990
OP-100 NEW!!	OP-100 is a x 1 / x 10 attenuation modular probe designed to be used with 100MHz oscilloscopes with an input impedance of 1MΩ.	1075	90308990
OP-250 NEW!!	OP-250 is a x 100 attenuation modular probe designed to be used with 250MHz oscilloscopes with an input impedance of 100MΩ.	6235	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
Digital Stroboscope			
DT-2350A	Digital Stroboscope, 50 to 12,000FPM, 230V Single Phase AC Operated	12911	90308990
DT-2350B	Digital Stroboscope, 50 to 40,000FPM, 230V Single Phase AC Operated	22978	90308990
DT-720 NEW!!	LED Stroboscope to measure high-speed rotating objects, and the value can be measured without direct contact. Measurements can be taken without using reflective tape. The measuring range is 60-49999 RPM.	9675	90308990
DT-720-2 NEW!!	LED Stroboscope to measure high-speed rotating objects, and the value can be measured without direct contact. Measurements can be taken without using reflective tape. The measuring range is 60-99999 RPM.	11825	90308990
Digital Tachometer			
DT-2235	Contact type Tachometer, measures up to 50,000RPM	2795	90292090
NCTM-500	Non Contact type Tachometer With Counter, Data Hold, Measures from 50mm to 200mm, RPM Up to 99999RPM, and Counts up to 99999 Counts	1881	90308990
NCTM-1000	Non Contact type Tachometer Cum Counter. Max / Min . Last Data Record, 2 to 99,999 RPM, 1 TO 99,999 Counts	3548	90308990
NCTM-2000	Contact cum Non Contact type Combined Tachometer, Max/Min, Last Record, 20,000RPM in contact mode and 99,999 RPM in non contact mode, measures Rotation speed, total revolution, frequency, surface speed and length	6450	90308990
NCTM-3000 NEW!!	Contact and Non Contact type Combined Tachometer with non-contact laser sighting for measuring from up to 12 feet distance. 20,000 RPM in contact mode and 200,000 RPM in non-contact mode.	7310	90308990
Digital Temperature Controller			
DTC-200	Digital Temperature Controller 96 x 96 mm sq, with 1NO + 1NC, Single Set Point, for K, J, R, S, PT-100 (Any One)	2338	84779000
DTC-202	Digital Temperature Controller 96 x 96 mm sq, with 2NO + 2NC, Two Set Point, for K, J, R, S, PT-100 (Any One)	2849	84779000
METCAT 96	Digital Temperature Controller, 4 Digits Display, up to 1200 Degree C, 96 x 96 mm sq, with 1NO + 1NC, Single Set Point, for K, J, PT-100 (User Programmable)	1935	84779000
METCAT 72	Digital Temperature Controller, 4 Digits Display, up to 1200 Degree C, 72 x 72 mm sq, with 1NO + 1NC, Single Set Point, for K, J, PT-100 (User Programmable)	1935	84779000

ITEM	DETAILS	NEW LIST PRICE	HSN
Digital Temperature & Humidity Meter			
HT-305	3-1/2 Digits Backlit LCD Dual Display, Measures Temperature in Celsius and Fahrenheit scales in the range of -10 to 60 Degree C with resolution of 0.1 and accuracy of 1.0 Degree C, Relative Humidity from 0 to 100% RH with resolution of 0.1%RH and 5%RH accuracy, It has Data Hold, MAX/MIN Record Function, Auto Power Off	2150	90258090
HT-305A	Backlit LCD Dual Display, with split type Sensor for temperature and Humidity, Data Hold, MAX / MIN Record, Auto Power Off, Measure Temperature from -10 to 60 Degree C, and Humidity Up to 100% RH	2688	90308990
HT-3004CT	Digital Thermo-Hygro Meter with in-built infra red thermometer. Has Backlit LCD Display	9353	90308990
HT-3005	Digital Thermo-Hygro Meter with K-type thermometer. Has Backlit LCD Display	4515	90258090
HT-3006	Digital Thermo-Hygro Meter with facility to measure wet bulb and dew point temperature	6450	90258090
HT-12	Digital Thermo-Hygro Meter with Jumbo Display, to measure Indoor and Outdoor Temperature measurement, with Humidity. Selectable scales, Alarm Clock and Comfort Level Indicator, Temperature range -10 to 50 Degree C and humidity from 20 to 95%	1398	90258090
HT-13	Digital Thermo-Hygro Meter with Jumbo Display, to measure Temperature measurement, with Humidity. Selectable scales, Alarm Clock and Comfort Level Indicator, Temperature range -10 to 50 Degree C and humidity from 20 to 95%	1290	90258090
HTC-01	Jumbo LCD Display, wall hanging, with time and alarm facility, -50 to 70 Degree C, 20% to 99%RH	699	90258090
TH-04	LCD Display, wall hanging, with time and alarm facility, calander, climatic condition display, 0 to 50 Degree C, 10% to 90%RH	1290	90308990
Digital Temperature Indicator			
DTI-101 48	Digital Temperature Indicator 96 x 48 mm sq, for K, J, R, S, PT-100 (Any One)	1451	90308990
DTI-101 96	Digital Temperature Indicator 96 x 96 mm sq, for K, J, R, S, PT-100 (Any One)	1451	90308990
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size or 96 x 48 mm sq size			
Digital Thermometer			
DTM-900	3-1/2 Digits, Measures from -50 to 1300°C / -50 to 1999°F, Contact type, to be used with K type thermocouple , with backlit display and kelvin scale	3655	90251990
DTM-901 NEW!!	3-1/2 Digits, Dual Channel Input, Measures from -50 to 1300°C / -50 to 1999°F, Contact type, to be used with K type thermocouple. with backlit display and kelvin scale	4193	90251990

ITEM	DETAILS	NEW LIST PRICE	HSN
DTM-903	Wide Temperature Range, High Accuracy, Battery Operated, Selectable Thermocouple between K / J type, MAX / MIN / AVG Recording, Data Hold to Freeze Displayed Data, Backlit Display Measures Temperature from -50 to 1300°C using K-type Sensor and from -50 to 1200°C using J-type Sensor Accuracy: ±0.5%	1720	90251990
DTM-100	3-1/2 Digits, Hand Held 9V battery operated, for PT-100 Sensor up to 600 Degree C	2016	90251990
DTM-902	Pen Type, Auto Power Off, -40 to 250°C / -40 to 482°F	806	90251990
DTM-925	Thermometer with eight types of thermocouples and PT-100 (385). Input is selectable through software, no need to change any component or add on card. The instrument is capable of measuring from -200°C to 1800°C depending on the sensor.	3763	90251990
ST-9283B	Hand Held, With High Temperature Alarm Facility, Auto Power Off, Data Hold, -50 to 300°C / -58 to 572°F	806	90251910
Digital Three Phase Ammeter			
CE-03A	Microprocessor Based, 96 x 96 mm sq, with in built three phase selector switch, displays Current in three phases, CT Ratio programmable. Programmable up to 3000A AC	2258	90303310
Digital Three Phase Voltmeter			
CE-03V	Microprocessor Based, 96 x 96 mm sq, with in built three phase selector switch, displays Line to Line and Line to Neutral Voltage. Direct Operated and PT Ratio programmable	2258	90303310
Digital Time Interval Meter			
NTT-4D	4 Digits Digital Time Interval Meter for measuring in the range of 999.9mS, 9.999S, 99.99S	17200	90318000
3CH-NTT-4D	4 Digits 3 Channel Digital Time Interval Meter for measuring in the range of 99.99mS, 999.9mS, 9.999S	74175	90318000
Digital Voltage Controller			
CE-0102VC 1SP	Digital Voltmeter with Single Set Point to control the Voltage below a given set point. Size - 96 x 96 mm sq. With 1NO + 1NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	3601	90303310
CE-0102VC 2SP	Digital Voltmeter with Two Set Point to control the Voltage between a given set points. Size - 96 x 96 mm sq. With 2NO + 2NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	4300	90303310
Digital Voltmeter			
CE-0102V	3-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1371	90303310

ITEM	DETAILS	NEW LIST PRICE	HSN
CE-0102V 96	3-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1371	90303310
CE-0102V	3-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1371	90303310
CE-0102V 96	3-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1371	90303310
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size			
CE-0102V 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2688	90303310
CE-0102V 96 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2688	90303310
CE-0102V 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2688	90303310
CE-0102V 96 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2688	90303310
Digital Wattmeter			
CE-0102W	Microprocessor Based, 96 x 48 mm sq, For Single Phase, Red LED Display	3655	90309090
CE-0102W 96 x 96	Microprocessor Based, 96 x 96 mm sq, For Single Phase, Red LED Display	3655	90309090
CE-0303W	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	4515	90309090
CE-0304W	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	4515	90309090
Discharge Rod (Single Phase) NEW!!			
DR 11-33kV NEW!!		4300	85479090
DR 33-66kV NEW!!		6450	85479090
DR 66-132kV NEW!!		10428	85479090
DR 132-220kV NEW!!		12900	85479090
DR 400kV NEW!!		16125	85479090
Discharge Rod (Three Phase) NEW!!			
DR 11-33kV NEW!!		20000	85479090
DR 33-66kV NEW!!			85479090

ITEM	DETAILS	NEW LIST PRICE	HSN
DR 66-132kV NEW!!			85479090
DR 132-220kV NEW!!			85479090
ELCB Tester			
1810D	Digital ELCB Tester with Current Rating up to 500mA, Trip Test, Fault Trip Time, Self Powered	6558	90308990
1811	Digital ELCB Tester with Current rating up to 500mA, Auto Ramp, Phase Switch, Reads Disconnection Time, Self-Powered	12900	90308990
1813	Digital ELCB Tester with Current rating up to 1A, Trip Test, Fault Trip Time, 230V AC Operated	11825	90308990
Electrical Tester			
AC-1	Audio and Visual output on detecting voltage from 90V - 1000A AC with built in flash light	403	90308990
AC-4	Non Contact Voltage Detector by flashing light for 100 - 600V, with built-in flash light	753	90308990
AC-5	Non Contact Voltage Detector by flashing light and buzzer sound for 100 - 600V, with built-in flash light	860	90308990
AC-6	Socket Polarity & Earth Leakage Tester. Checks for No Earth / Line Neutral Reversal / No Neutral / Line Earth Reversal / No Line states.	1505	90308990
AC-7	Phase Rotation Indicator, No Batter Required, Nomical Voltage 40 - 690V, 15 to 400Hz.	4193	90308990
AC-8	Self Operated, phase rotation indicator along with voltage and frequency display	2688	90308990
PRO ELEC+ NEW!!	Two-pole Voltage Tester with LCD display and LED signalling. Features Audible Continuity and RCD tripping test. Built-in LED flashlight, IP67 dust and splash proof, over-voltage protection with CAT III 1000V / CAT IV 600V.	6343	90303900
EMF Tester			
EMF-823	Measures from 0.1 to 200mG / 1 to 2000mG & 0.01 to 20uT / 0.1 to 200uT, Frequency Response 30Hz to 400Hz, Max Hold and Data Hold	8063	90308990
Event Counter			
CTR-49	6 Digits Red LED Display, Event Counter, 1 to 999999 Counts, 96 x 48 mm sq	2419	90292090
N.B. - Please ask for the prices in case if you require this in 96 x 96 mm sq size			
Forehead Infra Red Thermometer			
FIR-2	Non Contact Infra Red Thermometer for body temperature	3010	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
PIR-I	"A non-touch Infrared Thermometer to measure human body temperature via the hand wrist & palm. The PIR-1 is a non-touch Infrared Thermometer to measure human body temperature via the hand wrist, palm or even forehead. You just need to put your hand or your wrist over the sensor at a 2-8 cms distance and you will get the body temperature instantly. The PIR-1 uses 2 sensors – a distance sensor and a temperature sensor, to get accurate temperature measurements quickly and safely. When used at any Entry/Exits, people can walk through the check-points quickly without any crowding or queuing. The PIR-1 is mountable on almost any surface and comes with a multi-angle adjustment. It is the ideal solution for enabling safe access control so as to prevent spread of COVID-19."	37625	90230090
Frequency Transducer			
CE-0102FT	Frequency Transducer with single Output	6773	85045090
N.B. - For Dual Output Rs.500/- shall be charged extra			
Function Generator			
FG-1000	1MHz Function Generator with TTL / CMOS output	10105	90308990
FG-2000	2MHz Function Generator with TTL / CMOS output	10965	90308990
FG-5000	5MHz Function Generator with TTL / CMOS output	13975	90308990
FG-10000	10MHz Function Generator with TTL / CMOS output	23650	90308990
FG-20000	20MHz Function Generator	26875	90308990
Gauss Meter			
GM-197	Gauss Meter for both static and electromagnets, DC and AC (40-500Hz), determines N/S polarity of Static Magnets, measures intensity of magnetic Field in Gauss and Tesla both, measures up to 0~3000mT(milli Tesla)/0~30000G(Gauss), Relative / Peak Hold / Real time Zero function, Auto Range, DATA HOLD, MAX/MIN hold, GO and NO-GO alarm and alarm value set up the function, Production testing, Manual 200 capacity records, Auto 6000 capacity data logging, interval is set up by PC, USB interface to send data + PC connection application software, real time function.	27413	90303100
Gas Detectors			
GD-09-02 NEW!!	Portable and world's smallest Oxygen Gas Detector with audio & visual alarms. Detects Oxygen in the air.	15319	90271000
GD-09-1M NEW!!	Combustible Gas Detector and Alarm with high sensitivity, compact design and reliable performance for detecting combustible gas (like LPG) leaks. Features audible alarm with red flashing light, when gas concentrations reach or exceed the alarm set point.	1950	90271000

ITEM	DETAILS	NEW LIST PRICE	HSN
GD-09-X NEW!!	Portable single gas detector, which can be customised for more than 30 types of gases, as per the requirement of range and alarms.	On Request	90271000
GD-09-4M NEW!!	4-in-1 Multi Gas Detector for O2, CO, H2S and Explosive/Combustible Gas. Features IP65 protection and audio/visual alarms.	19350	90271000
GD-09-6M NEW!!	Six-in-one Pumping Multi Gas detector for 6 gases: Oxygen (O2), Carbon Di Oxide (CO2), Carbon Monoxide (CO), Hydrogen Sulfide (H2S), Nitrogen Di Oxide (NO2) and Explosive Gases (EX). Also features PM2.5/PM10 detection module, 4G module and GPS.	148000	90271000
High Voltage Detector			
277HP	Non Contact Type High Voltage Detector for presence of Voltage from 50V to 132kV with Buzzer and Light Indication	13438	90308990
275HP	Non Contact type, Light and Buzzer Indication, Detects Presence of High Voltage in AC Lines, 240V, 2KV, 6KV, 11KV, 22KV, 33KV, 132KV and 175KV Lines AC.	17200	90308990
275HP1 NEW!!	High Voltage Detectors (Electroscope) for electrical testing on high voltage transmission lines upto 275kV, with audible buzzer and visual light alarms.	7955	90308990
275HP2 NEW!!	High Voltage Detectors (Electroscope) for electrical testing on high voltage transmission lines upto 500kV, with audible buzzer and visual light alarms.	7955	90308990
276HD	Contact type, light and buzzer indication, detects presence of High Voltage in AC Lines, 354 to 1005mm length, detects 3kV to 24kV AC and 80 to 600V AC	17953	90308990
276SHD	Contact type, light and buzzer indication, detects presence of High Voltage in AC Lines, 230 to 880mm length, detects 3kV to 24kV AC and 80 to 600V AC	17953	90308990
290HD	7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout	22575	90292090
WT500 NEW!!	A handy, wearable (wrist-type), close-range, non-contact, high voltage detector, featuring sound & light alarms when an operator wearing it gets close to a high voltage charged body upto 500kV.	4112	90303390
AT500 NEW!!	A handy, wearable (arm-type), close-range non-contact high voltage detector, featuring sound & light alarms when an operator wearing it gets close to a high voltage charged body upto 500kV.	4193	90303390
Hot Line Indicator			
6.6kV	Hot Line Indicator, Neon Glow type for 6.6kV	11503	90308990
11kV	Hot Line Indicator, Neon Glow type for 11kV	17200	90308990
33kV	Hot Line Indicator, Neon Glow type for 33kV	29025	90308990
# Hot Line Indicator with Neon glow and audible buzzer both are also available. Please refer back for their price.			

ITEM	DETAILS	NEW LIST PRICE	HSN
Hour Meter			
NE 045/7S DC	7 Digits, measures up to 99999.99 hours, 10 - 48V DC operated, 46 x 46 mm sq size panel cutout	1183	90292090
NE 045/7	7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout	645	90292090
HM-01 NEW!!	7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout	538	
Infrared Temperature Calibrator			
BB-500	Black Body Source for Calibrating Infrared Thermometer from 50 to 500 Degree C	76325	90308990
Insulation Tester			
IT-500	Test Voltage: 500V, Insulation Resistance Range: 0 - 1000M.Ohms, with AC Voltage Test Facility	2043	90308990
IT-1000	Test Voltage: 1000V, Insulation Resistance Range: 0 - 2000M.Ohms, with AC Voltage Test Facility	2150	90308990
Integrated Meter			
CE-0303IM	Three Phase Three Wire Two Element loads for energy and power measurement, measure each phase I, V, Hz, PF, KW, KVA, KVAh, KVAh, KVAh and MDI	8063	90308990
CE-0304IM	Three Phase Four Wire Three Element loads for energy and power measurement, measure each phase I, V, Hz, PF, KW, KVA, KVAh, KVAh, KVAh and MDI	8063	90308990
Kelvin Double Bridge			
KDBR	Oxford Brand Kelvin Double bridge, with spot reflecting galvanometer, High Current DC power supply and wooden stand for specimen	77400	90230090
Laser Distance Meter			
LDM-40H	Laser Distance Meter to measure up to 40m, with Area / Volume Calculations	4623	90308990
LDM-100H	Laser Distance Meter to measure up to 100m, with Area / Volume Calculations	6450	90303100
Metal Detector			
MD-300	High Sensitive Metal Detector with a circular sensor, the detector vibrates and provides audible alarm on detecting metal	1935	90308990
SUPER-V	High Sensitive Metal Detector with a straight sensor, the detector vibrates, provides visual and audible warning on detecting metal	3225	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
Million MegOhms Meter			
MMM-1	Analogue Million MegOhms Meter for test voltage of 100, 200, 300, 400 and 500V, measures up to 10 Million MegOhms	18275	90308990
Mini Environmental Meters			
ET-99A	Digital Anemometer	1935	90303100
ET-99L	Digital Lux Meter	1720	90303100
ET-99SL	Digital Sound Level Meter	1935	90303390
ET-99TH	Digital Temperature & Humidity Meter	1935	90258090
ET-99M	Digital Moisture Meter	1935	90308990
ET-99IR	Digital Infrared Thermometer	2096	90308990
ET-99P	Digital Manometer	4623	90268090
ET-99HT	Digital HCHO and TVOC Meter	6450	90271000
Mixed Signal Oscilloscope			
MSO-5062D	60MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate	75680	90302000
MSO-5102D	100MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate	82184	90302000
MSO-5202D	200MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate	94600	90302000
Motor Checker			
MC-22	Electric Motor Checker with analogue display	27950	90308990
MC-22D	Digital Motor Checker with insulation resistance test of 1000V	34400	90308990
MC-38D	Digital Motor Checker with insulation resistance test of 500 and 1000V	18813	90308990
Multifunction Environment Meter			
ET-2	Four-in-One Digital dB, Lux, temperature and Humidity meter with RS-232C PC Interface cable and software	7740	90278090
ET-3	Six-in-One Digital dB, Lux, Humidity, temperature, Multimeter and AC Voltage Detector	8278	90278090
Multi-point Temperature Indicator			
DTI-101M 6 CH	6 Channel Digital Multi-Point Temperature Indicate for K, J,R, S, PT-100 (Any One) type of sensor	4031	90308990
DTI-101M 12 CH	12 Channel Digital Multi-Point Temperature Indicate for K, J,R, S, PT-100 (Any One) type of sensor	4838	90308990
Non Contact Temperature Controller			
IT-91	Infrared Temperature controller for -50 to 950 Degree C, 50:1 D:S Ratio, adjustable emissivity, relay output, controller cut out 72 x 72 mm sq	20425	84779000
Oil Test Set			
50-OTS	50kV Manually operated Oil Test Set	33325	84212900
50-MOTS	50kV Motor operated Oil Test Set	42463	84212900

ITEM	DETAILS	NEW LIST PRICE	HSN
60-OTS	60kV Manually operated Oil Test Set	37088	84212900
60-MOTS	60kV Motor operated Oil Test Set	46225	84212900
70-OTS	70kV Manually operated Oil Test Set	44075	84212900
70-MOTS	70kV Motor operated Oil Test Set	52675	84212900
75-OTS	75kV Manually operated Oil Test Set	47300	84212900
75-MOTS	75kV Motor operated Oil Test Set	56438	84212900
80-OTS	80kV Manually operated Oil Test Set	52998	84212900
80-MOTS	80kV Motor operated Oil Test Set	62350	84212900
90-OTS	90kV Manually operated Oil Test Set	58050	84212900
90-MOTS	90kV Motor operated Oil Test Set	66650	84212900
100-OTS	100kV Manually operated Oil Test Set	62350	84212900
100-MOTS	100kV Motor operated Oil Test Set	74175	84212900
120-OTS	120kV Manually operated Oil Test Set	84925	84212900
120-MOTS	120kV Motor operated Oil Test Set	106425	84212900
Digital Meters for above, extra to be paid			
Oscilloscopes			
OS-5010A	10MHz Single Channel, Cathode Ray Oscilloscope	19673	90302000
OS-5020	20MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with 1:1 and 10:1 probes	32143	90302000
OS-5020C	20MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with component test facility, comes complete with 1:1 and 10:1 probes	33863	90302000
OS-5030	30MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with 1:1 and 10:1 probes	34400	90302000
OS-5030C	30MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with component test facility, comes complete with 1:1 and 10:1 probes	36765	90302000
OS-5060	60MHz Dual Channel Four Trace Cathode Ray Oscilloscope with 1:1 and 10:1 Probes	74175	90302000
OS-5100	100MHz Dual Channel Four Trace Cathode Ray Oscilloscope with 1:1 and 10:1 Probes	88688	90302000
Oscillometer			
700S		68585	90302000
760	20MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software	114703	90302000
7100	100MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software, sampling rate 1GSa/Sec	303903	90302000
7200	200MHz Digital Storage Oscilloscope, color display, with 2 Channel Digital Multimeter with PC Interface cable and software, sampling rate 1GSa/Sec	390225	90302000
Power Meter			
PM-10	Bench-top high-precision Power Meter up to 900W	17200	90308990
PM-10B	Bench-top high-precision Power Meter up to 3000W	55900	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
Power Quality Analyser			
PRO 531 NEW!!	A comprehensive test instrument carefully developed and specially designed for field test of three phases, multi-functional and intelligent, concise man-machine operation. Clamps at extra cost.	188125	90308990
Set of 4 Clamps 10A Max NEW!!	Optional set of Clamps for the PRO 531 for 10A	21500	90308990
Set of 4 Clamps 100A Max NEW!!	Optional set of Clamps for the PRO 531 for 100A	24725	90308990
Set of 4 Clamps 1000A Max NEW!!	Optional set of Clamps for the PRO 531 for 1000A	44075	90308990
Set of 4 Clamps 6000A Max NEW!!	Optional set of Clamps for the PRO 531 for 6000A	76325	90308990
PC Based Oscilloscope			
DSO-2090	Dual Channel 40MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software	29563	90302000
DSO-2150	Dual Channel 60MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software	35475	90302000
DSO-2250	Dual Channel 100MHz PC Based Digital Storage Oscilloscope with USB PC interface cable and software	46118	90302000
PC Based Function Generator			
DDS-3005	5MHz PC Based Function generator with AM FM Modulation and TTL output along with sine, square, tri-angle, saw-tooth etc. with USB PC Interface cable and software	54395	90308990
PC Based Logic Analyzer			
LA-5034	34 Channel PC Based Logic Analyzer, with precision gripper, USB PC Interface cable and software	41388	90308990
pH Meter			
PH-600	Quality, portable pH Meter with glass bulb electrode for measuring 0.00-14.00pH	591	90308990
TDS Meter			
TDS-3	Handy Digital TDS Meter for measuring 0-9990 PPM TDS and 0° to 50°C temperature, using a titanium alloy electrode.	500	90308990
Power Guard			
PG-01	Multifunction Power Meter, works on 6A, 230V, indicates, voltage, current, power factor, Power, kWh, Calculates CO2 emission, Calculates total time the equipment is under test and calculates the cost of electricity consumed accordingly. During load shedding the instrument memorizes the readings, ideal for analyzing power consumed for different kinds of loads	2096	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
Primary Current Injection Test Set			
PCIT	On Request		90303390
Programmable DC Power Supply			
PRPS-3005 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 30V / 0– 5A DC	12040	90308990
PRPS-3003-2 NEW!!	Programmable DC Regulated Power Supply with Dual Output and Backlit LCD Display of Variable 0 – 30V / 0– 3A DC	33863	90308990
PRPS-3003-3 NEW!!	Programmable DC Regulated Power Supply with Triple Output and Backlit LCD Display of Variable 0 – 30V / 0– 3A DC	38270	90308990
PRPS-3005-2 NEW!!	Programmable DC Regulated Power Supply with Dual Output and Backlit LCD Display of Variable 0 – 30V / 0– 5A DC	38270	90308990
PRPS-3005-3 NEW!!	Programmable DC Regulated Power Supply with Triple Output and Backlit LCD Display of Variable 0 – 30V / 0– 5A DC	38270	90308990
PRPS-3005-4 NEW!!	Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 30V / 0– 5A DC	161411	90308990
PRPS-3010-4 NEW!!	Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 30V / 0– 10A DC	On Request	90308990
PRPS-3020 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 30V / 0– 20A DC	70950	90308990
PRPS-3030 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 30V / 0– 30A DC	84925	90308990
PRPS-6003-4 NEW!!	Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 60V / 0– 3A DC	On Request	90308990
PRPS-6005-4 NEW!!	Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 60V / 0– 5A DC	On Request	90308990
PRPS-6010 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 60V / 0– 10A DC	70950	90308990
Refrigerant Gas Leakage Detector			
RLD-01	16" Gooseneck sensor, detects all CFC Refrigerants such as R-22, R-124, R-11 and R-12 etc.	9675	90308990
Relay Test Set			
RNT-5	Relay Test Set, with current output upto 200A in various ranges	46225	90318000
RNT-5A	Relay Test Set with 200A in various ranges, Burden 1KVA, with AC/DC Voltage output	66650	90318000

ITEM	DETAILS	NEW LIST PRICE	HSN
RNT-33	Relay Test Set suitable for testing distance relay, 3 phase current / voltage output and Fixed DC Voltage output	268750	90318000
ZNT-34	Relay Test Set suitable for testing distance, over voltage relays etc., Variable three phase Voltage / Current and variable DC Voltage outputs	290250	90318000
Rotating Machine Tester			
RMT-10 NEW!!	One Single Meter that can test rotating machine, from insulation resistance to low resistance milli Ohms combined with a built-in T-RMS multimeters, Data logger, with Low pass Filter, Blue tooth Interface, Can measure AC/DC Voltage 1000V, DC/AC Current 10A, Resistance, Capacitance 5mF, Frequency 50Mhz, Temperature up to 1200 Degree C, Insulation Resistance can be measured up to 5000M.Ohms at test voltag of 50V / 100V / 250V / 500V / 1000V, with polarisation index and DAR, Low resistance from 1 m.Ohms to 2000 Ohms,	32465	90303900
RMTi-1 NEW!!	Rotating Machine Tester with Thermal Imager	80625	90303900
RPM METER			
CTR-49	6 Digits Red LED Display, Event Counter, 1 to 999999 Counts, 96 x 48 mm sq	2419	90292090
Short Turn Indicator			
EFD	Electric Fault Detector, to be used with more than two identical windings like general motors and transformers	22468	90308990
Little Giant	9V Battery operated, to be used in single coils, simple insertion of coil on mandrill.	17738	90308990
Socket Polarity Tester			
ST-09	Socket Polarity Tester to be used for currents up to 6A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral.	774	90308990
ST-09A	Socket Polarity Tester to be used for currents up to 16A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral.	817	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
ST-09B	Socket Polarity Tester to be used for currents up to 6A and input voltage up to 250V AC, when inserted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral. This can also be used for leakage test of up to 30mA	925	90308990
Sound Level Calibrator			
SC-05	Sound Level Calibrator provides signals of 94dB and 114dB	10535	90308990
Solar Power Meter			
207	Solar Power Meter, to measure the amount of sunlight falling on the solar panel or any surface exposed to sunlight	6343	90308990
Spectrum Analyzer			
AT-5010	1050MHz Spectrum Analyzer	105243	90308990
AT-5011	1050MHz Spectrum Analyzer With Marker Generator	164368	90308990
Static Charge Meter			
SC-291 NEW!!	Measuring range: 0~ +/- 20.000KV, Measuring distance: 2.54cm(1 inch), Warning alarm setting, DATA / PEAK hold. Backlight function, Auto power off with disable function, Zero function and low battery indicate, Manual data memory storing 99 data sets.	29563	90303100
Tachometer (Non Contact type) Calibrator			
CE-0102TMC	Calibrator for Non Contact Tachometer for up to 199,999RPM	13975	90308990
Thermal Imagers			
PRO TI-10P NEW!!	Handheld, pocket-sized Thermal Imager for upto 500°C with storage for images and videos, Wi-Fi and USB interfaces, 8 Colour Palettes and Digital Zoom.	54288	90251990
PRO TI-25 NEW!!	Handheld Thermal Imager for upto 550°C with 256x192 pixels resolution. Images & video recording along with touchscreen TFT LCD display, Wi-Fi, USB and free App.	84925	90251990
PRO TI-50 NEW!!	Handheld Thermal Imager for upto 650°C with 384x288 pixels resolution. Images & video recording along with touchscreen TFT LCD display, Auto-Fusion, Wi-Fi, USB and free App.	196725	90251990
Transistor Tester			
TT-01	Transistor Tester for Testing and Checking Bias Current and other parameters of Transistors	4999	90312000

ITEM	DETAILS	NEW LIST PRICE	HSN
Tap Position Indicator			
CE-0102V	Digital type, Panel Mounting, Tap Position indicator, 96mm sq or 96x48 mm sq	2580	85049010
Time Totalizer			
TT-300	6 Digits LED Display, 96 x 48 mm sq, Auto range from 9999.99 to 999999Hrs.	2419	90292090
TT-302	6 Digits LED Display, 96 x 96 mm sq, Auto range from 9999.99 to 999999Hrs.	2688	90292090
Transformer Turns Ratio Set			
TTRS-100	Transformer Turns Ratio Set to measure ratio in the range of 0.800 to 2021 & for Phase Deviation Measurement	129000	90303900
Two Color Infrared Thermometer			
ST-300A	Temperature range 600°C~1400°C, D:S 150:1, Output 4~20mA, RS485, Relay – 1A30VDC / 0.5A125VAC, Impedance: ≤50mΩ, IP-65 Casing	367650	90308990
ST-300B	Temperature range 700°C~1800°C, D:S 300:1, Output 4~20mA, RS485, Relay – 1A30VDC / 0.5A125VAC, Impedance: ≤50mΩ, IP-65 Casing	367650	90308990
ST-300C	Temperature range 1000°C~3000°C, D:S 300:1, Output 4~20mA, RS485, Relay – 1A30VDC / 0.5A125VAC, Impedance: ≤50mΩ, IP-65 Casing	397750	90308990
Ultrasonic Thickness Gauge			
UTG-01	Versatile Ultrasonic Thickness Gauge to measure thickness of high density material up to 200mm	12900	90292090
Vibration Meter			
VIB-30+	Digital Vibraton Meter, measures RMS velocity in the range of 0.1 to 199.9 mm/sec T-RMS & Peak	31175	90301000
AVD-80	Digital Vibration Meter, measures velocity, acceleration and displacement	39775	90308990
BCA-111	Bearing Condtion Analyzer, measures bearing test, vibration and has in-built tachometer.	145125	90308990
908	Measures velocity, acceleration and displacement along with the temperature, comes complete with the magnetic Base	18813	90308990
908T NEW!!		91053	90308990
PVB-820	Pen Type Vibration Meter, it can measure accelleration, velocity and displacement	18275	90308990
VT-141 NEW!!	Dual Channel Vibration meter, Wide frequency range of 10Hz to 5KHz, Acceleration, velocity and displacement, Vibration sensor with magnetic adapter on1.2M (47.2) cable, Frequency Lo range :10Hz~1KHz meets ISO 2954 measurement, Hi range : 10Hz~5KHz, MAX record, Auto power off with disable function	87075	90308990

ITEM	DETAILS	NEW LIST PRICE	HSN
VT-141D NEW!!	Dual Channel Vibration meter, Wide frequency range of 10Hz to 5KHz, Acceleration, velocity and displacement, Vibration sensor with magnetic adapter on 1.2M (47.2) cable, Frequency Lo range : 10Hz~1KHz meets ISO 2954 measurement, Hi range : 10Hz~5KHz, MIN/MAX record and recall, Data logger with 9999 records capacity, USB interface, Auto power off with disable function	94600	90308990
Voltage Transducer			
CE-0102VT	Voltage Transducer with single Output	3655	85045090
Video IR Thermometer			
VIT-20	Dual Laser Pointer, Color Display, Video and Still picture recording, In-built Contact Thermometer, uSD Card & PC interface, -50 to 1850°C, Adjustable Emissivity, D:S 50:1	59125	90251990
Weather Station			
WH-1081PC	Weather station, for prediction of weather and recording of temperature, humidity, wind chill, dew point, rainfall, wind speed, air pressure and storm warning	17738	90308990
WP-1050			
Wet Bulb Globe Temperature Meter			
WBGT-188 NEW!!	Quick-response capacitance sensor, accurate measurement for wet bulb globe temperature(WBGT), black globe temperature(TG), humidity(%RH), air temperature(TA), wet bulb(WET) and dew point(DEW). Max/Min and data hold, Low battery indication, LCD display with LED backlight, Viewing data records, Switch the temperature unit to °C or °F, Brass black ball in 50mm diameter, WBGT alarm setting, Auto power off with disable function	17738	90318000
WBGT-188D NEW!!	Quick-response capacitance sensor, accurate measurement for wet bulb globe temperature(WBGT), black globe temperature(TG), humidity(%RH), air temperature(TA), wet bulb(WET) and dew point(DEW). Max/Min and data hold, Low battery indication, LCD display with LED backlight, Viewing data records, Switch the temperature unit to °C or °F, Brass black ball in 50mm diameter, WBGT alarm setting, Auto power off with disable function, Data logging capacity: 12000 records, USB PC serial interface, Sampling interval: Max 24 hours; Min 1 Second	24725	90318000
Wheatstone Bridge			
WSB	OXFORD Brand Wheatstone Bridge	16663	90230090

ITEM	DETAILS	NEW LIST PRICE	HSN
TERMS & CONDITIONS			
VALIDITY:	PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE		
PRICES:	NETT, EX GODOWN KOLKATA		
PACKING:	PRICES INCLUSIVE OF PACKING CHARGES		
FREIGHT:	PRICES EXCLUSIVE OF FREIGHT CHARGES. IN CASE IF GOODS ARE REQUIRED BY ANY OTHER COURIER, OTHER THAN OUR NOMINATED COURIER ANY BY AIR, THEN THE FREIGHT SHALL BE CHARGED EXTRA AT ACTUALS		
DELIVERY:	READY STOCK SUBJECT TO PRIOR SALES, FOR HIGH VOLTAGE EQUIPMENTS 8-12 WEEKS DELIVERIES WILL BE MADE ONLY AFTER THE PAYMENT IS CREDITED TO OUR ACCOUNT		
INSURANCE:	TO BE COVERED BY THE BUYER THE GOODS WOULD BE PACKED SECURELY WITH OUR BEST INTENT TO PROTECT IT AGAINST ANY KIND OF TRANSIT DAMAGE. HOWEVER, IN CASE IF THE GOODS GET DAMAGED IN TRANSIT, THE BUYER WILL HAVE TO COVER ITS RISK		
PAYMENT:	100% AGAINST PROFORMA INVOICE / DOD / THROUGH BANK. 'ALTERNATIVELY' IF IT'S A TAILOR-MADE PRODUCT, 25% ADVANCE WITH THE ORDER BALANCE AGAINST PROFORMA INVOICE / DOD / THROUGH BANK		
SHIPMENT:	SHALL TAKE PLACE WITHIN 48 HOURS OF RECEIPT OF PAYMENT		
GOODS & SERVICE TAXES:	GST SHALL BE CHARGED EXTRA @18%. GST IS ALSO APPLICABLE ON FREIGHT CHARGES		
ORDERING VALUE:	<u>FOR ORDER VALUE LESS THAN RS.3000/- (RUPEES THREE THOUSAND) A CHARGE RS. TWO HUNDRED AS HANDLING CHARGES WILL BE LEVIED</u>		
DISCLAIMER:	WE TRY OUR BEST TO USE THE BEST OF COURIERS POSSIBLE FOR EARLIEST DELIVERY TIME BUT HAVE NO CONTROL OVER THE DELIVERIES BY THE COURIER. YOU MAY SUGGEST THE COURIER OF YOUR CHOICE AND WE SHALL SHIP THE GOODS THROUGH THEM, IF POSSIBLE. HOWEVER IN EITHER CASE, WE WILL NOT BE HELD RESPONSIBLE, UNDER ANY CIRCUMSTANCES, IF THE COURIER DELAYS THE DELIVERY FOR ANY REASON WHATSOEVER.		
JURISDICTION:	SUBJECT TO KOLKATA JURISDICTION ONLY		
THIS SUPERCEDES ALL PREVIOUS PRICE LISTS			