

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
ACIDITY TESTING KIT				
Acidity Testing Kit				
ATK	Testing Kit used to measure the Acidic content of Transformer Oil	2100	90314900	2835
ACOUSTIC IMAGERS				
Acoustic Imager				
AI-09	Industrial Acoustic Imager for gas leakage, partial discharge and other accidents with 128 MEMS microphones, multi-gas detection, IP56 and free software with reports as per ISO-50001 and data analysis.	On Request	90275090	
AI-09EX	Explosion-proof Industrial Acoustic Imager for gas leakage, partial discharge and other accidents with 128 MEMS microphones, multi-gas detection and free software with reports as per ISO-50001 and data analysis. With ATEX Certification. For use in hazardous environments.	On Request	90275090	
BATTERY TESTER				
Battery Impedance Tester				
TM-6002	Battery Impedance Tester to check Battery internal resistance, Voltage, Current and temperature, with 9999 memory, with PC Interface cable and software	87075	90303900	117551
CABLE FAULT LOCATOR				
Cable Fault Locator				
CFL-01	Digital Cable and Cable Fault Locator featuring a Transmitter and Receiver used to detect or trace conductors and find short faults in them.	19888	90303390	26848
CFL-02	Digital Cable Fault Locator for Power, Control and Telecom Cables buried underground, to pinpoint Open Circuit, Short Circuit and Medium/High Resistance Faults.	69875	90303390	94331
TDRL-912 NEW!!	Cable Fault Locator for Telecom Cables, measures exact fault location such as the broken line, cross faults, earthing, poor insulation and poor contact of the lead covered cables as well as plastic cables. With colour LCD display, Digital Gain Adjustment Control, Digital Waveform and rechargeable battery.	145000	90303390	195750
CABLE LOCATOR				
Cable Locator				
CL-2160A	Multi-frequency Cable Route Tracer & Locator serves as a Pipe and Cable Tracer for underground pipelines & cables without the need for excavations. For detecting position, direction and depth of underground water pipelines, metal pipelines and cables, the position and size of any damage points of the anticorrosion layer of steel pipelines, underground water pipelines, metal pipelines and cables.	On Request	90318000	
DC EARTH & GROUND FAULT LOCATOR				
DC Ground Fault Locator				
DCGFL-999 NEW!!	Earth and Ground Fault Locator for fast location of earth faults on the DC system, to avoid the damage in the event of a second fault. Directly locates earth faults, with no need to cut any cables. Current Waveform mode operation.	On Request	90303390	

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
CALIBRATORS				
Calibrator				
CAL-400-3	Hand Held, 3-1/2 Digits, Battery Operated, 0 - 19.99/24mA, -199.9mV to 199.9mV source and current & power measurement	5913	90318000	7982
CAL-400-4	Hand Held, 4-1/2 Digits, Battery Operated, 0 - 199.9mV / 0 - 19.999mA sourcing and measuring range	8600	90318000	11610
CAL-402-4	Bench type, 230V AC 50Hz Operated, 0 - 199.99mV / 1.9999 / 19.999V & 0 - 199.99u/1.999m / 19.999mA Sourcing & Measuring	9675	90318000	13061
CAL-408	Bench type RTD Calibrator, Outputs available at -200, -100, -50, -25, 0, 25, 50, 100, 150, 200, 300, 400, 500, 600 °C	8063	90318000	10885
CAL-500	Hand Held, 4 Digits Large LCD Display, Measures and Provides output for 20mV / 100mV / 15V DC, Current output up to 24mA, 24V Loop Power, and outputs for K, E, J, T, R, S, B and N types of thermocouples	15500	90318000	20925
CAL-600 NEW!!	Hand Held, 4 Digits Large LCD Display, Measures and Provides output for 20mV / 100mV / 15V DC, Current output up to 24mA, 24V Loop Power, Resistance output and measurement and outputs for K, E, J, T, R, S, B, N & PT-100 types of thermocouples	17000	90318000	22950
M-01S NEW!!	5 Digits LCD Display, 0.05% accuracy, provides output only for DC Voltage, Resistance, Thermocouples - R, S, K, E, J, T, N, B, A, C, D and Thermal Resistance RTD - PT-100, PT-200, PT-500, PT-1000, Cu-50. The output temperature value and the corresponding temperature signal are displayed on the same screen. With Auto power-off, backlight, flashlight.	29000	90318000	39150
M-2S NEW!!	5 Digits LCD Display, 0.05% accuracy, The measured / output temperature value and the corresponding temperature signal are displayed on the same screen. measures - DC voltage, resistance, thermocouple, thermal resistance RTD, on/off. 2W / 3W / 4W measurements are available for OHM and RTD. output - DC voltage, resistance, thermocouple, thermal resistance RTD, H/L settings are available for OHM excitation current. Thermocouples - R, S, K, E, J, T, N, B, A, C, D and Thermal Resistance - PT-100, PT-200, PT-500, PT-1000, Cu-50	29000	90318000	39150
03+	5 Digits 0.5% Accuracy, Sources and Measures Resistance, PT-100 Sensor and Cu-50 Sensors	26338	90318000	35556
05+ DISCONTINUED	5 Digits, 0.5% Accuracy, Sources DC Current, Analogue Transducer & Loop Power and Measures DC Voltage, DC Current and Loop Current	30100	90318000	40635
M-05S NEW!!	5 Digits, 0.05% Accuracy, Sources DC Current, Analogue Transducer & Loop Power and Measures DC Voltage, DC Current and Loop Power Supply. IP40 and 1m drop test.	30100	90318000	40635
11+	6 Digits, 0.2% Accuracy, Sources R, S, B, E, K, J, T, N types of thermocouples, PT-100, Cu-50, DC Voltage, DC Current, Resistance, Analogue Transducer, Frequency, Pulse Output and LOOP Power.	77400	90318000	104490
14+	6 Digits, 0.2% Accuracy, Sources and Measures DC Voltage, PT-100, Cu-50 Sensors and R, S, B, E, K, J, T & N types of Thermocouples.	77400	90318000	104490
15+	6 Digits, 0.2% Accuracy, Sources and Measures DC Voltage, DC Current, Analogue Transducer and LOOP Power.	77400	90318000	104490
25 NEW!!	50,000 Counts, 0.2% Universal Calibrator for DC Voltage, Current, Resistance, Frequency, all thermocouples and thermo-resistance and for pressure	268750	90318000	362813
709H	mA Loop Calibrator with HART COMMUNICATOR, Accuracy 0.01%	102125	90318000	137869

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
Vibration Calibrator				
VIB-CAL-01	Vibration Calibrator. Combines signal generator, power amplifier, standard transducer and a shaker in one housing and features a small size, high accuracy and easy operation.	219300	90318000	296055
Earth Resistance Tester Calibrator				
CAL-ER NEW!!	Earth Resistance Tester Calibrator. Used for calibrating grounding resistance testers, equipotential testers and other instruments which require a standard resistor.	34400	90318000	46440
Sound Level Calibrator				
CEM SC-05	Sound Level Calibrator provides signals of 94dB and 114dB. Accurate and simple to use; Fits 1/2" diameter microphone.	10800	90309090	14580
Non-contact Tachometer Calibrator				
CE-0102TMC	Calibrator for Non Contact Tachometer for up to 199,999RPM	14000	90292090	18900
Infrared Thermometer Calibrator				
CEM BX-500	Black Body Source for Calibrating Infrared Thermometer from 50 to 500°C	78750	90318000	106313
Process Meter				
PM-29 NEW MODEL!!	4 & 5 digits Digital Multimeter with DC mV / Voltage / Frequency / Resistance / mA Calibrator and also provides output for all types of Thermocouples	45000	90308990	60750
PM-39	5 Digits, Digital Multimeter combined with source for DC voltage, resistance, frequency, all kind of thermocouples, thermal resistance, and DC current. supply power to 24V circuits and meanwhile measure current; with built-in 250 Ω HART loop resistance	51750	90308990	69863
Accessories for Calibrators				
709H-USB	USB communication interface cable and software for 709H	43000	90318000	58050
PM-S Series NEW!!	Pressure Calibration Modules for 15+	On Request	90318000	
CAPACITANCE METER				
Digital Capacitance Meter				
DCM-1502	3-1/2 Digits, LCD, Zero Adjustment, up to 20mF Capacitance Measurement	2849	90303100	3846
CLAMP METER				
Analogue Clamp Meter				
M-300	Clamp Jaw Dia 34mm, AC/DC Voltage, AC Current up to 300A, Resistance & Temperature. Pointer Lock Facility, with temperature probe	2835	90303100	3827
M-600	Clamp Jaw Dia 34mm, AC/DC Voltage, AC Current up to 600A, Resistance & Temperature. Pointer Lock	3120	90303100	4212
M-1000	Clamp Jaw Dia 48mm, AC Voltage up to 600V, DC Voltage up to 300V, AC Current in the range of 0-50/250/500/1000A AC, Resistance up to 2000K. Ohms, Temperature, Audible continuity Test	4840	90303100	6534
Digital AC Clamp Meter				

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
DT-225	3-3/4 Digits, Backlit LCD, Data Hold, Max Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 400A, Resistance, Temperature, Frequency, Diode and Continuity Test. 500V DC/AC Protection in all ranges.	3010	90303100	4064
DT-115	6000 Counts, Backlit LCD, With Flashlight, Autoranging, Auto Power Off, T-RMS, Non-contact voltage detection, Flashlight, Data Hold, 40 mm Jaw Size, AC/DC Voltage, AC Current up to 600A T-RMS, Capacitance, Frequency, Temperature, Resistance, Continuity & Diode test.	1950	90303100	2633
DT-115A	6000 Counts Backlit LCD Display, Built-in Flashlight to access dark Areas, Non Contact Voltage Detection, Simple to use, Just provide the input and the instrument, detects the signal and displays the parameter, No Selection required, Just provide Input, Automatic Selection of AC/DC Voltage, Resistance, Capacitance, Diode Test, T-RMS, 600A T-RMS Measurements	2400	90303100	3240
DT-369	3-4/5 Digits 6000 Counts, LCD, Data Hold, T-RMS, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Frequency and Temperature & Continuity Test	2475	90303100	3341
DT-1150	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A Clamp Meter with AC/DC Voltage	2025	90303100	2734
DT-1150A	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A Clamp Meter with AC/DC Voltage, Resistance, Capacitance, Temperature and Frequency	2450	90303100	3308
DT-1250	3-1/2 Digits, Backlit LCD, Data Hold, Max Hold, 30mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Diode and Continuity Test. 500V DC/AC Protection in all ranges.	3100	90303100	4185
DT-2250	3-3/4 Digits, Backlit LCD, Data Hold, 30mm Jaw size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Duty Cycle, Diode and Continuity Test Facility.	3655	90303100	4934
DT-2255	3-1/2 Digits, LCD, Data Hold, Auto-ranging, 57mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test.	3700	90303100	4995
DT-3150	3-3/4 Digits, Backlit LCD, Data Hold, 57mm Jaw Size, AC/DC Voltage, AC Current up to 1000A, Resistance, Capacitance, Frequency, Duty Cycle, Diode and Continuity Test Facility. 1000V DC/AC Protection in all ranges.	3850	90303100	5198
DT-7250	3-1/2 Digits, LCD, Data Hold, Auto-ranging, 57mm Jaw Size, AC/DC Voltage, AC Current up to 2000A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test.	5900	90303100	7965
PRO IRC-600 NEW!!	6000 counts, Data Hold, NCV, 34mm Jaw Size, AC/DC Voltage 1000V, T-RMS AC Current up to 1000A, VFD Voltage, Resistance, Capacitance, Frequency, Duty Cycle, Diode & Continuity Test, with Backlit LCD, Flashlight, built-in Infrared Thermometer for up to 350°C.	8280	90303100	11178
UNIKS C-126 NEW!!	6000 Counts, Backlit 2" LCD, LED Flashlight, Autoranging & Manual, Auto Power Off, T-RMS, Non-contact Voltage detection, Data Hold, AC/DC Voltage, AC Current up to 1000A, InRush Current, VFD Filter, LoZ, Capacitance, Frequency, Temperature, Resistance, Continuity & Diode test. CATIV 600V, CATIII 1000V. Made in Europe.	8200	90303100	11070
Digital AC/DC Clamp Meter				
DT-230 PHASED OUT!	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 400A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test. THIS MODEL HAS BEEN PHASED OUT. PLEASE CHECK OUT METRAVI DT-725 INSTEAD FOR SIMILAR AND BETTER SPECIFICATIONS.	5105	90303100	6892

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
DT-325	3-3/4 Digits 3999 Counts, Digital AC/DC Clamp Meter, Confirming to CAT-III 300V, Jaw Size 28 mm, Auto Power Off, Data Hold, AC/DC Voltage up to 600V, AC/DC Current up to 400A, Resistance, Frequency, Duty Cycle, Diode & Continuity Test Facility	3720	90303100	5021
DT-725	3-5/6-digit 5999 Count, Backlight LCD, T-RMS, Auto-Ranging, NCV, Flashlight, Relative Measurement, AC(750V)/DC(1000V) Voltage, 600A AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity. Square Wave Output, CAT-IV 600V	2990	90303100	4037
DT-425T	3-3/4 Digits 3999 Counts Backlit LCD, T-RMS AC/DC Clamp meter, Confirms to CAT-III 600V, Data Hold, MAX/MIN, Relative, In-Built Flash Light, Overload Protection, 30mm Clamp Jaw Dia, Auto Power Off, AC T-RMS / DC Current 600A, AC T-RMS / DC Voltage 600V, Resistance, Capacitance, Temperature, Frequency, Non Contact Voltage Detector, Diode and Cotinuity Test	5915	90303100	7985
DT-1350	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A AC/DC Clamp Meter with AC/DC Voltage, Resistance, Diode and Continuity Check	2950	90303100	3983
DT-1350A	3-1/2 Digits LCD, Peak Hold, Hard Carrying Case, 1000A AC/DC Clamp Meter with AC/DC Voltage, Resistance, Capacitance, Temperature and Frequency	3300	90303100	4455
DT-1350AT	3-5/6 digit, 6000 Counts, backlit LCD, Measure TRMS AC/DC Current & Voltage, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity. Protected in all ranges.	3440	90303100	4644
DT-3690	3-4/5 Digits 6000 Counts, LCD, Data Hold,T-RMS, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 1000A, Resistance,Capacitance, Frequency and Temperature & Continuity Test	3980	90303100	5373
DT-3250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC Voltage,1000A DC/AC Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency measurement from input terminals and also through clamp, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	7380	90303100	9963
DT-4250	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Duty Cycle, Diode & Continuity Test.	7420	90303100	10017
DT-3600	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage,1200A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	7600	90303100	10260
DT-5250	3-3/4 Digits, LCD, Data Hold, 30mm Jaw Size, T-RMS, AC/DC Voltage, AC/DC Current up to 1000A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test.	7740	90303100	10449
PRO 419	3-3/4 Digit Professional T-RMS AC/DC Clamp Meter, 4000 Count, 1000V AC T-RMS/DC, 1000A AC T-RMS/DC, Auto Power Off, Non Contact Voltage Detector, Flashlight, Data Hold, MAX-MIN Record, Relative Measurement, 100mF Capacitance, 100kHz Frequency, 40MOhms Resistance, 1000°C Temperature measurement using K type sensor, Continuity.	7205	90303100	9727
PRO Solar-2A	3-3/4 digits (4000 counts) backlit LCD, TRMS, PV Voltage upto 1500V DC, AC Voltage, AC/DC Current. Peak Current, Resistance, Capacitance, Frequency, Diode & Continuity, Temperature, Auto-range, 52mm Jaw, Data Hold, Auto Power-off, over-range protection, CAT III 1000V, CAT IV 600V	7850	90303100	10598

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
PRO 421	3 5/6 Digits TRMS Clamp Meter, 6000 Counts, 1000V AC/DC, 1000A AC/DC with LoZ, Inrush, Peak, VFD, Capacitance, Frequency, Resistance, Temperature, Continuity Test, NCV	7955	90303100	10739
DT-8250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC Voltage, 2000A DC/AC Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	8055	90303100	10874
METRACLAMP-15	3999 Counts, Backlit LCD, 52mm jaw Dia, Non Contact Voltage Detector, Auto Power Off, T-RMS, AC/DC Voltage, AC T-RMS/DC 1000A, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test, double Injection mould, CAT-IV 600V	8600	90303100	11610
PRO IRC-700 NEW!!	6000 counts, Data Hold, NCV, 34mm Jaw Size, AC/DC Voltage 1000V, T-RMS AC Current up to 1000A, DC Current 1000A, VFD Voltage, Resistance, Capacitance, Frequency, Duty Cycle, Diode & Continuity Test, with Backlit LCD, Flashlight, REL function and built-in Infrared Thermometer for up to 350°C.	9180	90303100	12393
DT-9250	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage, 2000A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	9400	90303100	12690
2003A	3-3/4 Digits 41 segment Backlit LCD, Data & Peak Hold, Auto-ranging, 52mm Jaw Size, DC/AC T-RMS Voltage, 2000A DC/AC T-RMS Current, Frequency, Temperature, Capacitance, Resistance, Duty Cycle, Diode and Continuity Test Facility, 600V AC/DC Protection on all ranges, Frequency through voltage and Current measurement possible, Auto Power Off, Confirms CAT-III 600V & CAT-IV 1000V	9400	90303100	12690
METRACLAMP-20	4-3/4 Digits, 40,000 Counts, Backlit, T-RMS, Autoranging, 52mm Jaw Dia, Non Contact Voltage Detector, Fully Protected, AC/DC Voltage, AC/DC Current up to 1500A, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Diode and Continuity Test	12900	90303100	17415
DT-5250W	3-3/4 Digits, Backlit LCD, 30mm jaw size, T-RMS AC Current 1000A, DC Current 1000A, T-RMS AC Voltage 600V, DC Voltage 600V, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test, Peak & Data Hold, Wireless PC Interface, IEC 61010 CAT III 600V / CAT II 1000V	10200	90303100	13770
PRO EV-C1 NEW!!	3-3/4 digits, backlit LCD, T-RMS, wide AC/DC Ampere range (4.000 to 1000A), bar graph, high resolution, best accuracy, one-touch zero, Inrush current, Low Pass filter, non-contact Frequency and Voltage detection, data hold, auto power-off.	15750	90303100	21263
PRO 474	6000 counts, digital AC/DC T-RMS clamp meter, TFT LCD display, Bluetooth, 1000V AC T-RMS /DC, 1000A AC T-RMS/DC, 34mm Jaw, 10" Flexible Clamp adaptor for upto 3000A AC, AC+DC Voltage, Inrush Current, VFD AC T-RMS Voltage, Lo-Z Voltage, NCV, Capacitance, Resistance, Frequency, Temperature, Continuity and Duty Cycle, Free APP, Datalogging, Trend Capture on device and APP simultaneously	24190	90303100	32657
PRO Solar-3	Professional T-RMS Industrial AC/DC Clamp Meter with TFT Colour Display with Bluetooth and IP65. High accuracy & 1500V DC for Solar & Photovoltaic Applications. In-rush current and VFD measurement for all Motor Applications.	21000	90303100	28350

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
PRO Solar-3 with Flexible Clamp	Professional T-RMS Industrial AC/DC Clamp Meter with 3000A Flexible Clamp, TFT Colour Display with Bluetooth and IP65. High accuracy & 1500V DC for Solar & Photovoltaic Applications. In-rush current and VFD measurement for all Motor Applications.	23500	90303100	31725
UNIKS C-128 NEW!!	6000 Counts, Backlit 2" LCD, LED Flashlight, Autoranging & Manual, Auto Power Off, T-RMS, Non-contact Voltage detection, Data Hold, AC/DC Voltage, AC/DC Current up to 1000A, InRush Current, VFD Filter, LoZ, Capacitance, Frequency, Temperature, Resistance, Continuity & Diode test. CATIV 600V, CATIII 1000V. Made in Europe.	11000	90303100	14850
Flexible High Current Clamp Meter				
PRO FCM-900A NEW!!	Flexible/Rogowski Φ 300mm Coil Clamp for AC Current 0mA ~ 10000A, AC Voltage 0.0V ~ 750V AC, DC Voltage 0.0V ~ 1000V, Resistance 0 Ω ~ 2k Ω and Continuity	16500	90303100	22275
PRO FCM-900P NEW!!	Flexible Coil Clamp Power Meter for the field measurement of Three Phase AC Voltage, Current, Leakage Current, Phase between Voltage, Phase between Voltage and Current, Frequency, Phase Sequence, Electric Energy, Active Power, Reactive Power, Apparent Power, Power Factor and Total Power. Φ 200mm flexible Clamp (80mmX80mm: can clamp & test Φ 80mm cable, or 96mmX4mm flat steel grounding leads). With Data Logging, Backlit LCD Display, Data Hold.	22000	90303100	29700
Digital Clamp-on Power Meter				
307N	4 Digits, Dual LCD, Single Phase and Three Phase, Max /Min / Peak Hold, 55mm Jaw Dia, T-RMS, AC Voltage, AC Current up to 1000A, KW, KVA, KVAR, Power Factor, Phase Angle, KWh, Frequency and Temperature. With Data Logging and PC Interface	10150	90303100	13703
307	6000 Counts, Backlit LCD, Single Phase and Three Phase, Non Contact Voltage Detector, Data Hold, Peak Hold, Relative, Max/Min Record, Single Phase KW, KVA, KVAR, PF, KWh and KW & PF for Three Phase. Clamp Jaw Size 56mm. AC Current up to 1500A AC.	16448	90303100	22204
107F	10000 Counts Digital Clamp On Power Meter, AC/DC Voltage and AC/DC Current Auto Detection, NCV, Jaw Dia 42mm, KW, PF, THD up to 25th Harmonics	27000	90303100	36450
607	4 Digits, Dual LCD, Harmonic Analysis up to 50th Harmonic, PC Interface, Single Phase & Three Phase, Maximum Demand, KW, KVA, KVAR, KWh, KVAh, KVARh, Power Factor, Real time output of waveform, Power Parameters and Harmonics. Clamp Jaw Size - 55mm.	78750	90303100	106313
Digital AC Leakage Current Clamp Meter				
4671	3-3/4 Digits, Analogue Bargraph, LCD, Data Hold, MAX/MIN Record, 30mm Jaw Size, AC Voltage, AC Current, Resistance. Has Low Pass Filter to filter out noise.	6700	90303100	9045
6054	3-1/2 Digits LCD, Data Hold, Max Hold, 30mm Jaw Dia, 0 - 200mA / 2A / 200A AC.	5590	90303100	7547
4675 NEW!!	AC Current 10mA-300A, AC Voltage 10mV-600V, Frequency 35Hz-65Hz, Phase Angle 1° to 360°, 42mm Jaw, 99 Data Sets	20475	90303100	27641
MULTI-140	3-1/2 Digits, 3200 Counts LCD, Data Hold, 40mm jaw Dia, 0 - 30m/300m/30/300A AC	33750	90303100	45563

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
PRO 468AC	6000 Counts, Auto-Backlit LCD Display, Auto Power Off, as per IEC 61557-13: Class 2, 40mm Jaw Dia, IEC / EN 61010-1, IEC / EN 61010-2-032, CAT. III 600V, Pollution Degree 2, EN 61326-1 EN 61326-2-2, bandwidth up to 1kHz, 1% accuracy, 0 - 6mA / 60mA / 600mA / 6A / 60A, With resolution of 1uA, Bluetooth connection to connect it to freely available APP for recording data	33540	90303100	45279
Digital AC/DC Leakage Current Clamp Meter				
4672	3-3/4 Digits, LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Leakage Current measurement, Capacitance, Resistance, Frequency, Duty Cycle, Diode & Continuity Test	6975	90303100	9416
4673	3-1/2 Digits, LCD, T-RMS., AC/DC Leakage Current Meter, Non contact voltage detector, Data Hold, Can be used for Variable Frequency Control Drives, Measures from 1mA, AC/DC Current up to 100A, AC/DC Voltage, Resistance, Capacitance, Diode and Continuity Test	5800	90303100	7830
PRO 2010 NEW!!	AC/DC Auto-ranging Leakage Current Clamp Meter, 0.1mA resolution, 5000 counts, Backlit LCD, Data Hold, 23mm Jaw Size, AC/DC Voltage, AC/DC Leakage Current, Resistance, Continuity Test	23000	90303100	31050
Digital AC Leakage Current Clamp Meter with Harmonics				
PRO HCM-60 NEW!!	AC 0.00mA ~ 300A. Jaw Size Φ 40mm. True virtual value measurement, filtering function, maximum/minimum /average value, harmonics, distortion rate, etc., which can test the current in the frequency range of 40Hz to 1kHz. Backlight, flashlight, data hold, and Bluetooth communication. IEC1010-1, IEC1010-2-032, Pollution2, CAT III(600V)	15000	90303100	20250
PRO HCM-65 NEW!!	AC 0.00mA ~ 1200A. Jaw Size Φ 70mm. True virtual value measurement, filtering function, maximum/minimum /average value, harmonics, distortion rate, etc., which can test the current in the frequency range of 40Hz to 1kHz. Backlight, flashlight, data hold, and Bluetooth communication. IEC1010-1, IEC1010-2-032, Pollution2, CAT III(600V)	25000	90303100	33750
PRO HCM 69 NEW!!	AC 0.00mA ~ 2000A. Jaw Size 80mm. True virtual value measurement, filtering function, maximum/minimum /average value, harmonics, distortion rate, etc., which can test the current in the frequency range of 40Hz to 1kHz. Backlight, flashlight, data hold, and Bluetooth communication. IEC1010-1, IEC1010-2-032, Pollution2, CAT III(600V)	38500	90303100	51975
Digital Process Clamp Meter				
771+	Milliamp Process Clamp Meter, measures 4-20 mA DC without breaking the electrical circuit. DC mA measurement (4-20mA) using a remotely connected clamp via extension cable, Electronic zero, Percentage span (0-100%), Data Hold, Backlit Display, Measurement spotlight LED, Auto Power Off, 0mA... \pm 20.99mA, Resolution 0.01mA, Accuracy: 0.3% re-reading \pm 8 digits, Also measures \pm 21.0mA, \pm 99.9mA with Resolution of 0.1mA, Clamp Jaw 4.5mm, IP40, IEC 61010-1, 61010-2-032, CAT II 300V	22575	90303100	30476
COMPONENT TESTERS				
Digital SMT Component Tester				
SMT-01	SMT Component tester that can measure Capacitance and Resistance values of SMT components, it can also measure AC/DC Voltage, continuity and Diode test	4300	90303100	5805
DATA LOGGERS				

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
Data Logger for Sound Level				
DL-SL-01	Sound Level Data logger to record sound, from 30 to 130 dB, with 129920 data Points	12911	90278090	17430
Data Logger for Temperature & Humidity				
DL-TH-01	Temperature and Humidity Data Logger with digital display and data logging up to 32700 points	5053	90308990	6821
DL-TH-02 NEW!!	Dry Ice Data Logger for to -80~70°C(-112~158°F), 17280 records, USB interface and IP67 protection	7525	90258090	10159
Data Logger for Voltage and Current				
DL-VL-01	Data Logger for Voltage and Current with digital display and 100096 data points	16200	90303100	21870
Multi-channel Data Logger				
TP-700 NEW!!	Multi-channel Data Logger with IoT. 8 groups of different modules can be inserted for various data acquisitions and functions, like relay output, power supply and wireless transmission, etc. Features high-definition display graphs, digital graphs, bar graphs, data overview, etc. Strong anti-interference ability, highest accuracy, 7" Touchscreen colour display. RS485 connects external acquisition modules and increase numbers of channels upto 200*. Displays: Comprehensive, Number, Alarm, Real time curves, Historical curves, Bar-graph. Input Signals: Thermocouples, Thermal Resistance, Current, Voltage.	135000	90251920	182250
	Extra module for 8 programmable input	58000	90251920	78300
	Extra Module for WiFi	27000	90251920	36450
	Extra Module for 4G	27000	90251920	36450
DL-T-2000 NEW!!	32 channels displayed simultaneously, 1 second Interval, can record for 97 days. List, Curve, Histogram display. Customise channel names & export EXCEL files, Multistage Alarms, Double Relay Output, supports Multiple Sensor Inputs: K, J, E, T, N, S, R, B. 5" true colour touchscreen, Standard model with 8 channels.	63450	90251920	85658
	Extra Module for 8 Channels	19350	90251920	26123
DISCHARGE RODS				
Single Phase Discharge Rod				
DR 11-33kV	Insulated 11-33kV Single Phase FRP Telescopic Earth/Discharge Rod manufactured in fully-automatic Pultrusion Plant having strong electrical & mechanical strength	4300	85441920	5805
DR 33-66kV	Insulated 33-66kV Single Phase FRP Telescopic Earth/Discharge Rod manufactured in fully-automatic Pultrusion Plant having strong electrical & mechanical strength	6450	85441920	8708
DR 66-132kV	Insulated 55-132kV Single Phase FRP Telescopic Earth/Discharge Rod manufactured in fully-automatic Pultrusion Plant having strong electrical & mechanical strength	10428	85441920	14077
DR 132-220kV	Insulated 132-220kV Single Phase FRP Telescopic Earth/Discharge Rod manufactured in fully-automatic Pultrusion Plant having strong electrical & mechanical strength	12900	85441920	17415
DR 400kV	Insulated 400kV Single Phase FRP Telescopic Earth/Discharge Rod manufactured in fully-automatic Pultrusion Plant having strong electrical & mechanical strength	16125	85441920	21769
Three Phase Discharge Rod				

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
Upto 66kV NEW!!	Three Phase FRP Telescopic Earth/Discharge Rod manufactured in fully automatic Pultrusion Plant for up to 66kV having strong electrical & mechanical strength. Set of three, telescopic 15 feet rods	18300	85441920	24705
Upto 132kV NEW!!	Three Phase FRP Telescopic Earth/Discharge Rod manufactured in fully automatic Pultrusion Plant for up tp 132kV, having strong electrical & mechanical strength. Set of three, telescopic 15 feet rods	24000	85441920	32400
Upto 220kV NEW!!	Three Phase FRP Telescopic Earth/Discharge Rod manufactured in fully automatic Pultrusion Plant for up tp 220kV, having strong electrical & mechanical strength. Set of three, telescopic 15 feet rods	30000	85441920	40500
Upto 400kV NEW!!	Three Phase FRP Telescopic Earth/Discharge Rod manufactured in fully automatic Pultrusion Plant for up to 400kV, having strong electrical & mechanical strength. Set of three, telescopic 15 feet rods	36000	85441920	48600
Accessories for Three Phase Discharge Rods				
10 sq. mm. Cable (1m)	ISI Marked PVC insulated multi-stranded 440/1100V grade transparent copper cable 10 sq.mm as per IS-694	210	85441920	284
25 sq. mm. Cable (1m)	ISI Marked PVC insulated multi-stranded 440/1100V grade transparent copper cable 25 sq.mm as per IS-695	480	85441920	648
35 sq. mm. Cable (1m)	ISI Marked PVC insulated multi-stranded 440/1100V grade transparent copper cable 35 sq.mm as per IS-696	620	85441920	837
Grounding C Clamp	Die Cast Aluminium Grounding C Clamp	700	85441920	945
Note: CABLE NEEDS TO BE ADDED WHILE PLACING THE ORDER FOR 3 PHASE DISCHARGE ROD. DIE CASE ALUMINIUM GROUNDING C CLAMP IS PROVIDED WITH THE EQUIPMENT, EXTRA UNITS ARE AVAILABLE AT EXTRA COST AS ABOVE.				
DISTANCE METERS				
Digital Distance Meter				
DM-09	Digital Ultrasonic Distance Meter to measure up to 16m	1881	90303100	2540
LDM-40H	Laser Distance Meter to measure up to 40m, with Area / Volume Calculations	4000	90303100	5400
LDM-100H	Laser Distance Meter to measure up to 100m, with Area / Volume Calculations	7600	90303100	10260
ELECTRICAL TESTERS				
ELCB Tester				
1810D	Digital ELCB Tester with Current Rating up to 500mA, Trip Test, Fault Trip Time, Self Powered. With two pin plug.	6800	90308990	9180
1810DE	Digital ELCB Tester with Current Rating up to 500mA, Trip Test, Fault Trip Time, Self Powered. With 3 pin plug.	6950	90308990	9383
1811	Digital ELCB Tester with Current rating up to 500mA, Auto Ramp, Phase Switch, Reads Disconnection Time, Self-Powered	12900	90308990	17415
1813	Digital ELCB Tester with Current rating up to 1A, Trip Test, Fault Trip Time, 230V AC Operated	12200	90308990	16470
1812EL NEW!!	Digital ELCB Tester with Current Rating up to 500mA, Trip Test, Fault Trip Time, DC Test, Auto Ramp Test, Self Powered, verifies wiring connection, 1000mS readout for testing latest ELCB	10500	90308990	14175
Two Pole Voltage Tester				
PRO ELEC+	Two-pole Voltage Tester with LCD display and LED signalling. Features Audible Continuity and RCD tripping test. Built-in LED flashlight, IP67 dust and splash proof, over-voltage protection with CAT III 1000V / CAT IV 600V.	6500	90303100	8775

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
Phase Sequence Indicator for upto 700V				
AC-7	Phase Rotation Indicator, no battery required, Nominal Voltage 40 - 690V, 15 to 400Hz.	4300	90309090	5805
AC-8	Self-operated, Phase Rotation Indicator along with voltage and frequency display. Detects 50 – 500V and 20 – 400Hz.	2700	90309090	3645
Phase Sequence Indicator for High Voltage				
PSI-HV NEW!!	Automatic Phase Detection from 10V to 500kV, test Phase, Frequency, Phase Frequency, along with Electricity Testing & Line Circuit Voltage display. 3.5 inch colour LCD screen displays all on the same screen, simultaneously. Wireless interface with Voice prompts, monitoring software with online real-time monitoring, historical data reading, viewing, saving, printing and query, vector graph indication and phase indication	75000	90309090	101250
Socket Polarity Tester				
AC-6	Socket Polarity & Earth Leakage Tester. Checks for No Earth / Line Neutral Reversal / No Neutral / Line Earth Reversal / No Line states.	1590	90319000	2147
ST-09	Socket Polarity Tester to be used for currents up to 6A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral.	790	90319000	1067
ST-09A	Socket Polarity Tester to be used for currents up to 16A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral.	850	90319000	1148
ST-09B	Socket Polarity Tester to be used for currents up to 6A and input voltage up to 250V AC, when insterted in the plug, it indicates whether the connections of LINE, NEUTRAL & EARTH is correct, indicates errors for missing earth, Live earth reversal, Live Neutral Reversal, Missing Neutral, Live Earth Reversal & Missing Neutral. This can also be used for leakage test of up to 30mA	950	90319000	1283
Power Guard				
PG-01	Multifunction Power Meter, works on 6A, 230V, indicates, voltage, current, power factor, Power, kWh, Calculates CO2 emission, Calculates total time the equipment is under test and calculates the cost of electricity consumed accordingly. During load shedding the instrument memorizes the readings, ideal for analyzing power consumed for different kinds of loads	2140	90303100	2889
Multifunction Tester				
UNIKS RAPID PRO NEW!!	Smart, Multifunction, Installation Tester, Socket size. Test/measure/record Socket Polarity, ELCB/RCD, PSC, Earth Loop, Voltage and Harmonics. Auto Data Logging for 64 sets. Built-in Reporting which can be shared via QR Code. TFT Colour display, CATIII 300V. Made in Europe.	19950	90303100	26933
EMF/GAUSS METERS				
EMF Tester				
EMF-823	Measures from 0.1 to 200mG / 1 to 2000mG & 0.01 to 20uT / 0.1 to 200uT, Frequency Response 30Hz to 400Hz, Max Hold and Data Hold	8280	90318000	11178

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
Gauss Meter				
GM-197	For both static and electromagnets, DC and AC (40-500Hz), N/S polarity of Static Magnets, measures intensity of magnetic Field in Gauss and Tesla both, measures up to 0~3000mT(milli Tesla)/0~30000G(Gauss), Relative / Peak Hold / Real time Zero function, Auto Range, DATA HOLD, MAX/MIN hold, GO and NO-GO alarm and alarm value set up the function, Production testing, Manual 200 capacity records, Auto 6000 capacity data logging, interval is set up by PC, USB interface to send data + PC connection application software, real time function.	28000	90318000	37800
ENVIRONMENTAL METERS				
Air Particle Counters				
CEM DT-9880	Air Particle Counter with unique 2.8"colour TFT LCD display, built-in camera for capturing videos/photos, internal memory or microSD card, for viewing on PC, providing fast, easy and accurate readings for particle counter, Air Temperature, Relative Humidity, Dew Point & Wet Bulb Temperature. Up to 6 channels of particle sizes . Free software to generate reports with videos, photos, and data points.	88000	90303900	118800
CEM DT-9881	Air Particle Counter with unique 2.8"colour TFT LCD display, built-in camera for capturing videos/photos, internal memory or a microSD card, for viewing on PC, providing fast, easy and accurate readings for particle counter, Air Temperature, Relative Humidity, Dew Point & Wet Bulb Temperature and , Gas Detection. Up to 6 channels of particle sizes. Free software to generate reports with videos, photos, and data points. Measure HCHO (Methanal) Gas and CO (Carbon Mono-Oxide) Gas.	102750	90303900	138713
CEM DT-9883M	Air Particle Counter + Gas Detector to measure Mass Concentration, GAS Formaldehyde (HCHO), Carbon Dioxide (CO2), TVOC detection, Air Temperature & Relative Humidity and most surface temperature measurements. Particles up to 0.3, 2.5 and 10 µm, PM 2.5 and PM 10 mass concentration, Formaldehyde content in PPM, temperature, ambient humidity, dew point, internal Data Storage, free software for reporting.	127650	90303900	172328
Thermo-Anemometer				
ET-99A	Thermo-anemometer with backlit LCD display, Data Hold, Max/Avg Records. Measures Air Velocity up to 30m/sec, measures in km/hr, ft/min, knots, mph as well. Measures Air Temperature -20° to 50°C.	1980	90303100	2673
AVM-03 NEW MODEL!!	Smart Thermo-anemometer measures Wind Speed, Temperature, Humidity, Dew Point, Wet Bulb Temperature, Wind Chill, Air Volume. Data Logging 8000 sets. WiFi and USB Interface. Smartphone App. Trend Graph, Statistical functions. Rechargeable Battery.	6750	90268090	9113
AVM-04	Digital Thermo-Anemometer with extendable vane and facility to measure up to 45m/Sec and in ft/min also	6300	90268090	8505
AVM-05	Digital Thermo-Anemometer with extendable vane and facility to measure wind flow (CFM / CMM)	7875	90268090	10631
AVM-07	Digital Thermo-Anemometer to measure up to 30m/Sec with metal blade vane, Temp. -10 to 60°C / 14 to 140°F	5625	90268090	7594
AVM-08	Digital Thermo-Anemometer with facility to measure wind flow (CFM / CMM) and built in infrared thermometer to measure from -50 to 260°C, 8:1 D:S Ratio and Emissivity Fixed at 0.95	13230	90268090	17861
AVM-09	Digital Thermo-Anemometer with facility to measure wind flow (CFM/CMM) with built in Pressure Meter	19800	90268090	26730

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
AVM-10	Digital Hot Wire Anemometer with telescopic probe, Dual Display backlit LCD, 0.1 to 20m/Sec and Temperature from -20 to 80°C / -5 to 175°F	15300	90268090	20655
Lux Meter				
ET-99L	Digital Lux Meter measuring upto 200000 Lux with backlit display, high accuracy, selectable range, MAX/MIN/REL, Data Hold, User-selectable unit and range.	1935	90268090	2612
1310	4 Digits Backlit LCD Display, Data Hold, Hi/Lo Indication, Split Probe, Lux and Foot Candle Measurement, Auto Power Off, Lo-Battery Indication, Measures up to 199,900 Lux / Fc	3290	90278090	4442
1330	Measures up to 50,000 Lux with extendable sensor	2780	90278090	3753
1331	Measures up to 50,000 Lux / Ft Candle with Max Hold, Data Hold, with extendable sensor	3330	90278090	4496
1332	Measures up to 200,000 Lux / Ft Candle with Peak Hold and Data Hold	6075	90278090	8201
1332A	Measures up to 200,000 Lux / Ft Candle with Max Hold and Data Hold	8000	90278090	10800
1333	Measures up to 0 - 20 / 200 / 2000 / 200000 / 200,000 Lux / Ft Candle with Max Hold and Data Hold	5350	90278090	7223
1334	Measures up to 400,000 Lux/40,000 Ft Candle, Data & Peak Hold, Max Min Record, USB PC Interface, Backlit LCD with Analogue Bargraph	6705	90278090	9052
1335	Measures visible light up to 400000 Lux from luminaries equipped with white light LED, fluorescent, metal halide, high-pressure sodium and incandescent sources.	8730	90303100	11786
Solar Power & Irradiance Meter				
207	Solar Power Meter / Sunlight Meter, to measure the sunlight intensity falling on solar panels or on any surface exposed to sunlight, using a sensitive silicon sensor. It measures up to 1999W/m2 or 634BTU / (Ft2*hr) irradiance. With high accuracy and fast Response, it also features Data Hold function.	6480	90318000	8748
PRO IM-09 NEW!!	Multifunction, high accuracy instrument to measure Irradiance up to 1400 W/m2, Temperature, Inclination Angle with a built in compass, backlit large LCD, selectable °C/°F units, Data Hold, Auto Off and a self-calibratable compass.	11200	90318000	15120
Sound Level Meter				
ET-99SL	Class II, 30dB to 130dB with backlit 3 1/2 digits display, data hold, Min/Max, Slow/Fast response and ±1.5 dB accuracy.	1980	90268090	2673
SL-4010	3-1/2 Digits Backlit LCD, has A & C Weighting, measures in the range of 30 to 130 dB, with maximum hold. Class II.	6300	90303900	8505
SL-4005	3-1/2 Digits, has A & C Weighting, measures in the range of 35 to 130 dB, with data hold and maximum hold, with built in calibration check. Class II.	7200	90303900	9720
SL-4015	4 Digits, has A & C Weighting, measures in the range of 30 to 130 dB, USB PC Interface, with Max/Min Data Hold and Data Logging facility. Class II	12500	90303390	16875
Temperature & Humidity Meter				
HTC-1	Jumbo LCD display, wall hanging, with time and alarm facility, -50 to 70°C, 20% to 99%RH	695	90258090	938
TH-04	LCD Display, wall hanging, with time and alarm facility, calander, climatic condition display, 0 to 50°C, 10% to 90%RH	1290	90258090	1742

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
HT-13	Digital Thermo-Hygro Meter with jumbo display, to measure Temperature measurement, with Humidity. Selectable scales, Alarm Clock and Comfort Level Indicator, Temperature range -10 to 50°C and humidity from 20 to 95%.	1290	90258090	1742
HT-12	Digital Thermo-Hygro Meter with jumbo display, to measure Indoor and Outdoor Temperature measurement simultaneously, with Humidity. Selectable scales, Alarm Clock and Comfort Level Indicator, Temperature range -10 to 50°C and humidity from 20 to 95%	1395	90258090	1883
ET-99TH	Thermo-hygro Meter with dual backlit display, measures Temperature -20° to 60°C and Humidity 0% to 100%RH with high accuracy.	2150	90258090	2903
HT-305A	Backlit LCD dual display, with split type Sensor for temperature and Humidity, Data Hold, MAX / MIN Record, Auto Power Off, Measure Temperature from -10 to 60 Degree C, and Humidity Up to 100% RH	2850	90258090	3848
HT-3005	Digital Thermo-Hygro Meter with K-type thermometer and backlit LCD display	4600	90258090	6210
HT-3006	Digital Thermo-Hygro Meter with facility to measure wet bulb and dew point temperature	6700	90258090	9045
HT-3004CT	Digital Thermo-Hygro Meter with in-built infrared thermometer and backlit LCD display	9590	90258090	12947
Wet Bulb Globe Temperature Meter				
WBGT-188	Quick-response capacitance sensor, accurate measurement for wet bulb globe temperature(WBGT), black globe temperature(TG), humidity(%RH), air temperature(TA), wet bulb(WET) and dew point(DEW). Max/Min and data hold, Low battery indication, LCD display with LED backlight, Viewing data records, Switch the temperature unit to °C or °F, Brass black ball in 50mm diameter, WBGT alarm setting, Auto power off with disable function	18500	90258090	24975
WBGT-188D	Quick-response capacitance sensor, accurate measurement for wet bulb globe temperature(WBGT), black globe temperature(TG), humidity(%RH), air temperature(TA), wet bulb(WET) and dew point(DEW). Max/Min and data hold, Low battery indication, LCD display with LED backlight, Viewing data records, Switch the temperature unit to °C or °F, Brass black ball in 50mm diameter, WBGT alarm setting, Auto power off with disable function, Data logging capacity: 12000 records, USB PC serial interface, Sampling interval: Max 24 hours; Min 1 Second	25000	90258090	33750
FREQUENCY COUNTER				
Digital Frequency Counter				
FC-2700	8 Digits Green LED Frequency Counter up to 2.7GHz	12600	90303100	17010
FUNCTION GENERATOR				
Function Generator				
FG-1000	1MHz Function Generator with TTL / CMOS output	10350	85432000	13973
FG-2000	2MHz Function Generator with TTL / CMOS output	11250	85432000	15188
FG-5000	5MHz Function Generator with TTL / CMOS output	13975	85432000	18866
DDS Function Generator				

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
DDS-30 NEW!!	30MHz DDS Function Generator with full-band resolution of 1μHz, 200MSa/s sampling rate and USB interface.	22040	85432000	29754
DDS-35 NEW!!	35MHz DDS Function Generator with full-band resolution of 1μHz, 200MSa/s sampling rate and USB interface.	20570	85432000	27770
DDS-60	60MHz DDS Function Generator with full-band resolution of 1μHz, 200MSa/s sampling rate and USB interface.	27410	85432000	37004
DDS-70 NEW!!	70MHz DDS Function Generator with full-band resolution of 1μHz, 200MSa/s sampling rate and USB interface.	26000	85432000	35100
DDS-1010	10 MHz DDS Function generator, 125MSa/s sampling rate	23650	85432000	31928
DDS-1025	25 MHz DDS Function generator, 125MSa/s sampling rate	43320	85432000	58482
DDS-1060	60 MHz DDS Function generator, 125MSa/s sampling rate	64500	85432000	87075
DDS-1080 NEW!!	80MHz DDS Function generator, 320MSa/s sampling rate	113950	85432000	153833
DDS-1120 NEW!!	120MHz DDS Function generator, 320MSa/s sampling rate	146200	85432000	197370
GAS DETECTORS & ANALYSERS				
Carbon Monoxide Meter				
CO-09	Detects Presence of Carbon Mono-Oxide. Range 0 to 1000PPM, Backlit LCD	15300	90271000	20655
CO-10	Detects Presence of Carbon Mono-Oxide. Range 0 to 1000PPM, Backlit LCD, With Audio and Buzzer Alarm	16600	90271000	22410
CO-110	Compact device to detect Carbon Monoxide (CO) and measures concentrations between 1-1000 parts per million (PPM), with visual and audible alarms	15300	90271000	20655
GD-09-CO	Portable Carbon Monoxide detector for 100ppm, with sound, light & vibration alarms. Rechargeable battery, IP65, explosion-proof.	15120	90271000	20412
GD-09-CO-A	Portable Carbon Monoxide detector for 1000ppm, with sound, light & vibration alarms. Rechargeable battery, IP65, explosion-proof.	11500	90271000	15525
GD-09-CO-B	Portable Carbon Monoxide detector for 2000ppm, with sound, light & vibration alarms. Rechargeable battery, IP65, explosion-proof.	22220	90271000	29997
Combustible Gas Leakage Detector				
GLD-01	16" Gooseneck detector for detecting Combustible Gas Leakage. With Audio and Visual Alarm	6000	90271000	8100
GD-09-1M	Plug type, Combustible Gas Detector and Alarm with high sensitivity, compact design and reliable performance for detecting combustible gas (like LPG) leaks. Features audible alarm with red flashing light, when gas concentrations reach or exceed the alarm set point.	1950	90271000	2633
Multi Gas Detector				
GD-09-4M	4-in-1 Multi Gas Detector for O2, CO, H2S and Explosive/Combustible Gas. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	19350	90271000	26123
GD-09-6M	Six-in-one Pumping Multi Gas detector for 6 gases: Oxygen (O2), Carbon Di Oxide (CO2), Carbon Monoxide (CO), Hydrogen Sulfide (H2S), Nitrogen Di Oxide (NO2) and Explosive Gases (EX). Also features PM2.5/PM10 detection module, 4G module and GPS. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	158000	90271000	213300

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
CEM GD-3803	Multiple gas analyser to measure Oxygen, Carbon Monoxide and Carbon Dioxide. Can also measure the Air Temperature and Humidity. With data logging for 500 data sets.	37320	90271000	50382
Single Gas Detector				
GD-09-O2	Portable and world's smallest, clip-on Oxygen Gas Detector with audio & visual alarms. Detects Oxygen concentration in the air.	15750	90271000	21263
ET-99HT	High-precision HCHO (Formaldehyde) and TVOC (Total Volatile Organic Compounds) meter with backlit LCD display, dual readings, Data Hold and Max/Min.	6750	90271000	9113
GD-09-X	Portable single gas detector, which can be customised for more than 30 types of gases, as per the requirement of range and alarms. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	On Request	90271000	
GD-09-EX	Portable single gas detector, for Explosive and combustible gases. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	8100	90271000	10935
GD-09-CH4	Portable single gas detector, for Explosive and combustible gases. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	8100	90271000	10935
GD-09-H2S	Portable single gas detector, for Explosive Hydrogen Sulfide. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	10500	90271000	14175
GD-09-O2-A	Portable single gas detector, for Oxygen 0-30%vol. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	12500	90271000	16875
GD-09-NH3	Portable single gas detector, for Ammonia gas. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	28500	90271000	38475
GD-09-H2-A	Portable single gas detector, for Hydrogen gas. 0-100%LEL. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	9000	90271000	12150
GD-09-H2-B	Portable single gas detector, for Hydrogen gas. 0-1000ppm. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	28500	90271000	38475
GD-09-CL2-A	Portable single gas detector, for Chlorine 0-20ppm. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	28500	90271000	38475
GD-09-CL2-B	Portable single gas detector, for Chlorine 0-50ppm. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	28500	90271000	38475
GD-09-O3	Portable single gas detector, for Ozone gas. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	28500	90271000	38475
GD-09-CO2	Portable single gas detector, for Carbon di Oxide. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	52000	90271000	70200
GD-09-SO2	Portable single gas detector, for Sulfur Dioxide gas. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	29000	90271000	39150
GD-09-NO	Portable single gas detector, for Nitrous Oxide gas.. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	29000	90271000	39150
GD-09-NO2	Portable single gas detector, for Nitrogen di Oxide gas. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Batter	29000	90271000	39150

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
GD-09-N2	Portable single gas detector, for Nitrogen gas. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	29000	90271000	39150
GD-09-C2H4O	Portable single gas detector, for Ethylene Oxide gas. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	29000	90271000	39150
GD-09-PH3	Portable single gas detector, for Phosphane gas. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	29000	90271000	39150
GD-09-HCL	Portable single gas detector, for Hydrogen Chloride gas. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	29000	90271000	39150
GD-09-CH2O	Portable single gas detector, for Formaldehyde. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	29000	90271000	39150
GD-09-HCN	Portable single gas detector, for Hydrogen Cyanide. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	29000	90271000	39150
GD-09-VOC	Portable single gas detector for Volatile Organic Compounds. Explosion-proof, IP65 protection and audio/visual alarms and Rechargeable Battery	29000	90271000	39150
GD-3805	Intelligent, portable Ammonia Detector 0-100ppm & 0.1ppm resolution. With built-in pump detection mode. Integrated water vapour and dust filter for use in high humidity and dust environments. Measures in both ppm and mg/m3. Rechargeable Battery, Data Logging, 2.8" colour LCD display.	33300	90271000	44955
Refrigerant Gas Leakage Detector				
RLD-01	16" Gooseneck sensor, detects all CFC Refrigerants such as R-22, R-124, R-11 and R-12, R-134a, R-404A, and new R-22 replacements, R-410A and R-407C.	9675	90271000	13061
Accessories for Gas Detectors & Analysers				
GD-GSP NEW!!	Portable Gas Sampling Pump compatible with GD-09-4M and GD-09-X series	7100	90271000	9585
GROUND AND EARTH RESISTANCE TESTER				
Digital Earth Resistance Tester				
ERT-1501	0 - 10 / 100 / 1000Ω, 4 Terminal with Testing Kit and Cables in hard carrying case	7900	90303900	10665
ERT-1501R	0 - 10 / 100 / 1000Ω, 4 Terminal with Testing Kit and Cables in hard carrying case as above with Rechargeable Battery and Battery Charger	11900	90303900	16065
ERT-1502	0 - 10 / 100 / 2000Ω, 4 Terminal with Testing Kit and Cables in hard carrying case	8900	90303900	12015
ERT-1502R	0 - 10 / 100 / 2000Ω, 4 Terminal with Testing Kit and Cables in hard carrying case as above with Rechargeable Battery and Battery Charger	12900	90303900	17415
PRO ERT-1602	Earth Resistance 0-30.00kΩ, Earth Voltage 0.0~600V AC, Soli Resistivity 9000kΩm. Precision 4-wire, 3-wire and simple 2-wire measurements. Complete kit in hard carrying case.	36000	90303900	48600
PRO ERT-1635	Earth Resistance 0.00Ω ~ 30KΩ, Earth Voltage 0.0 ~ 100.0V AC, Earth Current 0.0mA ~ 600.0A, Soli Resistivity 0.00Ωm ~ 9000KΩm. Double Clamp, multi-function, Earth and Grounding Resistance Tester for on-site measurement of grounding resistance, soil resistivity, grounding voltage, grounding line leakage current, AC current and DC resistance. Offers precision 4-wire method, 3-wire method and simple 2-wire method, selection method, double-clamp methods.	85000	90303900	114750

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
Clamp-on Ground Resistance Tester				
CET-01	4 Digits LCD, 32mm Clamp Jaw Dia, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms	21825	90303900	29464
CET-02	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms	21825	90303900	29464
CET-03	4 Digits LCD, 32 X 65 mm Clamp Jaw, with Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 35A.	26000	90303900	35100
CET-04	4 Digits LCD, 32mm Clamp Jaw Dia, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms. With Leakage Current Measurement up to 35A.	26000	90303900	35100
CET-05	4 Digits LCD, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms	20000	90303900	27000
CET-06	4 Digits LCD, 32 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms	20000	90303900	27000
CET-02EX	Explosion Proof Clamp On Ground Resistance Tester, 32 X 65 mm Clamp Jaw, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 35A.	39600	90303900	53460
CET-09	4 Digits LCD, 35 mm Elliptical Clamp Jaw, Range 0.01Ω to 1500Ω, Max Resolution 0.001Ω, Data Hold, Open Clamp Jaw Indication. With USB Interface & Rechargeable Battery – features Ground Resistance, Loop Resistance, Leakage Current measurements as well as judges Ground Faults.	60000	90303900	81000
CET-01B NEW!!	4 Digits LCD, 32mm Clamp Jaw Dia, with Bluetooth, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms	21825	90303900	29464
CET-02B NEW!!	4 Digits LCD, 32 X 65 mm Clamp Jaw, with Bluetooth, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms	21825	90303900	29464
CET-03B NEW!!	4 Digits LCD, 32 X 65 mm Clamp Jaw, with Bluetooth, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms, With Leakage Current Measurement up to 35A.	29000	90303900	39150
CET-04B NEW!!	4 Digits LCD, 32mm Clamp Jaw Dia, with Bluetooth, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 1500 Ohms. Maximum Resolution 0.001 Ohms. With Leakage Current Measurement up to 35A.	26000	90303900	35100
CET-05B NEW!!	4 Digits LCD, 32 X 65 mm Clamp Jaw, with Bluetooth, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms	20000	90303900	27000
CET-06B NEW!!	4 Digits LCD, 32 mm Clamp Jaw, with Bluetooth, Data Hold, Open Clamp Jaw Indication, Range 0.010 to 200 Ohms. Maximum Resolution 0.001 Ohms	20000	90303900	27000
HIGH VOLTAGE TESTING EQUIPMENT				
AC High Voltage Test Set				
ACHV	Please refer to Annexure 1		90303390	
DC High Voltage Test Set				
DCHV	Please refer to Annexure 2		90303390	
Motor Operated Oil Test Set				

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
50-MOTS	50kV Motor operated Oil Test Set	45000	84212900	60750
60-MOTS	60kV Motor operated Oil Test Set	46225	84212900	62404
70-MOTS	70kV Motor operated Oil Test Set	52675	84212900	71111
75-MOTS	75kV Motor operated Oil Test Set	56438	84212900	76191
80-MOTS	80kV Motor operated Oil Test Set	62350	84212900	84173
90-MOTS	90kV Motor operated Oil Test Set	66650	84212900	89978
100-MOTS	100kV Motor operated Oil Test Set	77145	84212900	104146
120-MOTS	120kV Motor operated Oil Test Set	120000	84212900	162000
Digital Meter for above, extra to be paid		2140	84212900	2889
Manual Oil Test Set				
50-OTS	50kV Manually operated Oil Test Set	34285	84212900	46285
60-OTS	60kV Manually operated Oil Test Set	37090	84212900	50072
70-OTS	70kV Manually operated Oil Test Set	44075	84212900	59501
75-OTS	75kV Manually operated Oil Test Set	47300	84212900	63855
80-OTS	80kV Manually operated Oil Test Set	52998	84212900	71547
90-OTS	90kV Manually operated Oil Test Set	58050	84212900	78368
100-OTS	100kV Manually operated Oil Test Set	62350	84212900	84173
120-OTS	120kV Manually operated Oil Test Set	85700	84212900	115695
Digital Meter for above, extra to be paid		2140	84212900	2889
Primary Current Injection Test Set				
PCIT	Please refer to Annexure 3		90303390	
Relay Test Set				
RNT-5	Relay Test Set, with current output upto 200A in various ranges	47000	90308200	63450
RNT-5A	Relay Test Set with 200A in various ranges, Burden 1KVA, with AC/DC Voltage output	68500	90308200	92475
RNT-33	Relay Test Set suitable for testing distance relay, 3 phase current / voltage output and Fixed DC Voltage output	268750	90308200	362813
ZNT-34	Relay Test Set suitable for testing distance, over voltage relays etc., Variable three phase Voltage / Current and variable DC Voltage outputs	290250	90308200	391838
Transformer Turns Ratio Set				
TTRS-100	Transformer Turns Ratio Set to measure ratio in the range of 0.800 to 2021 & for Phase Deviation Measurement	133000	90303390	179550
IC TESTER				

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
IC Tester				
DICT-2040	40 pin Digital IC Tester to test 54 / 74 series TTL and 4000 & 4500 series CMOS ICs, tests more than 2000 kinds of devices	34650	90308200	46778
LCR METERS				
Digital LCR Meter				
460	11,000 Counts Backlit LCD, Data Hold, MAX/MIN Record, RELATIVE, Inductance, Capacitance, Resistance, Diode & Continuity Test	5850	90303100	7898
4070D	5 Digits, LCD, Dual Display, Inductance, Capacitance, Resistance, Impedance, D, ESR and Q Test Facility, Test Frequency of 100Hz, 120Hz, 1kHz, 10kHz and 100kHz	13050	90303100	17618
4090D NEW!!	LCR Meter	33750	90303100	45563
Digital LCR Multimeter				
451	3-1/2 Digits, Backlit LCD, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Inductance, Frequency, Temperature, Diode, Transistor and Continuity Test	4150	90303100	5603
506	3-3/4 Digits, Backlit, LCD Dual Display, T-RMS, RS-232 PC Interface, Internal Memory, Min, Max, Avg, Relative Modes, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Inductance, Duty Cycle, Temperature, dBm, Logic, Diode, Signal Output & Continuity Test	22040	90303100	29754
MANOMETERS				
Digital Differential Pressure Meter (Manometer)				
PM-01	Backlit LCD Display, measures up to 5 psi and in various other units of Pressure	11655	90262000	15734
ET-99P	Differential Pressure Manometer for -5000Pa to +5000Pa, with backlit LCD display and Data Hold.	4650	90308990	6278
PM-05	Differential Pressure Manometer measures negative, positive and differential pressure. Option for 11 measurement units: bar, ozin ² , psi, mbar, mmHg, cmH ₂ O, ftH ₂ O, kgcm ² and kPa.	4750	90268090	6413
METAL DETECTORS				
Metal Detector				
MD-300	Highly sensitive Metal Detector with a circular sensor, the detector vibrates and provides audible alarm on detecting metal	1950	85438910	2633
SUPER-V	Higly sensitive Metal Detector with a straight sensor, the detector vibrates, provides visual and audible warning on detecting metal	3225	85438910	4354
MOISTURE METERS				
Digital Moisture Meter				
ET-99M	Digital Moisture Meter for wood, sawn timber, cardboard, paper, as well as hardened materials like plastic, concrete and mortar, using pin probe sensors	1980	90268090	2673
CEM DT-120	Compact, pin-type Digital Moisture Meter for wood and building materials.	2160	90268090	2916
MM-1	Digital Moisture Meter for paper, wood and hardned material like plaster, concrete and mortar	3600	90268090	4860
MM-2	Digital Moisture Meter for wood, bamboo, cotton, tobacco, paper, foodstuffs	1800	90268090	2430
MM-5	Digital Wood Moisture Meter that can measure moisture in up to 150 different kinds of wood	6700	90268090	9045

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
MM-10	Digital Pinless Moisture Meter, Range 0 - 100%, auto power off, backlit display, Min/Max function, Measure and Hold, works on most of the products	8730	90268090	11786
MOTOR CHECKERS				
Analogue Motor Checker				
MC-22	Electric Motor Checker with analogue display	27950	90303900	37733
Digital Motor Checker				
MC-22D	Digital Motor Checker with insulation resistance test of 1000V	34400	90303900	46440
MC-38D	Digital Motor Checker with insulation resistance test of 500 and 1000V	18800	90303900	25380
Rotating Machine Tester				
RMT-10	One Single Meter that can test rotating machines, from insulation resistance to low resistance milli ohms combined with a built-in T-RMS Multimeter, Data logger, with Low pass Filter, Bluetooth, can measure AC/DC Voltage 1000V, DC/AC Current 10A, Resistance, Capacitance 5mF, Frequency 50Mhz, Temperature up to 1200°C, Insulation Resistance 5000MΩ at test voltage of 50V / 100V / 250V / 500V / 1000V, with polarisation index and DAR, Low resistance from 1 mΩ to 2000Ω	33300	90303900	44955
RMTi-1	One Single Meter that can test rotating machines, from insulation resistance to low resistance milli ohms combined with a built-in Thermal Imager, T-RMS Multimeter, Data logger, with Low pass Filter, Bluetooth, can measure AC/DC Voltage 1000V, DC/AC Current 10A, Resistance, Capacitance 5mF, Frequency 50Mhz, Temperature up to 1200°C, Insulation Resistance 5000MΩ at test voltage of 50V / 100V / 250V / 500V / 1000V, with polarisation index and DAR, Low resistance from 1 mΩ to 2000Ω	82800	90303900	111780
MULTIMETERS				
Analogue Multimeter				
250TR	Measures AC/DC Voltage, DC Current, Resistance, Battery Test and dB.	1065	90303100	1438
260TR	Measurs AC/DC Voltage, DC Current, Resistance, Transistor Polarity Test, Audible Continuity	1720	90303100	2322
2010BA	Measures AC/DC Voltage, up to 10A AC/DC, Resistance, Transistor and Audible Continuity	2560	90303100	3456
5050E	Measures AC/DC Voltage up to 1000V, AC/DC Current up to 10A, Resistance up to 2000M.Ohms, Frequency up to 25kHz, Transistor Testing, Diode Testing and audible continuity testing	3750	90303100	5063
6060	Measures AC / DC Voltage up to 2500V, AC/DC Current up to 10A, Resistance up to 10M.Ohms, Diode and continuity test facility	14500	90303100	19575
Digital Multimeter				
XB-30	3-1/2 Digits, LCD, Data Hold, AC Voltage, DC Voltage, DC Current, Resistance, Diode & Transistor Test.	1500	90303100	2025
XB-33A	6000 Counts, Auto-ranging, T-RMS Digital multimeter with backlit LCD display. Can measure AC T-RMS Voltage and Current, DC Current / Voltage, Frequency, Resistance, Capacitance, Temperature, Diode and Continuity Test and Non-contact Voltage Detection, along with overload protection.	1650	90303100	2228

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
XB-33CF	6000 Counts Backlit LCD, Flash Light, NCV, MAX/MIN Record, T-RMS, Measures AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Frequency, Diode and Continuity Test	1750	90303100	2363
603	3-1/2 Digits, Backlit LCD, Data Hold, AC Voltage, DC Voltage, AC Current, DC Current, Resistance, Capacitance, Frequency, Temperature, Hot Wire, Diode, Transistor and Continuity Test.	2100	90303100	2835
6030A+	6000 Counts Backlit LCD, T-RMS Multimeter, Auto Power Off, Data Hold, MAX/MIN, AC / DC Voltage, AC/DC Current 20A, Resistance, Capacitance, Frequency, Temperature, Transistor Test, Diode and Continuity Test	2200	90303100	2970
19 TRMS NEW MODEL!!	3-3/4 Digits, LCD, Auto-ranging, Relative, Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, 30MHz Frequency, Duty Cycle, Temperature, Diode, Transistor and Continuity Test.	2350	90303100	3173
19-SUPER	6000 Counts LCD Display, NCV, T-RMS Multimeter, Measures AC/DC Voltage, AC/DC Current up to 20A, Resistance, Temperature, Frequency, Capacitance, Diode, Transistor Test and Continuity Test Facility	2500	90303100	3375
Metrasafe-10	6000 Counts Backlit LCD, T-RMS, Flashlight, Live-Neutral detection, Non contact voltage detector, Audio and visual alarm for continuity, Transistor Test, AC/DC Voltage, AC/DC Current up to 20A, Resistance, Capacitance, Frequency, Temperature, Duty Cycle, Diode and Continuity Test.	2700	90303100	3645
SOLAR-1B NEW!!	6000 Counts Backlit LCD, TRMS, Live/Neutral Detection, NCV, Double integral A/D conversion, AC Voltage, DC Voltage, AC/DC High Voltage 2000V, AC Current, DC Current, Capacitance, Frequency, Diode Test, intelligent voice alarm values, 2000V AC/DC Voltage and high voltage diode output measurement. Overload protection.	2800	90303100	3780
DT-19TB	3-3/4 Digits, Backlit LCD, Auto-ranging, Terminal Blocking Facility, Relative & Data Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Battery Test, Diode & Continuity Test. 500V AC/DC Protection in all ranges	3600	90303100	4860
PRO 7	4000 counts, TRMS, auto-ranging with backlit display, backlit switch as well as backlit ranges. Measure AC/DC Voltage, VFD Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Duty Cycle, Diode & Continuity Test, NCV detection, Live Line test & Square Wave Output. Heavy-duty, rugged design, double-injection moulding, built-in Flashlight, CATIII 600V. Data Hold, MAX/MIN, Auto Power Off.	3700	90303100	4995
540	4-1/2 Digits, LCD, Data Hold, T-RMS, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Diode & Continuity Test.	3825	90303100	5164
23S-TRMS	4-1/2 Digits 19,999 Counts, T-RMS, Backlit LCD, NCV, Data Hold, Peak Hold, Relative, Auto Power Off, Dual Display to show Voltage & Current with Frequency on the same screen, AC/DC Voltage, AC/ DC Current 10A, Resistance, Capacitance, Temperature, Frequency, Diode & Continuity Test both Audio and Visual.	4050	90303100	5468
901-III	3-5/6 Digits, 6000 Counts Backlit LCD, Autor-ranging, 600V AC/DC Protection, AC/DC Voltage, AC/DC Current, Resistance, 4mF capacitance, 20MHz Frequency, temperature diode and continuity	4455	90303100	6014

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
PRO-11	4000 Count Backlight LCD Display, Auto-Ranging, IP67 Dust and Waterproof, 600V AC/DC Voltage, 10A AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, UL 61010-1, CAT-III 600V, Class 2 Double Insulation, Built-in flashlight, Over range indication, Auto Power Off, Min/Max Data Hold. Hand-Held Waterproof and Dust proof, Double moulded injection body.	4700	90303100	6345
Metrasafe-13	3-3/4 Digits, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Relative, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Continuity and Battery Test. Confirms to CAT IV 600V	4750	90303100	6413
901-IV	3-5/6 Digits, 6000 Counts Backlit LCD, Autor-ranging, T-RMS, 600V AC/DC Protection, AC/DC Voltage, AC/DC Current, Resistance, 4mF capacitance, 20MHz Frequency, temperature diode and continuity	5355	90303100	7229
Metrasafe-14	3-3/4 Digits, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Relative, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Duty Cycle, Temperature, Continuity and Battery Test. Confirms to CAT IV 600V	5360	90303100	7236
PRO-12B	4000 Counts, Backlight LCD Display, TRMS, IP 67, 600V AC(TRMS)/DC Voltage, 10A AC(TRMS)/DC Current, LoZ, Resistance, Capacitance, Frequency, Temperature, Diode & Continuity test, 50 to 400Hz AC Bandwidth, Bluetooth, Free Smartphone App, Data Hold, MAX/MIN Record, built-in Flashlight, double-moulded injection body, Auto Power Off, Low battery indication, CAT-III 600V.	5500	90303100	7425
PRO 21	6000 counts backlit LCD display, TRMS, Auto-ranging, Heavy Duty, Industrial-grade Digital Multimeter with VFD Measurement. IP67 dust and water proof as well as 2 metres drop/shock-proof!	5920	90303100	7992
Metrasafe-15	3-3/4 Digits, Analogue Bargraph, Backlit LCD, Autoranging, Fully Protected, Data Hold, Max/Min, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test. Confirms to CAT IV 600V.	6530	90303100	8816
PRO 27	6000 counts backlit LCD display, Auto-Ranging T-RMS Multimeter with VFD, LoZ, 61 Segment Analogue Bar-graph and IP67- best fit for all applications regarding electrical motors.	6665	90303100	8998
PRO SOLAR-1A	1500VDC, 1000VAC, 6000 counts backlit LCD display, TRMS, Auto-ranging, Heavy Duty, Industrial-grade Digital Multimeter with VFD Measurement. IP67 & 2 metres drop/shock-proof. Perfect for Solar & PV Applications.	6988	90303100	9433
Metrasafe-16	3-3/4 Digits, Analogue Bargraph, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data Hold, Max/Min, Peak Hold, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Temperature, Diode and Continuity Test. Confirms to CAT IV 600V.	7500	90303100	10125
DM-454	22,000 Counts LCD Display, Peak Hold, Data Hold, Relative Measurement, T-RMS Multimeter, Confirms to CAT III 1000V, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Frequency, Diode & Continuity Test, USB PC Interface.	11000	90303100	14850
PRO 587	6,000 /60,000 Counts user selectable, Backlit LCD Display, Bargraph, T-RMS Multimeter, 1000V AC/DC Current, 10A AC/DC Current, 100kHz AC Response, Resistance, Capacitance, Electrical and Electronic Frequency, Temperature, Duty Cycle, Low Pass Filter, 4-20mA measurement, Continuity and Diode testing.	13438	90303100	18141

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
Metrasafe-18	4-3/4 Digits, Analogue Bargraph, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data & Peak Hold, Max/Min Record, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Non Contact type Infrared Thermometer, Duty Cycle, Diode & Continuity Test. Confirms to CAT IV 600V.	15265	90303100	20608
Metrasafe-19	4-3/4 Digits, Analogue Bargraph, Wireless PC Interface, T-RMS, Backlit LCD, Autoranging, FULLY PROTECTED, Data & Peak Hold, Max/Min Record, AC/DC Voltage, AC/DC Current, Resistance, Capacitance, Temperature, Non Contact type Infrared Thermometer, Duty Cycle, Diode & Continuity Test. Confirms to CAT IV 600V.	17550	90303100	23693
PRO SOLAR-1	6000 Counts, Auto-backlit LCD, EN 61010-1, EN 61010-2-033 for CAT III 1000V, CAT IV 600V, EN 61326-1, designed for Solar PV application, to measure 2000V DC and 1500V AC T-RMS & DC/AC mV, AC/DC Current up to 10A, Resistance 40MΩ, Capacitance 10mF, Frequency 100kHz, Temperature 400°C, NCV, Diode & Continuity Test.	17600	90303100	23760
PRO 589	50,000 Counts TFT LCD Colour Display, 100kHz Bandwidth, Bluetooth, Trend Capture, Low Pass Filter, Surge Protection up to 8kV Peak, Full Overload Protection, UL Certified, CATIII 1000V, CATIV 600V, 0.05% Accuracy, T-RMS, MAX/MIN/AVG, PEAK MAX/MIN, Peak values of transients up to 250uS, AC+DC Measurement, Relative Function, Data Hold, Data Logging, Histogram Data with time stamp, Voltage 1000V AC/DC, Current 10A AC/DC, Resistance, Capacitance, Frequency, Temperature, Duty Cycle, Diode & Continuity	22725	90303100	30679
Metrasafe-20	4-5/6 Digits, 60,000 Counts, T-RMS Multimeter, OLED Display, 100kHz Bandwidth, Accuracy 0.025%, Lo-Z, AC/DC Voltage, AC/DC Current, Resistance, Process Measurement, Conductance, Capacitance, Frequency, Duty Cycle, Temperature, Diode & Continuity, Rechargeable battery, Mis-operation Alarm, Data Logger. Optional Bluetooth.	29250	90303100	39488
Digital Multimeter with Thermal Imager				
PRO TIM-900 NEW!!	4000 Counts, 2.4" TFT Colour Display, A/D Conversion with high sampling rate, High Accuracy, with built-in 80x80px Thermal Imager with Max, Min and Center crosshair targeting, 50Hz fast thermal image frame rate, Bluetooth interface, free Smartphone App, DC Voltage, AC & AC+DC TRMS Voltage, DC Current, AC & AC+DC TRMS Current, Resistance and Continuity test, Diode Test, Capacitance, Frequency, Duty Cycle, Auto Ranging, Auto Power-off, Built-in flashlight to access dark areas, Rechargeable battery, Surge Protection: 6kV peak per IEC 61010, CAT III 600V, CAT IV 300V	53550	90303100	72293
CEM DT-9889		73800	90303100	99630
Bench Type Multimeter				
45-TRMS	4½ digits bench multimeter for measuring DC and AC Voltage, DC and AC Current, Resistance, Capacitance, eHz, hFE, Diodes and Continuity.	10530	90303100	14216
55-TRMS	5-1/2 Digits Bench type Multimeter, 2,00,000 counts, high precision, multi-function and fully automatic functions of mathematical operations, capacitance, temperature and other basic measurements, 4.3-inch 480*272 TFT display, supports LAN, USB, RS-232C and GPIB (optional)	55625	90303100	75094
M-3511A	6-1/2 Digits Bench type Multimeter AC/DC V, AC/DC Current, Resistance, Cap and Frequency	61000	90303100	82350
M-3510A	6-1/2 Digits Bench type Multimeter AC/DC V, AC/DC Current, Resistance, Cap., Temp. and Frequency	76000	90303100	102600

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
M-3500A	6-1/2 Digits Bench type Multimeter with multiple options	112000	90303100	151200
Accessories for Digital Multimeter				
CA-01	Clamp On Current Adaptor to be used with any Multimeter with mV range, measures up to 200A AC	1350	90309090	1823
CA-1000D	Clamp On Current Adaptor to be used with any Multimeter with mV range, measures up to 600A/1000A AC/DC	5850	90309090	7898
TS-03	Infrared Temperature Adaptor to measure from -30 to 550 Degree C, can be used with any Multimeter with mV range	3750	90251920	5063
PD-28	High Voltage probe to measure 40kV DC and 28kV AC	8870	90303100	11975
ATL-PV	High Voltage Probe for P-V Multimeter SOLAR-1 and PV Clamp meter SOLAR-2	3225	90303100	4354
TL-70	Test Leads with right angled shrouded termination to fit modern multimeters, fitted with a 4mm shrouded socket, CAT III 1000V / 20A Rating	215	90303100	290
TL-74	1m silicon single insulated test leads with right angle shrouded banana plugs, CAT IV 600V, CAT III 1000V with protective cap, banana plug termination, dia of test lead point 2mm	390	90303100	527
TL-75	1m silicon double insulated test leads with right angle shrouded banana plugs, CAT IV 600V, CAT III 1000V with protective cap, banana plug termination, dia of test lead point 2mm	540	90303100	729
Flex Clamp	For PRO 27 and PRO Solar-3	4500	90303100	6075
ALCOHOL BREATH ANALYSER				
Alcohol Breath Analyser				
CEM DT-800A	Fuel cell type digital Alcohol Sensor with high accuracy, fast response/recovery time, convenient and fast detection. Two acousto-optic alarms for drink and drunkenness. Disposable blowing nozzle, Rechargeable Battery, Real time LCD display, Auto power-off.	16227	90308990	21906
OHMS METERS / INSULATION TESTERS				
Analogue Insulation Tester				
IT-500	Test Voltage: 500V, Insulation Resistance Range: 0 - 1000MΩ, with AC Voltage Test Facility	2100	90303900	2835
IT-1000	Test Voltage: 1000V, Insulation Resistance Range: 0 - 2000MΩ, with AC Voltage Test Facility	2200	90303900	2970
Digital Micro Ohms Meter				
53C	Digital Micro Ohms Meter to measure from 1uΩ to 2kΩ	6345	90303900	8566
53C-II	Micro-Processor based, Digital Micro Ohms meter to measure from 1uΩ to 2kΩ, with digital selection of ranges	6860	90303900	9261
UOT-10A	Digital Micro Ohms Meter with Test Current of 10A	90000	90303900	121500
7272A	10A Micro Ohms Meter with backlit LCD display, USB PC Interface, 500 Internal Memory, Four Wire measurement, Testing Current of 10A, Battery Operated, Measures from 10.0uΩ-50.00KΩ with accuracy of ±0.2%FS±10 dgt.	46000	90303900	62100

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
PRO 7273 NEW!!	1mA/10mA/100mA/1A/5A/10A, 1.0uΩ~50.00kΩ, Resolution 0.001Ω, Accuracy 0.2%±2uΩ, microprocessor technology, precise 4-wire method, with fast testing speed. Features Automatic & Manual Modes, Auto Test Current & 7 Manual Gears, Backlit Colour LCD Display, Bluetooth with Mobile App, USB Interface, Monitoring Software, Data Hold, Data Logging 600 Sets, Temperature Compensation, Automatic Discharge, user-settable Alarms, Rechargeable Battery & AC 220V Power options, IP65 dust & water proof.	50000	90303900	67500
PRO 7274 NEW!!	1mA/10ma/100mA/1A/5A/10A, 200.0uΩ~50.00kΩ, Resolution 0.1uΩ, Accuracy 0.2%±2dgt, precise 4-wire method, 2-channel A/D simultaneous detection, Automatic & Manual Modes, Auto Test & 7 Current Gears, 5" true colour LCD Touchscreen display with backlight adjustment, Bluetooth with Mobile App, USB Interface, Monitoring Software, built-in Printer, Data Logging 600 sets, Data Hold, Temperature Compensation, Automatic Discharge, user-settable Alarms, Clock function, Rechargeable Battery & AC 220V Power options, IP65 dust & water proof.	82000	90303900	110700
UONT-100A	Digital Micro Ohms Meter with Test Current of 100A	98500	90303900	132975
UONT-200A	Digital Micro Ohms Meter with Test Current of 200A	188125	90303900	253969
PRO 8100 NEW!!	≤ 5A/10A/30A/50A/80A/100A, Step Current: 2.5A, up to 87 current gears, 1μΩ~5mΩ, High Resolution:0.01μΩ, Accuracy ±(reading*0.1%+measurement range*0.2%+1μΩ). Features 4-wire measurement, high stability with open circuit and overheating protection, 5.6" industrial backlit LCD with high-brightness colour, Data Logging upto 999 sets, Data Query function, built-in Printer, Rechargeable Battery, IEC61010-1, CAT III 600V, Pollution Level 2, Regulation of DC Digital Ohmmeter, JIG166-1993 Verification Regulation of DC Resistors, DL/T967-2005 Verification regulation of loop resistance tester and DC resistance high-speed tester. Portable & hand-held.	200000	90303900	270000
PRO 8220 NEW!!	≤ 5A/10A/30A/50A/80A/100A/200A/220A, Step Current: 2.5A, up to 87 current gears, 1μΩ~500uΩ, High Resolution:0.01μΩ, Accuracy ±(reading*0.1%+measurement range*0.2%+1μΩ). Features 4-wire measurement, high stability with open circuit and overheating protection, 5.6" industrial backlit LCD with high-brightness colour, Data Logging upto 999 sets, Data Query function, built-in Printer, Rechargeable Battery, IEC61010-1, CAT III 600V, Pollution Level 3, Regulation of DC Digital Ohmmeter, JIG166-1993 Verification Regulation of DC Resistors, DL/T967-2005 Verification regulation of loop resistance tester and DC resistance high-speed tester. Portable & hand-held.	300000	90303900	405000
Digital Milli Ohms Meter				
52C	Hand Held, 0.1mΩ to 40Ω, 4 wire Kelvin type connection, also measures AC/DC Voltage, AC/DC Current, Resistance, Capacitance and continuity	10300	90303900	13905
Digital Insulation Tester				
DIT-99A	Digital Battery Cum Mains Operated Insulation Tester for 100V / 200MΩ	3065	90303900	4138
DIT-99B	Digital Battery Cum Mains Operated Insulation Tester for 250V / 200MΩ	3065	90303900	4138
DIT-99C	Digital Battery Cum Mains Operated Insulation Tester for 500V / 1GΩ	3065	90303900	4138

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
DIT-99D	Digital Battery Cum Mains Operated Insulation Tester for 1000V / 2GΩ	3065	90303900	4138
DIT-909	9999 Counts Backlit LCD, Low Battery Indication, Dat Hold, Timer Function up to 10mins, Comparator, 99 Data Records, USB PC Interface (optional) Test Voltage: 50V / 100V / 250V / 500V / 1000V, 200GΩ, AC Voltage T-RMS, DC Voltage, Freuqnecy, Capacitance, Continuity Test, With Remote Probe, IP54	29850	90303900	40298
DIT-910	4 Digits, with GO-NO-GO functions, 250V/500MΩ, 500V/1GΩ, 1000V/2GΩ. With in-built DC voltage converter – can change 12V voltage into 250V / 500V / 1000V DC voltage. Accuracy: ±10%, Short Circuit Current: <1.6mA.	4730	90303900	6386
DIT-911 NEW!!	3 1/2 Digits 1999 Counts, 0.00MΩ~11.0GΩ at 250V / 500V / 1000V, Accuracy ±3%+5dgt, with DC Open Circuit Voltage, Short Circuit Current, Rated Test Current, AC Voltage Test, PI, DAR and Automatic Discharge	4400	90303900	5940
DIT-912	4 Digits with Analogue Bargraph, measures upto 2000M.Ohms at 250V / 500V / 1000V, measures 600V AC/DC, Low Resistance up to 4000 Ohms and Continuity test. Fully Protected on all ranges	10900	90303900	14715
DIT-913	3 1/2 Digits 1999 Counts, 2000MΩ @250V / 20GΩ @500V / 20GΩ @1000V / 20GΩ @2500V, Accuracy: ±3%, Data Hold	6300	90303900	8505
DIT-913A NEW!!	3 1/2 Digits 1999 Counts, 0.00MΩ~22.0GΩ at 500V / 1000V / 2500V, Accuracy ±2%+3dgt, with DC Open Circuit Voltage, Short Circuit Current, Rated Test Current, AC Voltage Test, PI, DAR and Automatic Discharge	5175	90303900	6986
DIT-321	Digital Insulation Resistance Tester with Bui-in Multimeter, 3-3/4 Digits 3999 Counts, Backlit LCD, Data Hold, Test Voltage: 250V / 500V / 1000V, upto 40G.Ohms, Measures AC/DC Voltage, AC/DC Current up to 400mA, Resistance, Capacitance, Frequency, Diode & Continuity Test Facility.	4950	90303900	6683
DIT-322	Digital Insulation Resistance Tester with Built-in Multimeter, 3-3/4 Digits 3999 Counts, Backlit LCD, Data Hold, Test Voltage: 500V / 1000V / 2500V, upto 40G.Ohms, Measures AC/DC Voltage, AC/DC Current up to 400mA, Resistance, Capacitance, Frequency, Diode & Continuity Test Facility.	6450	90303900	8708
DIT-914	Battery cum Mains Operated, with facility to measure AC Voltage, Low Resistance, Continuity, 500V/2000MΩ, 1000V/2000MΩ, 2500V/20GΩ, 5000V/200GΩ	16650	90303900	22478
DIT-916	Selectable testing voltages - one testing instrument for low and high voltage systems from 500/1000/2500 and 5000V, Insulation resistance measurement up to 1T Ω, User selectable programmable timer (10s to 30 min), Automatic discharge of test object after completion of measurement, Diagnostic tools, Polarization index (PI), Dielectric absorption ratio (DAR), USB PC Interface	32110	90303900	43349
DIT-921	Battery cum Mains Operated, with facility to measure, PI, DAR, AC Voltage, Low Resistance, Continuity, 500V/6GΩ, 1000V/6GΩ, 2500V/60GΩ, 5000V/60GΩ	29500	90303900	39825
High Voltage Digital Insulation Tester				
PRO DIT-925 NEW!!	0.50MΩ ~ 2.00TΩ, 250V/500V/1000V/2500V/5000V/5kV, Accuracy ±5%, with Polarisation Index measurement (PI); Absorption Ratio (DAR); Ramp Test mode (RAMP) ; Dielectric discharge, Filtered Resistance test (FR), Voltage measurement (V); Current measurement (nA), Data Logging, Automatic Discharge, Full-colour Touchscreen, Rechargeable Battery, IP65 protection, USB PC Interface for data download and analysis.	60500	90303900	81675

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
PRO DIT-927 NEW!!	0.50MΩ ~ 5.00TΩ, 250V/500V/1000V/2500V/5000V/10kV, Accuracy ±5%, with Polarisation Index measurement (PI); Absorption Ratio (DAR); Ramp Test mode (RAMP) ; Dielectric discharge, Filtered Resistance test (FR), Voltage measurement (V); Current measurement (nA), Data Logging, Automatic Discharge, Full-colour Touchscreen, Rechargeable Battery, IP65 protection, USB PC Interface for data download and analysis.	67000	90303900	90450
DIT-930	0.01MΩ ~ 10TΩ, 100V/250V/500V/1000V/2500/5kV, Resolution 0.01MΩ, Accuracy ±3%rdg ±5dgt, Absorption Ratio and Polarization Index Measurement, Test Insulation resistance, Voltage, Current, Capacitance. With Rechargeable Battery, 4-bit large LCD backlit display, USB interface, Monitoring Software, Data Storage. Certified IEC61010-1, IEC1010-2-31, IEC61557-1,5, IEC60529(IP54) pollution grade 2, CAT III 1000V	63000	90303900	85050
DIT-930E	0.01MΩ ~ 35TΩ, 250V/500V/1000V/2500V/5000V/10kV, Resolution 0.01MΩ, Accuracy ±3%rdg ±5dgt, Absorption Ratio and Polarization Index Measurement, Test Insulation resistance, Voltage, Current, Capacitance. With Rechargeable Battery, 4-bit large LCD backlit display, USB interface, Monitoring Software, Data Storage. Certified IEC61010-1, IEC1010-2-31, IEC61557-1,5, IEC60529(IP54) pollution grade 2, CAT III 1000V.	69350	90303900	93623
DIT-930F	0.01MΩ ~ 50TΩ, 500V/1000V/2500V/5000V/10kV/15kV, Resolution 0.01MΩ, Accuracy ±3%rdg ±5dgt, Absorption Ratio and Polarization Index Measurement, Test Insulation resistance, Voltage, Current, Capacitance. With Rechargeable Battery, 4-bit large LCD backlit display, USB interface, Monitoring Software, Data Storage. Certified IEC61010-1, IEC1010-2-31, IEC61557-1,5, IEC60529(IP54) pollution grade 2, CAT III 1000V.	106000	90303900	143100
DIT-931 NEW!!	0.50MΩ ~ 10.0TΩ, 250V/500V/1kV/2.5kV/5kV, Accuracy ±5%rdg±3dgt, Large Touchscreen with Multifunction Colour Display. Test Voltage, Capacitance, Current. Insulation Resistance test (IR), Polarisation Index test (PI), Dielectric Absorption Ratio Test (DAR), Ramp Test mode (RAMP), Dielectric Discharge (DD). With Voltage monitor function, Test Timer function, Automatic Discharge, Data Logging for 1000 sets, Rechargeable Battery, USB PC Interface for data download & analysis, IP65 protection, Certification IEC61010-1, IEC61326-1	97800	90303900	132030
DIT-931E NEW!!	0.50MΩ ~ 20.0TΩ, 250V/500V/1kV/2.5kV/5kV/10kV, Accuracy ±5%rdg±3dgt, Large Touchscreen with Multifunction Colour Display. Test Voltage, Capacitance, Current. Insulation Resistance test (IR), Polarisation Index test (PI), Dielectric Absorption Ratio Test (DAR), Ramp Test mode (RAMP), Dielectric Discharge (DD). With Voltage monitor function, Test Timer function, Automatic Discharge, Data Logging for 1000 sets, Rechargeable Battery, USB PC Interface for data download & analysis, IP65 protection, Certification IEC61010-1, IEC61326-1	117000	90303900	157950
DIT-931F NEW!!	0.50MΩ ~ 30.0TΩ, 250V/500V/1kV/2.5kV/5kV/10kV/15kV, Accuracy ±5%rdg±3dgt, Large Touchscreen with Multifunction Colour Display. Test Voltage, Capacitance, Current. Insulation Resistance test (IR), Polarisation Index test (PI), Dielectric Absorption Ratio Test (DAR), Ramp Test mode (RAMP), Dielectric Discharge (DD). With Voltage monitor function, Test Timer function, Automatic Discharge, Data Logging for 1000 sets, Rechargeable Battery, USB PC Interface for data download & analysis, IP65 protection, Certification IEC61010-1, IEC61326-1	162000	90303900	218700

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
DIT-950	High Precision IR Tester 10kΩ to 50TΩ, 500V, High measurement accuracy: ±2% (< 1TΩ), Dual Channel, 320×240 dot-matrix LCD Display, Contact detection function, 7 Current Ranges, Manual or Auto Range modes, 4-bin Comparison function, Programmable Sequence Test mode, R-T and I-T Curve test and display mode, Auto store setup parameters. Interfaces: GPIB, (optional); RS232C; HANDLER interface output; USB (USBTMC and USB CDC support); USB HOST; SCANNING.	423000	90303900	571050
DIT-951	High Precision IR Tester 10kΩ to 100TΩ, 1000V, High measurement accuracy: ±2% (< 1TΩ), Dual Channel, 320×240 dot-matrix LCD Display, Contact detection function, 7 Current Ranges, Manual or Auto Range modes, 4-bin Comparison function, Programmable Sequence Test mode, R-T and I-T Curve test and display mode, Auto store setup parameters. Interfaces: GPIB, (optional); RS232C; HANDLER interface output; USB (USBTMC and USB CDC support); USB HOST; SCANNING.	400000	90303900	540000
Million MegOhms Meter				
MMM-1	Analogue Million MegOhms Meter for test voltage of 100, 200, 300, 400 and 500V, measures up to 10 Million MegOhms	18275	90303900	24671
OSCILLOSCOPES				
Cathode Ray Oscilloscopes				
OS-5010A	10MHz Single Channel, Cathode Ray Oscilloscope	19675	90302000	26561
OS-5020	20MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with 1:1 and 10:1 probes	22900	90302000	30915
OS-5020C	20MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with component test facility, comes complete with 1:1 and 10:1 probes	25000	90302000	33750
OS-5030	30MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with 1:1 and 10:1 probes	23600	90302000	31860
OS-5030C	30MHz Dual Channel Dual Trace Cathode Ray Oscilloscope with component test facility, comes complete with 1:1 and 10:1 probes	27000	90302000	36450
OS-5060	60MHz Dual Channel Four Trace Cathode Ray Oscilloscope with 1:1 and 10:1 Probes	74175	90302000	100136
OS-5100	100MHz Dual Channel Four Trace Cathode Ray Oscilloscope with 1:1 and 10:1 Probes	88690	90302000	119732
OS-6010 NEW!!	10MHz Single Channel Oscilloscope	14250	90302000	19238
Digital Storage Oscilloscope				
DSO-5050E	50MHz DSO with colour display, 500MSa/Sec sampling rate, with USB PC Interface cable and software	23000	90302000	31050
DSO-5100E	100MHz DSO with colour display, 1GSa/Sec sampling rate, with USB PC Interface cable and software	25000	90302000	33750
DSO-5150E	150MHz DSO with colour display, 1GSa/Sec sampling rate, with USB PC Interface cable and software	32000	90302000	43200
DSO-5200E	200MHz DSO with colour display, 1GSa/Sec sampling rate, with USB PC Interface cable and software	40000	90302000	54000
DSO-6050 NEW!!	50MHz DSO with colour display, 1GSa/Sec sampling rate, with USB PC Interface cable and software, with USB device & host	22400	90302000	30240
DSO-6100 NEW!!	100MHz DSO with colour display, 1GSa/Sec sampling rate, with USB PC Interface cable and software	26500	90302000	35775
DSO-6200 NEW!!	200MHz DSO with colour display, 1GSa/Sec sampling rate, with USB PC Interface cable and software	39700	90302000	53595

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
DSO-5074E	70MHz DSO with 4 channels, colour display, 500MSa/Sec sampling rate, with USB PC Interface cable and software	67000	90302000	90450
DSO-5104E	100MHz DSO with 4 channels, colour display, 500MSa/Sec sampling rate, with USB PC Interface cable and software	71250	90302000	96188
DSO-6104 NEW!!	100MHz DSO with 4 channels, colour display, 1GSa/Sec sampling rate, with USB PC Interface cable and software	39700	90302000	53595
Mixed Signal Oscilloscope				
MSO-6102E NEW!!	100MHz Mixed Signal Oscilloscope, Dual Channel DSO and 16 Channel Logic Analyzer, 1GSA/s sampling rate	85000	90302000	114750
PC Based Digital Storage Oscilloscope				
PDSO-6074 NEW!!	70MHz, PC based, 4 Channel Digital Storage Oscilloscope, 8 bits	49500	90302000	66825
PDSO-6074A NEW!!	70MHz, PC based, 4 Channel Digital Storage Oscilloscope, 8/12/14 bits	67000	90302000	90450
PDSO-6104 NEW!!	100MHz, PC based, 4 Channel Digital Storage Oscilloscope, 8 bits	54500	90302000	73575
PDSO-6104A NEW!!	100MHz, PC based, 4 Channel Digital Storage Oscilloscope, 8/12/14 bits	79200	90302000	106920
Accessories to Digital Storage Oscilloscope				
PD-20S	High Voltage Probe to be used with any oscilloscope (Analogue or Digital Storage) to measure High Voltage Waveform of 30kV DC and 20kV AC	9900	90308990	13365
OP-60	OP-60 is a x 1 / x 10 attenuation modular probe designed to be used with 60MHz oscilloscopes with an input impedance of 1MΩ.	800	90308990	1080
OP-100	OP-100 is a x 1 / x 10 attenuation modular probe designed to be used with 100MHz oscilloscopes with an input impedance of 1MΩ.	1200	90308990	1620
OP-250	OP-250 is a x 100 attenuation modular probe designed to be used with 250MHz oscilloscopes with an input impedance of 100MΩ.	6235	90308990	8417
PANEL METERS				
Digital Ammeter				
CE-0102A 96x48	3-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 48 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	1400	90303100	1890
CE-0102A 96x96	3-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 96 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	1400	90303100	1890
CE-0102A 96x48	3-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 48 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	1400	90303100	1890
CE-0102A 96x96	3-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 96 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	1400	90303100	1890
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size				
CE-0102A 96x48	4-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 48 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	2520	90303100	3402
CE-0102A 96x96	4-1/2 Digits Panel Flush Mounting AC Ammeter, Size - 96 x 96 mm For CT Operated -/5A or -/1A or for Direct Operated up to 20A AC. For CT Operated the maximum current shall be 1999 A	2520	90303100	3402

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
CE-0102A 96x48	4-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 48 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	2520	90303100	3402
CE-0102A 96x96	4-1/2 Digits Panel Flush Mounting DC Ammeter, Size - 96 x 96 mm , For Shunt Operated 75mV or for Direct Operated up to 20A DC. For Shunt Operated the maximum current shall be 1999 A	2520	90303100	3402
Digital Ammeter Controller				
CE-0102AC 2SP	Digital Ammeter with Two Set Point to control the current below a given pair of set points. Size - 96 x 96 mm sq. With 2NO + 2NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	4500	90303100	6075
Digital Frequency Meter				
CE-500F 99.99Hz	4 Digits, Panel Flush Mounting, 96 X 48 mm sq, Input 10 - 500V, Measuring range 20 - 99.99 Hz.	1320	90303100	1782
CE-500F 96 x 96	4 Digits, Panel Flush Mounting, 96 X 96 mm sq, Input 10 - 500V, Measuring range 20 - 99.99 Hz.	1320	90303100	1782
CE-500F 999.9Hz	4 Digits, Panel Flush Mounting, 96 X 48 mm sq, Input 50 - 500V, Measuring range 0 - 999.9 Hz.	1450	90303100	1958
CE-500F 96 x 96	4 Digits, Panel Flush Mounting, 96 X 96 mm sq, Input 50 - 500V, Measuring range 0 - 999.9 Hz.	1450	90303100	1958
Digital VA Meter				
CE-0303VA	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	4380	90303100	5913
CE-0304VA	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	4380	90303100	5913
Digital VAR Meter				
CE-0303VAR	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	4380	90303100	5913
CE-0304VAR	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	4380	90303100	5913
Digital KWh Meter				
CE-0102EML NEW!!	Digital KWh Meter with LCD Display for Single phase Two wire loads	3975	90303100	5366
CE-0303EML	Digital KWh Meter with LCD Display for Three phase Three wire Two element loads	4630	90303100	6251
CE-0304EML	Digital KWh Meter with LCD Display for Three Phase Four wire Three Element loads	4630	90303100	6251
Digital Phase Angle Meter				
CE-0102D	Digital Phase Angle Meter, 96 x 96 mm sq, can measure Phase Angle between Voltage and Current	3900	90303100	5265
Digital Power Factor Meter				
CE-0102PF 96x48	Microprocessor Based, 96 x 48 mm sq, For Single Phase, Red LED Display	3550	90303100	4793
CE-0102PF 96x96	Microprocessor Based, 96 x 96 mm sq, For Single Phase, Red LED Display	3550	90303100	4793
CE-0303PF	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element , Red LED Display	4515	90303100	6095

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
CE-0304PF	Microprocessor Based, 96 x 96 mm sq, For Three Phase Four Wire Three Element, Red LED Display	4515	90303100	6095
Digital Power Analyser				
CE-0102PA	Digital Ampere, Volt,PF and Watt meter combined in 96 x 96 mm sq for single phase loads	4900	90303100	6615
Digital Three Phase Ammeter				
CE-03A	Microprocessor Based, 96 x 96 mm sq, with in built three phase selector switch, displays Current in three phases, CT Ratio programmable. Programmable up to 3000A AC	2100	90303100	2835
Digital Three Phase Voltmeter				
CE-03V	Microprocessor Based, 96 x 96 mm sq, with in built three phase selector switch, displays Line to Line and Line to Neutral Voltage. Direct Operated and PT Ratio programmable	2100	90303100	2835
Digital Voltage Controller				
CE-0102VC 2SP	Digital Voltmeter with Two Set Point to control the Voltage between a given set points.Size - 96 x 96 mm sq. With 2NO + 2NC Contact. Auxiliary Power Supply 230V AC / 110V AC 50Hz. (Any One)	4300	90303100	5805
Digital Voltmeter				
CE-0102V	3-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1400	90303100	1890
CE-0102V 96	3-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1400	90303100	1890
CE-0102V	3-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1400	90303100	1890
CE-0102V 96	3-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	1400	90303100	1890
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size				
CE-0102V 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2690	90303100	3632
CE-0102V 96 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting AC Voltmeter, for measuring AC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2690	90303100	3632
CE-0102V 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 48 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2690	90303100	3632
CE-0102V 96 4-1/2 Digits	4-1/2 Digits Red LED Display, panel flush mounting DC Voltmeter, for measuring DC Voltage, Size - 96 x 96 mm, range 0 - 20mV / 200mV / 2V / 200V / 1000V (Any One Range)	2690	90303100	3632
Digital Wattmeter				
CE-0102W	Microprocessor Based, 96 x 48 mm sq, For Single Phase, Red LED Display	3655	90303100	4934
CE-0102W 96 x 96	Microprocessor Based, 96 x 96 mm sq, For Single Phase, Red LED Display	3655	90303100	4934
CE-0303W	Microprocessor Based, 96 x 96 mm sq, For Three Phase Three Wire Two Element, Red LED Display	4515	90303100	6095

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
CE-0304W	Microprocessor Based, 96 x 96 mm sq, For Thre Phase Four Wire Three Element, Red LED Display	4515	90303100	6095
Event Counter				
CTR-49	6 Digits Red LED Display, Event Counter, 1 to 999999 Counts, 96 x 48 mm sq	2600	90292090	3510
N.B. - Please ask for the prices in case if you require this in 96 x 96 mm sq size				
Hour Meter				
NE 045/7S DC	7 Digits, measures up to 99999.99 hours, 10 - 48V DC operated, 46 x 46 mm sq size panel cutout	1185	90292090	1600
NE 045/7	7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout	645	90292090	871
HM-01	7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout	540	90292090	729
Integrated Meter				
CE-0303IM	Three Phase Three Wire Two Element loads for energy and power measurment, measure each phase I, V, Hz, PF, KW, KVA, KVAR, KWh, KVAh, KVARh and MDI	8065	90303100	10888
CE-0304IM	Three Phase Four Wire Three Element loads for energy and power measurment, measure each phase I, V, Hz, PF, KW, KVA, KVAR, KWh, KVAh, KVARh and MDI	8065	90303100	10888
RPM Meter				
CTR-49	6 Digits Red LED Display, Event Counter, 1 to 999999 Counts, 96 x 48 mm sq	3000	90292090	4050
Tap Position Indicator				
CE-0102V	Digital type, Panel Mounting, Tap Position indicator, 96mm sq or 96x48 mm sq	2580	85049010	3483
Time Totaliser				
TT-300	6 Digits LED Display, 96 x 48 mm sq, Auto range from 9999.99 to 999999Hrs.	2700	90292090	3645
TT-302	6 Digits LED Display, 96 x 96 mm sq, Auto range from 9999.99 to 999999Hrs.	2700	90292090	3645
POWER METERS & ANALYSERS				
Power Quality Analyser				
PRO 531 NEW!!	5.6" LCD colour display, high resolution, shock-proof shell structure. Simultaneously measures 4-channel Current (ABC three phase and neutral wire current), 4-channel Voltage (ABC three-phase voltage & neutral line voltage to ground), Peak Value of Current Voltage, Max/Min, Three Phase Imbalance Factor, Short-time Voltage Flicker, Transformer K Factor, Active Power, Reactive Power, Apparent Power, Power Factor and Displacement Power Factor, Total Harmonic Distortion and Harmonic, etc., display Real-time Waveform, Harmonic Ratio Bar Charts of Current Voltage; dynamically capture instantaneous change of Voltage Current, monitoring Starting Current & Power Parameters, Alarm List, Trend Charts, Data Logging. Adopts DSP + ARM double processor architecture.	192000	90308990	259200
Set of 4 Clamps 10A NEW!!	Optional set of 10A Clamps for the PRO 531	21900	90308990	29565
Set of 4 Clamps 100A NEW!!	Optional set of 100A Clamps for the PRO 531	24800	90308990	33480

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
Set of 4 Clamps 1000A NEW!!	Optional set of 1000A Clamps for the PRO 531	44800	90308990	60480
Set of 4 Clamps 6000A NEW!!	Optional set of Clamps for the 6000A PRO 531	78500	90308990	105975
PRO 540 NEW!!	Portable Power Quality Analyser	On Request	90308990	
PRO 541 NEW!!	Portable Power Quality Analyser with built-in Thermal Imager	On Request	90308990	
Power Meter				
PM-10 NEW!!	Bench-top high-precision Power Meter up to 900W, measure true-value Voltage, true-value Current, Peak Current, Power, Power Factor and Frequency simultaneously with automatic switching and high accuracy of $\pm 0.4\%$ reading+0.1% range.	17700	90303100	23895
PM-10B NEW!!	Bench-top high-precision Power Meter up to 3000W, measure true-value Voltage, true-value Current, Peak Current, Power, Power Factor and Frequency simultaneously with automatic switching and high accuracy of $\pm 0.4\%$ reading+0.1% range.	57600	90303100	77760
New Model		9700	90303100	13095
POWER SUPPLIES				
AC Power Supply				
APS-4002 NEW!!	Adjustable, multi-function AC power source that integrates voltage, current, power and power factors. Single Output with Backlit LCD Display of Variables. 0 - 40V / 0 - 2A AC.	57825	85042100	78064
APS-4003 NEW!!	Adjustable, multi-function AC power source that integrates voltage, current, power and power factors. Single Output with Backlit LCD Display of Variables. 0 - 40V / 0 - 3A AC.	73575	85042100	99326
APS-4005 NEW!!	Adjustable, multi-function AC power source that integrates voltage, current, power and power factors. Single Output with Backlit LCD Display of Variables. 0 - 40V / 0 - 5A AC.	83925	85042100	113299
APS-6003 NEW!!	Adjustable, multi-function AC power source that integrates voltage, current, power and power factors. Single Output with Backlit LCD Display of Variables. 0 - 60V / 0 - 3A AC.	34200	85042100	46170
APS-6006 NEW!!	Adjustable, multi-function AC power source that integrates voltage, current, power and power factors. Single Output with Backlit LCD Display of Variables. 0 - 60V / 0 - 6A AC.	44550	85042100	60143
APS-60031 NEW!!	Adjustable, multi-function AC power source that integrates voltage, current, power and power factors. Single Output with Backlit LCD Display of Variables. 0 - 600V / 0 - 30A AC.	39375	85042100	53156
APS-7002 NEW!!	Adjustable, multi-function AC power source that integrates voltage, current, power and power factors. Single Output with Backlit LCD Display of Variables. 0 - 70V / 0 - 2A AC.	73575	85042100	99326
APS-7004 NEW!!	Adjustable, multi-function AC power source that integrates voltage, current, power and power factors. Single Output with Backlit LCD Display of Variables. 0 - 70V / 0 - 4A AC.	86175	85042100	116336
APS-7008 NEW!!	Adjustable, multi-function AC power source that integrates voltage, current, power and power factors. Single Output with Backlit LCD Display of Variables. 0 - 70V / 0 - 8A AC.	146925	85042100	198349
APS-51005 NEW!!	5KVA Single phase input and Single Phase Output with RS-232 interface	222000	85042100	299700
APS-51008 NEW!!	8KVA Single phase input and Single Phase Output with RS-232 interface	298980	85042100	403623
APS-51010 NEW!!	10KVA Single phase input and Single Phase Output with RS-232 interface	345400	85042100	466290
APS-51015 NEW!!	15KVA Three Phase Input and Single phase output with RS-232 interface	453860	85042100	612711
APS-51020 NEW!!	20KVA Three Phase Input and Single phase output with RS-232 interface	515680	85042100	696168

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
APS-51030 NEW!!	30KVA Three Phase Input and Single phase output with RS-232 interface	773520	85042100	1044252
APS-51045 NEW!!	45KVA Three Phase Input and Single phase output with RS-232 interface	979660	85042100	1322541
APS-51050 NEW!!	50KVA Three Phase Input and Single phase output with RS-232 interface	1082840	85042100	1461834
APS-51060 NEW!!	60KVA Three Phase Input and Single phase output with RS-232 interface	1186000	85042100	1601100
APS-51075 NEW!!	75KVA Three Phase Input and Single phase output with RS-232 interface	1495340	85042100	2018709
APS-51100 NEW!!	100KVA Three Phase Input and Single phase output with RS-232 interface	1701480	85042100	2296998
APS-51150 NEW!!	150KVA Three Phase Input and Single phase output with RS-232 interface	2320340	85042100	3132459
DC Regulated Power Supply				
RPS-3002	Single Output with Backlit LCD Display of Variable 0 - 30V / 0 - 2A DC	8545	85042100	11536
RPS-3005	Single Output with Backlit LCD Display of Variable 0 - 30V / 0 - 5A DC	8545	85042100	11536
RPS-3010	Single Output with LED Display of Variable 0 - 30V / 0 - 10A DC	20910	85042100	28229
RPS-3020	Single Output with LED Display of Variable 0 - 30V / 0 - 20A DC	32500	85042100	43875
RPS-3030	Single Output with LED Display of Variable 0 - 30V / 0 - 30A DC	55000	85042100	74250
RPS-6005	Single Output with LED Display of Variable 0 - 60V / 0 - 05A DC	21500	85042100	29025
RPS-6010	Single Output with LED Display of Variable 0 - 60V / 0 - 10A DC	39399	85042100	53188
RPS-6030	Single Output with LED Display of Variable 0 - 60V / 0 - 30A DC	77500	85042100	104625
RPS-10003 NEW!!	Single Output with LED Display of Variable 0 - 100V / 0 - 03A DC	29565	85042100	39913
RPS-20002 NEW!!	Single Output with LED Display of Variable 0 - 200V / 0 - 02A DC	34400	85042100	46440
RPS-20005 NEW!!	Single Output with LED Display of Variable 0 - 200V / 0 - 05A DC	40680	85042100	54918
RPS-3002-2	Dual Output with Backlit LCD Display of Variable 0 - 30V / 0 - 3A DC	16665	85042100	22498
RPS-3005-2	Dual Output with Backlit LCD Display of Variable 0 - 30V / 0 - 5A DC	20855	85042100	28154
RPS-3003-3	Triple Output with Backlit LCD Display, Dual 0 - 30V / 0 - 3A DC and Fixed 5V/3A	16665	85042100	22498
RPS-3005-3	Triple Output with Backlit LCD Display, Dual 0 - 30V / 0 - 5A DC and Fixed 5V/3A	20855	85042100	28154
Programmable DC Power Supply				
PRPS-3005 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD. Variable 0-30V/0-5A DC. Remote control from computer via USB.	12040	85042100	16254

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
PRPS-3010 NEW!!	Programmable DC Regulated Power Supply with with Single Output and Backlit LCD. Variable 0–30V/0–10A DC. Remote control from computer via USB.	38375	85042100	51806
PRPS-3020 NEW!!	Programmable DC Regulated Power Supply with with Single Output and Backlit LCD. Variable 0–30V/0–20A DC. Remote control from computer via USB.	52550	85042100	70943
PRPS-3030 NEW!!	Programmable DC Regulated Power Supply with with Single Output and Backlit LCD. Variable 0–30V/0–30A DC. Remote control from computer via USB.	84925	85042100	114649
PRPS-6005 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 60V / 0–5A DC	36800	85042100	49680
PRPS-6010 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 60V / 0– 10A DC	52100	85042100	70335
PRPS-10003 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 100V / 0–3A DC	49850	85042100	67298
PRPS-100100 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 100V / 0– 100A DC	364000	85042100	491400
PRPS-20002 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 200V / 0–2A DC	72125	85042100	97369
PRPS-20050 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 200V / 0– 50A DC	364000	85042100	491400
PRPS-30001 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 300V / 0– 1A DC	74375	85042100	100406
PRPS-30030 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 300V / 0– 30A DC	345000	85042100	465750
PRPS-40025 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 400V / 0– 25A DC	364000	85042100	491400
PRPS-50020 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 500V / 0– 20A DC	364000	85042100	491400
PRPS-60015 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 600V / 0– 15A DC	347000	85042100	468450
PRPS-75013 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 750V / 0– 13A DC	360000	85042100	486000
PRPS-100010 NEW!!	Programmable DC Regulated Power Supply with Single Output and Backlit LCD Display of Variable 0 – 1000V / 0– 10A DC	365000	85042100	492750
PRPS-3003-3 NEW!!	Programmable DC Regulated Power Supply with Triple Output and Backlit LCD Display of Variable 0 – 30V / 0– 3A DC	28025	85042100	37834
PRPS-3005-3 NEW!!	Programmable DC Regulated Power Supply with Triple Output and Backlit LCD Display of Variable 0 – 30V / 0– 5A DC	32525	85042100	43909
PRPS-3010-3 NEW!!	Programmable DC Regulated Power Supply with Triple Output and Backlit LCD Display of Variable 0 – 30V / 0– 10A DC	51875	85042100	70031
PRPS-6003-3 NEW!!	Programmable DC Regulated Power Supply with Triple Output and Backlit LCD Display of Variable 0 – 60V / 0– 3A DC	49625	85042100	66994
PRPS-6005-3 NEW!!	Programmable DC Regulated Power Supply with Triple Output and Backlit LCD Display of Variable 0 – 60V / 0– 5A DC	54125	85042100	73069
PRPS-3005-4 NEW!!	Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 30V / 0– 5A DC	147375	85042100	198956
PRPS-3010-4 NEW!!	Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 30V / 0– 10A DC	207675	85042100	280361
PRPS-6003-4 NEW!!	Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 60V / 0– 3A DC	174374	85042100	235405
PRPS-6005-4 NEW!!	Programmable DC Regulated Power Supply with Four Outputs and Backlit LCD Display of Variable 0 – 60V / 0– 5A DC	228375	85042100	308306

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
RESISTANCE BRIDGES (KELVIN & WHEATSTONE)				
Kelvin Double Bridge				
KDBR	Oxford Brand Kelvin Double bridge, with spot reflecting galvanometer, High Current DC power supply and wooden stand for specimen	77400	90230090	104490
Wheatstone Bridge				
WSB	OXFORD Brand Wheatstone Bridge	16600	90230090	22410
RPM METERS				
Stroboscope				
DT-2350A	Digital Stroboscope, 50 to 12,000FPM, 230V Single Phase AC Operated	13275	90292090	17921
DT-2350B	Digital Stroboscope, 50 to 40,000FPM, 230V Single Phase AC Operated	23625	90292090	31894
DT-720	LED Stroboscope to measure high-speed rotating objects without direct contact. No reflective tape required. 60-49999 RPM. Accuracy 0.001%. Luminance 750 LUX. Rechargeable battery with USB charging.	9675	90292090	13061
DT-720-2	LED Stroboscope to measure high-speed rotating objects without direct contact. No reflective tape required. 60-99999 RPM. Accuracy: 0.001%. Luminance: 1500 LUX. Rechargeable battery with USB charging.	11825	90292090	15964
Tachometer				
DT-2235	Contact type Digital Tachometer, measures up to 50,000RPM	2995	90292090	4043
NCTM-500	Non-contact type Digital Tachometer With Counter, Data Hold, Measures from 50mm to 200mm, RPM Up to 99999RPM, and Counts up to 99999 Counts	2275	90292090	3071
NCTM-1000	Non-contact type Digital Tachometer Cum Counter. Max / Min . Last Data Record, 2 to 99,999 RPM, 1 TO 99,999 Counts	3750	90292090	5063
NCTM-2000	Contact cum Non-contact type Digital Combined Tachometer, Max/Min, Last Record, 20,000RPM in contact mode and 99,999 RPM in non contact mode, measures Rotation speed, total revolution, frequency, surface speed and length	6750	90292090	9113
NCTM-3000	Contact and Non-contact type Digital Combined Tachometer with non-contact laser sighting for measuring from up to 12 feet distance. 20,000 RPM in contact mode and 200,000 RPM in non-contact mode.	7500	90292090	10125
SHORT TURN INDICATOR				
Short Turn Indicator				
Little Giant	9V Battery operated, to be used in single coils, simple insertion of coil on mandrill.	17740	90308990	23949
SPECTRUM ANALYSER				
Spectrum Analyzer				
AT-5010	1050MHz Spectrum Analyzer	125245	90302000	169081
AT-5011	1050MHz Spectrum Analyzer With Marker Generator	174000	90302000	234900
STATIC CHARGE METER				
Static Charge Meter				

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
SC-291	0~±20.000kV, Measuring distance: 2.54cms (1 inch), Warning alarm setting, DATA / PEAK hold. Backlight function, Auto power off with disable function, Zero function and low battery indicate, Manual data memory storing 99 data sets.	30375	90303100	41006
TEMPERATURE CONTROLLERS & INDICATORS				
Digital Temperature Controller				
DTC-200	Digital Temperature Controller 96 x 96 mm sq, with 1NO + 1NC, Single Set Point, for K, J, R, S, PT-100 (Any One)	2550	90251920	3443
DTC-202	Digital Temperature Controller 96 x 96 mm sq, with 2NO + 2NC, Two Set Point, for K, J, R, S, PT-100 (Any One)	2900	90251920	3915
METCAT 96	Digital Temperature Controller, 4 Digits Display, up to 1200 Degree C, 96 x 96 mm sq, with 1NO + 1NC, Single Set Point, for K, J, PT-100 (User Programmable)	1950	90251920	2633
METCAT 72	Digital Temperature Controller, 4 Digits Display, up to 1200 Degree C, 72 x 72 mm sq, with 1NO + 1NC, Single Set Point, for K, J, PT-100 (User Programmable)	1950	90251920	2633
Digital Temperature Indicator				
DTI-101 48	Digital Temperature Indicator 96 x 48 mm sq, for K, J, R, S, PT-100 (Any One)	1460	90251920	1971
DTI-101 96	Digital Temperature Indicator 96 x 96 mm sq, for K, J, R, S, PT-100 (Any One)	1460	90251920	1971
N.B. - Please ask for the prices in case if you require this in 72 x 72 mm sq size or 96 x 48 mm sq size				
Multi-point Temperature Indicator				
DTI-101M 6 CH	6 Channel Digital Multi-Point Temperature Indicate for K, J,R, S, PT-100 (Any One) type of sensor	4200	90251920	5670
DTI-101M 12 CH	12 Channel Digital Multi-Point Temperature Indicate for K, J,R, S, PT-100 (Any One) type of sensor	4900	90251920	6615
THERMAL IMAGERS				
Thermal Imagers				
PRO TI-10P	Handheld, pocket-sized Thermal Imager for upto 500°C with storage for images and videos, Wi-Fi and USB interfaces, 8 Colour Palettes and Digital Zoom. Rechargeable battery.	55500	90251920	74925
PRO TI-25	Handheld Thermal Imager for upto 550°C with 256×192 pixels resolution. Images & video recording along with touchscreen TFT LCD display, Wi-Fi, USB and free App. Rechargeable battery.	85000	90251920	114750
PRO TI-50	Handheld Thermal Imager for upto 650°C with 384×288 pixels resolution. Images & video recording along with touchscreen TFT LCD display, Auto-Fusion, Wi-Fi, USB and free App. Rechargeable battery.	198750	90251920	268313
THERMOMETERS				
Digital Thermometer				
ST-9283B	Hand-held, High Temperature Alarm Facility, Auto Power Off, Data Hold, -50 to 300°C / -58 to 572°F	805	90251920	1087
DTM-902	Pen Type, Waterproof, Auto Power Off, -40 to 250°C / -40 to 482°F. Ideal for food grade usage	830	90251920	1121
DTM-903	-50 to 1300°C using K-type Sensor and -50 to 1200°C using J-type Sensor Accuracy: ±0.5%. Wide Temperature Range, High Accuracy, Battery Operated, Selectable Thermocouple between K / J type, MAX / MIN / AVG Recording, Data Hold to Freeze Displayed Data, Backlit Display.	1720	90251920	2322
DTM-100 -100 to 200°C	3-1/2 Digits, Hand Held 9V battery operated, for PT-100 Sensor up to 200°C (customised sensor at extra cost).	2050	90251920	2768

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
DTM-100 -100 to 400°C	3-1/2 Digits, Hand Held 9V battery operated, for PT-100 Sensor up to 400°C (customised sensor at extra cost).	2050	90251920	2768
DTM-100 -100 to 600°C	3-1/2 Digits, Hand Held 9V battery operated, for PT-100 Sensor up to 600°C (customised sensor at extra cost).	2250	90251920	3038
DTM-100 -100 to 1200°C	3-1/2 Digits, Hand Held 9V battery operated, for PT-100 Sensor up to 1200°C (customised sensor at extra cost).	2250	90251920	3038
DTM-900	3-1/2 Digits, -50 to 1300°C / -50 to 1999°F, Contact type, to be used with K type thermocouple , with backlit display and kelvin scale	3720	90251920	5022
DTM-901	3-1/2 Digits, Dual Channel Input, -50 to 1300°C / -50 to 1999°F, Contact type, to be used with K type thermocouple. with backlit display and kelvin scale	4230	90251920	5711
DTM-925	Thermometer with eight types of thermocouples and PT-100 (385). Input is selectable through software, no need to change any component or add on card. The instrument is capable of measuring from -200°C to 1800°C depending on the sensor.	3765	90251920	5083
Portable Non-contact Infrared Thermometers (Pyrometers)				
ET-99IR	Measures upto 250°C with backlit LCD display, D:S Ratio 8:1, adjustable Emissivity, 2m drop tested, compact & pocket-sized.	1980	90251920	2673
MT-2	Measures -50°C to 550°C, D:S Ratio 12:1, Fixed Emissivity 0.95, Backlit LCD with laser sighting.	2300	90251920	3105
PRO 65 MAX	With Circular Laser, IR Temperature -50 to 800°C, D:S Ratio 16:1, Resolution: 0.1°C < 1000; 1°C > 1000, Accuracy ±0.5% ±1.5°C, Response Time 150mS, Spectral Response 8 – 14um, Tk Contact Temperature -50 to 1370°C, IP54 Rated for Dust / Water Proof, 2m Drop Tested, Automatic Data Hold, Non-contact and Contact Thermometer combined, Adjustable Emissivity 0.10 to 1.00, MAX / MIN / AVG / DIF Temperature display, Backlit LCD Display, Set High and Low Alarms, Battery Operated, CE Compliant with EMC.	4730	90251920	6386
PRO 65 MAX+	With Circular Laser, IR Temperature -50 to 1000°C, D:S Ratio 20:1, Accuracy: ±0.5% ±1.5°C, Resolution 0.1°C < 1000; 1°C > 1000, Response Time 150mS, Spectral Response 8 – 14um, Tk Contact Temperature -50 to 1370°C, IP54 Rated for Dust / Water Proof, 2m Drop Tested, Automatic Data Hold, Non-contact and Contact Thermometer combined, Adjustable Emissivity 0.10 to 1.00, MAX / MIN / AVG / DIF Temperature display, Backlit LCD Display, Set High and Low Alarms, Battery Operated, CE Compliant with EMC.	5915	90251920	7985
MT-10	3-1/2 Digits Backlit LCD, fixed emissivity of 0.95, D:S Ratio of 50:1, measures from -50 to 1000°C / -58 to 1832°F, with laser pointer	15700	90251920	21195
MT-13	Measures -18 to 1050°C, with Backlit LCD, Contact cum Non-contact type Pyrometer, -50 to 1370°C in Contact Mode, Emissivity adjustable from 0.10 to 1.0, D:S Ratio 30:1, with wireless USB PC Interface and facility to calculate the emissivity of the surface.	20250	90251920	27338
MT-14	4 Digits Backlit LCD, Contact cum Non Contact type, measures -50 to 1300°C in non contact mode and contact mode. D:S Ratio 30:1, Emissivity Adjustable 0.10 to 1.00, mV output /°C, Trigger Lock, battery cum mains operated, Records 20 Data, Max/Min/Dif/Avg recording	13500	90251920	18225
MT-15	Measures -50°C to 1200°C with dual laser pointer, D:S Ratio 50:1, Adjustable Emissivity from 0.10 ~ 1.0., contact cum non-contact type, with USB PC Interface ,Max./Min./Dif/AVG., 4 Digits Backlit LCD.	19800	90251920	26730

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
MT-16	Measures -50°C to 1800°C with dual laser pointer, Adjustable Emissivity from 0.10 ~ 1.0, D:S Ratio 50:1, 4 Digits Backlit LCD, Contact cum Non-contact type with USB PC Interface, in non contact mode measures from -50°C to 1370°C, Max./Min./Dif/Avg. readings.	24300	90251920	32805
MT-18	Measures -50°C to 2200°C with dual laser pointer, Adjustable Emissivity from 0.10 ~ 1.0, D:S Ratio 50:1, Contact cum Non-contact type, with USB PC Interface, Max./Min./Dif/Avg. readings, 4 Digits Backlit LCD.	30100	90251920	40635
MT-19	Measures -50° to 2200°C with D:S Ratio 75:1. Features Dot Matrix Backlit LCD, Bluetooth, up to 32000 data points, adjustable emissivity with dual laser pointer and Max./Min./Dif/AVG. readings	31700	90251920	42795
MT-20	Telescopic sighting, 500°C to 3000°C, 4 digits LCD, Adjustable Emissivity 0.10 to 1.00, Distance to Sighting Ratio 120:1, Accuracy ±1%, with Max/Min/Avg/DT and High/Low Alarms.	On Request	90251920	
Video Infrared Thermometer with Data Logger				
VIT-20	Measures -50°C to 1850°C, Adjustable Emissivity, D:S 50:1. With Dual Laser Pointer, Colour LCD Display, Data Logging, Image & Video Capture facility, In-built Contact Thermometer. Features microSD Card & PC interface.	59125	90251920	79819
Fixed Online Non-contact Infrared Thermometer				
ST-201A NEW!!	Fixed Online Infrared Thermometer 300°C~1300°C. Spectral Response 2.6 µm	152000	90251920	205200
ST-201AK NEW!!	Fixed Online Infrared Thermometer 500°C~1400°C. Spectral Response 2.6 µm	163000	90251920	220050
ST-201B NEW!!	Fixed Online Infrared Thermometer 600°C~1600°C. Spectral Response 1.7 µm	152000	90251920	205200
ST-202A NEW!!	Fixed Online Infrared Thermometer 600°C~1800°C. Spectral Response 1µm	148500	90251920	200475
ST-202B NEW!!	Fixed Online Infrared Thermometer 800°C~2500°C. Spectral Response 1µm	156000	90251920	210600
ST-202C NEW!!	Fixed Online Infrared Thermometer 1000°C~3000°C. Spectral Response 1µm	169500	90251920	228825
Two Colour Non-contact Infrared Thermometer				
ST-300A	Temperature range 600°C~1400°C, D:S 150:1, Output 4~20mA, RS485, Relay – 1A30VDC / 0.5A125VAC, Impedance : ≤50mΩ, IP-65 casing	351000	90251920	473850
ST-300B	Temperature range 700°C~1800°C, D:S 300:1, Output 4~20mA, RS485, Relay – 1A30VDC / 0.5A125VAC, Impedance : ≤50mΩ, IP-65 casing	351000	90251920	473850
ST-300C	Temperature range 1000°C~3000°C, D:S 300:1, Output 4~20mA, RS485, Relay – 1A30VDC / 0.5A125VAC, Impedance : ≤50mΩ, IP-65 casing	387000	90251920	522450
Non-contact Infrared Thermometer for Human Fever				
CEM DT-8806H	Clinical Forehead Infrared Thermometer, measuring distance upto 15cm, LCD screen, store upto 32 readings. Safety Conformance ASTM E1965-1998, EN 980, EN 1041, EN 60601-1, IEC: 60601-1:1998), EN 60601-1-2, (IEC 60601-1-2:2001). FDA approved.	4000	90251920	5400
FIR-2	Non-contact Infrared Thermometer for body temperature	3010	90251920	4064

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
PIR-I	Non-contact Infrared Thermometer to measure human body temperature via the hand, wrist, palm or forehead. For Entry/Exits, to avoid crowding or queuing. Mountable on almost any surface. Multi-angle adjustable mounting.	37625	90251920	50794
THICKNESS GAUGES				
Coating Thickness Gauge				
CTG-01	Measures coating thickness on both ferrous and Non Ferrous materials	11795	90303900	15923
CTG-02	Measures coating thickness on both ferrous and Non Ferrous materials with extended flexible cable with sensor	22450	90173029	30308
CTG-03 NEW!!	Coating Thickness Gauge with USB Interface. Single probe for coating measurements, for both ferrous and non-ferrous metal substrates.	13450	90173029	18158
Ultrasonic Thickness Gauge				
UTG-01	Versatile Ultrasonic Thickness Gauge to measure thickness of high density material up to 200mm	13300	90173029	17955
UTG-02 NEW!!	Versatile Ultrasonic Thickness Gauge to measure thickness of high density material up to 300mm, with Data Logging and Rechargeable Battery	10125	90173029	13669
TIME INTERVAL METER				
Digital Time Interval Meter				
NTT-4D	4 Digits Digital Time Interval Meter for measuring in the range of 999.9mS, 9.999S, 99.99S	17500	90303390	23625
3CH-NTT-4D	4 Digits 3 Channel Digital Time Interval Meter for measuring in the range of 99.99mS, 999.9mS, 9.999S	77000	90303390	103950
TRANSISTOR TESTER				
Transistor Tester				
TT-01	Transistor Tester for Testing and Checking Bias Current and other parameters of Transistors	5175	90303100	6986
TRANSDUCERS				
Transducers NEW!!				
CE-0102A AC	CURRENT TRANSDUCER: INPUT 1A AC or 5A AC I/P DUAL OUTPUT (DC AUX SUPPLY)	3650	90318000	4928
CE-0102A DC	CURRENT TRANSDUCER: DC CURRENT INPUT, DUAL OUTPUT(DC AUX SUPPLY)	3650	90318000	4928
CE-0102V AC	VOLTAGE TRANSDUCER: AC VOLT I/P, DUAL OUTPUT(DC AUX SUPPLY)	3985	90318000	5380
CE-0102V DC	VOLTAGE TRANSDUCER: DC VOLT I/P,DUAL OUTPUT(DC AUX SUPPLY)	3650	90318000	4928
CE-0102 IS	DC ISOLATION TRANSDUCER: ISOLATOR , DUAL OUTPUT(DC AUX SUPPLY)	3650	90318000	4928
CE-0102 RTD	TEMPERATURE TRANSDUCER: RTD (PT-100) TRANSDUCER (DC AUX SUPPLY) SINGLE O/P	3650	90318000	4928
CE-0102 RTD-2	TEMPERATURE TRANSDUCER: RTD (PT-100) TRANSDUCER (DC AUX SUPPLY) DUAL O/P	3985	90318000	5380
CE-0102 RTK	TEMPERATURE TRANSDUCER (K-TYPE) DC AUX SUPPLY SINGLE O/P	3650	90318000	4928
CE-0102 RTK-2	TEMPERATURE TRANSDUCER (K-TYPE) DC AUX SUPPLY DUAL O/P	3985	90318000	5380
CE-50 FT	FREQUENCY TRANSDUCER -I/P:45-55Hz, O/P:4-20mA, DC AUX SUPPLY	5200	90318000	7020

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
CE-0102 WT	WATT TRANSDUCER: 1 PH, 4-20mA Dual O/P, Aux:90-270VAC/DC	5400	90318000	7290
CE-0303 WT	WATT TRANSDUCER: 3 PH 3 WIRE WATT TRANSDUCER, 4-20mA Dual O/P, Aux:90-270VAC/DC	7375	90318000	9956
CE-0304 WT	WATT TRANSDUCER: 3 PH 4 WIRE WATT TRANSDUCER, 4-20mA Dual O/P, Aux:90-270VAC/DC	7375	90318000	9956
CE-0102 VAT	VA TRANSDUCER: 1 PH, 4-20mA Dual O/P, Aux:90-270VAC/DC	5400	90318000	7290
CE-0303 VAT	VA TRANSDUCER: 3 PH 3 WIRE, 4-20mA Dual O/P, Aux:90-270VAC/DC	7375	90318000	9956
CE-0304 VAT	VA TRANSDUCER: 3 PH 4 WIRE, 4-20mA Dual O/P, Aux:90-270VAC/DC	7375	90318000	9956
CE-0102 QT	KVAR TRANSDUCER: 1 PH, 4-20mA Dual O/P, Aux:90-270VAC/DC	5400	90318000	7290
CE-0303 QT	KVAR TRANSDUCER: 3 PH 3 WIRE, 4-20mA Dual O/P, Aux:90-270VAC/DC	7375	90318000	9956
CE-0304 QT	KVAR TRANSDUCER: 3 PH 4 WIRE, 4-20mA Dual O/P, Aux:90-270VAC/DC	7375	90318000	9956
CE-0102 PFT	POWER FACTOR TRANSDUCER: 1 PH, 4-20mA Dual O/P, Aux:90-270VAC/DC	5400	90318000	7290
CE-0303 PFT	POWER FACTOR TRANSDUCER: 3 PH 3 WIRE, 4-20mA Dual O/P, Aux:90-270VAC/DC	7375	90318000	9956
CE-0304 PFT	POWER FACTOR TRANSDUCER: 3 PH 4 WIRE, 4-20mA Dual O/P, Aux:90-270VAC/DC	7375	90318000	9956
	EXTRA FOR DC POWER SUPPLY FOR ANY OF THE ABOVE	550	90318000	743
VIBRATION METERS				
Vibration Meter				
VIB-30+	Digital Vibratoin Meter, measures RMS velocity in the range of 0.1 to 199.9 mm/sec T-RMS & Peak	35000	90318000	47250
AVD-80	Digital Vibration Meter, measures velocity, acceleration and displacement	41500	90318000	56025
BCA-111	Bearing Condtion Analyzer, measures bearing test, vibration and has in-built tachometer.	145125	90318000	195919
908	Measures velocity, acceleration and displacement along with the temperature, comes complete with the magnetic Base	18815	90318000	25400
PVB-820	Pen Type Vibration Meter, it can measure accelleration, velocity and displacement	18275	90318000	24671
VT-141	Dual Channel Vibration meter, Wide frequency range of 10Hz to 5KHz, Acceleration, velocity and displacement, Vibration sensor with magnetic adapter on1.2M (47.2) cable, Frequency Lo range :10Hz~1KHz meets ISO 2954 measurement, Hi range : 10Hz~5KHz, MAX record, Auto power off with disable function	89000	90318000	120150
VT-141D	Dual Channel Vibration meter, Wide frequency range of 10Hz to 5KHz, Acceleration, velocity and displacement, Vibration sensor with magnetic adapter on1.2M (47.2) cable, Frequency Lo range :10Hz~1KHz meets ISO 2954 measurement, Hi range : 10Hz~5KHz, MIN/MAX record and recall, Data logger with 9999 records capacity, USB interface, Auto power off with disable function	97000	90318000	130950
VT-150 NEW!!	3-in-1 Vibration Tester with Bearing Condition analyser. Measures Velocity, Acceleration, Displacement, Bearing Condition and non-contact infrared temperature and features Alarm indication. IP65. Electromagnetic capability.	225000	90318000	303750
VT-151W NEW!!	Rechargeable, Portable, Single Axis Piezo-electric Wireless Accelerometer which operates on Android Mobile / Tab. Built-in analysis for all leading models of bearings and IP67 protection. Vibration Meter with magnetic suction base, Vibration Analysis and Fault Diagnosis.	253000	90318000	341550

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
VOLTAGE TESTERS				
Low Voltage Tester				
AC-1	Audio and Visual output on detecting voltage from 90V - 1000A AC with built in flash light	405	90303390	547
AC-4	Non Contact Voltage Detector by flashing light for 100 - 600V, with built-in flash light	755	90303390	1019
AC-5	Non Contact Voltage Detector by flashing light and buzzer sound for 100 - 600V, with built-in flash light	860	90303390	1161
High Voltage Tester (Contact Type)				
276HD	Contact type, light and buzzer indication, detects presence of High Voltage in AC Lines, 354 to 1005mm length, detects 3kV to 24kV AC and 80 to 600V AC	17955	90303390	24239
290HD	7 Digits, measures up to 99999.99 hours, 230V AC / 110V AC (Any One) operated, 46 x 46 mm sq size panel cutout	22575	90303390	30476
High Voltage Tester (Non-contact Type)				
277HP	Non Contact Type High Voltage Detector for presence of Voltage from 50V to 132kV with Buzzer and Light Indication	13440	90308990	18144
275HP	Non Contact type, Light and Buzzer Indication, Detects Presence of High Voltage in AC Lines, 240V, 2KV, 6KV, 11KV, 22KV, 33KV, 132KV and 175KV Lines AC.	17200	90308990	23220
275HP1	High Voltage Detectors (Electroscope) for electrical testing on high voltage transmission lines upto 275kV, with audible buzzer and visual light alarms.	7955	90308990	10739
275HP1 with FRP Rod Kit	High Voltage Detectors (Electroscope) for electrical testing on high voltage transmission lines upto 275kV, with audible buzzer and visual light alarms. Comes complete with a 4.5m FRP Rod, together is a portable, easy to carry case.	19250	90308990	25988
275HP2	High Voltage Detectors (Electroscope) for electrical testing on high voltage transmission lines upto 500kV, with audible buzzer and visual light alarms. Comes complete with a 4.5m FRP Rod, together is a portable, easy to carry case.	20250	90308990	27338
HT500	A handy, hard hat/helmet accessory, close-range non-contact high voltage detector, featuring sound & light alarms when an operator wearing it gets close to a high voltage charged body upto 500kV.	3500	90308990	4725
WT500	A handy, wearable (wrist-type), close-range, non-contact, high voltage detector, featuring sound & light alarms when an operator wearing it gets close to a high voltage charged body upto 500kV.	3500	90318000	4725
AT500	A handy, wearable (arm-type), close-range non-contact high voltage detector, featuring sound & light alarms when an operator wearing it gets close to a high voltage charged body upto 500kV.	3900	90308990	5265
FRP Rods	4.5m FRP Rod to be used with above non-contact high voltage detectors	4400	85441920	5940
Hot Line Indicator				
6.6kV	Hot Line Indicator, Neon Glow type for 6.6kV	12800	90303390	17280
11kV	Hot Line Indicator, Neon Glow type for 11kV	19200	90303390	25920
33kV	Hot Line Indicator, Neon Glow type for 33kV	32000	90303390	43200
# Hot Line Indicator with Neon glow and audible buzzer both are also available. Please refer back for their price.				

This is a Temporary Revised Price List as on 1st March 2024 and supercedes all earlier price lists.

MODEL NO.	DETAILS	LIST PRICE AS ON 070623 (Rs.)	HSN	MRP / AMAZON PRICE (Rs.)
WATER QUALITY TESTING METERS				
pH Meter				
PH-600	Quality, portable pH Meter with glass bulb electrode for measuring 0.00-14.00pH. Easily calibratable. Comes with 2 free buffer powder sachets.	590	90278990	797
PH-700 NEW!!	Compact & portable. Measures pH level upto 14.00pH and temperature upto 60°C with replaceable glass electrode. High definition, negative display. Easily calibratable, comes with 3 free buffer powder sachets.	1125	90278990	1519
TDS Meter				
TDS-3	Handy Digital TDS Meter for measuring 0-9990 PPM TDS and 0° to 50°C temperature, using a titanium alloy electrode.	500	90278990	675
WEATHER STATION				
Wireless Weather Station				
WS-1051	Professional, multifunction, intelligent Weather Station, high accuracy, measurements of Wind Speed & Direction, Rainfall, Temperature & Humidity, Air Pressure. Features WiFi interface.	15750	90158020	21263
TERMS & CONDITIONS:				
VALIDITY:	PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE			
PRICES:	NETT, EX GODOWN KOLKATA			
PACKING:	PRICES INCLUSIVE OF PACKING CHARGES			
FREIGHT:	PRICES EXCLUSIVE OF FREIGHT CHARGES. IN CASE IF GOODS ARE REQUIRED BY ANY OTHER COURIER, OTHER THAN OUR NOMINATED COURIER ANY BY AIR, THEN THE FREIGHT SHALL BE CHARGED EXTRA AT ACTUALS			
DELIVERY:	READY STOCK SUBJECT TO PRIOR SALES, FOR HIGH VOLTAGE EQUIPMENTS 8-12 WEEKS DELIVERIES WILL BE MADE ONLY AFTER THE PAYMENT IS CREDITED TO OUR ACCOUNT			
INSURANCE:	TO BE COVERED BY THE BUYER THE GOODS WOULD BE PACKED SECURELY WITH OUR BEST INTENT TO PROTECT IT AGAINST ANY KIND OF TRANSIT DAMAGE. HOWEVER, IN CASE IF THE GOODS GET DAMAGED IN TRANSIT, THE BUYER WILL HAVE TO COVER ITS RISK			
PAYMENT:	100% AGAINST PROFORMA INVOICE / DOD / THROUGH BANK. 'ALTERNATIVELY' IF IT'S A TAILOR-MADE PRODUCT, 25% ADVANCE WITH THE ORDER BALANCE AGAINST PROFORMA INVOICE / DOD / THROUGH BANK			
SHIPMENT:	SHALL TAKE PLACE WITHIN 48 HOURS OF RECEIPT OF PAYMENT			
GOODS & SERVICE TAXES:	GST SHALL BE CHARGED EXTRA @18%. GST IS ALSO APPLICABLE ON FREIGHT CHARGES			
ORDERING VALUE:	<u>FOR ORDER VALUE LESS THAN RS.3000/- (RUPEES THREE THOUSAND) A CHARGE RS. TWO HUNDRED AS HANDLING CHARGES WILL BE LEVIED</u>			
DISCLAIMER:	WE TRY OUR BEST TO USE THE BEST OF COURIERS POSSIBLE FOR EARLIEST DELIVERY TIME BUT HAVE NO CONTROL OVER THE DELIVERIES BY THE COURIER. YOU MAY SUGGEST THE COURIER OF YOUR CHOICE AND WE SHALL SHIP THE GOODS THROUGH THEM, IF POSSIBLE. HOWEVER IN EITHER CASE, WE WILL NOT BE HELD RESPONSIBLE, UNDER ANY CIRCUMSTANCES, IF THE COURIER DELAYS THE DELIVERY FOR ANY REASON WHATSOEVER.			
JURISDICTION:	SUBJECT TO KOLKATA JURISDICTION ONLY			
THIS SUPERCEDES ALL PREVIOUS PRICE LISTS				