AN ISO 9001:2015 COMPANY

QUOTATION FOR ALL MOTWANE PRODUCTS

(EFFECTIVE FROM 15/04/2021)

MODEL	DESCRIPTION	PRICE (INR)	HSN CODE	MRP ON THE BOX
HIGH VOLTAGI	E INDICATORS			
HV-50	High Voltage detector 6.6 KV to 33 KV with 3 meters telescopic fiber glass rod and carrying case.	35130	90303390	43940
HV-132	High Voltage detector 11 KV to 132 KV with 5 meters telescopic fiber glass rod and carrying case.	41600	90303390	52030
HV-220	High Voltage detector 33 KV to 220 KV with 5 meters telescopic fiber glass rod and carrying case.	54630	90303390	
HV-440	High Voltage detector 66KV to 440 KV with 5 meters telescopic fiber glass rod and carrying case.	61770	90303390	
Optional	3 mtr. Telescopic Fiber glass rod	8710	90309010	
Accessories	5.5 mtr. Telescopic Fiber glass rod	14580	90309010	
DIGITAL EARTH	H CLAMP TESTER-CLAMP ON TYPE			an a
DECT - 2	 4-digit LCD Digital Earth Clamp (Resistance) Tester - 0.01 to 1200 Ohms with Memory & Alarm feature a. Standard Loop Resistance 5.1 Ohm b. Instruction Manual c. Calibration Certificate d. Carrying Case 	92860	90303390	nissaidyo Interastisticia Cinatrin
DECT - 3	 4 digits Digital Earth Clamp (Resistance) Tester - 0.01 to 1200 Ohms with Leakage Current Measurement 0.05 mA to 20 A a. Standard Loop Resistance 5.1 Ohm b. Instruction Manual c. Calibration Certificate d. Carrying Case e. RS232 Cable & PC Software CD 	100000	90303390	





AN ISO 9001:2015 COMPANY

QUOTATION FOR ALL MOTWANE PRODUCTS

(EFFECTIVE FROM 15/04/2021)

MODEL	DESCRIPTION	PRICE (INR)	HSN CODE	MRP ON THE BOX
GROUND FAUL	T LOCATOR			
MGFL	 Motwane Ground Fault Locator with following accessories: a. Receiver Unit b. Transmitter Unit c. Test Lead Set with Crocodile clips d. Clamp 55 mm & Clamp 20 mm e. Spare Battery – 9V f. Charger for 9V Battery- Receiver unit g. Charger -5 V-Transmitter unit h. Instruction Manual 	On Request	90303390	
INSULATION TE	ESTER			
IT250G SPOT	5KV,250GΩ Digital Insulation Tester with Programmable Timer a. Test Lead Set-3 x 3m long Shrouded banana with crocodile clip b. Instruction Manual c. Carrying Case	51430	90303350	
Optional	3 x 3 meter test lead with crocodile clip	8810	90309010	
Accessories	Carrying case for IT250G	820	90309010	
IT250G	3 x 10 meter test lead with crocodile clip	12140	90309010	
IT-51	 5 KV Digital Insulation Tester With measurement of 1 T Ohm with PI facility, AC/DC voltage measurement up to 600 V, internal rechargeable battery a. 3 x 3 m test leads for earth, guard & line connection. b. 1.5 m AC mains cord. c. Mains protected fuse d. Carrying case e. Calibration Certificate 	85715	90303350	
Optional	3 x 10 m test leads with large insulated clamps.	23840	90309010	ningergen in Lyric Fran
Accessories IT-51	3 x 3 m test leads with large insulated clamps.	7550	90309010	



JM

e

AN ISO 9001:2015 COMPANY

QUOTATION FOR ALL MOTWANE PRODUCTS

(EFFECTIVE FROM 15/04/2021)

MODEL	DESCRIPTION	PRICE (INR)	HSN CODE	MRP ON THE BOX
5KPI	 Diagnostic insulation Tester Model 5kPl with following accessories. a. 3 x 3 m test leads for earth, guard & line connection. b. 1.5 m AC mains chord. c. Mains protected fuse d. Instruction manual e. Carrying case. f. Calibration certificate 	245860	90303350	
	3 x 10 m test leads with large insulated clamps.	43600	90309010	
Optional Accessories for	3 x 3 m test leads with large insulated lamps.	10910	90309010	
5KPI	Carrying case	7240	90309010	
	Software CD with RS 232 & USB cable	23600	90309010	
10KPI	 Diagnostic insulation Tester Model 10KPI with following accessories. a. 3 x 3 m test leads for earth, guard & line connection. b. 1.5 m AC mains chord. c. Mains protected fuse d. Instruction manual e. Carrying case. f. Calibration certificate 	On Request	90303350	
Optional Accessories for 10KPI	3 x 10 m test leads with large insulated clamps	On Request	90309010	
	3 x 3 m test leads with large insulated clamps	On Request	90309010	
	Carrying case	On Request	90309010	
	Software CD with RS 232 & USB cable	On Request	90309010	5 (P)(1)

TA 2

Rev No. B/21-22/01



AN ISO 9001:2015 COMPANY

QUOTATION FOR ALL MOTWANE PRODUCTS

(EFFECTIVE FROM 15/04/2021)

MODEL	DESCRIPTION	PRICE (INR)	HSN CODE	MRP ON THE BOX
MLCM	 Motwane Leakage Current Monitor To monitor LA healthiness.Simultaneous and continuous display of fundamental & 3 harmonic leakage current. a. 50 mm High sense current probe. b. Hook stick, base plate, cables for B2 variants. c. Smart phone with inbuilt printer. d. MLCM app - software e. Charger for MLCM f. USB cable and Smart phone charger. 	On Request		
	g. Operating and instruction manual.	a second a s		
LR 2045	4½ Digit Bench Micro-ohm meter with set of leads with GP Kelvin Clips Jaw: 25 MM,RS232 cable, main cord, instruction Manual	81430	90303390	n jéreseni Pojs
LR 2065	4½ Digit Bench Micro-ohm meter with set of leads with GP Kelvin Clips Jaw: 25 MM & GP crocodile clips, mains cord and Instruction Manual	117140	90303390	na papa at a t
	Test Lead with GP Crocodile clips 2 mtr for LR2045/LR2065	6930	90309010	.*93967.
	C Clamp with 10 mtr Long Leads	11290	90309010	
Optional Accessories for LR 2045 / LR 2065	Test Leads with Heavy Duty Bond Testing Probe	11290	90309010	
	10 mtr. long test leads with Heavy Duty Crocodile Clips.	12140	90309010	
	Test Lead Assy. With G.P. Kelvin Clip for LR2065- 2 mtr, Jaw: 9 MM	6930	90309010	
	Test Lead Assy. with G.P. Kelvin Clip for LR2065- 2 mtr Jaw: 25 MM	6930	90309010	
	Battery Pack Assembly(NI CAD 1.2V) for LR2065	16400	90309010	
LR201	3 ¹ / ₂ Digit heavy duty hand held Safety ohm Meter with a set of leads with GP Kelvin Clips Jaw: 25 MM.	59000	90303390	

JM

L



AN ISO 9001:2015 COMPANY

QUOTATION FOR ALL MOTWANE PRODUCTS

(EFFECTIVE FROM 15/04/2021)

DESCRIPTION	PRICE (INR)	HSN CODE	MRP ON THE BOX
Test Lead GP Crocodile Clip for LR201- 2 mtr, Jaw: 25 MM	6930	90309010	t that the
 4½ Digit Micro-Ohm Meter with Back Emf protection suitable for Inductive loads along with following accessories. a. 3m leads with GP Kelvin Clip b. Three pin mains cord. c. Input protection fuse d. Mains Protection fuse e. User Manual f. Calibration Certificate g. Carrying case. 	85715	90303390	
10 mtr Long leads with large crocodile clips and shrouded banana, Jaw: 40MM	28470	90309010	
10 mtr long test leads with Heavy duty Kelvin clip Jaw: 35MM	9280	90309010	
10 mtr test leads with C clamp with normal banana clips, Jaw: 80MM	11960	90309010	
Software with USB interfacing cable	10660	90309010	
Test Lead Assembly With One End Kelvin Clip & Shrouded Banana 3 mtr Long For LR2045-S	6930	90309010	
Test Lead with Heavy Duty GP Bond Testing Probe Assembly	11290	90309010	
Carrying case	6930	90309010	
 4½ digit display Contact Resistance Meter 100 A with 4 wire Measurement with following accessories. a. 15 m long cable with Heavy Duty C clamp with 75 mm jaw size b. Master Earth Cable 7 meter c. Mains power cord d. Mains protection fuse e. User Manual f. Calibration sheet g. Thermal Paper roll h. Carrying case 	On Request	90303390	
the first state of the state of	. won	11	
	 Test Lead GP Crocodile Clip for LR201-2 mtr, Jaw: 25 MM 4½ Digit Micro-Ohm Meter with Back Emf protection suitable for Inductive loads along with following accessories. a. 3m leads with GP Kelvin Clip b. Three pin mains cord. c. Input protection fuse d. Mains Protection fuse e. User Manual f. Calibration Certificate g. Carrying case. 10 mtr Long leads with large crocodile clips and shrouded banana, Jaw: 40MM 10 mtr long test leads with Heavy duty Kelvin clip Jaw: 35MM 10 mtr test leads with C clamp with normal banana clips, Jaw: 80MM Software with USB interfacing cable Test Lead Assembly With One End Kelvin Clip & Shrouded Banana 3 mtr Long For LR2045-S Test Lead with Heavy Duty GP Bond Testing Probe Assembly Carrying case 4½ digit display Contact Resistance Meter 100 A with 4 wire Measurement with following accessories. a. 15 m long cable with Heavy Duty C clamp with 75 mm jaw size b. Master Earth Cable 7 meter c. Mains protection fuse e. User Manual f. Calibration sheet g. Thermal Paper roll 	DESCRIPTION(INR)Test Lead GP Crocodile Clip for LR201- 2 mtr, Jaw: 25 MM69304½ Digit Micro-Ohm Meter with Back Emf protection suitable for Inductive loads along with following accessories. a. 3m leads with GP Kelvin Clip b. Three pin mains cord. c. Input protection fuse d. Mains Protection fuse e. User Manual f. Calibration Certificate g. Carrying case.8571510 mtr Long leads with large crocodile clips and shrouded banana, Jaw: 40MM2847010 mtr long test leads with Heavy duty Kelvin clip Jaw: 35MM928010 mtr test leads with C clamp with normal banana clips, Jaw: 80MM11960Software with USB interfacing cable10660Test Lead Assembly With One End Kelvin Clip & Shrouded Banana 3 mtr Long For LR2045-S6930Test Lead with Heavy Duty GP Bond Test Lead with Heavy Duty GP Bond Test Lead with Heavy Duty GP Bond Test Icad probe Assembly11290Carrying case69304½ digit display Contact Resistance Meter 100 A with 4 wire Measurement with following accessories. a. 15 m long cable with Heavy Duty C clamp with 75 mm jaw size b. Master Earth Cable 7 meter c. Mains protection fuse e. User Manual f. Calibration sheet g. Thermal Paper rollOn Request	DESCRIPTION(INR)HSN CODETest Lead GP Crocodile Clip for LR201- 2 mtr, Jaw: 25 MM6930903090104½ Digit Micro-Ohm Meter with Back Emf protection suitable for Inductive loads along with following accessories. a. 3m leads with GP Kelvin Clip b. Three pin mains cord. c. Input protection fuse e. User Manual f. Calibration Certificate g. Carrying case.857159030339010 mtr Long leads with large crocodile clips and shrouded banana, Jaw: 40MM284709030901010 mtr long test leads with Heavy duty Kelvin clip Jaw: 35MM92809030901010 mtr test leads with Clamp with normal banana clips, Jaw: 80MM1196090309010Software with USB interfacing cable1066090309010Carrying case693090309010Cong For LR2045-S Test Lead with Heavy Duty GP Bond Long For LR2045-S1129090309010Carrying case6930903090104½ digit display Contact Resistance Meter 100 A with 4 wire Measurement with following accessories. a. 15 m long cable with Heavy Duty C clamp with 75 mm jaw size b. Master Earth Cable 7 meter c. Mains protection fuse e. User Manual -f. Calibration sheet g. Thermal Paper rollOn Request90303390

JM

2

Rev No. B/21-22/01



AN ISO 9001:2015 COMPANY

QUOTATION FOR ALL MOTWANE PRODUCTS

(EFFECTIVE FROM 15/04/2021)

MODEL	DESCRIPTION	PRICE (INR)	HSN CODE	MRP ON THE BOX
Optional accessories for	22 M long cable with Heavy duty C clamp with 50 / 100 / 150 mm jaw size / heavy crocodile clip 25 mm jaw size	On Request	90309010	
PCRM 100S	Software CD & USB cord	On Request	90309010	
PCRM 200S	 4½ digit display Contact Resistance Meter 100 A with 4 wire Measurement with following accessories. a) 15M long cable with C Clamp 75mm opening: 1 Set. b) Master Earthing Cable (5M): 1 Set c) Mains power cord: 1 No. d) Instruction Manual: 1 No. e) Calibration Sheet: 1 No. f) Carrying Case for test lead: 1No g) Thermal Paper Role: 1 No. h) Spare Fuse (250mA/250V slow blow): 1 No. 	On Request	90303390	
6	22 meter strong cable with C Clamp 50 mm opening	On Request	90309010	ins strate
Optional accessories PCRM 200S	03 meter cable with Heavy Crocodile clip 25mm opening	On Request	90309010	; 25455 97.
FCRW 2003	Software CD & USB cord	On Request	90309010	
XWRM-10	 4½ digit display with 10A, 4 wire Measurement, 3 voltage channels, 1 current channel, 2 temperature channel with temperature correction for Cu and Al with following accessories. a. 15m Test Lead Set b. Mains power cord c. Short link (5 M) d. Earthling cable (2 x 5 M) e. User Manual f. Calibration sheet g. Carrying case 	On Request	90303390	
Optional Accessories	Test Lead Set For XWRM-10 (ACCY)	On Request	90309010	
XWRM-10	Software & USB cable for XWRM-10	On Request	90309010	

TM

AN ISO 9001:2015 COMPANY

QUOTATION FOR ALL MOTWANE PRODUCTS

(EFFECTIVE FROM 15/04/2021)

MODEL	DESCRIPTION	PRICE (INR)	HSN CODE	MRP ON THE BOX
XWRM-25	 4½ digit display with 25A, 4 wire Measurement, 3 Voltage channels, 1 current channel 2 temperature channel with temperature correction for Cu and A with following accessories. a. 15m Test Lead Set b. Mains power cord c. Short link 2 No d. Earth cable 1 No e. User Manual f. Calibration sheet g. Carrying case 	On Request	90303390	
XTRM-3	 Fully automatic Transformer Turns Ratio Meter Testing single phase & three- phase transformers Automatic detection of transformer vector group. a. Test Lead Set 15M (10M + 5M Extension) b. Mains power cord c. Thermal Paper roll d. Instruction Manual e. Calibration Certificate 	On Request	90303390	
Optional Accessories	Software & USB cable for XTRM-3	On Request	90309010	he-alti
Oil Testing				
MOTR	Motwane Oil Tan Delta & Resistivity Kit with following accessories: a. Heating Chamber-01No b. Three Terminal Oil Cell-01No c. Calibrator-01No d. Test Lead Set e. Temperature Sensor PT100-01No f. Mains Cord-02Nos g. 20mm Glass Fuse-5A-05Nos, 2A-02Nos h. Thermal Printer Roll i. Software CD & USB Cable-01No j. Instruction Manual-01No	On Request	90303390	
Optional Accessories	Carrying Case for MOTR & Heating Chamber	On Request	90309010	
MOTR	Extra Three Terminal Oil Cell-01No	Request	90309010	
	r. I. frior	WHANE .		

AN ISO 9001:2015 COMPANY

QUOTATION FOR ALL MOTWANE PRODUCTS

(EFFECTIVE FROM 15/04/2021)

MODEL	DESCRIPTION	PRICE (INR)	HSN CODE	MRP ON THE BOX
MOTR+	Motwane Oil Tan Delta & Resistivity Kit with following accessories: a. Three Terminal Oil Cell-01No b. Calibrator-01No c. Test Lead Set d. Temperature Sensor PT100-01No e. Mains Cord-01Nos f. Thermal Printer Roll g. Software CD & USB Cable-01No h. Instruction Manual-01No	On Request	90303390	
OTS60 DS	Digital Oil Test Set 60 KV	On Request	90303390	
OTS80 DS	Digital Oil Test Set 80 KV	On Request	90303390	
OTS100 DS	Digital Oil Test Set 100 KV	On Request	90303390	
OTS 60 A	Fully Automatic Oil Test Set 60 KV	On Request	90303390	
OTS 80 A	Fully Automatic Oil Test Set 80 KV	On Request	90303390	
OTS 100 A	Fully Automatic Oil Test Set 100 KV	On Request	90303390	
OTS-60	0-60 KV Motorized / Manual Operated Oil Break Down Test Set	On Request	90.30.3390	
OTS-80	0-80 KV Motorized / Manual Operated Oil Break Down Test Set	On Request	90.30.3390	Handing J Philambaryk
OTS-100	0-100 KV Motorized / Manual Operated Oil Break Down Test Set	On Request	90.30.3390	
OTS-60 (with stirrer)	0-60 KV Motorized / Manual Operated Oil Break Down Test Set	On Request	90.30.3390	
OTS-80 (with stirrer)	0-80 KV Motorized / Manual Operated Oil Break Down Test Set	On Request	90.30.3390	91-010
OTS-100 (with stirrer)	0-100 KV Motorized / Manual Operated Oil Break Down Test Set	On Request	90.30.3390	



THE MOTWANE MANUFACTURING COMPANY PVT. LTD. MOTWANE AN ISO 9001:2015 COMPANY QUOTATION FOR ALL MOTWANE PRODUCTS

(EFFECTIVE FROM 15/04/2021)

Commercial Information & Terms

- 1. One Calibration Certificate & Instruction Manual is supplied along with each of the above stated Motwane Make Instrument.
- 2. Freight Charges Are Extra.
- **3.** GST CGST / SGST / IGST is applicable @ 18%. However, tax shall be charged extra at the rates prevailing at the time of actual dispatch.
- **4.** Any other local Taxes and Other Government levies, applicable at the time of dispatch, will be to Purchaser's account.
- **5.** Prices, Delivery period and specifications are subject to change without notice. Please check while Ordering.
- 6. Prices prevailing at the time of supply shall be applicable.
- **7.** Each Instrument is warranted for one year from the date of dispatch against any manufacturing defect subject to our standard warranty clause.

Th



이 가지 영상 위에 가는 것은 것입니다. 가지 않는

그는 것 이렇게 한 감독을 다 귀엽을 다 같다. 가슴을 가지 않는 것이 같아요.

网络马克莱尔马克 网络马克马克马克马克

- (Constructing Section 1) And the sector of white a sector and the sector of spectral construction. Set and the sector of the sector of the sector of the sector.
 - 그는 말을 다 한 것이 한 것을 많을 때 것을 했다.
- e frigeste en entre en entre internet en entre en transmitte van en anvestet en internet en en entre entre en Entre estimater entre entre entre
- 는 중도가 도둑하는 것으로 가지 않는 것 위에는 동안했다. 것은 것으로 도둑하는 것이 있는 것으로 것 같은 것이 같은 것이 같다. 것은 말했다. 것이 같은 것이 있다. 것은 말했다. 것이 있는 것은 - 소신들은 것은 가지 않는 것
 - ्र संदर्भ एक एक स्थाप के दिया है के के प्राप्त के सुधार के लिए के स्थित के स्थित के स्थित के स्थाप के स्थाप के
 - Eare instrument is unresolativer one year furmine date of dispatch against ever minutariarity defact subject to jun marchini workerlay saides.