

PRICE LIST FROM - 15-02-2021-To 31-07-2021

TESTRONIX

Skyking INSTRUMENTS

Skyking Chambers, Shop No. 2, Ground Floor, 374 Lamington Road, Mumbai 400 (Tel : 35930820 / 23887629 / 23886857 / 23871542 Mobile : 9322240682 / 7021545

RESESTANCE METERS (Micro-Ohm/milli/ohm Meters)		
TESTRONIX - 53 C	Useful for winding resistance, conductor resistance, contact resistance 1 Micro ohms to 19.99 K ohm in 8 full scale ranges of 1999 micro ohms, 19.99 mill ohms, 199.9 milli ohms, 1999 milli ohms, 19.99 ohms, 199.9 ohms, 1999 ohms and 19.99 K ohms. Size 200 mm (W) x 90 mm (H) x 240 mm (D), 4 Kgs.	5000/-
pH METERS/ELECTRODES		
TESTRONIX - 511	pH Meter, 3½ digit, mains operated, 0 to 14 pH, 0 to 2000 mV, supplied with electrode Glass combination type. Size 200 mm (W) X 90 mm (H) X 240 mm (D), 4 Kgs.	5500/-
ELECTRODE	combination types of pH Electrode, Suitable for TESTRONIX - 511 and similar pH Meters.	850/-
CONDUCTIVITY METERS/CELLS		
TESTRONIX -15	Conductivity Meter, Meter, 3½ digit, mains operated, 0 to 20 / 200 / 2m / 20m / 200 m sec/cm, supplied with conductivity cell. Size 200 mm (W) X 90 mm (H) X 240 mm (D), 4 Kgs.	5500/-
CONDUCTIVITY CELL	conductivity cell for conductivity meters, having cell constant of 1	1500/-
TESTRONIX -72	Sine : Square wave Generator. 1 Hz to 1 MHz, sine wave output from 0 to 30 volts peak o peak, square wave output 0 to 15 volts to peak, output impedance 600 - 0 ohms. Size 200 mm (W) X 90 mm (H) X 240 mm (D), 4 Kgs.	5500/-
TESTRONIX -100	High Voltage Breakdown (Flash) Testers (With KV Meter automatic tripping facility, safety probe, audio alarm) 0 to 5 KV, 3 to 30 milli amps tripping level setting Size 365 mm (W) x 135 mm (H) x 240 mm (D), 9 kgs.	10000/-
TESTRONIX - 30B	0 to 5 volts at 0 to 2 amps. Size 125mm (W) x 125 mm (H) x 210 mm (D), 2.5 kgs.	3000/-
TESTRONIX - 30C	0 to 5 volts at 0 to 5 amps. Size 125mm (W) x 125 mm (H) x 240 mm (D), 3.5 kgs	4000/-
TESTRONIX - 30D	0 to 5 volts at 0 to 10 amps. Size 195mm (W) x 135 mm (H) x 270 mm (D), 5 kgs.	5500/-

Model No.	DETAILS OF PRODUCTS	Rate Per
TESTRONIX - 34 B	0 to 16 volts at 0 to 2 amps. Size 125mm (W) x 125 mm (H) x 240 mm (D), 3 kgs.	4000/-
TESTRONIX - 34 C	0 to 16 volts at 0 to 5 amps. Size 195mm (W) x 135 mm (H) x 270 mm (D), 5 kgs.	5500/-
TESTRONIX - 34 D	0 to 16 volts at 0 to 10 amps. Size 365 mm (W) x 135 mm (H) x 300 mm (D), 10 kgs.	8500/-
TESTRONIX - 34 E	0 to 16 volts at 0 to 20 amps. Size 255 mm (W) x 255 mm (H) x 300 mm (D), 14 kgs.	14000/-
TESTRONIX - 92 A	0 to 32 volts at 0 to 1 amps. Size 125mm (W) x 125 mm (H) x 240 mm (D), 3.5 kgs.	4000/-
TESTRONIX - 92 B	0 to 32 volts at 0 to 2 amps. Size 195mm (W) x 135 mm (H) x 270 mm (D), 5 kgs.	5500/-
TESTRONIX - 92 C	0 to 32 volts at 0 to 5 amps. Size 365 mm (W) x 135 mm (H) x 270 mm (D), 10 kgs.	8500/-
TESTRONIX - 92 D	0 to 32 volts at 0 to 10 amps. Size 255 mm (W) x 255 mm (H) x 300 mm (D), 14 kgs.	12000/-
TESTRONIX - 36 A	0 to 65 volts at 0 to 1 amps. Size 195 mm (W) x 135 mm (H) x 270 mm (D), 4.5 kgs.	5500/-
TESTRONIX - 36 B	0 to 65 volts at 0 to 2 amps. Size 195 mm (W) x 135 mm (H) x 270 mm (D), 5.5 kgs.	8500/-
TESTRONIX - 36 C	0 to 65 volts at 0 to 5 amps. Size 255 mm (W) x 255 mm (H) x 300 mm (D), 12 kgs.	12000/-
TESTRONIX - 31A	0 to 125 volts at 0 to 1 amps. Size 365 mm (W) x 135 mm (H) x 300 mm (D), 10 kgs.	On
TESTRONIX - 31B	0 to 125 volts at 0 to 2 amps. Size 255 mm (W) x 255 mm (H) x 300 mm (D), 14 kgs.	On
POWER SUPPLIERS VARIABLE, DUAL AND MULTI OUTPUTS (Dc regulated, short circuit and overload protected) having digital meters for V and A measurements)		
TESTRONIX-15D1V	Dual tracking power supply with meter for volt. Output 0 to $\pm$ 15 volt 1 amp	4500/-
TESTRONIX - 35 B	Dual tracking or 2 independent outputs of 0 to 16 volts at 0 to 2 amps, 4 digital meters for V and A measurements of both outputs. Size 245 mm (W), x 135 mm (H) x 270 mm (D), 5 kgs.	8000/-
TESTRONIX - 93 B	Dual tracking or 2 independent outputs of 0 to 32 volts at 0 to 2 amps, 4 digital meters for V and A measurements of both outputs. Size 365 mm (W) x 135 mm (H) x 270 mm (D), 9 kgs.	11000/-
TESTRONIX - 93 C	Dual tracking or 2 independent outputs of 0 to 32 volts at 0 to 5 amps, 4 digital meters for V and A measurements of both outputs. Size 255 mm (W) x 255 mm (H) x 300 mm (D), 13.5 kgs.	14000/-
TESTRONIX - 35	Multi outputs 0 to 32 volts at 2 amps at 2 amps, 0 to 5 volts at 5 amps, 0 to $\pm$ 16 volts tracking at 0 to 500 milli amps, having digital volts meters to measure any of the output voltage or any external voltage. Size 365 mm (W) x 135 mm (H) x 270 mm (D), 9 kgs.	12000/-

TERMS & CONDITIONS

Delivery Period	: Ready stock or 6 weeks
Guarantee	: One Year
Jurisdiction	: Mumbai
Payment Terms	: 20% advance with order and balance through same against documents of despatch
GST	: 18%
GST IN No.	: 27ABFPL6347P1Z0

We reserve our right to revise the data without prior intimation and retaxes may vary as per government rules.