KYORITSU India Product Price List - 2020-21

KEW India								
Product Category	Product Category	Product Image	HS Code	Model Number	Short Description	KKIIPL LP (in INR)	MRP (in INR)	Standard Certificate
L	Digital Multimeters		9030 3100	<u>1018H</u>	Digital Multimeter: Display: 4000 counts. Auto range. Diode test feature. Capacitance test feature. Continuity test. Inc. Accessories: LR44× 2, Instruction Manual, Hard Case REL AUTOPOWER OFF	2,910	3,548	Certificate of Conformity
L		NEW SEE	9030 3100	1019R (NEW)	Digital Multimeter: Elegant shiny-black finish Comes with user-friendly Hard case Large Display Accurate reading with True-RMS technology Electronic protection (no fusel) on ohm and continuity ranges Safety Standard IEC 61010-1 / 61010-031 / 61010-2-033 CAT III 300V / CAT II 600V Inc. Accessories: 9188 (Hard case), CR2032 × 1, Instruction manual	7,162	8,734	Certificate of Conformity
L		P1553	9030 3100	<u>1009</u>	Digital Multimeter; Display: 4000 counts. Auto range and manual range selector provided. (with range hold feature) Resistance range provides audible continuity test. Automatically turns power off in about 30 minutes to conserve battery life. Direct current measurement up to 10A AC and DC. With Holster. Inc. Accessories: 7066A (Test leads), 8919 (Ceramic fuse [10A/600V])× 1, 8923 (Fuse [0.5A/600V])× 1, R6x 2. Instruction Manual	4,476	5,459	Certificate of Conformity
L		NEW SOOD	9030 3100	1021R (NEW)	Digital Multimeter: Elegant and easy-to-use cabinet Large display with 6000 counts and Backlight Enhanced current measuring function using an external clamp sensor Two detachable holders, flat and wing type Accurate reading with True RMS Safety Standard IEC 61010-1 CAT IV 300V / CAT III 600V Inc. Accessories: Wing-type holder, Flat-type holder, 7066A (Test leads), 8919 (Ceramic fuse [10A/600V]) × 1 (included), 9097 (Carrying case), R03 × 2, Instruction manual TRUE RMS CAT IV 300V CAT III 2C AT ACCESSORIES CAT IV 300V CAT III 2C ACCESSORIES ACCESSORIES ACCESSORIES CAT IV 300V CAT III 2C ACCESSORIES ACCE	6,022	7,344	Certificate of Conformity
н		0	9030 3100	<u>1051</u>	Digital Multimeter: For Electrical and Electronic Troubleshootings High Accuracy, High Performance and Reliable Measurements • 0.09% basic DC accuracy • Large display with 6,000 counts • True-RMS Measurements • Low-pass filter for motor drive measurements • User Test function Safety design for industrial use • Complies with IEC 61010-1 CAT IV 600V, CAT III 1000V • Terminal shutter to prevent incorrect test leads' insertion in current terminals • Very wide operating temperature range from -10 to 55°C Inc. Accessories: 7220A (Test leads), R6×4, Instruction manual, 8926 (Fuse [440m/A/100VIV.1 (included) 8927 (Fuse 110A/1000VIV.1 (included)) RMS • APATA	26,290	32,060	Test Certificate from KEW (A4 Size)
L	Digital Pen Type Multimeter		9030 3100	<u>1030</u>	Digital Pen Type Multimeter: Compact in Size, Light in Weight and Simple in Use. Double moulding provides comfortable and good feeling in hand. Penlight illuminates brightly the point to be measured, even in dark place. Backlight LCD is highly visible, even in darkness. Unique wrapping mechanism for test lead in the rear side compartment. Unique protection mechanism for the test prod for safety. All ranges including Ohm range are protected against overload voltage of 600V. Inc. Accessories: Carrying case, LR44 (1.5V) × 2. Instruction manual □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □	5,372	6,551	Certificate of Conformity

KYORITSU India Product Price List - 2020-21

1/E11/: "			1 1				✓ App	roved
KEW India Product Category	Product Category	Product Image	HS Code	Model Number	Short Description	KKIIPL LP (in INR)	MRP (in INR)	Standard Certificate
L	AC Analog Clamp Meter		9030 3900	<u>2608A</u>	AC Analog Clamp Meter: DC voltage range is also available especially for checking emergency battery operated power supply. Can measure temperature using optional probe. Tear drop shaped transformer jaws for ease of use. Inc. Accessories: 7066A (Test leads), 8923 (Fuse [0.5A/600V]) × 2, 9097 (Carrying case), R6 (AA) × 1, Instruction Manual	8,281	10,099	Certificate of Conformity
L	Digital AC Clamp Meters	NEW	9030 3900	2117R (NEW)	Digital Clamp Meter:	8,505	10,372	Certificate of Conformity
L		S. S	9030 3900	<u>200</u>	Digital AC Clamp Meter: • Measures Current up to 400A AC & Voltage up to 600V AC • Resistance, Continuity buzzer • Conductor Size \$30mm • Data hold memory function and Sleep feature • Display: 4000 counts • Complies to IEC61010-1 (CAT. III) UL3111 & VDE0411 300V Inc. Accessories: Test leads, Batteries, Instruction manual	5,372	6,551	Certificate of Conformity
L	Digital AC/DC Clamp Meters	O	9030 3900	<u>2003A</u>	Digital Clamp Meter: • Equipped to measure both AC and DC current with transformer jaws of large diameter. • Can measure AC and DC currents up to 2000A. • Output terminal for connection to recorders. Inc. Accessories: 7107A (Test leads), 8201 (Output Plug), 9094 (Carrying Case), R6 (AA) × 2, Instruction Manual CATIV Φ55 2MAX AC	21,934	26,749	Certificate of Conformity
L			9030 3900	<u>203</u>	Digital Clamp Meter: • Measures Current up to 400A AC/DC & Voltage up to 600V AC/DC • Resistance, Continuity buzzer • Conductor Size *30mm • Data hold memory function and Sleep feature • Display: 4000 counts • Complies to IEC61010-1 (CAT. III) UL3111 & VDE0411 300V Inc. Accessories: Test leads, Batteries, Instruction manual	8,443	10,297	Certificate of Conformity
L		9	9030 3900	<u>2055</u>	Digital Clamp Meter: Designed to meet international safety standard IEC 61010-1 CAT IV 600V. CAT IV Clamp Meters can measure the Voltage and Current in both every low and high power circuits. Thus, very useful for power distribution companies, power utilities and maintenance fields. Inc. CATIV Φ40 1 MAX 1000A PEV PATA Ω ●)) Hz DUTY → □ □ MAXMIN REL AUTOPROWER SAVE	15,220	18,561	Certificate of Conformity
L	Digital AC/DC Fork Current Tester		9030 3900	<u>2300R</u>	Fork Current Tester: • True RMS reading is an essential feature for accurate measurement. • "Non Contact" voltage function indicates the presence of AC voltage by warning the user with an audible signal. • Set the DC current range to zero in one touch with the Zero Adjust function. Inc. Accessories: Carrying Case, R03 (AAA) × 2, Instruction Manual TRUE ### ### #### #######################	11,639	14,194	Certificate of Conformity
L	Digital AC Leakage Current Clamp Meter		9030 3900	<u>2434</u>	Leakage Clamp Meter - Least affected by external stray magnetic field. - 20mA AC max. in proximity to a 15mm-dia conductor carrying 100A AC - Frequency Selector Switch to eliminate the effect of harmonics. - Resolution 0.1mA. Inc. Accessories: 9097 Carrying Case, R03 × 2, Instruction Manual - 28 MAX TOOA Filter	24,620	30,025	Test Certificate from KEW (B6 Size)

KYORITSU India Product Price List - 2020-21

KEW India Product Category	Product Category	Product Image	HS Code	Model Number	Short Description	KKIIPL LP (in INR)	MRP (in INR)	Standard Certificate
L	Insulation Tester Digital		9030 3900	<u>3005A</u>	Digital Insulation/Continuity Tester Bargraph to display insulation resistance. Displays the value of external AC voltage along with flashing symbol. Auto null function to automatically subtract the test lead resistance before displaying the real continuity resistance value. Live circuit warning beeper. Releasing the test button automatically discharges the charges stored in the circuit under test. 200mA continuity measuring current to IEC 61557. Minimum 1mA current on insulation tests to IEC 61557. Inc. Accessories: 7122B (Test leads) Pouch for test leads, 8923 (F500mA/600V fuse) × 2, R6 (AA) × 8. Shoulder Strap. Instruction Manual Ac V Ω (A)	27,057	32,996	Test Certificate from KEW (A4 Size)
н		NEW	9030 3900	<u>3552</u>	Digital Insulation / Continuity Testers World's fastest measurement speed (0.5 sec.) Six ranges available for insulation resistance test (50/100/125/250/500/1000 V) Insulation measurement up to 40GΩ Diagnostic Insulation Test: PI, DAR KEW3552: With memory function Incl.Accessories: 7260 (Test leads with remote control switch, 7261A (Test leads with alligator clip), 8017A (Extension prod long), 9173 (Carrying case), 9121 (Shoulder strap), LR6 (AA) (1.5V) x4, Instruction manual OFF 50V 100V 125V 250V 500V 1000V 2€ V	53,730	65,525	Certificate of Conformity
L			9030 3900	<u>3125A(NEW</u>)	High Voltage Insulation Tester Insulation Resistance up to 1TD Short-Circuit Current up to 1.5mA Wide Test Voltage from 250V to 5000V Diagnosis Function of PI and DAR Newly-designed alligator clip It comes with a tough hard case Filter function reduces noise interference for obtaining stable measurement Large display with Bar Graph indication and backlight Live voltage warning Safety standard IEC 61010-1 CAT IV 300V / CAT III 600V Inc. Accessories: 7165A (Line probe: 3m), 7264 (Earth cord: 3m), 7265 (Guard cord: 3m), 8019 (Hook type prod), 9180 (3025A Hard case), 9181 (3125A Hard case), LR14 (Alkaline battery size C) x 8. Instruction manual CATIV CATIV CATIV CATIV CATIV COVERNORS (OFF) LIVE VOLTAGE COVERNORS (OFF) LR14 (Alkaline battery size C) x 8. Instruction manual LR14 (Alkaline battery size C) x 8. Instruction manual LR15 (Alkaline battery size C) x 8. Instruction manual	80,128	97,717	Calibration Certificate from KEW (A4 Size)
L	Earth Tester Digital		9030 3320	<u>4105A</u>	Earth Resistance Tester Dust and drip proof. (designed to IEC 529 IP54) In addition to the facility for precision measurement, test leads for simplified two wire easuring system also supplied as standard accessories. (unit can be hung from the neck for simplified measurement) Designed to meet IEC 61010-1 safety standard. Capable of measuring earth voltage. Automatic warning when resistance of auxiliary earth spikes is in excess of tolerance. Small and lightweight. Shock resistant new case material. 2mA measuring current permits earth resistance tests without tripping earth leakage current breakers in the circuit under test. Inc. Accessories: 7095A (Earth resistance test leads) × 1set (red-20m, yellow-10m, green-5m), 8032 (Auxiliary earth spikes) × 1set, 7127A (Simplified measurement probe) × 1set, R6 (AA) × 6, Neck strap, Instruction Manual Carrying case: 9084(Carrying case)Soft]:4105A only)	25,292	30,844	Certificate of Conformity
L	RCD Testers		9030 3900	<u>5406A</u>	Digital RCD Tester Custom microprocessor controlled for highest accuracy and reliability. 3 LEDs for checking correct wiring status. 0 and 180 degree phase angle switch permits quick tests and consistent readings. Digital read-out of tripping time. Constant current source circuitry ensures that a fluctuating mains voltage does not affect the accuracy of readings. Large custom digital display readout. Visual indication of reversed phase and neutral wiring at socket. Designed to IP54 Rating. Complies with IEC 61557 Test of a large kind of RCD's: Standard, Selective, AC and A (DC sensitive breakers) Inc. Accessories:Molded plug test leads, Pouch for test leads Shoulder Strap, Instruction Manual	29,936	36,507	Test Certificate from KEW (A4 Size)
L		9	9030 3390	<u>8031</u>	Phase Indicator Digital Phase Indicator with open phase checker. Phase indicator designed to check the presence of open phase and also the phase sequence by LED and buzzer at the same time. Small, lightweight, and portable. Inc. Accessories: 9029 (Carrying Case), Instruction manual	9,177	11,191	Certificate of Conformity