



Your smart class room

HE LEADER DIGITAL PODIUM

Podium Specification

Podium Body Type Metal

Touch Monitor 22"(16:9 Wide) Touch Monitor

Switcher for Source Selection (VGA)

like, Laptop, PC, Document Camera

Integrated User Interface Laptop Interface (HDMI(1 IN/ 1Out) (VGA-1 Out-1

IN)VGA, LAN, MIC, AC Power

Audio System

Expended Interface VGA, LAN, MIC, AC Power

Microphones Gooseneck(Frequency Response- 100-15,000 Hrz

1000 Ω + 7mV/Pa Wireless

Mic (Hand + PIN- Audio output from receiver available at OUT 1 & OUT 2 individually and as

mixed output at OUT 1 + 2.

Amplifier 60W (4 Mic & 1 Aux Inputs.

Speaker 2 Wall Mount (10 W Each)

Drawing S/W Writing & Drawing /Capture

Manufacture Divine IC



Touch Monitor	
Item	Specification
Screen Size	51cm (22" WIDE)
Back light	LED
Resolution	1920 x 1080
PC Connection	USB Port
Luminosity	250 cd/m^2
Input Signal	RGB Input Signal, DVI
Outer Dimensions	454mm(W) x 320mm(h) x 62mm(D)
O/S	Windows 98, XP, Vista, 7,Max More than
Input Voltage, Ampere	DC12V, 4A
Sensor Method	Electromagnetic
Power Supply	100 ~ 250V AC

Document Camera



Model	VT-9988
Lens	8Mega Pixels 22-26×Optical Zoom, 10×Digital Zoom
Focus	Auto
Light	LED side lights , Base light(Optional)
Input	VGA*1、HDMI*1; VIDEO*1(Optional)、AUDIO
Output	VGA*1、HDMI*1; VIDEO*1(Optional)、AUDIO*1
Control	RS-232、USB
TV Line	≥1200TV Lines
N.W./G.W.	5Kg/6Kg±0.5Kg
Dimension	Closed ≤470*370*135 (mm) Openning ≤410*375*550 (mm)
Package size	440*200*550(mm)
Control Mode	Remote controller and touch panel
Digital function	Support annotation without PC Screen split, Freeze, Auto Focus Positive/Negative, Auto white balance Text/Image mode, Mirror Image, Image storage and replay, USB output
Power	12V DC power adapter