


Anti-Ambient Light

Bright light sources, such as a window with exposure to direct sunlight, won't reduce the contrast of the projected image



High Accuracy Touch

Infrared technology precise position

SMART BOARD VT/82



Ten Point Multi-Touch

Support for six simultaneous touches enables up to six users to interact with the interactive whiteboard by using the pens or other objects, or by using their fingers to write and to perform gestures.



USB Power Supply

Without external power supply, driven by USB 2.0 cable provides both a digital signal and power from your computer to your interactive whiteboard, you don't require an additional power supply.

Touch and Gestures

All board operations can be performed with finger touch or movement on the board surface. You can use the pen for writing and drawing. Both options offer smooth comfortable handwriting.

High Quality Ceramic Steel Surface

Ceramic board is optimized for projection and is compatible with dry-erase markers. It can be easily cleaned with whiteboard cleaner.

Quick Start Hot Keys

(22 Shortcut Keys on both side)

You can easily select a tool from these shortcut keys to click, write, erase and so on.

SMART BOARD

VT/82

voitto

INTERACTIVE SMART BOARD SOLUTION

SPECIFICATIONS

Model Number	SMART BOARD	
Outline Size	85" (1238 * 1775 mm)	
Inside Size	82.3" (1187 * 1710 mm)	
Display Ratio	4:3	
Toolbar	Two Sides, 22 Buttons Each Side	
Touch Technology	Infrared 10 Touch	
Response Object	Finger, Pen, any other Opaque Object	
Points Input	2/4/6	
Resolution	4096 * 4096	
Coordinate Accuracy	<2 mm	
Response Size	Ø3.0 mm, Recommended Size Ø5.0 mm	
Cursor Speed	180 d/s	
Respond Speed	First Dot (Click): 25 ms; Continuous Dots (Write) : 6 ms	
Board Material	Cold Press Steel Surface, High Density Polyfoam Core and Steel Back	High Density Ceramic Surface with Steel Back
Projection Effect	Excellent with Low Glare	
System Support	Windows 7/8/10, Linux Ubuntu 14.04/15.04, Android 4.0 and up, Mac 10.5 and up Version	
Interface	USB 2.0/3.0	

ACCESSORIES LIST (STANDARD)

USB Cable 5M, A-A 	Pens 	Extend Pen 	Eraser 	Application CD 	Wall Mount Bracket & Screws 	Quick Installation Pointor Guide 
--	---	---	---	--	--	---

PACKAGE INFORMATION

Model number	VT-82	VT-82CS
Packing Type	Double K & K Cartons	Double K & K Cartons
Package Size	1358*1920*90 mm (Approx)	1358*1920*90 mm (Approx)
Net Weight	22 KG (Approx)	24 KG (Approx)
Gross Weight	32 KG (Approx)	34 KG (Approx)

POWER SUPPLY

Power Supply	USB Power Supply
Voltage	DC 4.6V- 5.0V
Power Consumption	<1W (200mA at 5V)

ENVIRONMENT DATA

Temperature	Working Temperature: -10 °C to 50 °C
	Storage Temperature: -30 °C to 60 °C
Humidity	Working Humidity: 10% to 90%
	Storage Humidity: 0~95%

*Specification are subject to changed without any notice



Contact No: 9654779936

Email: sales@divineint.in