

**8mega  
pixel**

**Full HD  
1080**

**CCFL  
backlight**

**Multiple  
Porst**

**Touch  
Control  
Panel**

**HDMI  
IN/OUT**



**PANEL**

The control panel reacts only to human touch to avoid unintended manipulation. The one-piece surface protects the panel from dust and water, Various functions like freeze, positive/negative, image source switch are available



# Visualizer features



## HD 1080P

Display amazing high quality document images and full-length presentations.



## 270° Tilt Range of Camera

The camera can be tilted 270° towards the audience.



## Led light System

A high brightness led light provide smooth and consistent lighting for accurate color reproduction.



RS-232

## External Controlling

Use serial RS232 port to control the visualizer by control system.



## PC Input

Switch signal between Visualizer image and computer image from a PC which connected to external input.



## USB Device Port

Can be connected to a computer by USB 2.0 port using with Gaoke software to video capture



**Camera Lens**  
A large high precision premium quality lens creates a better image than a small low price lens



**Light System**  
A high power lamp provides smooth and consistent lighting for accurate colour reproduction



**Electronic Hardware**  
High end components deliver high performance, stability and reliability





# Standard accessories

3.5KG



## Accessories:



VGA



USB



HDMI(Optional)



Power adaptor



Remote controller



CD



## 01 CCD CAMERA

1/3-inch camera with 22-26 optical zoom, equipped with both auto and manual mode

## 02 BUILT-IN SLOT FOR FILM SLIDE

Built-in slot for film slide as well as the camera lens cover

## 03 REMOTE CONTROL

Remote control with all the functions, can be stored at the side of the machine

## 04 HID TECHNOLOGY

Equipped with HID technology, the visualizer can be used right after power on

## 05 PANEL

The control panel reacts only to human touch to avoid unintended manipulation. The one-piece surface protects the panel from dust and water. Various functions like freeze, positive/negative, image source switch are available

## 06 SAFE AND ENERGY EFFICIENT POWER SUPPLY UNIT

12V low voltage supply with anti-leakage circuit to avoid damage the electronic component by high voltage



|                  |  |
|------------------|--|
| Model            | <b>VT-999</b>  |
| Lens             | 8Mega Pixels<br>22-26×Optical Zoom, 10×Digital Zoom  |
| Focus            | Auto   |
| Light            | LED side lights , Base light(Optional)   |
| Input            | VGA*1、HDMI*1 ; VIDEO*1(Optional)、AUDIO   |
| Output           | VGA*1、HDMI*1 ; VIDEO*1(Optional)、AUDIO*1   |
| Control          | RS-232、 USB  |
| TV Line          | ≥1200TV Lines  |
| N.W./G.W.        | 5Kg/6Kg±0.5Kg  |
| Dimension        | Closed ≤470*370*135 (mm)<br>Opening ≤410*375*550 (mm)  |
| Package size     | 440*200*550(mm)  |
| Control Mode     | Remote controller and touch panel  |
| Digital function | Support annotation without PC<br>Screen split, Freeze, Auto Focus<br>Positive/Negative, Auto white balance<br>Text/Image mode, Mirror Image,<br>Image storage and replay, USB output |
| Power            | 12V DC power adapter   |



|                   |  |
|-------------------|--|
| Optional function | <ol style="list-style-type: none"> <li>1, 3.5" LCD screen</li> <li>2, Card reader</li> <li>3, Streaming function (can read files in USB disk or play video)</li> <li>4, MIC</li> <li>5, Simple controller</li> <li>6, Output function</li> <li>7, TV function</li> <li>8, Aluminum alloy suitcase</li> </ol> |
|-------------------|--|