

VIVA

All In One Heat Pump



Features

- ✓ R290 low GWP(GWP=3)
- ✓ WiFi Smart Control
- ✓ Energy Efficient Class (A++)
- ✓ Microchannel Heat Exchanger



Stable Silent Operation



20dB(A)*
Rustle of leaves



30dB(A)*
Whisper



43dB(A)
VIVA Heat
Pump



50dB(A)*
Fridge



70dB(A)*
Car

*dB results calculated from 1 meter distance

Technical Data



Model	YT-200TD2	YT-270TD2
Power Supply	220V~240V/50HZ	220V~240V/50HZ
Rated Input Power (Heat pump)	0.611KW	0.611KW
Rated Input Current (Heat pump)	2.71A	2.71A
Rated Heating Capacity (Heat pump)	3.037KW	3.037KW
Rated Input Power (Resistance)	1.8KW	1.8KW
Rated Input Current (Resistance)	8A	8A
Max Current (HP & Resistance)	8.2A	8.2A
Water Tank Volume	200L	270L
Recovery Rates (lires per hour)	60	60
COP (A 20/15, W 15-55)	4.97	4.97
STC in Zone 4	32	33
Refrigerant	R290 (400g)	R290 (400g)
Compressor	GMCC / Rotary	GMCC / Rotary
Expansion Valve	EEV	EEV
Fan	Axial	Axial
Ventilation	Horizontal discharge	Horizontal discharge
Heat Exchanger	Microchannel / Wrap around tank	Microchannel / Wrap around tank
Inner Tank Material	Enamel	Enamel
Inner Tank Thickness	Dome 3.0mm / Wall 2.5mm	Dome 3.0mm / Wall 2.5mm
Inner Tank Type	Concave	Concave
Insulation / thickness	Polyurethane / 40mm	Polyurethane / 40mm
Outer Casing	Galvanized painted sheet	Galvanized painted sheet
TPR Valve	850KPA	850KPA
Rated Outlet Water Temperature	60°C	60°C
Max Outlet Water Temperature	75°C	75°C
Working Range with Element	-15°C-43°C	-15°C-43°C
Working Range without Element	-7°C-43°C	-7°C-43°C
Anti Legionella	Water heated up to 70°C	Water heated up to 70°C
IP Class	IPX4	IPX4
Electric Shock Proof	I	I
Unpacked Dimension (outdoor unit)	φ620mm*1520mm	φ620mm*1840mm
Packed Dimension (outdoor unit)	700*700*1565mm	700*700*1885mm
Noise	43dB (A)	43dB(A)

Viva Heating And Air

Address: Se 2 321-323 Chapel Street, Prahran VIC 3181

Email: info@vivaheat.com.au

vivaheat.com.au



Hot Water Solutions For Life