



**THERMAL CONDUCTING CEMENTS  
FAMILY-OWNED & OPERATED SINCE 1954**

## **Banding/Fastening Straps**

### **200 Ft. Economy Coils**

#### **APPLICATIONS**

High corrosion-resistant non-magnetic stainless steel strapping, in a self-dispensing carton. Used for fastening tracers to process piping. May also be used to secure **Chemax CC** galvanized or stainless channels.

Use the **BT-001 Banding Tool** for tensioning.



#### **304 STAINLESS STEEL**

Type 304 is an 18% chromium and 8% nickel-alloyed stainless steel. It offers good corrosion resistance and is weldable. 304 is the preferred grade used in outdoor industrial applications.

Part NO.	Description	Package Type	Weight
SSB-050	1/2" X .020 (12.70 x .51 mm) Type 304 Stainless Steel	Self-Dispensing Carton, 200 ft. Roll	7 lb. (3.2 kg.)
SSB-075	3/4" X .020 (19.05 x .51 mm) Type 304 Stainless Steel	Self-Dispensing Carton, 200 ft. Roll	11.2 lb. (5.1 kg.)

## **BT-001 Banding Tool**

### **Heavy Duty Windlass Tensioner**

#### **APPLICATIONS**

For use with stainless steel strapping. It features a cutter and hammer knob for wing seal closing.

Highly portable, fast, reliable ratchet type tool.

