



## Banding/Fastening Straps

### 200 Ft. Economy Coils

#### APPLICATIONS

High corrosion-resistant non-magnetic stainless steel strapping, in a self-dispensing carton. Used for fastening tracers to process piping. May also be used to secure **Chemax CC** galvanized or stainless channels.

Use the **BT-001 Banding Tool** for tensioning.



#### 304 STAINLESS STEEL

Type 304 is an 18% chromium and 8% nickel-alloyed stainless steel. It offers good corrosion resistance and is weldable. 304 is the preferred grade used in outdoor industrial applications.

Type 316 stainless steel banding also available (**Part No. SSB-316**).

Part NO.	Description	Package Type	Weight
<b>SSB-050</b>	1/2" X .020 (12.70 x .51 mm) Type 304 Stainless Steel	Self-Dispensing Carton, 200 ft. Roll	7 lb. (3.2 kg.)
<b>SSB-075</b>	3/4" X .020 (19.05 x .51 mm) Type 304 Stainless Steel	Self-Dispensing Carton, 200 ft. Roll	11.2 lb. (5.1 kg.)
<b>SSB-316</b>	1/2" X .030 (12.70 x .76 mm) Type 316 Stainless Steel	Self-Dispensing Carton, 100 ft. Roll	5 lb. (2.3 kg.)

## Banding Tool

### Heavy Duty Windlass Tensioner

#### APPLICATIONS

For use with stainless steel strapping. It features a cutter and hammer knob for wing seal closing.

Highly portable, fast, reliable ratchet-type tool.

**Part No. BT-001**

