



HEAVY DUTY HELIFLEX / KANAFLEX



RECOMMENDATION:

Spirally reinforced heavy duty PVC suction hose. Available in 30M lengths in green. 150mm-300mm. Also available in yellow / clear. Used for suction and delivery of liquids and mixtures in open cast mine dewatering, agriculture, mining, industrial, civils, fishing, dredging and offshore diamond dredging.

ADVANTAGES:

Flexible, UV stabilized smooth bore, full flow. Abrasion, shock and crash resistant. Non-toxic PVC. Can withstand vacuum. Spirally reinforced, green or yellow with white rigid.

RECOMMENDED TEMP. RANGE:

0°C to + 60°C

LENGTHS:

30 Metre Lengths

ID (MM)	ID (INCHES)	WORKING PRESSURE (KPA)	BEND RADIUS (MM)	WEIGHT (Kg /M)	WEIGHT PER ROLL
25.4mm	1"	970	80	0.4	12
31.8mm	1.25"	720	120	0.6	18
38.1mm	1.5"	720	170	0.9	27
50.8mm	2"	620	250	1.2	30.6
63.5mm	2.5"	620	350	1.58	47.5
76.2mm	3"	480	400	1.8	54
101.6mm	4"	380	500	3.2	96
127mm	5"	240	800	5.2	156
152.4mm	6"	240	900	7	210
203.2mm	8"	220	1000	14	420
254mm	10"	200	*	17	510
304.8mm	12"	*	*	21	630