

XPEDITION TRAILERS VOYAGER CHECKLISTS

TAKING OUT OF STORAGE

- Inspect interior & exterior for damage sustained while stored.
- Take REDARC out of Storage Mode & put into Touring Mode.
- Check battery level & charge if needed.
- Grease suspension arms & hubs if needed (every 5,000 miles).
- Check lights / DOT lights.
- Disinfect water system.
- Run water through system & check for leaks.
- Test carbon monoxide detector, fire extinguisher & smoke detector.
- Test Truma Combi.
- Check seals/sealants.
- Test all connections & circuits.
- Test brakes & brakeaway switch.

COUPLING

- Make sure tow vehicle & hitch are rated for the GVWR of your trailer.
- Park trailer & tow vehicle on firm, level surface.
- Place wheel chocks.
- Align trailer coupler to tow vehicle hitch & lower into hitch using tongue jack & lock into place w/hitch pin & retaining pin.
- Connect safety chains (crossing first).
- Connect breakaway lanyard to tow vehicle frame, lock into place.
- Connect 7-pin plug.
- Connect DC to DC charger.
- Raise jack & lock in stowed position.
- Remove wheel chocks.
- Drive tow vehicle forward.

PRE-TOW

- Check tires, wheels & lug nuts.
- Check tire pressure: inflate to pressure stated on VIN label.
- Coupler secured & locked.
- Safety chains properly rigged to tow vehicle.
- Test DOT lighting.
- Test trailer brakes.
- Safety breakaway lanyard fastened to the tow vehicle.
- Cargo properly loaded, balanced & tied down.
- Proper weight distribution & tongue weight.

GENERAL TRAILER MAINTENANCE

- Lug Nuts: re-tighten at first 10/25/50/100 miles & every 3000 miles.
- Brakes: Adjust within first 200 miles & every 3000 miles. Replace as recommended by a professional.
- Suspension Arms & Hubs: grease every 5000 miles.
- Tires: Rotate every 5000 miles & replace as needed.
- Slides, Hinges & Latches: lubricate & tighten as needed.
- Test/replace smoke detector, fire extinguisher & carbon monoxide detector according to manufacturer.
- Use mild cleanser w/microfiber cloth to clean interior & exterior.
- Replace seals/sealants as needed.

PUTTING INTO STORAGE

- Store trailer in dry, level, well-ventilated area protected from animals & insects. Stabilize wheels.
- Clean out fridge/freezer & dry thoroughly. Prop open.
- Clean all interior & exterior surfaces and dry thoroughly.
- Check tires & set tire pressure to recommended psi.
- Grease suspension arms & hubs if needed.
- Winterize water system.
- Inspect all seals & repair if needed.
- Extend tent, awning(s) & shower (if applicable) and clean & dry before storing.
- Secure all components & attachments.
- Put REDARC into Storage Mode (all circuits off).
- Plug trailer into shore power.

WINTERIZING

For detailed instructions, go to: xpeditiontrailers.com/owner-resources.

- Turn off Truma & cool completely.
- Depressurize water system.
- Drain tank w/faucet & shower on.
- Put Truma in bypass mode.
- Open Truma valve & drain all water from tank.
- Turn off sink, close petcock valve. Turn shower hose on warm.
- With air compressor set to 45 psi, blow air into tank fill port, until no water comes out of breather & shower hose. Repeat on cold.

continued ⇨

WINTERIZING CONTINUED

- Turn on kitchen faucet to warm & repeat process of blowing air into fill port until empty. Repeat with faucet water on cold.
- Remove/clean out strainer & replace.

To return your Voyager trailer to service:

- Close Truma drainage valve.
- Take Truma out of bypass mode.
- Refill water tank.

DISINFECTING THE WATER SYSTEM

- Prepare chlorine solution using 2.5 gallons water & 5/8ths cup household bleach.
- With tank empty, pour chlorine solution into tank.
- Fill remainder of tank with potable water.
- Open each faucet and run water until chlorine odor is detected in the water discharged. Don't forget both hot & cold water taps.
- Allow system to stand for at least 4 hours with solution.
- Drain and flush with potable water.

