

# **AES MUL PLUS**

#### **SECTION 1. IDENTIFICATION**

Product Identifier AES MUL PLUS
Other Means of Blended Emulsifier

Identification

**Recommended Use** Drilling Fluid Additive.

Manufacturer / AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales &

**Supplier** Information, 281-556-5628

Emergency Phone No. CHEMTREC, 1-800-424-9300, 24-hour Emergency

**Date of Preparation** April 17, 2015

# **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Acute toxicity (Dermal) - Category 4; Skin corrosion/irritation - Category 3; Serious eye damage/eye irritation - Category 2B; Skin sensitization - Category 1B; Specific target organ toxicity (single exposure) - Category 3; Aspiration hazard - Category 2

## **GHS Label Elements**





# Signal Word:

Warning

Hazard Statement(s):

H303 May be harmful if swallowed.

H305 May be harmful if swallowed and enters airways.

H312 Harmful in contact with skin. H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H320 Causes eye irritation.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary Statement(s):

Prevention:

P264 Wash hands and skin thoroughly after handling.

P261 Avoid breathing vapours, mist, spray.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

Product Identifier: AES MUL PLUS

Date of Preparation: April 17, 2015 Page 01 of 07

and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Blend of chemically modified tall oil derivative	68154,94-9, 8050-09-7	10-20	
Mixture of Fatty acids, tall oil	61790-12-3	20	
Trade Secret	CBI*	Confidential	
Trade Secret	CBI*	Confidential	
Trade Secret	CBI*	Confidential	

#### **Notes**

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

CBI = Confidential Business Information.

#### **SECTION 4. FIRST-AID MEASURES**

#### **First-aid Measures**

#### Inhalation

Remove source of contaminant or move to fresh air. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. Get medical advice/attention if you feel unwell or are concerned.

#### **Skin Contact**

Immediately rinse with lukewarm, gently flowing water for 15-20 minutes. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Seek medical advice/attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

### **Eye Contact**

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Seek medical advice/attention.

#### Ingestion

Immediately call a Poison Centre or doctor. Rinse mouth with water. Do not induce vomiting. If vomiting occurs, have victim lean forward to reduce the risk of aspiration.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

## **Suitable Extinguishing Media**

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

#### **Specific Hazards Arising from the Chemical**

Product can ignite if strongly heated and exposed to open flames. Closed containers may rupture violently when heated releasing contents.

Oxides of carbon.

# **Special Protective Equipment and Precautions for Fire-fighters**

Use water spray to cool containers/tanks. Dike and collect water used to fight fire.

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

Product Identifier: AES MUL PLUS

Date of Preparation: April 17, 2015 Page 02 of 07

# **SECTION 6. ACCIDENTAL RELEASE MEASURES**

## Personal Precautions, Protective Equipment, and Emergency Procedures

Isolate the hazard area. Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

#### **Environmental Precautions**

Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Prevent product from entering drains, soil, ditches, sewers, waterways and/or groundwater.

# Methods and Materials for Containment and Cleaning Up

Dike spilled product to prevent runoff. Do not use absorbents. Contain spill using noncombustible material such as vermiculite, earth or sand. Place contaminated vermiculite, earth or sand into suitable, covered, labelled containers for disposal. Store recovered product in suitable containers for disposal according to local regulations.

#### Other Information

Contact EH&S regarding spill as spills of certain products and certain quantities may require reporting to various authorities.

#### **SECTION 7. HANDLING AND STORAGE**

## **Precautions for Safe Handling**

Avoid breathing in this product. Avoid contact with eyes, skin and clothing. Do not ingest product. Do not eat, drink or smoke in areas where product is handled. Employees should wash hands after working with product and before going on breaks outside of the work area. Avoid generating vapours or mists. Ensure adequate ventilation. Keep containers tightly closed when not in use or empty. Keep away from heat and open flames. See Section 8 for appropriate Personal Protective Equipment (PPE).

#### **Conditions for Safe Storage**

Store in an area that is: cool, dry, well-ventilated. Away from open flames, excessive heat or sources of ignition. Separate from incompatible materials (see Section 10: Stability and Reactivity). Keep containers tightly closed when not in use. Empty containers may contain hazardous residue. Store separately. Keep closed. Follow all precautions given on this safety data sheet.

# **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## **Control Parameters**

Chemical Name	ACGIH® TLV®		OSHA PEL		AIHA® WEEL™	
	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]
Trade Secret	5 mg/m3	10 mg/m3	5 mg/m3	Not established	Not established	Not established
Trade Secret	5 mg/m3		Not established		Not established	
Mixture of Fatty acids, tall oil	5 mg/m3	10 mg/m3	5 mg/m3	Not established	Not established	Not established
Trade Secret	5 mg/m3	10 mg/m3	5 mg/m3	Not established	Not established	Not established
Blend of chemically modified tall oil derivative	Not established		Not established		Not established	

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. C = Ceiling limit. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL<sup>TM</sup> = Workplace Environmental Exposure Limit.

OEL values are for Oil Mist. There is no established TLV or OEL's for petroleum distillates.

#### **Appropriate Engineering Controls**

Product Identifier: AES MUL PLUS

Date of Preparation: April 17, 2015 Page 03 of 07

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with the product an eyewash and safety shower should be within acceptable distance to the work area.

#### **Individual Protection Measures**

#### **Eye/Face Protection**

Wear safety glasses and if contact is possible wear chemical safety goggles.

#### **Skin Protection**

Wear gloves with appropriate chemical resistance, see manufacturers specifications for suitability. Wear long sleeves, long pants and appropriate footwear while working with product. If a splashing hazard exists wear chemical protective clothing e.g. gloves that extend up arms, aprons, boots.

#### **Respiratory Protection**

If conditions exist above the OEL wear a NIOSH approved air-purifying respirator with an appropriate cartridge.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

## **Basic Physical and Chemical Properties**

**Appearance** Amber liquid.

**Odour** Faint

Odour Threshold Not available pH Not available

Melting Point/Freezing Point Not available (melting); Not available (freezing)

Initial Boiling Point/RangeNot availableFlash Point> 230 °F (110 °C)Evaporation RateNot available

**Upper/Lower Flammability or** 

**Explosive Limit** 

Not available (upper); Not available (lower)

Vapour Pressure Not available Vapour Density (air = 1) Not available

Relative Density (water = 1) 0.95

Solubility Insoluble in water Partition Coefficient, Not available

n-Octanol/Water (Log Kow)

Auto-ignition TemperatureNot availableDecomposition TemperatureNot available

Other Information

Physical State Liquid

# **SECTION 10. STABILITY AND REACTIVITY**

## Reactivity

Not reactive under normal conditions of use.

#### **Chemical Stability**

Stable under normal conditions.

# Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

#### **Conditions to Avoid**

Open flames, sparks, static discharge, heat and other ignition sources.

#### **Incompatible Materials**

Strong Oxidizing Agents.

#### **Hazardous Decomposition Products**

Carbon oxides.

Product Identifier: AES MUL PLUS

Date of Preparation: April 17, 2015 Page 04 of 07

# **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Likely Routes of Exposure**

Inhalation; skin contact; eye contact; ingestion.

#### **Acute Toxicity**

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Trade Secret	Not available	>5000 mg/kg (rat)	Not available
Trade Secret	Not available	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Mixture of Fatty acids, tall oil	Not available	> 10000 mg/kg	Not available
Trade Secret	Not available	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Blend of chemically modified tall oil derivative	Not available	Not available	Not available

## Skin Corrosion/Irritation

May cause skin irritation.

#### Serious Eye Damage/Irritation

May cause eye irritation. Symptoms include pain, redness and tearing.

# STOT (Specific Target Organ Toxicity) - Single Exposure

#### Inhalation

May cause irritation of the mucous membranes and upper respiratory tract. May cause depression of the central nervous system.

#### **Skin Absorption**

No information was located.

#### Ingestion

May cause irritation of the mouth, throat and stomach. May cause depression of the central nervous system.

## **Aspiration Hazard**

Liquid may be aspirated into the lungs during ingestion or vomiting resulting in lung injury.

## STOT (Specific Target Organ Toxicity) - Repeated Exposure

Prolonged skin contact may aggravate existing skin conditions such as dermatitis.

# Respiratory and/or Skin Sensitization

May cause skin sensitization through skin contact. May cause sensitization by inhalation.

# Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Trade Secret	Not Listed	Not Listed	Not Listed	Not Listed
Trade Secret	Not Listed	Not Listed	Not Listed	Not Listed
Mixture of Fatty acids, tall oil	Not Listed	Not Listed	Not Listed	Not Listed
Trade Secret	Group 3	A4	Not Listed	Not Listed
Blend of chemically modified tall oil derivative	Not Listed	Not Listed	Not Listed	Not Listed

Not known to cause cancer.

Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 3 = Not classifiable as to its carcinogenicity to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A4 = Not classifiable as a human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

#### **Reproductive Toxicity**

# **Development of Offspring**

No information was located.

Product Identifier: AES MUL PLUS

Date of Preparation: April 17, 2015 Page 05 of 07

#### **Sexual Function and Fertility**

No information was located.

#### **Germ Cell Mutagenicity**

No information was located.

## **SECTION 12. ECOLOGICAL INFORMATION**

Do not allow product to contaminate domestic or irrigation water supplies, lakes, streams, ponds or rivers.

## **Toxicity**

No information was located.

#### **Acute Aquatic Toxicity**

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Trade Secret	Not available	Not available	Not available	Not available
Trade Secret	2.9 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour)	Not available	Not available	Not available
Mixture of Fatty acids, tall oil	Not available	Not available	Not available	Not available
Trade Secret	Not available	Not available	Not available	Not available
Blend of chemically modified tall oil derivative	Not available	Not available	Not available	Not available

# Persistence and Degradability

No information was located.

#### **Bioaccumulative Potential**

No information was located.

#### **Mobility in Soil**

No information was located.

#### SECTION 13. DISPOSAL CONSIDERATIONS

## **Disposal Methods**

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

#### **SECTION 14. TRANSPORT INFORMATION**

Not regulated under US DOT Regulations.

# **SECTION 15. REGULATORY INFORMATION**

# Safety, Health and Environmental Regulations USA

## Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or exempt from the TSCA.

#### **Additional USA Regulatory Lists**

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA.

SARA Title III - Section 302: No listed components.

SARA Title III - Section 311/312: Immediate Health Hazard

SARA Title III - Section 313: May contain <1.0% Glycol Ether.

Product Identifier: AES MUL PLUS

Date of Preparation: April 17, 2015 Page 06 of 07

# **SECTION 16. OTHER INFORMATION**

NFPA Rating Health - 2 Flammability - 1 Instability - 0

SDS Prepared By AES Drilling Fluids Phone No. 281-556-5628

Date of Preparation April 17, 2015

**Disclaimer** Do not handle or use until precautions on MSDS are read and understood. The information on

this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss,

damage, direct or consequential, arising out of their use.

Product Identifier: AES MUL PLUS
Date of Preparation: April 17, 2015

Page 07 of 07

