



# **GXM PLUS**

## **SECTION 1. IDENTIFICATION**

Product Identifier GXM PLUS

Other Means of Blended Graphite

Identification

**Recommended Use** Drilling Fluid Additive.

Manufacturer / AES Drilling Fluids, LLC, 11767 Katy Freeway, Suite 230, Houston, TX, 77079, Sales &

Supplier Information, 281-556-5628

Emergency Phone No. CHEMTREC, 1-800-424-9300, 24-hour Emergency

**Date of Preparation** March 04, 2015

## **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Acute toxicity (Oral) - Category 4; Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 1

OSHA Defined Hazards: Combustible dust

## **GHS Label Elements**





Signal Word:

Danger

Hazard Statement(s):

H302 + H332 Harmful if swallowed or if inhaled. Dust in eve may result in mechanical irritation.

May cause lung cancer through prolonged or repeated inhalation exposure

May form combustible dust concentrations in air

Precautionary Statement(s):

Prevention:

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/eye protection/face protection.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

P330 Rinse mouth.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Product Identifier: GXM PLUS

Date of Preparation: March 04, 2015 Page 01 of 06

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No.	%	Other Identifiers
Graphite (natural)	7782-42-5	<100	
Silica, quartz	14808-60-7	<4	

### **SECTION 4. FIRST-AID MEASURES**

#### **First-aid Measures**

#### Inhalation

Remove source of contaminant or move to fresh air. Get medical advice/attention if irritation develops.

#### **Skin Contact**

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If irritation persists, get medical advice/attention.

## **Eye Contact**

Flush eyes thoroughly with lukewarm water for 15 minutes. If eye irritation persists, get medical advice/attention.

#### Ingestion

Rinse mouth with water. Seek medical advice.

## **SECTION 5. FIRE-FIGHTING MEASURES**

## **Suitable Extinguishing Media**

Water, Carbon Dioxide, Foam, Dry chemical.

## **Specific Hazards Arising from the Chemical**

Does not burn.

Oxides of carbon.

### **Special Protective Equipment and Precautions for Fire-fighters**

If product ground to sub-micron sizes, graphite may present a hazard of igniting spontaneously in air in high dust concentrations.

When fighting chemical fires, emergency responders should wear NIOSH approved self contained breathing apparatus and appropriate protective clothing.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

### Personal Precautions, Protective Equipment, and Emergency Procedures

Isolate the hazard area. Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

#### **Environmental Precautions**

It is good practice to prevent releases into the environment. Do not allow into any sewer, on the ground or into any waterway.

### Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources. Vacuum or sweep product up, try to minimize dust build-up. Wet sweeping may be used to minimize dust build-up. Store recovered product in suitable containers that are: tightly-covered. Containerize for solid waste disposal. Spill material may cause floors and contact surfaces to become slippery, flush slowly with water, collect and store in suitable containers.

## **SECTION 7. HANDLING AND STORAGE**

#### **Precautions for Safe Handling**

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. Only use where there is adequate ventilation. Avoid creating excessive dust while handling the product. See Section 8 for appropriate Personal Protective Equipment (PPE).

Product Identifier: GXM PLUS

Date of Preparation: March 04, 2015 Page 02 of 06

### **Conditions for Safe Storage**

Store in an area that is: well-ventilated. Keep containers tightly closed when not in use. Eliminate nearby ignition sources. Use good housekeeping to prevent accumulation of dust.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control Parameters**

	ACGIH®	ACGIH® TLV®		OSHA PEL		AIHA® WEEL™	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term TWA [C]	
Silica, quartz	0.025 mg/m3 A2		0.1 mg/m3		Not established		
Graphite (natural)	2 mg/m3 (R)		3 mg/m3 (R)		Not established		

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA® = AIHA® Guideline Foundation. WEEL™ = Workplace Environmental Exposure Limit. R = Respirable fraction.

### **Appropriate Engineering Controls**

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. While working with this product an eyewash should be within acceptable distance to the work area.

### **Individual Protection Measures**

### **Eye/Face Protection**

Safety glasses or goggles.

#### **Skin Protection**

Work gloves. Wear long sleeves, long pants and appropriate footwear while working with product.

## **Respiratory Protection**

If conditions of use promote large amounts of dust to gather in the work area, wear NIOSH approved dust mask or respirator.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

## **Basic Physical and Chemical Properties**

**Appearance** Dark grey - black powder.

**Odour** Faint

**pH** Not available

Melting Point/Freezing Point Not applicable (melting); Not applicable (freezing)

Initial Boiling Point/RangeNot availableFlash PointNot applicableEvaporation RateNot applicableFlammability (solid, gas)Not available

**Upper/Lower Flammability or** 

**Explosive Limit** 

Not applicable (upper); Not applicable (lower)

Vapour Pressure Not available
Vapour Density (air = 1) Not available

Relative Density (water = 1) 2.26

**Solubility** Insoluble in water **Auto-ignition Temperature** Not available

Other Information

Physical State Solid

Product Identifier: GXM PLUS

Date of Preparation: March 04, 2015 Page 03 of 06

### **SECTION 10. STABILITY AND REACTIVITY**

#### Reactivity

Not reactive.

#### **Chemical Stability**

Stable under normal conditions.

### **Possibility of Hazardous Reactions**

None expected under normal conditions of storage and use.

### **Conditions to Avoid**

Strong oxidizers.

#### **Incompatible Materials**

Strong Oxidizing Agents.

#### **Hazardous Decomposition Products**

Oxides of carbon.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Likely Routes of Exposure**

Inhalation; eye contact; skin contact; ingestion.

### **Acute Toxicity**

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Silica, quartz	Not available	500 mg/kg (rat)	Not available
Graphite (natural)	Not available	Not available	Not available

#### Skin Corrosion/Irritation

May cause skin irritation.

### Serious Eye Damage/Irritation

May cause eye irritation. May cause mechanical irritation to eyes.

## STOT (Specific Target Organ Toxicity) - Single Exposure

#### Inhalation

May cause irritation of the mucous membranes and upper respiratory tract.

## **Skin Absorption**

Not harmful.

### Ingestion

May be harmful if ingested may cause. irritation of the gastrointestinal tract, nausea, vomiting, diarrhea.

### STOT (Specific Target Organ Toxicity) - Repeated Exposure

This product contains small amounts of crystalline silica (quartz). long term exposure to respirable crystalline silica dust over the TLV may lead to the development of silicosis or other respiratory problems. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. Chronic inhalation exposure to natural graphite is associated with the development of pneumoconiosis, a disease of the lungs.

#### Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

### Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Silica, quartz	Group 1	A2	Known carcinogen	Not Listed
Graphite (natural)	Not Listed	Not Listed	Not Listed	Not Listed

This product contains free silica which the International Agency for Research on Cancer (IARC) has listed as causing cancer in humans.

Product Identifier: GXM PLUS

Date of Preparation: March 04, 2015 Page 04 of 06

### Key to Abbreviations

IARC = International Agency for Research on Cancer. Group 1 = Carcinogenic to humans. ACGIH® = American Conference of Governmental Industrial Hygienists. A2 = Suspected human carcinogen. NTP = National Toxicology Program. OSHA = US Occupational Safety and Health Administration.

#### Reproductive Toxicity

### **Development of Offspring**

Not known to harm the unborn child.

#### **Sexual Function and Fertility**

Not known to cause effects on sexual function or fertility.

### **Germ Cell Mutagenicity**

Not known to be a mutagen.

#### **Interactive Effects**

Smoking and being exposed to free silica may cause a greater risk of developing certain pulmonary illnesses.

### **SECTION 12. ECOLOGICAL INFORMATION**

Environmental information was not located.

#### **Toxicity**

No information was located.

## **Acute Aquatic Toxicity**

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Silica, quartz	Not available	Not available	Not available	Not available
Graphite (natural)	Not available	Not available	Not available	Not available

### Persistence and Degradability

No information was located.

#### **Bioaccumulative Potential**

No information was located.

### **Mobility in Soil**

No information was located.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal Methods**

Dispose of in accordance with all local, state and federal regulations. Not classified as RCRA Hazardous. RCRA WASTE NUMBER: Not Applicable.

## **SECTION 14. TRANSPORT INFORMATION**

Not regulated under US DOT Regulations.

## **SECTION 15. REGULATORY INFORMATION**

### Safety, Health and Environmental Regulations

#### **USA**

### Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

## **Additional USA Regulatory Lists**

CERCLA: Product does not contain any chemicals subject to the reporting requirement of CERCLA.

SARA Title III - Section 302: No listed components.

SARA Title III - Section 311/312: Chronic Health Hazard.

SARA Title III - Section 313: No chemicals are reportable under Section 313.

Product Identifier: GXM PLUS

Date of Preparation: March 04, 2015 Page 05 of 06

## **SECTION 16. OTHER INFORMATION**

NFPA Rating Health - 1 Flammability - 1 Instability - 0

SDS Prepared By AES Drilling Fluids Phone No. 281-556-5628

Date of Preparation March 04, 2015

**Disclaimer** Do not handle or use until precautions on MSDS are read and understood. The information on

this form is furnished solely for the purpose of enabling those who transport, handle or use our products to ensure the safety and health of their employees and to comply with various laws and regulations (federal, state and local). We believe the statements, technical information and recommendations contained herein are reliable but, they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss,

damage, direct or consequential, arising out of their use.

Product Identifier: GXM PLUS

Date of Preparation: March 04, 2015 Page 06 of 06

