

PHASETREAT 15712 Page 1

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

SECTION 1. IDENTIFICATION

Identification of the

company:

Clariant Corporation 4000 Monroe Road

Charlotte, NC, 28205

Telephone No.: +1 704-331-7000

Information of the substance/preparation:

BU Oil & Mining Services

Product Stewardship +1-704-331-7710

Emergency tel. number: +1 800-424-9300(CHEMTREC)

Trade name: PHASETREAT 15712

Material number: 306802

Primary product use: Industrial use
Chemical family: demulsifier

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2

Skin irritation : Category 2

Serious eye damage : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity

- repeated exposure

Category 2 (Kidney, Liver, Central nervous system, hearing

organs)

Specific target organ toxicity

- repeated exposure

(Inhalation)

Category 2 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements



PHASETREAT 15712 Page 2

Substance key: 000000720848 Revision Date: 03/26/2020 Date of printing:04/15/2021 Version: 2-2/USA

Hazard pictograms









Signal word Danger

H225 Highly flammable liquid and vapour. Hazard statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eve damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs (Kidney, Liver, Central nervous system, hearing organs) through prolonged or repeated

exposure.

H373 May cause damage to organs (Central nervous system)

through prolonged or repeated exposure if inhaled.

Precautionary statements Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.



PHASETREAT 15712 Page 3

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Xylene	1330-20-7	30 - 50
Toluene	108-88-3	30 - 50
Ethylbenzene	100-41-4	5 - 10
Dodecylbenzene sulphonate-MEA salt (Analogy)	26836-07-7	3 - 5
Hydrocarbons, C10, aromatics, >1% naphthalene	64742-94-5	1 - 5
Benzenesulfonic acid, C10-16-alkyl derivs.	68584-22-5	0.1 - 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Remove/ Take off immediately all contaminated clothing.

Get medical advice/ attention if you feel unwell.

If inhaled : Move the victim to fresh air.

Give oxygen or artificial respiration if needed. Get immediate medical advice/ attention.

Never give anything by mouth to an unconscious person.

In case of skin contact : Wash thoroughly with soap and water for 15 minutes. If skin



PHASETREAT 15712 Page 4

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

irritation occurs, seek medical attention.

In case of eye contact : Rinse thoroughly with plenty of water for at least 15 minutes

and consult a physician.

If swallowed : Get medical attention immediately.

Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed

The possible symptoms known are those derived from the

labelling (see section 2).

No additional symptoms are known.

The possible risks known are those derived from the labelling

(see section 2).

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water mist

Alcohol-resistant foam

Dry chemical

Carbon dioxide (CO2)

Cool containers/tanks with water spray.

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

In case of fires, hazardous combustion gases are formed:

Carbon monoxide (CO) Carbon dioxide (CO2)

Further information : Wear positive pressure self-contained breathing apparatus

and full protective gear. Do not direct a solid stream of water or foam into hot burning pools; this may spread fire, cause frothing, and increase fire intensity. Containers can build up pressure if exposed to heat and/or fire. Vapors may form an explosive mixture with air. Vapors may travel to source of ignition and flash back. Use water spray to keep containers

cool.

Special protective equipment:

for firefighters

Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Wear personal protective equipment.

Remove all spark producing devices or ignition sources. Wear proper personnel protective equipment. Using non-sparking tools collect as a liquid for recycling/disposal or absorb onto a



PHASETREAT 15712 Page 5

Substance key: 000000720848 Revision Date: 03/26/2020 Version: 2-2/USA Date of printing :04/15/2021

suitable absorbant and secure in a suitable container. Collect

any contaminated soils or cleaning waste in a suitable

container for proper disposal.

Absorbent materials such as dry sand, absorbent booms, and vermiculite may be used to keep material from entering drains,

sewers, or streams.

Do not allow spilt product to enter soil or waterways Environmental precautions

Methods and materials for containment and cleaning up Take measures to prevent the build up of electrostatic charge.

Dispose of in accordance with local regulations.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Observe the general rules of industrial fire protection

Advice on safe handling Keep away from sources of ignition - No smoking.

> Keep tightly closed in a dry, cool and well-ventilated place. Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres. Wash thoroughly after handling. Incompatible with oxidizing agents.

Further information on storage conditions

Store in original container. Keep container tightly closed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2



PHASETREAT 15712

Page 6

Substance key: 000000720848	Revision Date: 03/26/2020
Version: 2 - 2 / USA	Date of printing :04/15/2021

			(10 minutes)	
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
Xylene	1330-20-7	Methylhippu ric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of workwee k	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl	Urine	End of shift (As soon as possible	0.15 g/g creatinine	ACGIH BEI



PHASETREAT 15712 Page 7

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

glyoxylic after exposure ceases)

Engineering measures : A system of local and/or general exhaust is recommended

where employee exposures are at or above Occupational

Exposure Limits (OEL).

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Hand protection

Material : Silver Shield(R) gloves

Remarks : Viton® PVA gloves or gauntlets

Eye protection : Wear safety glasses with side shelds, chemical splash

goggles, and /or full face shield to prevent contact with eyes.

Skin and body protection : Flame retardant protective clothing

Protective measures : Observe the usual precautions for handling chemicals.

Hygiene measures : The usual Industrial Hygiene precautions must be taken

during work, in particular: do not drink, eat or smoke during the handling of the product and clean hands and face during

work intervals and after work.

Ensure that eyewash stations and safety showers are close

to the workstation location.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : Straw-colored, to, amber

Odour : characteristic

Odour Threshold : no data available

pH : Not applicable

Melting point : $> 32 \, ^{\circ}\text{F} / > 0 \, ^{\circ}\text{C}$

Boiling point : 219 - 340 °F / 104 - 171 °C

Flash point : $< 73 \,^{\circ}\text{F} / < 23 \,^{\circ}\text{C}$



PHASETREAT 15712 Page 8

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Evaporation rate : 0.8

Flammability (solid, gas) : Not applicable

Self-ignition : no data available

Upper explosion limit / upper

flammability limit

7 %(V)

Lower explosion limit / Lower :

flammability limit

0.8 %(V)

Vapour pressure : 0.027 kPa

Relative vapour density : 2.1

Density : 0.87 - 0.91 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : < 1 mg/l insoluble

Partition coefficient: n-

octanol/water

no data available

Auto-ignition temperature : 725 °F / 385 °C

Decomposition temperature : no data available

Viscosity

Viscosity, dynamic : 1.38 mPa.s (77 °F / 25 °C)

Viscosity, kinematic : no data available

Explosive properties : Not explosive

Oxidizing properties : no data available

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : Stable

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : Keep away from open flames, hot surfaces and sources of

ignition.



PHASETREAT 15712 Page 9

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Incompatible materials : Oxidizing agents

Strong acids and strong bases

Hazardous decomposition

products

Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 24.67 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 2,801 mg/kg

Method: Calculation method

Components:

Xylene:

Acute oral toxicity : LD50 (Rat, male and female): 3523 - > 4000 mg/kg

Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

GLP: no

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat, male): 27.571 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: Directive 67/548/EEC, Annex V, B.2.

GLP: No information available.

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : Other (Rabbit, male): > 4,200 mg/kg

Method: Other

GLP: No information available.

Assessment: The component/mixture is moderately toxic after



PHASETREAT 15712 Page 10

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

single contact with skin.

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Symptoms: Vomiting, Stomach/intestinal disorders

Acute inhalation toxicity : (Rat): > 20 mg/l

Exposure time: 4 h

Target Organs: Lungs, Respiratory system, Liver, Kidney,

Nervous system

Symptoms: Lung oedema, Breathing difficulties, Vomiting,

Pain, Dizziness

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Ethylbenzene:

Acute oral toxicity : LD50 (Rat, male and female): ca. 3,500 mg/kg

Method: Other GLP: no

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after

short term inhalation.

Skin corrosion/irritation

Product:

Result: Irritating to skin.

Components:

Xylene:

Species: Rabbit Method: Other

Result: Irritating to skin. GLP: No information available.

Toluene:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

Ethylbenzene:

Species: Rabbit Method: Other Result: slight irritation

GLP: no

Dodecylbenzene sulphonate-MEA salt (Analogy):



PHASETREAT 15712

Page 11

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Result: Irritating to skin.

Hydrocarbons, C10, aromatics, >1% naphthalene:

Result: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product:

Result: Risk of serious damage to eyes.

Components:

Xylene:

Species: rabbit eye Result: Irritating to eyes.

Method: Other

GLP: No information available.

Toluene:

Species: rabbit eye Result: slight irritation

Assessment: No eye irritation Method: OECD Test Guideline 405

Ethylbenzene:

Species: rabbit eye Result: slight irritation

Method: Other GLP: no

Dodecylbenzene sulphonate-MEA salt (Analogy):

Result: Risk of serious damage to eyes.

Benzenesulfonic acid, C10-16-alkyl derivs.:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Product:

Result: non-sensitizing

Components:

Xylene:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin contact

Species: Mouse



PHASETREAT 15712 Page 12

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Method: OECD Test Guideline 429 Result: Not a skin sensitizer. GLP: No information available.

Toluene:

Exposure routes: Skin contact

Species: Rat

Result: Does not cause skin sensitisation.

Ethylbenzene:

Remarks: not required

Germ cell mutagenicity

Components:

Xylene:

Genotoxicity in vitro : Test Type: sister chromatid exchange assay

Test system: Chinese hamster ovary cells

Concentration: 5 - 50 µg/ml

Metabolic activation: with and without metabolic activation

Method: Other Result: negative

GLP: No information available.

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Concentration: 15,1 - 100,5 µg/ml

Metabolic activation: with and without metabolic activation

Method: Directive 84/449/EEC, B.10

Result: negative

GLP: No information available.

Genotoxicity in vivo : Test Type: dominant lethal test

Species: Mouse (male and female)

Strain: Other

Application Route: Subcutaneous Exposure time: single injection

Dose: 1 ml/kg

Method: OECD Test Guideline 478

Result: negative

GLP: no

Germ cell mutagenicity -

Assessment

It is concluded that the product is not mutagenic based on

evaluation of several mutagenicity tests.

Toluene:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation



PHASETREAT 15712 Page 13

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Method: Regulation (EC) No. 440/2008, Annex, B.13/14

(Ames test) Result: negative

Test Type: gene mutation test Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Cytogenetic assay

Species: Rat Method: Other Result: negative

Germ cell mutagenicity -

Assessment

In vitro tests did not show mutagenic effects

In vivo tests did not show mutagenic effects

Ethylbenzene:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster ovary cells

Concentration: 75 - 125 µg/ml

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

GLP: no

Test Type: In vitro gene mutation study in mammalian cells

Test system: mouse lymphoma cells Concentration: 4,2 - 1060 µg/ml

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative GLP: yes

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male and female)

Strain: NMRI

Cell type: Bone marrow

Application Route: oral (gavage) Exposure time: 24 - 48 h Dose: 187,5-375-750 mg/kg Method: OECD Test Guideline 474

Result: negative

GLP: yes

Test Type: unscheduled DNA synthesis assay

Species: Mouse (male and female)

Strain: B6C3F1



PHASETREAT 15712 Page 14

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Application Route: Inhalation

Exposure time: 6 h

Dose: 375-500-750-1000 ppm Method: OECD Test Guideline 486

Result: negative GLP: yes

Germ cell mutagenicity -

Assessment

In vitro tests did not show mutagenic effects, In vivo tests did

not show mutagenic effects

Carcinogenicity

Components:

Xylene:

Carcinogenicity - Assessment

Animal testing did not show any carcinogenic effects.

Toluene:

Carcinogenicity -

Assessment

: Not classifiable as a human carcinogen.

Ethylbenzene:

Carcinogenicity -

Not classifiable as a human carcinogen.

Assessment

Hydrocarbons, C10, aromatics, >1% naphthalene:

Carcinogenicity - : Suspected human carcinogens

Assessment

IARC Listed

OSHA Not listed

NTP Not listed

Reproductive toxicity

Components:

Xylene:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female Application Route: Inhalation Dose: 25 - 100 - 500 ppm

Duration of Single Treatment: 6 h

General Toxicity - Parent: NOAEL: >= 2.171 mg/l General Toxicity F1: NOAEL: >= 2.171 mg/l General Toxicity F2: NOAEL: >= 2.171 mg/l

Method: Other



PHASETREAT 15712 Page 15

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

GLP: No information available.

Remarks: By analogy with a product of similar composition

Effects on foetal development

Test Type: Two-generation study

Species: Rat

Application Route: Inhalation Dose: 100 - 500 - 1000 ppm

Developmental Toxicity: NOAEL: 342 mg/kg body weight

Method: OPPTS 870.3800 GLP: No information available.

Remarks: Based on available data, the classification criteria

are not met.

Reproductive toxicity -

Assessment

Classification as "toxic for reproduction" is not justifiable.

Classification as "teratogenic" is not justifiable.

Toluene:

Reproductive toxicity -

Assessment

Some evidence of adverse effects on development, based on

animal experiments.

Ethylbenzene:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female Strain: Sprague-Dawley Application Route: Inhalation Dose: 25 - 100 - 500 ppm Duration of Single Treatment: 6 h

General Toxicity - Parent: NOAEL: 2.21 mg/l General Toxicity F1: NOAEL: 2.21 mg/l General Toxicity F2: NOAEL: 2.21 mg/l Method: OECD Test Guideline 416

GLP: yes

Effects on foetal development

Test Type: Fertility/early embryonic development

Species: Rat

Strain: Sprague-Dawley Application Route: Inhalation Dose: 100-500-1000-2000 ppm Duration of Single Treatment: 15 d General Toxicity Maternal: 500

Teratogenicity: 2,000 Developmental Toxicity: 500

Method: OECD Test Guideline 414 GLP: No information available.

Reproductive toxicity -

Assessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.



PHASETREAT 15712 Page 16

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

STOT - single exposure

Components:

Xylene:

Exposure routes: Inhalation

Assessment: May cause respiratory irritation.

Toluene:

Assessment: May cause drowsiness or dizziness.

Ethylbenzene:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Hydrocarbons, C10, aromatics, >1% naphthalene:

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Components:

Xylene:

Target Organs: Kidney, Liver, Central nervous system

Assessment: May cause damage to organs through prolonged or repeated exposure.

Toluene:

Assessment: May cause damage to organs through prolonged or repeated exposure.

Ethylbenzene:

Target Organs: hearing organs

Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Xylene:

Species: Rat, male and female

NOAEL: 250 mg/kg

Application Route: oral (gavage)

Exposure time: 103 w

Number of exposures: Once daily (5 days/week).

Dose: 250 - 500 mg/kg

Group: yes Method: Other

GLP: No information available.



PHASETREAT 15712 Page 17

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Species: Rat, male and female

NOAEL: 150 mg/kg LOAEL: 150 mg/kg

Application Route: oral (gavage)

Exposure time: 90 d

Number of exposures: once daily Dose: 150 - 750 - 1500 mg/kg

Group: yes

Method: OECD Test Guideline 408 GLP: No information available.

Species: Rat, male NOAEL: >= 3.515 mg/l Application Route: Inhalation

Exposure time: 13 w

Number of exposures: 6 hours/day, 5 days/week

Dose: 781 - 1996 - 3515 mg/m3

Group: yes Method: Other

GLP: No information available.

Application Route: Skin contact

Remarks: This information is not available.

Toluene:

Target Organs: Liver, Nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated

exposure, category 2. Remarks: no data available

Ethylbenzene:

Species: Rat, male and female

NOAEL: 75 mg/kg

Application Route: oral (gavage)

Exposure time: 3 m

Number of exposures: twice daily Dose: 75 - 250 - 750 mg/kg

Group: yes

Method: OECD Test Guideline 408

GLP: yes

Species: Rat, male and female NOAEL: 0.33 - 1.1 mg/l Application Route: Inhalation

Exposure time: 2 a

Number of exposures: 6 hours/day, 5 days/week

Dose: 75 - 250 - 750 ppm

Group: yes

Method: OECD Test Guideline 453

GLP: yes



PHASETREAT 15712 Page 18

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Application Route: Skin contact

Remarks: This information is not available.

Aspiration toxicity

Components:

Xylene:

May be fatal if swallowed and enters airways.

Toluene:

May be fatal if swallowed and enters airways.

Ethylbenzene:

May be fatal if swallowed and enters airways.

Hydrocarbons, C10, aromatics, >1% naphthalene:

May be fatal if swallowed and enters airways.

Experience with human exposure

Product:

General Information : The possible symptoms known are those derived from the

labelling (see section 2).

Further information

Components:

Toluene:

Remarks: Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Ingestion or inhalation of high concentrations may cause injuries to gastrointestinal tract, liver, kidneys and central nervous system.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Poisoning by resorption through skin possible.

Has a degreasing effect on the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: no data available

Toxicity to daphnia and other :



PHASETREAT 15712 Page 19

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

aquatic invertebrates Remarks: no data available

Toxicity to algae/aquatic

plants Remarks: no data available

Components:

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.6 mg/l

Exposure time: 96 h Test Type: semi-static test Analytical monitoring: yes

Method: OECD Test Guideline 203 GLP: No information available.

Remarks: By analogy with a product of similar composition

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): ca. 1 mg/l

Exposure time: 24 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 202 GLP: No information available.

Remarks: By analogy with a product of similar composition

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (microalgae)): 4.36

mg/l

End point: Growth rate Exposure time: 73 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 201

GLP: ves

Remarks: By analogy with a product of similar composition

EC50 (Pseudokirchneriella subcapitata (green algae)): 2.2

mg/l

End point: Biomass Exposure time: 73 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 201

GLP: yes

Remarks: By analogy with a product of similar composition

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.44

mg/l

Exposure time: 73 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 201

GLP: yes

Remarks: By analogy with a product of similar composition



PHASETREAT 15712 Page 20

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Toxicity to fish (Chronic

toxicity)

NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l

Exposure time: 56 d

Test Type: flow-through test Analytical monitoring: yes

Method: Other GLP: no

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Freshwater insects): 0.96 - 1.17 mg/l

End point: Reproduction rate

Exposure time: 7 d Test Type: semi-static test Analytical monitoring: yes

Method: Other GLP: no

Remarks: By analogy with a product of similar composition

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l

Exposure time: 24 h
Test Type: static test
Analytical monitoring: no

Method: Other

GLP: No information available.

Remarks: By analogy with a product of similar composition

The details of the toxic effect relate to the nominal

concentration.

EC50 (activated sludge, domestic): > 157 mg/l End point: Bacteria toxicity (respiration inhibition)

Exposure time: 3 h
Test Type: static test
Analytical monitoring: no

Method: OECD Test Guideline 209

GLP: yes

Remarks: By analogy with a product of similar composition

The details of the toxic effect relate to the nominal

concentration.

Toxicity to soil dwelling

organisms

Remarks: Not applicable

Plant toxicity : EC50: ca. > 1 mg/kg

>1 milligram per kilogram Exposure time: 14 d End point: Growth

Species: Lactuca sativa (lettuce) Analytical monitoring: yes Method: OECD Guide-line 208 GLP: No information available.

Remarks: By analogy with a product of similar composition

Sediment toxicity : Remarks: Not applicable



PHASETREAT 15712 Page 21

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Toxicity to terrestrial

organisms

Remarks: Not applicable

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Toluene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.5 mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l

Exposure time: 48 h Test Type: semi-static test

Method: EPA

Toxicity to algae/aquatic

plants

EC50 (Chlorella vulgaris (Fresh water algae)): 134 mg/l

Exposure time: 3 h Test Type: static test Method: Other

Toxicity to fish (Chronic

toxicity)

NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l

Exposure time: 40 d

Test Type: flow-through test

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Ceriodaphnia spec.): 0.74 mg/l

End point: Reproduction rate

Exposure time: 7 d Test Type: semi-static test

Method: Other

Toxicity to microorganisms : NOEC (Pseudomonas putida): 29 mg/l

Exposure time: 16 h

Toxicity to soil dwelling

organisms

Remarks: Not applicable

Plant toxicity : Remarks: Not applicable

Sediment toxicity : Remarks: Not applicable

Toxicity to terrestrial

organisms

Remarks: Not applicable

Ethylbenzene:

Toxicity to fish : LC50 (Menidia menidia (Atlantic silverside)): 5.1 mg/l

Exposure time: 96 h

Test Type: flow-through test Analytical monitoring: yes



PHASETREAT 15712

Page 22

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Method: Other GLP: yes

LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l

Exposure time: 96 h

Test Type: flow-through test Analytical monitoring: yes

Method: OECD Test Guideline 203 GLP: No information available.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l

Exposure time: 48 h Test Type: static test Analytical monitoring: yes

Method: EPA GLP: no

LC50 (Mysidopsis bahia (opossum shrimp)): 2.6 mg/l

Exposure time: 96 h

Test Type: flow-through test Analytical monitoring: yes

Method: EPA GLP: yes

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (microalgae)): 3.6 mg/l

End point: Biomass Exposure time: 96 h Test Type: static test Analytical monitoring: yes

Method: EPA GLP: yes

EC50 (Skeletonema costatum (marine diatom)): 7.7 mg/l

End point: Biomass Exposure time: 96 h Test Type: static test Analytical monitoring: yes

Method: EPA GLP: yes

Toxicity to fish (Chronic

toxicity)

Chronic Toxicity Value (Fish): 1.13 mg/l

Exposure time: 30 d Analytical monitoring: no Method: Expert judgement

GLP: no

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Ceriodaphnia spec.): 0.96 mg/l

End point: Reproduction rate

Exposure time: 7 d

Test Type: semi-static test Analytical monitoring: yes

Method: Other



PHASETREAT 15712 Page 23

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

GLP: no

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l

Exposure time: 24 h Test Type: static test Analytical monitoring: no

Method: Other GLP: no

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to soil dwelling

organisms

LC50 (Eisenia fetida (earthworms)): 0.047 mg/cm2

Exposure time: 48 h End point: mortality

Method: OECD Test Guideline 207

GLP: no

Plant toxicity : Remarks: Not applicable

Sediment toxicity : Remarks: Not applicable

Toxicity to terrestrial

organisms

Remarks: Not applicable

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Dodecylbenzene sulphonate-MEA salt (Analogy):

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Hydrocarbons, C10, aromatics, >1% naphthalene:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l

End point: mortality Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 - 10 mg/l

End point: Immobilization Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - <

3 mg/l

End point: Biomass Exposure time: 72 h Test Type: static test



PHASETREAT 15712 Page 24

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

NOELR (Oncorhynchus mykiss (rainbow trout)): 0.487 mg/l

Exposure time: 28 d

Method: Other

Remarks: Estimated value

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOELR (Daphnia magna (Water flea)): 0.851 mg/l

Exposure time: 21 d Method: Other

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Product:

Biodegradability : Remarks: no data available

Components:

Xylene:

Biodegradability : aerobic

Inoculum: activated sludge, non-adapted

Concentration: 41 mg/l BOD in % of theoretical OD Result: Readily biodegradable. Biodegradation: 87.8 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

GLP: yes

Toluene:

Biodegradability : aerobic

Result: Readily biodegradable.

Biodegradation: 86 % Exposure time: 20 d

Physico-chemical

removability

Remarks: Biodegradable

Ethylbenzene:

Biodegradability : aerobic

Inoculum: activated sludge Concentration: 22 mg/l

Dissolved organic carbon (DOC) Result: Readily biodegradable. Biodegradation: 70 - 80 %

Exposure time: 28 d



PHASETREAT 15712 Page 25

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Method: ISO/DIS 14853

GLP: yes

Photodegradation : Test Type: air

Concentration: 500000 molecule/cm³ Rate constant: 7,1E-12 cm³/(molecule*sec)

Degradation (indirect photolysis): 50 % Degradation half life:

2.3 d

GLP: No information available.

Hydrocarbons, C10, aromatics, >1% naphthalene:

Biodegradability : aerobic

Inoculum: activated sludge Result: Inherently biodegradable. Method: OECD Test Guideline 301F

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: no data available

Components:

Xylene:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): 7.2 - 25.9

Exposure time: 56 d

Concentration: 0.36 - 0.74 mg/l

Method: Other

GLP: No information available.

Toluene:

Bioaccumulation : Bioconcentration factor (BCF): 90

Remarks: Does not bioaccumulate.

Ethylbenzene:

Bioaccumulation : Species: Oncorhynchus kisutch (coho salmon)

Bioconcentration factor (BCF): 1

Exposure time: 42 d Concentration: 0.005 mg/l

Method: Other

GLP: No information available.

Mobility in soil

Product:

Distribution among : Remarks: no data available

environmental compartments



PHASETREAT 15712 Page 26

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Components:

Xylene:

Distribution among : Adsorption/Soil environmental compartments : Medium: water - soil

log Koc: 2.73

Method: OECD Test Guideline 121

Toluene:

Distribution among environmental compartments

Remarks: The product evaporates readily.

Ethylbenzene:

Distribution among : environmental compartments

Adsorption/Soil log Koc: 2.71 Method: estimated

Other adverse effects

Product:

Results of PBT and vPvB

assessment

Remarks: no data available

Additional ecological

information

No data is available on the product itself.

Components:

Xylene:

Environmental fate and

pathways

not available

Results of PBT and vPvB

assessment

The substance is not identified as a PBT or as a vPvB

substance.

Additional ecological

information

Do not allow to enter ground water, waterways or waste water.

Toluene:

Results of PBT and vPvB

assessment

This substance is not considered to be persistent,

bioaccumulating and toxic (PBT).

Additional ecological

information

The product should not be allowed to enter drains, water

courses or the soil.

Ethylbenzene:

Environmental fate and

pathways

not available



PHASETREAT 15712 Page 27

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Results of PBT and vPvB

assessment

The substance is not identified as a PBT or as a vPvB

substance.

Additional ecological

information

The product should not be allowed to enter drains, water

courses or the soil.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

RCRA - Resource

Conservation and Recovery

Authorization Act

This material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing, use or

contamination of this product may change the waste management options. State and local disposal regulations

Waste Code : D001

Waste from residues : Consult local, state, and federal regulations.

For disposal, this material is a flammable hazardous waste

under RCRA.

Contaminated packaging : Contaminated packaging material should be treated

equivalent to residual chemicals. Clean packaging material should be subjected to waste management schemes (recovery recycling, reuse) according to local legislation.

SECTION 14. TRANSPORT INFORMATION

DOT Regulation:

UN/NA-number: UN 1993

Proper shipping name: Flammable liquids, n.o.s.

Technical Name: Xylene TOLUENE

Primary hazard class: 3
Packing group: II

Reportable Quantity: 90.000 kg Xylene 908.000 kg TOLUENE

Emergency Response

Guide:

128

IATA

UN/ID number: UN 1993

Proper shipping name: Flammable liquid, n.o.s.

Hazard inducer(s): Xylene TOLUENE



PHASETREAT 15712 Page 28

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Primary risk: 3
Packing group: II

Remarks: Shipment permitted

IMDG

UN no.: UN 1993

Proper shipping name: Flammable liquid, n.o.s.

Hazard inducer(s): Xylene

TOLUENE

Primary risk: 3
Packing group: II

EmS: F-E S-E

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Xylene	1330-20-7	100	277

A characteristic waste RQ of 100 lbs applies to this product in a waste form: D001

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Sulphuric acid	7664-93-9	1000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Carcinogenicity

Skin corrosion or irritation

Aspiration hazard

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Flammable (gases, aerosols, liquids, or solids)

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

 Xylene
 1330-20-7
 30 - 50 %

 Toluene
 108-88-3
 30 - 50 %

 Ethylbenzene
 100-41-4
 5 - 10 %

Clean Water Act

Contains priority pollutants toluene and ethylbenzene at greater than 0.1%.

The components of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory



PHASETREAT 15712 Page 29


Substance key: 000000720848	Revision Date: 03/26/2020
Version: 2 - 2 / USA	Date of printing :04/15/2021

exemption., All components are compliant with the TSCA Inventory Notification (Active) rule.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-2 / TWA : 8-hour time weighted average
OSHA Z-2 / CEIL : Acceptable ceiling concentration

OSHA Z-2 / Peak : Acceptable maximum peak above the acceptable ceiling

concentration for an 8-hr shift

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -



PHASETREAT 15712 Page 30

 Substance key: 000000720848
 Revision Date: 03/26/2020

 Version: 2 - 2 / USA
 Date of printing: 04/15/2021

Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Observe all necessary precautions for handling flammable substances. Keep away from sources of heat and ignition. Smoking should be prohibited where material is being handled. Electrical grounding of equipment is required.

Revision Date : 03/26/2020

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Clariant makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Clariant's products for its particular application. NO EXPRESS OR IMPLIED WARRANTY IS MADE OF THE MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE OF ANY PRODUCT OR SERVICE. Nothing included in this information waives any of Clariant's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing Clariant products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet



PHASETREAT 15712

Page 31

Substance key: 000000720848	Revision Date: 03/26/2020
Version: 2 - 2 / USA	Date of printing :04/15/2021

information before handling any of these products. For additional information, please contact Clariant.

US / EN