

1

2

3

4

A

A

B

B

C

C

D

D

E

E

F

F

G

G

H

H

AA

6VOPT

BB

FAST Gas Tip

≈30' AGL

Unicable Top Bracket

SP8-PTC Spark Ignited Pilot

BB

≈23' AGL

Standard Guy Wire Tab

Tee Brackets per drawing

4" x 150# SORF LP Inlet Flange

≈11' AGL

4" x 150# SORF HP Inlet Flange

≈8' AGL

FAST Gas Regulator
0-100 as required.
Consumption @ 60 psi
is 78 mcf/day

Pilot Gas Regulator
set to 5 psi @ 78 scfh

Unicable Winch

4" x 150# SOFF Flange

Information contained on this document is proprietary and confidential. It is the property of D.B.I. It may not be reproduced, transmitted or otherwise disclosed, by or to any person or organization without the prior written consent of the authorized representative of D.B.I. This document is conditionally loaned and must be returned to D.B.I. upon request. Information contained herein may be used in no manner detrimental to the interests of D.B.I.

D.B.I. Bastrop, Texas USA 512-303-1941
www.dbiequipment.com

PROJECT: 4" x 30' TBF with 6VOPT and FAST Tips

TITLE: Conceptual View

DRAWING BY
DWB

DATE: 09-20-20 DWG.# 092020-1C SHEET: 1 of 1 REV. 0

1

2

3

4