



CSH1001-HH			
Operating Point	2950 GPM (US) @ 80' TDH		
Mainstream Flowrate	2360		
Sidestream Flowrate	590		
Separator - Size & Style	CS-10T-FLG, Carbon Steel, Powder Coated		
Frame Construction	Carbon Steel (Welded), Powder Coated		
Pipe Assy - Construction	Carbon Steel (Welded), Powder Coated		
ELECTRICAL - Motor & System			
Horsepower (HP)	75		
Power - Volts / Hz	460/60	575/60	230/60
RPM	1750	1750	1750
Motor Amperage	96	77	192
System Total Amperage	98	79	194
PUMP			
Installation	Flooded Suction Required		
Case Material	Cast Iron		
Impeller Material	304		
Mechanical Seal	EPDM - Carbon / Ceramic		
BASKET STRAINER (Optional)			
Body Construction	Cast Iron		
Strainer Mesh	Stainless Steel with 1/4" perforations		
Connection - Type & Size	10" FLG (150#)		
CONTROL PANEL (UL Listed & Labeled. Manufactured to UL 508A)			
Enclosure (UL listed & CSA approved)	NEMA 4 (STD) - Carbon Steel, Powder Coated NEMA 4X (Optional) - 304		
Electrical Components (UL listed & CSA approved)	Thermal Overload Starter, HOA, XFMR, "RUN" Light, Door Disconnect, Contactor, Purge Timer		
PROCESS INLET			
Connection - Type & Size	10" FLG (150#) - Butterfly Valve		
PROCESS OUTLET			
Connection - Type & Size	10" FLG (150#) - Butterfly Valve		
PURGE - MBV(Motorized Ball Valve) & RT (Recovery Tank)			
Actuator Motor	24-240V AC/DC		
MBV Connection Type	Female NPT 2"		
RT Size	RT-1.5		
RT Connection Type	RTM-20		
PRESSURE - Maximum Operating			
Pump Inlet	100 psi (6.9 bar)		
Vessel	150 psi (10.3 bar)		
TEMPERATURE - Maximum Operating			
System	34°F - 122°F (1°C - 50°C)		
WEIGHTS			
	DRY	SHIPPING	OPERATING
lbs (kg)	3832(1738)	4282(1942)	5346(2425)

PREPARED BY: VINH QUAN TRAN
PAGE: 1

RELEASED BY: BOB KAZANJY
DATE: 01/14/2019

REV: A

*UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN INCHES