



CSH201-HH

Operating Point	125 GPM (US) @ 80' TDH			
Mainstream Flowrate	100			
Sidestream Flowrate	25			
Separator - Size & Style	CS-2T-THD, Carbon Steel, Powder Coated			
Frame Construction	Carbon Steel (Welded), Powder Coated			
Pipe Assy - Construction	Carbon Steel (Welded), Powder Coated			

ELECTRICAL - Motor & System

Horsepower (HP)	5			
Power - Volts / Hz	460/60	575/60	230/60	208/60
RPM	3500	3500	3500	3500
Motor Amperage	7.6	6.1	15.2	16.7
System Total Amperage	9.6	8.1	17.2	18.7

PUMP

Installation	Flooded Suction Required			
Case Material	Cast Iron			
Impeller Material	Cast Iron			
Mechanical Seal	Buna - Carbon / Ceramic			

BASKET STRAINER (Optional)

Body Construction	Cast Iron			
Strainer Mesh	Stainless Steel with 1/4" perforations			
Connection - Type & Size	Female NPT 2"			

CONTROL PANEL (UL Listed & Labeled. Manufactured to UL 508A)

Enclosure (UL listed & CSA approved)	NEMA 4 (STD) - Carbon Steel, Powder Coated NEMA 4X (Optional) - 304			
Electrical Components (UL listed & CSA approved)	Thermal Overload Starter, HOA, XFMR, "RUN" Light, Door Disconnect, Contactor, Purge Timer			

PROCESS INLET

Connection - Type & Size	NPT 2" - Union Ball Valve			
--------------------------	---------------------------	--	--	--

PROCESS OUTLET

Connection - Type & Size	NPT 2" - Union Ball Valve			
--------------------------	---------------------------	--	--	--

PURGE - MBV(Motorized Ball Valve) & RT (Recovery Tank)

Actuator Motor	24-240V AC/DC			
MBV Connection Type	Female NPT 1"			
RT Size	RT-1			
RT Connection Type	RTM-10			

PRESSURE - Maximum Operating

Pump Inlet	100 psi (6.9 bar)			
Vessel	150 psi (10.3 bar)			

TEMPERATURE - Maximum Operating

System	34°F - 122°F (1°C - 50°C)			
--------	---------------------------	--	--	--

WEIGHTS

	DRY	SHIPPING	OPERATING
lbs (kg)	428(194)	538(244)	508(230)

PREPARED BY: VINH QUAN TRAN	PAGE: 1
RELEASED BY: BOB KAZANJY	DATE: 01/15/2019
	REV: A

*UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN INCHES