



### CSH400-HH

Operating Point	340 GPM (US) @ 80' TDH		
Mainstream Flowrate	272		
Sidestream Flowrate	68		
Separator - Size & Style	CS-4T-FLG, Carbon Steel, Powder Coated		
Frame Construction	Carbon Steel (Welded), Powder Coated		
Pipe Assy - Construction	Carbon Steel (Welded), Powder Coated		

#### ELECTRICAL - Motor & System

Horsepower (HP)	10			
Power - Volts / Hz	460/60	575/60	230/60	208/60
RPM	3500	3500	3500	3500
Motor Amperage	14	11	28	30.8
System Total Amperage	16	13	30	32.8

#### PUMP

Installation	Flooded Suction Required
Case Material	Cast Iron
Impeller Material	Cast Iron
Mechanical Seal	Buna - Carbon / Ceramic

#### BASKET STRAINER (Optional)

Body Construction	Cast Iron
Strainer Mesh	Stainless Steel with 1/4" perforations
Connection - Type & Size	4" FLG (150#)

#### CONTROL PANEL (UL Listed & Labeled. Manufactured to UL 508A)

Enclosure (UL listed & CSA approved)	NEMA 4 (STD) - Carbon Steel, Powder Coated NEMA 4X (Optional) - 304
Electrical Components (UL listed & CSA approved)	Thermal Overload Starter, HOA, XFMR, "RUN" Light, Door Disconnect, Contactor, Purge Timer

#### PROCESS INLET

Connection - Type & Size	4" FLG (150#) - Butterfly Valve
--------------------------	---------------------------------

#### PROCESS OUTLET

Connection - Type & Size	4" FLG (150#) - Butterfly Valve
--------------------------	---------------------------------

#### PURGE - MBV(Motorized Ball Valve) & RT (Recovery Tank)

Actuator Motor	24-240V AC/DC
MBV Connection Type	Female NPT 1.5"
RT Size	RT-1
RT Connection Type	RTM-10

#### PRESSURE - Maximum Operating

Pump Inlet	100 psi (6.9 bar)
Vessel	150 psi (10.3 bar)

#### TEMPERATURE - Maximum Operating

System	34°F - 122°F (1°C - 50°C)
--------	---------------------------

WEIGHTS	DRY	SHIPPING	OPERATING
lbs (kg)	1102(500)	1290(585)	1304(592)

## CSH400-HH

PREPARED BY:  
PEI-CHI (JASON) WU

PAGE:  
**1**

RELEASED BY:  
BOB KAZANJY

DATE:  
**01/09/2019**

REV:  
**A**

\*UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN INCHES