



CSH600-HH

Operating Point	825 GPM (US) @ 80' TDH		
Mainstream Flowrate	660		
Sidestream Flowrate	165		
Separator - Size & Style	CS-6T-FLG, Carbon Steel, Powder Coated		
Frame Construction	Carbon Steel (Welded), Powder Coated		
Pipe Assy - Construction	Carbon Steel (Welded), Powder Coated		

ELECTRICAL - Motor & System			
Horsepower (HP)	25		
Power - Volts / Hz	460/60	575/60	230/60
RPM	1750	1750	1750
Motor Amperage	34	27	68
System Total Amperage	36	29	70

PUMP	
Installation	Flooded Suction Required
Case Material	Cast Iron
Impeller Material	304
Mechanical Seal	EPDM - Carbon / Ceramic

BASKET STRAINER (Optional)	
Body Construction	Cast Iron
Strainer Mesh	Stainless Steel with 1/4" perforations
Connection - Type & Size	6" FLG (150#)

CONTROL PANEL (UL Listed & Labeled. Manufactured to UL 508A)	
Enclosure (UL listed & CSA approved)	NEMA 4 (STD) - Carbon Steel, Powder Coated NEMA 4X (Optional) - 304
Electrical Components (UL listed & CSA approved)	Thermal Overload Starter, HOA, XFMR, "RUN" Light, Door Disconnect, Contactor, Purge Timer

PROCESS INLET	
Connection - Type & Size	6" FLG (150#) - Butterfly Valve

PROCESS OUTLET	
Connection - Type & Size	6" FLG (150#) - Butterfly Valve

PURGE - MBV(Motorized Ball Valve) & RT (Recovery Tank)	
Actuator Motor	24-240V AC/DC
MBV Connection Type	Female NPT 1.5"
RT Size	RT-1
RT Connection Type	RTM-10

PRESSURE - Maximum Operating	
Pump Inlet	100 psi (6.9 bar)
Vessel	150 psi (10.3 bar)

TEMPERATURE - Maximum Operating	
System	34°F - 122°F (1°C - 50°C)

WEIGHTS	DRY	SHIPPING	OPERATING
lbs (kg)	1568(711)	1756(797)	1986(901)

PREPARED BY: PEI-CHI (JASON) WU	PAGE: 1
RELEASED BY: BOB KAZANJY	DATE: 01/09/2019

REV:
A
*UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN INCHES