



## CSH800-LH

Operating Point	1500 GPM (US) @ 40' TDH		
Mainstream Flowrate	1200		
Sidestream Flowrate	300		
Separator - Size & Style	CS-8T-FLG, Carbon Steel, Powder Coated		
Frame Construction	Carbon Steel (Welded), Powder Coated		
Pipe Assy - Construction	Carbon Steel (Welded), Powder Coated		

### ELECTRICAL - Motor & System

Horsepower (HP)	25		
Power - Volts / Hz	460/60	575/60	230/60
RPM	1750	1750	1750
Motor Amperage	34	27	68
System Total Amperage	36	29	70

### PUMP

Installation	Flooded Suction Required
Case Material	Cast Iron
Impeller Material	Cast Iron
Mechanical Seal	Buna - Carbon / Ceramic

### BASKET STRAINER (Optional)

Body Construction	Cast Iron
Strainer Mesh	Stainless Steel with 1/4" perforations
Connection - Type & Size	8" FLG (150#)

### CONTROL PANEL (UL Listed & Labeled. Manufactured to UL 508A)

Enclosure (UL listed & CSA approved)	NEMA 4 (STD) - Carbon Steel, Powder Coated NEMA 4X (Optional) - 304
Electrical Components (UL listed & CSA approved)	Thermal Overload Starter, HOA, XFMR, "RUN" Light, Door Disconnect, Contactor, Purge Timer

### PROCESS INLET

Connection - Type & Size	8" FLG (150#) - Butterfly Valve
--------------------------	---------------------------------

### PROCESS OUTLET

Connection - Type & Size	8" FLG (150#) - Butterfly Valve
--------------------------	---------------------------------

### PURGE - MBV(Motorized Ball Valve) & RT (Recovery Tank)

Actuator Motor	24-240V AC/DC
MBV Connection Type	Female NPT 2"
RT Size	RT-1.5
RT Connection Type	RTM-10

### PRESSURE - Maximum Operating

Pump Inlet	100 psi (6.9 bar)
Vessel	150 psi (10.3 bar)

### TEMPERATURE - Maximum Operating

System	34°F - 122°F (1°C - 50°C)
--------	---------------------------

WEIGHTS	DRY	SHIPPING	OPERATING
lbs (kg)	2716 (1232)	2976 (1350)	3228 (1614)

PREPARED BY: PEI-CHI (JASON) WU  
PAGE: 1

RELEASED BY: BOB KAZANJY  
DATE: 01/18/2019

REV: A

\*UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN INCHES

## CSH800-LH