



Pot Feeders



Pot Feeders

A Pot Feeder is not just a Pot Feeder

General Water Systems manufactures a complete line of chemical bypass feeders for chemical dosing of non-evaporative water loops. Our pot feeders are all made in the USA, durable and long lasting. ASME Certification is available, and can be manufactured in 304 and 316. With a complete line of compatible accessories.



Features



Safety Bar Closure™: easy-to-open lid design with a small adjustable wrench at low torque. The General Safety Bar Closure™ is inherently safe. If accidentally opened under pressure, the safety bar and lid are securely restrained. This makes it impossible for the lid to fly off and cause damage or injury



Powder-coated finish provides excellent protection, superior to other products with only a painted finish



All feeders are available in 304 or 316 stainless steel; custom fabrication quotes available on request



Any feeder can become a filter feeder simply by adding our stainless steel basket and filter bag



Any feeder with a Safety Bar Closure™ can become a cartridge filter feeder simply by adding our cartridge filter assembly



Installing feeders is fast and easy: low torque opening eliminates the need to anchor the feeder to the floor, and when used with the VP-75 valve package, installation materials include just two valves, no fittings, no unions, and two joints. This saves about \$300 in time and materials for each installation



Flat Bottom Safety Bar™ (FB-SB) feeders and Domed Bottom Safety Bar™ (DB-SB) feeders are rated at 320 psig at 250°F



ASME certified units are rated at 600 psig at 250°F



ASME certified units are available in stainless steel



High temperature gaskets (250°F) are available for any DB-GE feeder

All Feeders are Made in the USA!

Pot Feeders



Flat Bottom (FB) Series

Rugged Flat Bottom design allows floor or pedestal mounting

- ✓ Three Ports, two on neck, one on side base
- ✓ Powder Coated exterior
- ✓ Safety Bar Closures
- ✓ FB-SB's (Safety Bar) series rated: 320 psi and 250° F



Dome Bottom (DB) Series

Leg Mounted with bottom drain

- ✓ Four Ports, two on neck, one on side base and in bottom head
- ✓ Powder Coated exterior
- ✓ Safety Bar or Grooved End Cap Closures
- ✓ DB-SB (Safety Bar) series rated: 320 psi and 250° F
DB-GE's rated: 350 psi and 250° F



All Feeders are available in 2, 5 and 12 gallons.

COMPLETE LINE OF ACCESSORIES AVAILABLE - Add a filter to any feeder

Bag Filter
SB-SS



CFA Cartridge
Filter Assembly



Valve Package
VP-75



Funnel
Kit FP-75



Pedestal
P-12



O'Rings and Filter
Media





- Engineering integrated filtration products
- Maintaining a high level of applications experience and an in-depth water treatment knowledge base
- Manufacturing the best in shop-durable products
- Enhancing customers operational practices



P. O. Box 444 | Desert Hot Springs | CA 92240 386.255.3909 | janeen@gwslp.com