

UL651 Standard Plastic PVC/UPVC Electrical



File No. E542398

✓ **UL 651 -STANDARD FOR SAFETY**

Schedule 40, Type EB and A Rigid PVC Conduit and Fittings

Specifications and Parameters

PartNumber	Trade Size of conduit	Average Outside diameters(in.)	Inside Diameter (in.)	Average wall thickness(in.)	Length (feet)	Minimum Weight per 10 unit Lengths(lb)
CA01050	1/2"	0.840±0.004	0.600	0.120	10	1.82
CA01075	3/4"	1.050±0.004	0.802	0.124	10	2.42
CA01100	1"	1.315±0.005	1.027	0.144	10	3.54
CA01125	1-1/4"	1.660±0.005	1.356	0.152	10	4.81
CA01150	1-1/2"	1.900±0.006	1.588	0.156	10	5.71
CA01200	2"	2.375±0.006	2.049	0.163	10	7.61
CA01250	2-1/2"	2.875±0.007	2.441	0.217	10	12.08
CA01300	3"	3.500±0.008	3.040	0.230	10	15.85
CA01400	4"	4.500±0.009	4.000	0.250	10	22.36
CA01600	6"	6.625±0.011	6.027	0.299	10	39.84

- ✓ **Highest cost performance due to 100% self-production**
- ✓ **Fireproof, insulated, lightweight and easy to install**
- ✓ **Each item export must be passed at least 6 line test**
- ✓ **30-days-leadtime supported by 30,000 Tons annual capacity**
- ✓ **Widely distributed in Middle East & America**