DESALINATION REQUIRES THE COMBINATION OF AN EFFICIENT AND HEAVY-DUTY PUMP.

We select the right material

to avoid maintenance or replacements and to have lower life cycle costs.

We follow the customers

in the product selection process, to offer the best efficient solution, for their specific needs.

SEAWATER INTAKE

The vital characteristic of a seawater intake system is to grant a sufficient quantity and quality of water. Seawater reaches the system level through the action of centrifugal and submersible pumps.

SAER has a wide range of submersible pumps (till 14") as well as high flow split casing pumps both for vertical or horizontal installation:

- S semiaxial submersible pumps
- NR radial submersible pumps
- MS submersible motors till 300 kW
- SKD split casing pumps



PRE-TREATMENT

Prior to the desalination process, seawater is treated by removing rough elements such as solids, sand etc.

SAER has two new ranges of pumps for waste water (result of over 70 years of experience in water treatment), with different types of impellers: anticlogging, multi-channel, with closed impeller:

- SD submersible waste water pumps
- NCA end suction waste water pumps



FILTRATION PROCESS

The filtration stage is enabled by high pressure pumps and booster pumps, channeling the water through the filters.

SAER has an extensive range of multistage pumps with multiple configurations:

- TM horizontal multistage pump axial suction
- TMB horizontal multistage pump radial sucton
- TMV vertical multistage pump radial suction
- MK vertical multistage pump inline suction/outlet



SAER MATERIALS PALETTE

STAINLESS STEEL AISI 316
DUPLEX
SUPERDUPLEX 5A
BRONZE G-CuSn1O
Ni-AI BRONZE
DUCTILE CAST IRON
GREY CAST IRON

SAER MAY OFFER ON REQUEST

- PAINTING WITH RESISTANCE CORRESPONDING TO CYCLE C5
- OTHER SPECIAL COATINGS

CLEAN IN PLACE

This step entails a cleaning of the pipes and equipment, which ensures high performance, preventing ex-post maintenance.

- MG end suction EN733 stub shaft pumps
- IR end suction EN733 close coupled pumps
- NCB end suction EN733 bare shaft pumps
- NCBK end suction bare shaft pumps exceeding EN733



STORAGE & DISTRIBUTION

Having been stored, the SWRO process envisages treated water to be distributed via a pump station.

SAER can offer this service, almost with its entire range, according to clients' needs.

DELIVERY TIME

SAER is able to supply duplex and super duplex pumps as well bronze or AISI 316 with exceptional delivery time.

SAER's design & production is based in Italy.



TIPS

Motors driven by an VFD will be saving energy and relieve the stress on the pumps. An energy efficient pump, properly sized for its application, optimizes the process of water generation. Select the pump on BEP leads to maximize efficiency.

SAER has enlarged its motor production till 110kW. Motors available in IE4 to have a further energy saving.

